

Semantics and Verification

Lecture 2

9 February 2010

Last lecture:

- Binary relations
- Labeled transition systems
- CCS informally

This lecture:

- CCS: syntax
- semantics of CCS (as transition systems)

Next lecture:

- Behavioral equivalences

- 1 Introduction
- 2 Syntax
- 3 Semantics
- 4 Example

- *Nil* (or *0*) process (the only atomic process)
- action prefixing *a.P*
- names and recursive definitions via $\stackrel{\text{def}}{=}$
- nondeterministic choice $+$

This is Enough to Describe Sequential Processes

Any finite LTS can be (up to isomorphism) described by using the operations above.

- parallel composition $|$
(synchronous communication between two components = **handshake synchronization**)
- restriction $P \setminus L$
- relabelling $P[f]$

Definition of CCS (channels, actions, process names)

Let

- \mathcal{A} be a set of **channel names** (e.g. *tea*, *coffee* are channel names)
- $\mathcal{L} = \mathcal{A} \cup \overline{\mathcal{A}}$ be a set of **labels** where
 - $\overline{\mathcal{A}} = \{\overline{a} \mid a \in \mathcal{A}\}$
(\mathcal{A} are called names and $\overline{\mathcal{A}}$ are called co-names)
 - by convention $\overline{\overline{a}} = a$
- $Act = \mathcal{L} \cup \{\tau\}$ is the set of **actions** where
 - τ is the **internal** or **silent** action
(e.g. τ , *tea*, $\overline{\text{coffee}}$ are actions)
- \mathcal{K} is a set of **process names (constants)** (e.g. CM).

Definition of CCS (expressions)

$P ::=$	K		process constants ($K \in \mathcal{K}$)
	$\alpha.P$		prefixing ($\alpha \in Act$)
	$\sum_{i \in I} P_i$		summation (I is an arbitrary index set)
	$P_1 \mid P_2$		parallel composition
	$P \setminus L$		restriction ($L \subseteq \mathcal{A}$)
	$P[f]$		relabelling ($f : Act \rightarrow Act$ such that
			<ul style="list-style-type: none">• $f(\tau) = \tau$• $f(\bar{a}) = \overline{f(a)}$

The set of all terms generated by the abstract syntax is called **CCS process expressions** (and denoted by \mathcal{P}).

Notation

$$P_1 + P_2 = \sum_{i \in \{1,2\}} P_i$$

$$Nil = 0 = \sum_{i \in \emptyset} P_i$$

Precedence

- 1 restriction and relabelling (tightest binding)
- 2 action prefixing
- 3 parallel composition
- 4 summation

Example: $R + a.P \mid b.Q \setminus L$ means $R + ((a.P) \mid (b.(Q \setminus L)))$.

CCS program

A collection of **defining equations** of the form

$$K \stackrel{\text{def}}{=} P$$

where $K \in \mathcal{K}$ is a process constant and $P \in \mathcal{P}$ is a CCS process expression.

- Only one defining equation per process constant.
- Recursion is allowed: e.g. $A \stackrel{\text{def}}{=} \bar{a}.A \mid A$.

Syntax

CCS

(collection of defining equations)



Semantics

LTS

(labelled transition systems)

HOW?

Structural Operational Semantics (SOS) – G. Plotkin 1981

Small-step operational semantics where the behaviour of a system is inferred using syntax-driven rules.

Given a collection of CCS defining equations, we define the following LTS ($Proc, Act, \{\xrightarrow{a} \mid a \in Act\}$):

- $Proc = \mathcal{P}$ (the set of all CCS process expressions)
- $Act = \mathcal{L} \cup \{\tau\}$ (the set of all CCS actions including τ)
- transition relation is given by **SOS rules** of the form:

$$\text{RULE } \frac{\text{premises}}{\text{conclusion}} \text{ conditions}$$

SOS rules for CCS ($\alpha \in \text{Act}$, $a \in \mathcal{L}$)

$$\text{ACT} \frac{}{\alpha.P \xrightarrow{\alpha} P}$$

$$\text{SUM}_j \frac{P_j \xrightarrow{\alpha} P'_j}{\sum_{i \in I} P_i \xrightarrow{\alpha} P'_j} \quad j \in I$$

$$\text{COM1} \frac{P \xrightarrow{\alpha} P'}{P | Q \xrightarrow{\alpha} P' | Q}$$

$$\text{COM2} \frac{Q \xrightarrow{\alpha} Q'}{P | Q \xrightarrow{\alpha} P | Q'}$$

$$\text{COM3} \frac{P \xrightarrow{a} P' \quad Q \xrightarrow{\bar{a}} Q'}{P | Q \xrightarrow{\tau} P' | Q'}$$

$$\text{RES} \frac{P \xrightarrow{\alpha} P'}{P \setminus L \xrightarrow{\alpha} P' \setminus L} \quad \alpha, \bar{\alpha} \notin L$$

$$\text{REL} \frac{P \xrightarrow{\alpha} P'}{P[f] \xrightarrow{f(\alpha)} P'[f]}$$

$$\text{CON} \frac{P \xrightarrow{\alpha} P'}{K \xrightarrow{\alpha} P'} \quad K \stackrel{\text{def}}{=} P$$

Deriving Transitions in CCS

Let $A \stackrel{\text{def}}{=} a.A$. Let's check whether

$$((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}$$

Deriving Transitions in CCS

Let $A \stackrel{\text{def}}{=} a.A$. Let's check whether

$$((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}$$

$$\text{REL} \frac{}{((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}}$$

Deriving Transitions in CCS

Let $A \stackrel{\text{def}}{=} a.A$. Let's check whether

$$((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}$$

$$\text{REL} \frac{\text{COM1} \frac{}{(A \mid \bar{a}.Nil) \mid b.Nil \xrightarrow{a}}}{((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}}{((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}}$$

Deriving Transitions in CCS

Let $A \stackrel{\text{def}}{=} a.A$. Let's check whether

$$((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}$$

$$\text{REL} \frac{\text{COM1} \frac{\text{COM1} \frac{}{A \mid \bar{a}.Nil \xrightarrow{a}}{A \mid \bar{a}.Nil \xrightarrow{a}}}{(A \mid \bar{a}.Nil) \mid b.Nil \xrightarrow{a}}}{((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}}}$$

Deriving Transitions in CCS

Let $A \stackrel{\text{def}}{=} a.A$. Let's check whether

$$((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}$$

$$\text{REL} \frac{\text{COM1} \frac{\text{COM1} \frac{\text{CON} \frac{A \stackrel{\text{def}}{=} a.A}{A \xrightarrow{a}}}{A \mid \bar{a}.Nil \xrightarrow{a}}}{(A \mid \bar{a}.Nil) \mid b.Nil \xrightarrow{a}}}{((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}}$$

Deriving Transitions in CCS

Let $A \stackrel{\text{def}}{=} a.A$. Let's check whether

$$((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}$$

$$\begin{array}{c} \text{ACT} \frac{}{a.A \xrightarrow{a} A} \\ \text{CON} \frac{a.A \xrightarrow{a} A}{A \xrightarrow{a} A} \quad A \stackrel{\text{def}}{=} a.A \\ \text{COM1} \frac{}{A \mid \bar{a}.Nil \xrightarrow{a} A} \\ \text{COM1} \frac{}{(A \mid \bar{a}.Nil) \mid b.Nil \xrightarrow{a} A} \\ \text{REL} \frac{}{((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}} \end{array}$$

Deriving Transitions in CCS

Let $A \stackrel{\text{def}}{=} a.A$. Let's check whether

$$((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c}$$

$$\begin{array}{c} \text{ACT} \frac{}{a.A \xrightarrow{a} A} \\ \text{CON} \frac{a.A \xrightarrow{a} A}{A \xrightarrow{a} A} \quad A \stackrel{\text{def}}{=} a.A \\ \text{COM1} \frac{}{A \mid \bar{a}.Nil \xrightarrow{a} A \mid \bar{a}.Nil} \\ \text{COM1} \frac{}{(A \mid \bar{a}.Nil) \mid b.Nil \xrightarrow{a} (A \mid \bar{a}.Nil) \mid b.Nil} \\ \text{REL} \frac{}{((A \mid \bar{a}.Nil) \mid b.Nil)[c/a] \xrightarrow{c} ((A \mid \bar{a}.Nil) \mid b.Nil)[c/a]} \end{array}$$

