University of Amsterdam

Dept. of Social Science Informatics (SWI)
Roeterstraat 15, 1018 WB Amsterdam
The Netherlands
Tel. (+31) 20 5256786

SWI-Prolog 2.7

Reference Manual

Updated for version 2.7.15, October 1996

Jan Wielemaker

jan@swi.psy.uva.nl

SWI-Prolog is a Prolog implementation based on a subset of the WAM (Warren Abstract Machine [Warren, 1983]). SWI-Prolog has been designed and implemented such that it can easily be modified for experiments with logic programming and the relation between logic programming and other programming paradigms (such as the object oriented XPCE environment [Anjewierden & Wielemaker, 1989]). SWI-Prolog has a rich set of built-in predicates and reasonable performance, which makes it possible to develop substantial applications in it. The current version offers a module system, garbage collection and an interface to the C language.

This document gives an overview of the features, system limits and built-in predicates.

Copyright © 1990–1996, Jan Wielemaker

Contents

1 Introduction 1
- 1.1 SWI-Prolog 1
- 1.2 Status 2
- 1.3 Should you be Using SWI-Prolog? 2
- 1.4 Graphics 3
- 1.5 Version 1.5 Release Notes 3
- 1.6 Version 1.6 Release Notes 3
- 1.7 Version 1.7 Release Notes 4
- 1.8 Version 1.8 Release Notes 4
- 1.9 Version 1.9 Release Notes 4
- 1.10 Version 2.0 Release Notes 4
- 1.11 Version 2.1 Release Notes 5
- 1.12 Version 2.5 Release Notes 6
- 1.13 Version 2.6 Release Notes 6
- 1.14 Version 2.7 Release Notes 7
- 1.15 Acknowledgements 7

2 Overview 9
- 2.1 Starting SWI-Prolog from the Unix Shell 9
  - 2.1.1 Command Line Options 9
- 2.2 GNU Emacs Interface 11
- 2.3 Online Help 11
- 2.4 Query Substitutions 12
  - 2.4.1 Limitations of the History System 12
- 2.5 Reuse of toplevel bindings 14
- 2.6 Overview of the Debugger 14
- 2.7 Compilation 17
- 2.8 Environment Control 17
- 2.9 Saved States 20
  - 2.9.1 Types of Saved States and Portability 20
  - 2.9.2 Save Predicates 21
- 2.10 Automatic loading of libraries 23
  - 2.10.1 Notes on Automatic Loading 23
- 2.11 Garbage Collection 24
- 2.12 Syntax Notes 24
  - 2.12.1 ISO Syntax Support 24
- 2.13 System Limits 26
  - 2.13.1 Limits on Memory Areas 26
  - 2.13.2 Other Limits 26

  - 2.13.3 Reserved Names 26

3 Built-In Predicates 29
- 3.1 Notation of Predicate Descriptions 29
- 3.2 Consulting Prolog Source files 29
  - 3.2.1 Quick Load Files 33
- 3.3 Listing Predicates and Editor Interface 33
- 3.4 Verify Type of a Term 34
- 3.5 Comparison and Unification or Terms 35
  - 3.5.1 Standard Order of Terms 35
- 3.6 Control Predicates 36
- 3.7 Meta-Call Predicates 37
- 3.8 Advanced control-structures: blocks 38
- 3.9 Grammar rule interface (phrase) 39
- 3.10 Database 40
  - 3.10.1 Indexing databases 42
- 3.11 Declaring Properties of Predicates 42
- 3.12 Examining the Program 43
- 3.13 Input and Output 45
  - 3.13.1 Input and Output Using Implicit Source and Destination 45
  - 3.13.2 Explicit Input and Output Streams 47
  - 3.13.3 Switching Between Implicit and Explicit I/O 48
- 3.14 Status of Input and Output Streams 48
- 3.15 Primitive Character Input and Output 49
- 3.16 Term Reading and Writing 50
- 3.17 Analysing and Constructing Terms 53
- 3.18 Analysing and Constructing Atoms 55
- 3.19 Representing Text in Strings 56
- 3.20 Operators 57
- 3.21 Arithmetic 57
- 3.22 Arithmetic Functions 59
- 3.23 Adding Arithmetic Functions 62
- 3.24 List Manipulation 62
- 3.25 Set Manipulation 64
- 3.26 Sorting Lists 64
- 3.27 Finding all Solutions to a Goal 64
- 3.28 Invoking Predicates on all Members of a List 65
- 3.29 Forall 66
- 3.30 Formatted Write 66
  - 3.30.1 Writef 66
  - 3.30.2 Format 67
  - 3.30.3 Programming Format 69
- 3.31 Terminal Control 70
- 3.32 Operating System Interaction 70
- 3.33 File System Interaction 71
- 3.34 User Toplevel Manipulation 73
- 3.35 Creating a Protocol of the User Interaction 74
- 3.36 Debugging and Tracing Programs 74
- 3.37 Obtaining Runtime Statistics 76
- 3.38 Finding Performance Bottlenecks 77
- 3.39 Memory Management 78

3.40 Windows DDE interface . . . 78
3.40.1 DDE client interface . . . 79
3.40.2 DDE server mode . . . 80
3.41 Miscellaneous . . . 80

4 Using Modules **83**
4.1 Why Using Modules? . . . 83
4.2 Name-based versus Predicate-based Modules . . . 83
4.3 Defining a Module . . . 84
4.4 Importing Predicates into a Module . . . 85
4.4.1 Reserved Modules . . . 85
4.5 Using the Module System . . . 86
4.5.1 Object Oriented Programming . . . 86
4.6 Meta-Predicates in Modules . . . 87
4.6.1 Definition and Context Module . . . 88
4.6.2 Overruling Module Boundaries . . . 88
4.7 Dynamic Modules . . . 89
4.8 Module Handling Predicates . . . 89
4.9 Compatibility of the Module System . . . 90

5 Foreign Language Interface **93**
5.1 Overview of the Interface . . . 93
5.2 Linking Foreign Modules . . . 93
5.2.1 What linking is provided? . . . 94
5.2.2 What kind of loading should I be using? . . . 94
5.3 Dynamic Linking of shared libraries . . . 94
5.4 Using the library shlib for `.DLL` and `.so` files . . . 95
5.4.1 Static Linking . . . 96
5.4.2 Dynamic Linking based on `load_foreign/[2,5]` . . . 97
5.5 Interface Data types . . . 98
5.5.1 Type `term_t`: a reference to a Prolog term . . . 98
5.5.2 Other foreign interface types . . . 99
5.6 The Foreign Include File . . . 100
5.6.1 Argument Passing and Control . . . 100
5.6.2 Atoms and functors . . . 101
5.6.3 Analysing Terms via the Foreign Interface . . . 102
5.6.4 Constructing Terms . . . 106
5.6.5 Unifying data . . . 109
5.6.6 Calling Prolog from C . . . 112
5.6.7 Discarding Data . . . 113
5.6.8 Foreign Code and Modules . . . 114
5.6.9 Miscellaneous . . . 115
5.6.10 Catching Signals (Software Interrupts) . . . 115
5.6.11 Errors and warnings . . . 115
5.6.12 Environment Control from Foreign Code . . . 115
5.6.13 Querying Prolog . . . 115
5.6.14 Registering Foreign Predicates . . . 116
5.6.15 Foreign Code Hooks . . . 117
5.6.16 Embedding SWI-Prolog in a C-program . . . 117
5.7 Linking embedded applications using plld . . . 118
5.7.1 A simple example . . . 119

5.8 Example of Using the Foreign Interface . . . 120
5.9 Notes on Using Foreign Code . . . 123
5.9.1 Memory Allocation . . . 123
5.9.2 Debugging Foreign Code . . . 123
5.9.3 Name Conflicts in C modules . . . 123
5.9.4 Compatibility of the Foreign Interface . . . 123

6 Generating Runtime Applications **125**
6.1 Limitations of qsave_program . . . 127
6.2 Runtimes and Foreign Code . . . 127
6.3 Finding Application files . . . 128
6.4 Using chpl for Configuration Information . . . 129
6.4.1 Changing the emulator of a runtime application . . . 129
6.4.2 Passing a path to the application . . . 129
6.5 The Runtime Environment . . . 130
6.5.1 The Runtime Emulator . . . 130

A Hackers corner **133**
A.1 Examining the Environment Stack . . . 133
A.2 Intercepting the Tracer . . . 133
A.3 Exception Handling . . . 135
A.4 Readline Interaction . . . 135

B Summary **137**
B.1 Predicates . . . 137
B.2 Arithmetic Functions . . . 145
B.3 Operators . . . 146

Index

! /0, 36
! /1, 39
* /2, 59
** /2, 61
*-> +Action ; /2, 37
+ /2, 59
, /2, 37
- /1, 59
- /2, 59
-> /2, 37
. /2, 60
.so files, 94
/ /2, 59
// /2, 60
/\ /2, 61
; /2, 37
< /2, 58
<< /2, 61
= /2, 35
=.. /2, 54
=:= /2, 58
=< /2, 58
== /2, 35
=@= /2, 35
=\= /2, 58
> /2, 58
>= /2, 58
>> /2, 61
@< /2, 36
@=< /2, 36
@> /2, 36
@>= /2, 36
\ /1, 61
\+ /1, 37
\/ /2, 61
\= /2, 35
\== /2, 35
\=@= /2, 36
^ /2, 61
| /2, 37

abolish/2, 40
abort/0, 73
abs/1, 60
absolute_file_name/2, 72
absolute_file_name/3, 72
access_file/2, 71
acos/1, 61
append/1, 46
append/3, 63
apply/2, 38
apropos/1, 11
arg/3, 54
arithmetic_function/1, 62
asin/1, 61
assert/1, 40
assert/2, 41
asserta/1, 40
asserta/2, 41
assertz/1, 40
assertz/2, 41
at_end_of_stream/0, 50
at_end_of_stream/1, 50
at_halt/1, 32
at_initialization/1, 32
atan/1, 61
atan/2, 61
atom/1, 35
atom_char/2, 55
atom_chars/2, 55
atom_length/2, 56
atom_prefix/2, 56
atom_to_term/3, 56
atomic/1, 35
autoload/0, 126

bagof/3, 65
between/3, 58
block/3, 38
break/0, 73

call/1, 38
call_shared_object_function/2, 95
ceil/1, 60

ceiling/1, 60
character_count/2, 49
chdir/1, 73
checklist/2, 66
chpl, 126
clause/2, 44
clause/3, 45
clause_property/2, 45
close/1, 48
close_dde_conversation/1, 79
close_shared_object/1, 95
compiling/0, 32
compound/1, 35
concat/3, 56
concat_atom/2, 56
concat_atom/3, 56
consult/1, 30
context_module/1, 89
convert_time/8, 71
copy_term/2, 55
cos/1, 61
cputime/0, 62
current_arithmetic_function/1, 62
current_atom/1, 43
current_flag/1, 43
current_foreign_library/2, 95
current_functor/1, 43
current_input/1, 48
current_key/1, 43
current_op/3, 57
current_output/1, 48
current_predicate/2, 43
current_stream/3, 48

dde_current_connection/2, 80
dde_current_service/2, 80
dde_execute/2, 79
dde_poke/4, 79
dde_register_service/2, 80
dde_request/3, 79
dde_unregister_service/1, 80
debug/0, 75
debugging/0, 75
delete/3, 63
delete_file/1, 71
discontiguous/1, 42
display/1, 51
display/2, 51
displayq/1, 51
displayq/2, 51
dlopen, 94
dwim_match/2, 80
dwim_match/3, 81
dwim_predicate/2, 44
dynamic/1, 42

e/0, 62
ed/0, 34
ed/1, 34
edit/0, 34
edit/1, 34
Emacs, 11
ensure_loaded/1, 30
erase/1, 41
exception-handling, 38
exception/3, 135
exists_directory/1, 71
exists_file/1, 71
exit/2, 39
exp/1, 61
expand_file_name/2, 72
expand_term/2, 32
explain/1, 12
explain/2, 12
export/1, 89
export_list/2, 90

fail/0, 36
fail/1, 39
feature/2, 18
file_base_name/2, 71
file_directory_name/2, 71
file_name_extension/3, 72
file_search_path/2, 31
fileerrors/2, 49
findall/3, 64
flag/3, 41
flatten/2, 63
float/1, 34, 60
float_fractional_part/1, 60
float_integer_part/1, 60
floor/1, 60
flush/0, 49
flush_output/1, 49
forall/2, 66
foreign_file/1, 98
format/1, 67
format/2, 67
format_predicate/2, 69
free_variables/2, 54
functor/3, 53

garbage_collect/0, 78

gensym/2, 81
get/1, 50
get/2, 50
get0/1, 50
get0/2, 50
get_single_char/1, 50
get_time/1, 71
getenv/2, 70
GNU-Emacs, 11
ground/1, 35

halt/0, 73
halt/1, 73
hash_term/2, 42
help/0, 11
help/1, 11
history_depth/1, 53

ignore/1, 38
import/1, 85
index/1, 42
initialization/1, 32
int_to_atom/2, 55
int_to_atom/3, 55
integer/1, 34, 60
intersection/3, 64
is/2, 59
is_absolute_file_name/1, 72
is_list/1, 62
is_set/1, 64

keysort/2, 64

last/2, 63
leash/1, 75
length/2, 63
library_directory/1, 31
limit_stack/2, 78
line_count/2, 49
line_position/2, 49
list_to_set/2, 64
listing/0, 34
listing/1, 34
load_files/2, 29
load_foreign/2, 97
load_foreign_library/1, 95
load_foreign_library/2, 95
log/1, 61
log10/1, 61

make/0, 31
make_library_index/1, 23
maplist/3, 66
max/2, 60
member/2, 63
memberchk/2, 63
merge/3, 63
merge_set/3, 64
min/2, 60
mod/2, 59
module/2, 89
module_transparent/1, 89
msort/2, 64
multifile/1, 42

name/2, 55
nl/0, 49
nl/1, 49
nodebug/0, 75
nonvar/1, 34
noprotocol/0, 74
nospy/1, 75
nospyall/0, 75
not/1, 38
notrace/0, 74
notrace/1, 75
nth0/3, 63
nth1/3, 63
nth_clause/3, 45
number/1, 35
number_chars/2, 55
numbervars/4, 54

once/1, 38
op/3, 57
open/3, 47
open/4, 47
open_dde_conversation/3, 79
open_null_stream/1, 47
open_shared_object/2, 94
open_shared_object/3, 95

peek_byte/1, 50
peek_byte/2, 50
phrase/2, 39
phrase/3, 39
pi/0, 62
PL_abort_hook(), 117
PL_abort_unhook(), 117
PL_action(), 115
PL_atom_chars(), 102
PL_call(), 113
PL_call_predicate(), 113
PL_close_foreign_frame(), 113

PL_close_query(), 113
PL_compare(), 115
PL_cons_functor(), 108
PL_cons_list(), 108
PL_context(), 114
PL_copy_term_ref(), 99
PL_cut_query(), 113
PL_discard_foreign_frame(), 114
PL_dispatch_hook(), 117
PL_fail(), 100
PL_foreign_context(), 101
PL_foreign_context_address(), 101
PL_foreign_control(), 101
PL_get_arg(), 105
PL_get_atom(), 104
PL_get_atom_chars(), 104
PL_get_chars(), 104
PL_get_float(), 105
PL_get_functor(), 105
PL_get_head(), 106
PL_get_integer(), 105
PL_get_list(), 106
PL_get_list_chars(), 105
PL_get_long(), 105
PL_get_module(), 105
PL_get_name_arity(), 105
PL_get_nil(), 106
PL_get_pointer(), 105
PL_get_string(), 104
PL_get_tail(), 106
PL_halt(), 118
PL_initialise(), 118
PL_install_readline(), 118
PL_is_atom(), 103
PL_is_atomic(), 104
PL_is_compound(), 103
PL_is_float(), 103
PL_is_functor(), 104
PL_is_integer(), 103
PL_is_list(), 104
PL_is_number(), 104
PL_is_string(), 103
PL_is_variable(), 103
PL_module_name(), 115
PL_new_atom(), 101
PL_new_functor(), 102
PL_new_module(), 115
PL_new_term_ref(), 99
PL_new_term_refs(), 99
PL_next_solution(), 113
PL_open_foreign_frame(), 113
PL_open_query(), 112
PL_pred(), 112
PL_predicate(), 112
PL_predicate_info(), 112
PL_put_atom(), 106
PL_put_atom_chars(), 107
PL_put_float(), 108
PL_put_functor(), 108
PL_put_integer(), 108
PL_put_list(), 108
PL_put_list_chars(), 107
PL_put_nil(), 108
PL_put_pointer(), 108
PL_put_string_chars(), 107
PL_put_term(), 108
PL_put_variable(), 106
PL_query(), 115
PL_register_foreign(), 116
PL_reinit_hook(), 117
PL_reinit_unhook(), 117
PL_retry(), 101
PL_retry_address(), 101
PL_signal(), 115
PL_succeed(), 100
PL_term_type(), 103
PL_toplevel(), 118
PL_unify(), 109
PL_unify_arg(), 110
PL_unify_atom(), 109
PL_unify_atom_chars(), 109
PL_unify_float(), 110
PL_unify_functor(), 110
PL_unify_integer(), 110
PL_unify_list(), 110
PL_unify_list_chars(), 109
PL_unify_nil(), 110
PL_unify_pointer(), 110
PL_unify_string_chars(), 109
PL_unify_term(), 110
PL_warning(), 115
please/3, 18
plus/3, 58
portray/1, 51
portray_clause/1, 34
predicate_property/2, 43
predsort/3, 64
preprocessor/2, 33
print/1, 51
print/2, 51
profile/3, 77
profile_count/3, 77

profiler/2, 77
prolog/0, 73
prolog_current_frame/1, 133
prolog_frame_attribute/3, 133
prolog_load_context/2, 31
prolog_skip_level/2, 134
prolog_to_os_filename/2, 73
prolog_trace_interception/4, 133
prompt/2, 53
proper_list/1, 63
protocol/1, 74
protocola/1, 74
protocolling/1, 74
put/1, 49
put/2, 49

qcompile/1, 33
qload/1, 33
qsave_program/1, 126
qsave_program/2, 125

random/1, 60
read/1, 51
read/2, 51
read_clause/1, 52
read_clause/2, 52
read_history/6, 53
read_link/3, 73
read_term/2, 52
read_term/3, 53
read_variables/2, 52
read_variables/3, 52
recorda/2, 41
recorda/3, 41
recorded/2, 41
recorded/3, 41
recordz/2, 41
recordz/3, 41
redefine_system_predicate/1, 40
rem/2, 60
rename_file/2, 72
repeat/0, 36
require/1, 30
reset_profiler/0, 77
restore/1, 22
retract/1, 40
retractall/1, 40
reverse/2, 63
rl_add_history/1, 136
rl_read_init_file/1, 136
round/1, 60

same_file/2, 71
save/1, 21
save/2, 22
save_program/1, 21
save_program/2, 21
see/1, 46
seeing/1, 46
seen/0, 47
select/3, 63
set_feature/2, 20
set_input/1, 48
set_output/1, 48
set_tty/2, 70
setarg/3, 54
setenv/2, 71
setof/3, 65
sformat/2, 69
sformat/3, 69
shell/0, 70
shell/1, 70
shell/2, 70
show_profile/1, 77
sign/1, 60
sin/1, 61
size_file/2, 72
skip/1, 50
skip/2, 50
sleep/1, 81
sort/2, 64
source_file/1, 31
source_file/2, 31
source_location/2, 32
spy/1, 75
sqrt/1, 61
stack_parameter/4, 78
statistics/0, 76
statistics/2, 76
stream_position/3, 48
string/1, 35
string_concat/3, 57
string_length/2, 57
string_to_atom/2, 56
string_to_list/2, 57
style_check/1, 75
sublist/3, 66
subset/2, 64
substring/4, 57
subtract/3, 64
succ/2, 58
swritef/2, 67
swritef/3, 67

tab/1, 49
tab/2, 49
tan/1, 61
tell/1, 46
telling/1, 46
term_expansion/2, 32
term_to_atom/2, 55
time/1, 76
time_file/2, 72
tmp_file/2, 73
told/0, 47
trace/0, 74
trace/1, 74
trace/2, 74
tracing/0, 74
trim_stacks/0, 78
true/0, 36
truncate/1, 60
tty_get_capability/3, 70
tty_goto/2, 70
tty_put/2, 70
ttyflush/0, 49

union/3, 64
unknown/2, 75
unload_foreign_library/1, 95
unsetenv/1, 71
use_module/1, 85
use_module/2, 85

var/1, 34
visible/1, 75
volatile/1, 127

wait_for_input/3, 48
wildcard_match/2, 81
Win32s, 4
win_exec/2, 70
write/1, 51
write/2, 51
write_ln/1, 66
writef/1, 66
writef/2, 66
writeq/1, 51
writeq/2, 51

xor/2, 61

Chapter 1

Introduction

1.1 SWI-Prolog

SWI-Prolog has been designed and implemented to get a Prolog implementation which can be used for experiments with logic programming and the relation to other programming paradigms. The intention was to build a Prolog environment which offers enough power and flexibility to write substantial applications, but is straightforward enough to be modified for experiments with debugging, optimisation or the introduction of non-standard data types. Performance optimisation is limited due to the main objectives: portability (SWI-Prolog is entirely written in C and Prolog) and modifiability.

SWI-Prolog is based on a very restricted form of the WAM (Warren Abstract Machine) described in [Bowen & Byrd, 1983] which defines only 7 instructions. Prolog can easily be compiled into this language and the abstract machine code is easily decompiled back into Prolog. As it is also possible to wire a standard 4-port debugger in the WAM interpreter there is no need for a distinction between compiled and interpreted code. Besides simplifying the design of the Prolog system itself this approach has advantages for program development: the compiler is simple and fast, the user does not have to decide in advance whether debugging is required and the system only runs slightly slower when in debug mode. The price we have to pay is some performance degradation (taking out the debugger from the WAM interpreter improves performance by about 20%) and somewhat additional memory usage to help the decompiler and debugger.

SWI-Prolog extends the minimal set of instructions described in [Bowen & Byrd, 1983] to improve performance. While extending this set care has been taken to maintain the advantages of decompilation and tracing of compiled code. The extensions include specialised instructions for unification, predicate invocation, some frequently used built-in predicates, arithmetic, and control (`;/2`, `|/2`), if-then (`->/2`) and not (`\+/1`).

This manual does not describe the full syntax and semantics of SWI-Prolog, nor how one should write a program in Prolog. These subjects have been described extensively in the literature. See [Bratko, 1986], [Sterling & Shapiro, 1986], and [Clocksin & Mellish, 1981]. For more advanced Prolog material see [O'Keefe, 1990]. Syntax and standard operator declarations confirm to the 'Edinburgh standard'. Most built in predicates are compatible with those described in [Clocksin & Mellish, 1981]. SWI-Prolog also offers a number of primitive predicates compatible with Quintus Prolog[1] [Qui, 1987] and BIM_Prolog[2] [BIM, 1989].

[1] Quintus is a trademark of Quintus Computer Systems Inc., USA
[2] BIM is a trademark of BIM sa/nv., Belgium

1.2 Status

This manual describes version 2.7 of SWI-Prolog. SWI-Prolog has been used now for several years. The application range includes Prolog course material, meta-interpreters, simulation of parallel Prolog, learning systems, natural language processing and two large workbenches for knowledge engineering. Although we experienced rather obvious and critical bugs can remain unnoticed for a remarkable long period, we can assume the basic Prolog system is fairly stable. Bugs can be expected in infrequently used builtin predicates.

Some bugs are known to the author. They are described as footnotes in this manual.

1.3 Should you be Using SWI-Prolog?

There are a number of reasons why you better choose a commercial Prolog system, or another academic product:

- *SWI-Prolog is not supported*
  Although I usually fix bugs shortly after a bug report arrives, I cannot promise anything. Now that the sources are provided, you can always dig into them yourself.
- *Memory requirements and performance are your first concerns*
  A number of commercial compilers are more keen on memory and performance than SWI-Prolog. I do not wish to sacrifice some of the nice features of the system, nor its portability to compete on raw performance.
- *You need features not offered by SWI-Prolog*
  In this case you may wish to give me suggestions for extensions. If you have great plans, please contact me (you might have to implement them yourself however).

On the other hand, SWI-Prolog offers some nice facilities:

- *Nice environment*
  This includes 'Do What I Mean', automatic completion of atom names, history mechanism and a tracer that operates on single key-strokes. Interfaces to standard Unix editors are provided, as well as a facility to maintain programs (see `make/0`).
- *Very fast compiler*
  The compiler handles about 100K bytes per second on a SPARC-II processor.
- *Transparent compiled code*
  SWI-Prolog compiled code can be treated just as interpreted code: you can list it, trace it, assert to or retract from it, etc. This implies you do not have to decide beforehand whether a module should be loaded for debugging or not. Also, performance is much better than the performance of most interpreters.
- *Profiling*
  SWI-Prolog offers tools for performance analysis, which can be very useful to optimise programs. Unless you are very familiar with Prolog and Prolog performance considerations this might be more helpful than a better compiler without these facilities.

- *Flexibility*
  SWI-Prolog allows for easy and flexible integration with C, both Prolog calling C functions as C calling Prolog predicates. SWI-Prolog is provided in source form, which implies SWI-Prolog can be linked in with another package. Command line options and predicates to obtain information from the system and feedback into the system are provided.

- *Integration with PCE*
  SWI-Prolog offers a tight integration to the Object Oriented Package for User Interface Development, called PCE [Anjewierden & Wielemaker, 1989]. PCE is now also available for the X Window System.

1.4 Graphics

SWI-Prolog has no provisions for graphical applications itself. The standard graphical environment to be used with SWI-Prolog is XPCE. XPCE/SWI-Prolog provides an interactive graphical development platform that is portable over many Unix/X11 implementations as well as MS-Windows (3.1) and Windows NT (3.5).

XPCE is a licensed product. A fully functional free demo version for PC/Linux is available from `ftp://swi.psy.uva.nl/pub/xpce/linux`, for more information see URL

`http://www.swi.psy.uva.nl/projects/xpce/home.html`

or contact xpce-request@swi.psy.uva.nl

1.5 Version 1.5 Release Notes

There are not many changes between version 1.4 and 1.5. The C-sources have been cleaned and comments have been updated. The stack memory management based on using the MMU has been changed to run on a number of System-V Unix systems offering shared memory. Handling dates has been changed. All functions handling dates now return a floating point number, expressing the time in seconds since January 1, 1970. A predicate `convert_time/8` is available to get the year, month, etc. The predicate `time/6` has been deleted. `get_time/1` and `convert_time/8` together do the same.

From version 1.5, the system is distributed in source form, rather than in object form as used with previous releases. This allows users to port SWI-Prolog to new machines, extend and improve the system. If you want your changes to be incorporated in the next release, please indicate all changes using a C-preprocessor flag and send complete source files back to me. Difference listings are of no use, as I generally won't have exactly the same version around.

1.6 Version 1.6 Release Notes

Version 1.6 is completely compatible with version 1.5. Some new features have been added, the system has been ported to various new platforms and there is a provisional interface to GNU Emacs. This interface will be improved and documented later.

The WAM virtual-machine interpreter has been modified to use GCC-2's support for threaded code.

From version 1.6, the sources are now versioned using the CVS version control system.

1.7 Version 1.7 Release Notes

Version 1.7 integrates the GNU-readline library, offering powerful history and command-line editing both using Emacs and vi key-bindings.

1.8 Version 1.8 Release Notes

Version 1.8 offers a stack-shifter to provide dynamically expanding stacks on machines that do not offer operating-system support for implementing dynamic stacks.

1.9 Version 1.9 Release Notes

Version 1.9 offers better portability including an MS-Windows 3.1 version. Changes to the Prolog system include:

- *Redefinition of system predicates*
  Redefinition of system predicates was allowed silently in older versions. Version 1.9 only allows it if the new definition is headed by a :- `redefine_system_predicate/1` directive.

- *'Answer' reuse*
  The toplevel maintains a table of bindings returned by toplevel goals and allows for reuse of these bindings by prefixing the variables with the $ sign. See section 2.5.

- *Better source code administration*
  Allows for proper updating of multifile predicates and finding the sources of individual clauses.

1.10 Version 2.0 Release Notes

Version 2.0 is first of all a freeze of all the features added to the various 1.9.x releases. Version 2.0.6 for PC has moved from the WATCOM C 32-bit windows extender to Windows NT and runs under Windows 3.1 using the Win32s NT emulator.

New features offered:

- *32-bit Virtual Machine*
  Removes various limits and improves performance.

- *Inline foreign functions*
  'Simple' foreign predicates no longer build a Prolog stack-frame, but are directly called from the VM. Notably provides a speedup for the test predicates such as `var/1`, etc.

- *Various compatibility improvements*

- *Stream based I/O library*
  All SWI-Prolog's I/O is now handled by the stream-package defined in the foreign include file <SWI-Stream.h>. Physical I/O of Prolog streams may be redefined through the foreign language interface, facilitating much simpler integration in window environments.

Version 2.0.6 offers a few incompatibilities:

- `retractall/1`
  In previous releases, the definition of `retractall/1` was:

```
retractall(Term) :-
        retract(Term),
        fail.
retractall(_).
```

  As from version 2.0.6, `retractall/1` is implemented as a deterministic foreign predicate compatible with Quintus Prolog. It behaves as:

```
retractall(Head) :-
        retract(Head),
        fail.
retractall(Head) :-
        retract((Head :- _)),
        fail.
retractall(_).
```

  I.e. the definition behaves the same when handling predicates consisting of facts. Clauses with a non-true body will be retracted if their head matches.

- *Foreign interface types*
  All foreign interface types now have names ending in `_t` to lessen the chance for conflicts. `term`, `atomic`, `functor` and `module` have `#define`'s for backward compatibility.

- `PL_register_foreign()`
  The attributes is now a bitwise or of the attribute flags rather than a 0 terminated list. This has no consequences for predicates that have no attributes (99% of them), while predicates with just one attribute will generate a compiler warning, but work properly otherwise. Predicates with more than one attributes must be changed.

- `PL_dispatch_events`
  This pointer is replaced by PL_dispatch_hook(). A function was necessary for the Windows NT .DLL interface.

1.11 Version 2.1 Release Notes

In addition to several bug fixes, the 2.1 versions provide some new features:

- `setarg/3`
  A new predicate `setarg/3` for extra-logical (destructive) assignment to arguments of terms is provided.

- *Modified* `keysort/2`
  `keysort/2` is now stable with regard to multiple values on the same key. Makes this predicate compatible with SICStus and Quintus.

- *Modified grammar rule expansion*
  DCG translation of free variables now calls `phrase/3`, which has been changed slightly to deal with 'un-parsing'. Modification is probably not complete, but it fixes some problems encountered by Michael Böhlen.

- *Exception handling*
  The top of the runtime stack are automatically dumped on floating point exceptions.

- *Foreign interface*
  Added facilities to allow for embedding SWI-Prolog in C applications.

1.12 Version 2.5 Release Notes

Version 2.5 is an intermediate release on the path from 2.1 to 3.0. All changes are to the foreign-language interface, both to user- and system predicates implemented in the C-language. The aim is twofold. First of all to make garbage-collection and stack-expansion (stack-shifts) possible while foreign code is active without the C-programmer having to worry about locking and unlocking C-variables pointing to Prolog terms. The new approach is closely compatible to the Quintus and SICStus Prolog foreign interface using the `+term` argument specification (see their respective manuals). This allows for writing foreign interfaces that are easily portable over these three Prolog platforms.

According to the current plan, ISO compliant exception handling and hooks for source-code debugging will be added before the system will be called 3.0.

Apart from various bug fixes listed in the Changelog file, these are the main changes since 2.1.0:

- *ISO compatibility*
  Many ISO compatibility features have been added: `open/4`, arithmetic functions, syntax, etc.

- *WIN32*
  Many fixes for the Win32 (NT, '95 and win32s) platforms. Notably many problems related to pathnames and a problem in the garbage collector.

- *Performance*
  Many changes to the clause indexing system: added hash-tables, lazy computation of the index information, etc.

- *Portable saved-states*
  The predicate `qsave_program/[1,2]` allows for the creating of machine independent saved-states that load very quickly.

1.13 Version 2.6 Release Notes

Version 2.6 provides a stable implementation of the features added in the 2.5.x releases, but at the same time implements a number of new features that may have impact on the system stability.

- *32-bit integer and double float arithmetic*
  The biggest change is the support for full 32-bit signed integers and raw machine-format double precision floats. The internal data representation as well as the arithmetic instruction set and interface to the arithmetic functions has been changed for this.

- *Embedding for Win32 applications*
  The Win32 version has been reorganised. The Prolog kernel is now implemented as Win32 DLL that may be embedded in C-applications. Two front ends are provided, one for window-based operation and one to run as a Win32 console application.

- *Creating stand-alone executables*
  Version 2.6.0 can create stand-alone executables by attaching the saved-state to the emulator. See `qsave_program/2`.

1.14 Version 2.7 Release Notes

Version 2.7 reorganises the entire data-representation of the Prolog data itself. The aim is to remove most of the assumption on the machine's memory layout to improve portability in general and enable embedding on systems where the memory layout may depend on invocation or on how the executable is linked. The latter is notably a problem on the Win32 platforms. Porting to 64-bit architectures should be feasible now.

Furthermore, 2.7 lifts the limits on arity of predicates and number of variables in a clause considerably and allow for further expansion at minimal cost.

1.15 Acknowledgements

Some small parts of the Prolog code of SWI-Prolog are modified versions of the corresponding Edinburgh C-Prolog code: grammar rule compilation and `writef/2`. Also some of the C-code originates from C-Prolog: finding the path of the currently running executable and the code underlying `absolute_file_name/2`. Ideas on programming style and techniques originate from C-Prolog and Richard O'Keefe's *thief* editor. An important source of inspiration are the programming techniques introduced by Anjo Anjewierden in PCE version 1 and 2.

I also would like to thank those who had the fade of using the early versions of this system, suggested extensions or reported bugs. Among them are Anjo Anjewierden, Huub Knops, Bob Wielinga, Wouter Jansweijer, Luc Peerdeman, Eric Nombden, Frank van Harmelen, Bert Rengel.

Martin Jansche (jansche@novell1.gs.uni-heidelberg.de) has been so kind to reorganise the sources for version 2.1.3 of this manual.

Horst von Brand has been so kind to fix many typos in the 2.7.14 manual. Thanks!

Chapter 2

Overview

2.1 Starting SWI-Prolog from the Unix Shell

It is advised to install SWI-Prolog as 'pl' in the local binary directory. SWI-Prolog can then be started from the Unix shell by typing '`pl`'. The system will boot from the system's default boot file, perform the necessary initialisations and then enter the interactive top level.

After the necessary system initialisation the system consults (see `consult/1`) the user's initialisation file. This initialisation file should be named '`.plrc`'[1] and reside either in the current directory or in the user's home directory. If both exist the initialisation file from the current directory is loaded. The name of the initialisation file can be changed with the '`-f file`' option. After loading the initialisation file SWI-Prolog executes a user initialisation goal. The default goal is a system predicate that prints the banner message. The default can be modified with the '`-g goal`' option. Next the toplevel goal is started. Default is the interactive Prolog loop (see `prolog/0`). The user can overwrite this default with the '`-t toplevel`' option.

2.1.1 Command Line Options

The full set of command line options is given below:

`-help`
: When given as the only option, it summarises the most important options.

`-v`
: When given as the only option, it summarises the version and the architecture identifier.

`-arch`
: When given as the only option, it prints the architecture identifier (see feature(arch, Arch)) and exits.

`-Lsize`
: Give local stack size in K bytes (200 K default). Note that there is no space between the size option and its argument. For machines with dynamic stack allocation this flag sets the maximum value to which the stack is allowed to grow (2 Mbytes default). A maximum is useful to stop buggy programs from claiming all memory resources. `-L0` sets the limit to the highest possible value.

[1] Windows: '`_plrc`' as files cannot be named '`.plrc`'.

`-Gsize`
: Give global stack size in K bytes (100 K default). For machines with dynamic stack allocation the default is 4 Mbytes. See `-L` for more details.

`-Tsize`
: Give trail stack size in K bytes (50 K default). For machines with dynamic stack allocation the default is 4 Mbytes. See `-L` for more details.

`-Asize`
: Give argument stack size in K bytes (5 K default). For machines with dynamic stack allocation the default is 1 Mbytes. See `-L` for more details.

`-c file ...`
: Compile files into an 'intermediate code file'. See section 2.7.

`-o output`
: Used in combination with `-c` or `-b` to determine output file for compilation.

`-O`
: Optimised compilation. See `please/3`.

`-f file`
: Use *file* as initialisation file instead of '`.plrc`'. '`-f none`' stops SWI-Prolog from searching for an initialisation file.

`-F script`
: Selects a startup-script from the SWI-Prolog home directory. The script-file is named *script*`.rc`. The default *script* name is deduced from the executable, taking the leading alphanumerical characters (letters, digits and underscore) from the program-name. `-F none` stops looking for a script. Intended for simple management of slightly different versions. One could for example write a script `iso.rc` and then select ISO compatibility mode using `pl -F iso` or make a link from `iso-pl` to `pl`.

`-g goal`
: *Goal* is executed just before entering the top level. Default is a predicate which prints the welcome message. The welcome message can thus be suppressed by giving `-g true`. *goal* can be a complex term. In this case quotes are normally needed to protect it from being expanded by the Unix shell.

`-t goal`
: Use *goal* as interactive toplevel instead of the default goal `prolog/0`. *goal* can be a complex term. If the toplevel goal succeeds SWI-Prolog exits with status 0. If it fails the exit status is 1. This flag also determines the goal started by `break/0` and `abort/0`. If you want to stop the user from entering interactive mode start the application with '`-g goal`' and give 'halt' as toplevel.

`+/-tty`
: Switches tty control (using ioctl(2)) on (`+tty`) or off (`-tty`). Normally tty control is switched on. This default depends on the installation. You may wish to switch tty control off if Prolog is used from an editor such as Emacs. If switched off `get_single_char/1` and the tracer will wait for a return.

`-x bootfile`
: Boot from *bootfile* instead of the system's default boot file. A bootfile is a file resulting from a Prolog compilation using the `-b` or `-c` option or a program saved using `qsave_program/[1,2]`.

`-r restorefile`
: Restore a state created by `save_program/[1,2]` or `save/[1,2]` using the new-style saved-states. Equivalent to `restore(restorefile)` from Prolog.

`-p alias=path1[path2 ... ]`
: Define a path alias for file_search_path. *alias* is the name of the alias, *path1 ...* is a `:` separated list of values for the alias. A value is either a term of the form

alias(value) or pathname. The computed aliases are added to `file_search_path/2` using `asserta/1`, so they precede predefined values for the alias. See `file_search_path/2` for details on using this file-location mechanism.

`--`
Stops scanning for more arguments, so you can pass arguments for your application after this one.

The following options are for system maintenance. They are given for reference only.

`-b initfile ... -c file ...`
Boot compilation. `initfile ...` are compiled by the C-written bootstrap compiler, `file ...` by the normal Prolog compiler. System maintenance only.

`-d level`
Set debug level to *level*. System maintenance only.

2.2 GNU Emacs Interface

A provisional interface to GNU-Emacs has been included since version 1.6 of SWI-Prolog. The interface is based on the freely distributed interface delivered with Quintus Prolog. When running Prolog as an inferior process under GNU-Emacs, there is support for finding predicate definitions, completing atoms, finding the locations of compilation-warnings and many more. For details, see the files `pl/lisp/README` and `pl/lisp/swi-prolog.el`.

2.3 Online Help

Online help provides a fast lookup and browsing facility to this manual. The online manual can show predicate definitions as well as entire sections of the manual.

help
Equivalent to `help(help/1)`.

help(*+What*)
Show specified part of the manual. *What* is one of:

Name/Arity	give help on specified predicate
Name	give help on named predicate with any arity or C interface function with that name
Section	display specified section. section numbers are dash-separated numbers: `2-3` refers to section 2.3 of the manual. Section numbers are obtained using `apropos/1`.

Examples

`?- help(assert).`	give help on predicate assert
`?- help(3-4).`	display section 3.4 of the manual
`?- help('PL_retry').`	give help on interface function PL_retry()

apropos(*+Pattern*)
Display all predicates, functions and sections that have *Pattern* in their name or summary description. Lowercase letters in *Pattern* also match a corresponding uppercase letter. Example:

`?- apropos(file).` Display predicates, functions and sections that have 'file' (or 'File', etc.) in their summary description.

explain(*+ToExplain*)
Give an explanation on the given 'object'. The argument may be any Prolog data object. If the argument is an atom, a term of the form *Name/Arity* or a term of the form *Module:Name/Arity*, explain will try to explain the predicate as well as possible references to it.

explain(*+ToExplain, -Explanation*)
Unify *Explanation* with an explanation for *ToExplain*. Backtracking yields further explanations.

2.4 Query Substitutions

SWI-Prolog offers a query substitution mechanism similar to that of Unix csh (csh(1)), called 'history'. It allows the user to compose new queries from those typed before and remembered by the system. It also allows to correct queries and syntax errors. SWI-Prolog does not offer the Unix csh capabilities to include arguments. This is omitted as it is unclear how the first, second, etc. argument should be defined.[2]

The available history commands are shown in table 2.1. Figure 2.1 gives some examples.

`!!.`	Repeat last query
`!nr.`	Repeat query numbered `<nr>`
`!str.`	Repeat last query starting with `<str>`
`!?str.`	Repeat last query holding `<str>`
`^old^new.`	Substitute `<old>` into `<new>` of last query
`!nr^old^new.`	Substitute in query numbered `<nr>`
`!str^old^new.`	Substitute in query starting with `<str>`
`!?str^old^new.`	Substitute in query holding `<str>`
`h.`	Show history list
`!h.`	Show this list

Table 2.1: History commands

2.4.1 Limitations of the History System

When in top level SWI-Prolog reads the user's queries using `history_read/6` rather than `read/1`. This predicate first reads the current input stream up to a full stop. While doing so it maps all contiguous blank space onto a single space and deletes `/* ... */` and `% ... <cr>` comments. Parts between double quotes (") or single quotes (') are left unaltered. Note that a Prolog full stop consists of a 'non-symbol' character, followed by a period (`.`), followed by a blank character. 'Symbol' characters are: `#$&*+-./:<=>?@^~`. A single quote immediately preceded by a digit (`0-9`) is considered part of the `<digit>'<digit>...` (e.g. `2'101`; binary number 101) sequence.

After this initial parsing the result is first checked for the special `^old^new.` construction. If this fails the string is checked for all occurrences of the `!`, followed by a `!`, `?`, a digit, a letter or an underscore. These special sequences are analysed and the appropriate substitution from the history list is made.

[2] One could choose words, defining words as a sequence of alpha-numeric characters and the word separators as anything else, but one could also choose Prolog arguments

```
/u4/staff/jan/.plrc consulted, 0.066667 seconds, 591 bytes
Welcome to SWI-Prolog (version 2.1.11)
Copyright (c) 1993-1995 University of Amsterdam.  All rights reserved.

1 ?- append("Hello ", "World", L).

L = [72, 101, 108, 108, 111, 32, 87, 111, 114, 108, 100]

Yes
2 ?- !!, writef(´L = %s\n´, [L]).
append("Hello ", "World", L), writef(´L = %s\n´, [L]).
L = Hello World

L = [72, 101, 108, 108, 111, 32, 87, 111, 114, 108, 100]

Yes
3 ?- sublist(integer, [3, f, 3.4], L).

L = [3]

Yes
4 ?- ^integer^number.
sublist(number, [3, f, 3.4], L).

L = [3, 3.400000]

Yes
5 ?- h.
    1   append("Hello ", "World", L).
    2   append("Hello ", "World", L), writef(´L = %s\n´, [L]).
    3   sublist(integer, [3, f, 3.4], L).
    4   sublist(number, [3, f, 3.4], L).

5 ?- !2^World^Universe.
append("Hello ", "Universe", L), writef(´L = %s\n´, [L]).
L = Hello Universe

L = [72, 101, 108, 108, 111, 32, 85, 110, 105, 118, 101, 114, 115, 101]

Yes
6 ?- halt.
```

Figure 2.1: Some examples of the history facility

From the above it follows that it is hard or impossible to correct quotation with single or double quotes, comment delimiters and spacing.

2.5 Reuse of toplevel bindings

Bindings resulting from the successful execution of a toplevel goal are asserted in a database. These values may be reused in further toplevel queries as $Var. Only the latest binding is available. Example:

```
1 ?- maplist(plus(1), "hello", X).

X = [105,102,109,109,112]

2 ?- format(´~s~n´, [$X]).
ifmmp
```

Figure 2.2: Reusing toplevel bindings

Note that variables may be set by executing =/2:

```
6 ?- X = statistics.

X = statistics

7 ?- $X.
28.00 seconds cpu time for 183,128 inferences
4,016 atoms, 1,904 functors, 2,042 predicates, 52 modules
55,915 byte codes; 11,239 external references

                        Limit    Allocated       In use
Heap         :                                624,820 Bytes
Local  stack :    2,048,000        8,192          404 Bytes
Global stack :    4,096,000       16,384          968 Bytes
Trail  stack :    4,096,000        8,192          432 Bytes
```

2.6 Overview of the Debugger

SWI-Prolog has a standard 4-port tracer [Clocksin & Mellish, 1981] with an optional fifth port. This fifth port, called *unify* allows the user to inspect the result after unification of the head. The ports are called *call*, *exit*, *redo*, *fail* and *unify*. The tracer is started by the `trace/0` command, when a spy point is reached and the system is in debugging mode (see `spy/1` and `debug/1`) or when an error is detected at run time. Note that in the interactive toplevel goal `trace/0` means "trace the next query". The tracer shows the port, displaying the port name, the current depth of the recursion and the goal. The goal is printed using the Prolog predicate `print/1` (default), `write/1` or `display/1`. An example using all five ports is shown in figure 2.3.

```
Yes
2 ?- visible(+all), leash(-exit).

Yes
3 ?- trace, min([3, 2], X).
  Call:  ( 3) min([3, 2], G235) ? creep
  Unify: ( 3) min([3, 2], G235)
  Call:  ( 4) min([2], G244) ? creep
  Unify: ( 4) min([2], 2)
  Exit:  ( 4) min([2], 2)
  Call:  ( 4) min(3, 2, G235) ? creep
  Unify: ( 4) min(3, 2, G235)
  Call:  ( 5) 3 < 2 ? creep
  Fail:  ( 5) 3 < 2 ? creep
  Redo:  ( 4) min(3, 2, G235) ? creep
  Exit:  ( 4) min(3, 2, 2)
  Exit:  ( 3) min([3, 2], 2)
```

Figure 2.3: Example trace

On *leashed ports* (set with the predicate `leash/1`, default are *call, exit, redo* and *fail*) the user is prompted for an action. All actions are single character commands which are executed WITHOUT waiting for a return (Unix 'cbreak' mode), unless the command line option `-tty` is active. Tracer options:

`+` *Spy* all
Set a spy point (see `spy/1`) on the current predicate.

`-` *No spy* all
Remove the spy point (see `nospy/1`) from the current predicate.

`/` *Find* all
Search for a port. After the '/', the user can enter a line to specify the port to search for. This line consists of a set of letters indicating the port type, followed by an optional term, that should unify with the goal run by the port. If no term is specified it is taken as a variable, searching for any port of the specified type. If an atom is given, any goal whose functor has a name equal to that atom matches. Examples:

`/f`	Search for any fail port
`/fe solve`	Search for a fail or exit port of any goal with name `solve`
`/c solve(a, _)`	Search for a call to `solve/2` whose first argument is a variable or the atom `a`
`/a member(_, _)`	Search for any port on `member/2`. This is equivalent to setting a spy point on `member/2`.

`.` *Repeat find* all
Repeat the last find command (see '/')

`A` *Alternatives* all
Show all goals that have alternatives.

`C` *Context* all
Toggle 'Show Context'. If *on* the context module of the goal is displayed between square brackets (see section 4). Default is *off*.

`L` *Listing* all
List the current predicate with `listing/1`.

`a` *Abort* all
Abort Prolog execution (see `abort/0`).

`b` *Break* all
Enter a Prolog break environment (see `break/0`).

`c` *Creep* all
Continue execution, stop at next port. (Also return, space).

`d` *Display* all
Write goals using the Prolog predicate `display/1`.

`e` *Exit* all
Terminate Prolog (see `halt/0`).

`f` *Fail* call, redo, exit
Force failure of the current goal

`g` *Goals* all
Show the list of parent goals (the execution stack). Note that due to tail recursion optimization a number of parent goals might not exist any more.

`h` *Help* all
Show available options (also '?').

`i` *Ignore* call, redo, fail
Ignore the current goal, pretending it succeeded.

`l` *Leap* all
Continue execution, stop at next spy point.

`n` *No debug* all
Continue execution in 'no debug' mode.

`p` *Print* all
Write goals using the Prolog predicate `print/1` (default).

`r` *Retry* redo, exit, fail
Undo all actions (except for database and i/o actions) back to the call port of the current goal and resume execution at the call port.

`s` *Skip* call, redo
Continue execution, stop at the next port of *this* goal (thus skipping all calls to children of this goal).

`u` *Up* all
Continue execution, stop at the next port of *the parent* goal (thus skipping this goal and all calls to children of this goal). This option is useful to stop tracing a failure driven loop.

`w` *Write* all
Write goals using the Prolog predicate `write/1`.

The ideal 4 port model as described in many Prolog books [Clocksin & Mellish, 1981] is not visible in many Prolog implementations because code optimisation removes part of the choice- and exit points. Backtrack points are not shown if either the goal succeeded deterministically or its alternatives were removed using the cut. When running in debug mode (`debug/0`) choice points are only destroyed when removed by the cut. In debug mode tail recursion optimisation is switched off.[3]

2.7 Compilation

Collections of SWI-Prolog source files can be compiled into an *intermediate code file*. An intermediate code file is a data file from which SWI-Prolog can be started. The command to compile a bundle of source files is:

```
pl [options] [-o output] -c file ...
```

The individual source files may include other files using the standard list notation, `consult/1`, `ensure_loaded/1` and `use_module/[1,2]`. When the `-o file` option is omitted a file named `a.out` is created that holds the intermediate code file.

Intermediate code files start with the BSD Unix magic code `#!` and are executable. This implies they can be started as a command:

```
sun% pl -o my_program -c ...
...
sun% my_program [options]
```

Alternatively, `my_program` can be started with

```
sun% pl -x my_program [options]
```

The following restrictions apply to source files that are to be compiled with '`-c`':

- `term_expansion/2` should not use `assert/1` and or `retract/1` other than for local computational purposes.
- Files can only be included by the standard include directives: [...], `consult/1`, `ensure_loaded/1` and `use_module/[1,2]`. User defined loading predicate invocations will not be compiled.

Directives are executed both when compiling the program and when loading the intermediate code file.

2.8 Environment Control

The current system defines 3 different mechanisms to query and/or set properties of the environment: `please/3`, `flag/3` and `feature/2` as well as a number of special purpose predicates of which

[3] This implies the system can run out of local stack in debug mode, while no problems arise when running in non-debug mode.

`unknown/2`, `fileerrors/2` are examples. The ISO standard defines prolog_flag. It is likely that all these global features will be merged into a single in the future.

please(*+Key, -Old, +New*)
The predicate `please/3`[4] is a solution to avoid large numbers of environment control predicates. Later versions will support other environment control as now provided via the predicates `style_check/2`, `leash/1`, `unknown/2`, the tracer predicates, etc. These predicates are then moved into a library for backwards compatibility. The currently available options are:

optimise *on/off* (default: *off*)
Switch optimise mode for the compiler `on` or `off` (see also the command line option `-O`). Currently optimise compilation only implies compilation of arithmetic, making it fast, but invisible to the tracer. Later versions might imply various other optimisations such as incorporating a number of basic predicates in the virtual machine (`var/1`, `fail/0`, `=/2`, etc.) to gain speed at the cost of crippling the debugger. Also source level optimisations such as integrating small predicates into their callers, eliminating constant expressions and other predictable constructs. Source code optimisation is never applied to predicates that are declared dynamic (see `dynamic/1`).

autoload *on/off* (default: *on*)
If `on` autoloading of library functions is enabled. If `off` autoloading is disabled. See section 2.10.

verbose_autoload *on/off* (default: *off*)
If `on` the normal consult message will be printed if a library is autoloaded. By default this message is suppressed. Intended to be used for debugging purposes (e.g. where does this predicate come from?).

feature(*?Key, -Value*)
The predicate `feature/2` defines an interface to installation features: options compiled in, version, home, etc. With both arguments unbound, it will generate all defined features. With the 'Key' instantiated it unify the value of the feature. Features come in three types: boolean features, features with an atom value and features with an integer value. A boolean feature is true iff the feature is present **and** the *Value* is the atom `true`. Currently defined keys:

arch (*atom*)
Identifier for the hardware and operating system SWI-Prolog is running on. Used to determine the startup file as well as to select foreign files for the right architecture. See also `load_foreign/5`.

version (*integer*)
The version identifier is an integer with value:

$$10000 \times Major + 100 \times Minor + Patch$$

Note that in releases upto 2.7.10 this feature yielded an atom holding the three numbers separated by dots. The current representation is much easier for implementing version-conditional statements.

home (*atom*)
SWI-Prolog's notion of the home-directory. SWI-Prolog uses it's home directory to find its startup file as <home>/startup/startup.<arch> and to find its library as <home>/library.

[4] The idea comes from BIM_Prolog. The options supported by this predicate are not compatible with those for BIM_Prolog however.

pipe (*bool*)
If true, tell(pipe(command)), etc. are supported.

load_foreign (*bool*)
If true, `load_foreign/[2,5]` are implemented.

open_shared_object (*bool*)
If true, `open_shared_object/2` and friends are implemented, providing access to shared libraries (.so files). This requires the C-library functions dlopen() and friends as well as the configuration option `--with-dlopen`.

dynamic_stacks (*bool*)
If true, the system provides virtual memory based stack expansion. This makes stack-expansion safe when called from C and while running C-defined functions without these functions taking any precautions. Pure Prolog programs are not affected by this feature as the system will use stack-shifting to expand the stacks at runtime.

c_libs (*atom*)
Libraries passed to the C-linker when SWI-Prolog was linked. May be used to determine the libraries needed to create statically linked extensions for SWI-Prolog.

c_staticlibs (*atom*)
On some machines, the SWI-Prolog executable is dynamically linked, but requires some libraries to be statically linked.

c_cc (*atom*)
Name of the C-compiler used to compile SWI-Prolog. Normally either gcc or cc.

c_ldflags (*atom*)
Special linker flags passed to link SWI-Prolog.

save (*bool*)
If true, `save/[1,2]` is implemented.

save_program (*bool*)
If true, `save_program/[1,2]` is implemented.

readline (*bool*)
If true, SWI-Prolog is linked with the readline library. This is done by default if you have this library installed on your system.

saved_program (*bool*)
If true, Prolog is started from a state saved with `qsave_program/[1,2]`.

runtime (*bool*)
If true, SWI-Prolog is compiled with -DO_RUNTIME, disabling various useful development features (currently the tracer and profiler).

max_integer (*integer*)
Maximum integer value. Most arithmetic operations will automatically convert to floats if integer values above this are returned.

min_integer (*integer*)
Minimum integer value.

max_tagged_integer (*integer*)
Maximum integer value represented as a 'tagged' value. Tagged integers require 4-bytes storage and are used for indexing. Larger integers are represented as 'indirect data' and require 16-bytes on the stacks (though a copy requires only 4 additional bytes).

min_tagged_integer (*integer*)
Start of the tagged-integer value range.

float_format (*atom*)
C `printf()` format specification used by `write/1` and friends to determine how floating point numbers are printed. The default is `%g`. May be changed. The specified value is passed to printf() without further checking. For example, if you want more digits printed, `%.12g` will print all floats using 12 digits instead of the default 6. See also `format/[1,2]`, `write/1`, `print/1` and `portray/1`.

compiled_at (*atom*)
Describes when the system has been compiled. Only available if the C-compiler used to compile SWI-Prolog provides the __DATE__ and __TIME__ macros.

character_escapes (*bool*)
If true (default), `read/1` interprets \ escape sequences in quoted atoms and strings. May be changed.

gc (*bool*)
If true (default), the garbage collector is active. If false, neither garbage-collection, nor stack-shifts will take place, even not on explicit request. May be changed.

trace_gc (*I*)
f true (false is the default), garbage collections and stack-shifts will be reported on the terminal. May be changed.

max_arity (*unbounded*)
ISO feature describing there is no maximum arity to compound terms.

integer_rounding_function (*down,toward_zero*)
ISO feature describing rounding by `//` and `rem` arithmetic functions. Value depends on the C-compiler used.

bounded (*true*)
ISO feature describing integer representation is bound by `min_integer` and `min_integer`.

tty_control (*bool*)
Determines whether the terminal is switched to raw mode for `get_single_char/1`, which also reads the user-actions for the trace. May be set. See also the `+/-tty` command-line option.

debug_on_error (*bool*)
If `true`, start the tracer after an error is detected. Otherwise just continue execution. The goal that raised the error will normally fail. See also `fileerrors/2` and the feature `report_error`. May be changed. Default is `true`, except for the runtime version.

report_error (*bool*)
If `true`, print error messages, otherwise suppress them. May be changed. See also the `debug_on_error` feature. Default is `true`, except for the runtime version.

set_feature(*+Key, +Value*)
Define a new feature or change its value. Both arguments must be atoms.

2.9 Saved States

2.9.1 Types of Saved States and Portability

On some architectures, SWI-Prolog allows for the creation of saved states. Currently, the C-sources define two alternative implementations for them. The old implementation[5] creates an en-

[5] This implementation is based on GNU's unexec() function, creating a new executable from the running process. It is selected using the `O_STORE_PROGRAM` option in the machine-description file.

tirely self-contained executable. It supports only the `save_program/[1,2]` predicates. The new implementation[6] creates a file that is read by the 'base' program. This file contains the data-area of the SWI-Prolog process and optionally the Prolog- and C stacks. This implementation supports `save_program/[1,2]`, `save/[1,2]` and `restore/1`. The state-file depends entirely on *exactly* the Unix program-file used to create it.

2.9.2 Save Predicates

save_program(*+NewProgram, +ListOfOptions*)
Create a new executable which will be named *NewProgram*. *ListOfOptions* is a list of *Key = Value* pairs that specify the default command line options that will be saved into the new program. If a default is not specified the default compiled into the currently running Prolog executable is used.[7] The available keys are given in table 2.2

Key	Option	Type	Description
local	**-L**	K-bytes	Size (Limit) of local stack
global	**-G**	K-bytes	Size (Limit) of global stack
trail	**-T**	K-bytes	Size (Limit) of trail stack
argument	**-A**	K-bytes	Size (Limit) of argument stack
goal	**-g**	atom	Initialisation goal
toplevel	**-t**	atom	Prolog toplevel goal
init_file	**-f**	atom	Personal initialisation file
tty	**+/−tty**	on/off	Use ioctl(2) calls

Table 2.2: Key = Value pairs for `save_program/2`

As the entire data image of the current process will be saved on the new executable it is desirable to keep this small. Notably the Prolog machine stacks should be kept small. The best way to do this is first to compile the program using the `-c` option. If this is not possible try to find the smallest possible stack sizes to compile the program. On machines with dynamic stack allocation the stacks are **not** written to file and so their size does not matter. Figure 2.4 shows a possible session. Note the use of 'initialise', which is supposed to be a predicate of the application doing time consuming initialisation.

The resulting program can be used for incremental compilation using `-c` or another `save_program/2`.

save_program(*+NewProgram*)
Equivalent to '`save_program(NewProgram, [])`'.

save(*+State*)
Writes the current status on the program, Prolog- and C-stacks to the file *State*. When this file is restored, `save/1` succeeds in the restored state and execution continues as illustrated by the following example:

[6] This implementation is selected by the O_SAVE option in the machine-description file.
[7] These are NOT the defaults compiled into an intermediate code file created with pl -c ...


```
sun% pl -c load
foreign file dbase loaded 0.066667 seconds, 1578 bytes.
setup consulted, 0.500000 seconds, 5091 bytes.
main consulted, 0.333333 seconds, 3352 bytes.
load consulted, 1.000000 seconds, 9867 bytes.
sun% a.out -f none -L10 -G10 -T5
foreign file dbase loaded 0.066667 seconds, 1578 bytes.
Welcome to SWI-Prolog (version 2.1.11)
Copyright (c) 1993-1995 University of Amsterdam.  All rights reserved.

1 ?- initialise.

Yes
2 ?- save_program(my_program,
        [ local     = 500
        , goal      = go
        , init_file = none
        ]).
Running executable: /usr/local/bin/pl
Saving to my_program; text: 204800 ... data: 357000 ... symbols ... done.
Yes
2 ?- halt.
sun%
```

Figure 2.4: Create a stand-alone executable

```
1 ?- save(state), format(´Hello World~n´).
Hello World

Yes
2 ?- halt.
machine% ./state
Hello World

Yes
2 ?- h.
    1   save(state), format(´Hello World~n´).
2 ?-
```

The `save/1` predicate is normally used for debugging purposes. `save_program/[1,2]` is the preferred way to create a new program.

save(*+State, -Rval*)
Like `save/1`, but unifies *Rval* with 0 when `save/2` returns from a real save and with 1 when `save/2` returns from a restore.

restore(*+State*)
Equivalent to restarting *State*.

2.10 Automatic loading of libraries

If —at runtime— an undefined predicate is trapped the system will first try to import the predicate from the module's default module. If this fails the *auto loader* is activated. On first activation an index to all library files in all library directories is loaded in core (see `library_directory/1`). If the undefined predicate can be located in the one of the libraries that library file is automatically loaded and the call to the (previously undefined) predicate is resumed. By default this mechanism loads the file silently. The `please/3` option `verbose_autoload` is provided to get verbose loading. The please option `autoload` can be used to enable/disable the entire auto load system.

Autoloading only handles (library) source files that use the module mechanism described in chapter 4. The files are loaded with `use_module/2` and only the trapped undefined predicate will be imported to the module where the undefined predicate was called. Each library directory must hold a file `INDEX.pl` that contains an index to all library files in the directory. This file consists of lines of the following format:

```
index(Name, Arity, Module, File).
```

The predicate `make/0` scans the autoload libraries and updates the index if it exists, is writable and out-of-date. It is advised to create an empty file called `INDEX.pl` in a library directory meant for auto loading before doing anything else. This index file can then be updated by running the prolog `make_library_index/1` ('%' is the Unix prompt):

```
% mkdir ~/lib/prolog
% cd !$
% pl -g true -t 'make_library_index(.)'
```

If there are more than one library files containing the desired predicate the following search schema is followed:

1. If a there is a library file that defines the module in which the undefined predicate is trapped, this file is used.
2. Otherwise library files are considered in the order they appear in the `library_directory/1` predicate and within the directory alphabetically.

make_library_index(*+Directory***)**
Create an index for this directory. The index is written to the file 'INDEX.pl' in the specified directory. Fails with a warning if the directory does not exist or is write protected.

2.10.1 Notes on Automatic Loading

The autoloader is a new feature to SWI-Prolog. Its aim is to simplify program development and program management. Common lisp has a similar feature, but here the user has to specify which library is to be loaded if a specific function is called which is not defined. The advantage of the SWI-Prolog schema is that the user does not have to specify this. The disadvantage however is that the user might be wondering "where the hell this predicate comes from". Only experience can learn whether the functionality of the autoloader is appropriate. Comments are welcome.

The autoloader only works if the unknown flag (see `unknown/2`) is set to `trace` (default). A more appropriate interaction with this flag will be considered.

2.11 Garbage Collection

SWI-Prolog version 1.4 was the first release to support garbage collection. Together with tail-recursion optimisation this guaranties forward chaining programs do not waste indefinite amounts of memory. Previous releases of this manual stressed on using failure-driven loops in those cases that no information needed to be passed to the next iteration via arguments. This to avoid large amounts of garbage. This is no longer strictly necessary, but it should be noticed that garbage collection is a time consuming activity. Failure driven loops tend to be faster for this reason.[8]

2.12 Syntax Notes

SWI-Prolog uses standard 'Edinburgh' syntax. A description of this syntax can be found in the Prolog books referenced in the introduction. Below are some non-standard or non-common constructs that are accepted by SWI-Prolog:

- `0'<char>`
  This construct is not accepted by all Prolog systems that claim to have Edinburgh compatible syntax. It describes the ASCII value of `<char>`. To test whether *C* is a lower case character one can use '`between(0'a, 0'z, C)`'.
- `/* ... /* .... */ ... */`
  The `/* ... */` comment statement can be nested. This is useful if some code with `/* ... */` comment statements in it should be commented out.

2.12.1 ISO Syntax Support

SWI-Prolog offers ISO compatible extensions to the Edinburgh syntax.

Character Escape Syntax

Within quoted atoms (using single quotes: `'atom'`) special characters are represented using escape-sequences. An escape sequence is lead in by the backslash (\) character. The list of escape sequences is compatible with the ISO standard, but contains one extension and the interpretation of numerically specified characters is slightly more flexible to improve compatibility.

`\a`
Alert character. Normally the ASCII character 7 (beep).

`\b`
Backspace character.

`\c`
No output. All input characters upto but not including the first non-layout character are skipped. This allows for the specification of pretty-looking long lines. For compatibility with Quintus Prolog. Nor supported by ISO. Example:

[8] BUG: The garbage collector is deactivated when Prolog is called back from a foreign language predicate. This implies there is no garbage collection within a break environment. More seriously, there is no garbage collection when handling call-backs from —for example— the XPCE package.

```
format('This is a long line that would look better if it was \c
        split across multiple physical lines in the input')
```

\<RETURN>
: No output. Skips input till the next non-layout character or to the end of the next line. Same intention as `\c` but ISO compatible.

`\f`
: Form-feed character.

`\n`
: Next-line character.

`\r`
: Carriage-return only (i.e. go back to the start of the line).

`\t`
: Horizontal tab-character.

`\v`
: Vertical tab-character (ASCII 11).

`\x23`
: Hexadecimal specification of a character. `23` is just an example. The 'x' may be followed by a maximum of 2 hexadecimal digits. The closing \ is optional. The code `\xa\3` emits the character 10 (hexadecimal 'a') followed by '3'. The code `\x201` emits 32 (hexadecimal '20') followed by '1'. According to ISO, the closing \ is obligatory and the number of digits is unlimited. The SWI-Prolog definition allows for ISO compatible specification, but is compatible with other implementations.

`\40`
: Octal character specification. The rules and remarks for hexadecimal specifications apply to octal specifications too, but the maximum allowed number of octal digits is 3.

\<character>
: Any character immediately preceded by a \ is copied verbatim. Thus, `'\\'` is an atom consisting of a single \ and `'\''` and `''''` both describe an atom with a single '.

Character escaping is only available if the feature(character_escapes, true) is active (default). See `feature/2`. Character escapes conflict with `writef/2` in two ways: `\40` is interpreted as decimal 40 by `writef/2`, but character escapes handling by read has already interpreted as 32 (40 octal). Also, `\l` is translated to a single 'l'. Double the \ (e.g. `\\l`), use the above escape sequences or use `format/2`.

Syntax for Non-Decimal Numbers

SWI-Prolog implements both Edinburgh and ISO representations for non-decimal numbers. According to Edinburgh syntax, such numbers are written as <radix>'<number>, where <radix> is a number between 2 and 36. ISO defines binary, octal and hexadecimal numbers using `0`<bxo><number>. For example: `A is 0b100 \/ 0xf00` is a valid expression. Such numbers are always unsigned.

2.13 System Limits

2.13.1 Limits on Memory Areas

SWI-Prolog has a number of memory areas which are not enlarged at run time, unless you have a version with dynamic stack allocation. The default sizes for these areas should suffice for small applications, but most serious application require larger ones. They all can be modified by command line options. The table below shows these areas. The first column gives the option name to modify the size of the area. This option character should be followed immediately by a number and expresses the number of kilo bytes to use for the area. There are no other limits than the available memory of the machine to the sizes of the areas. The areas are described in table 2.3.

The heap is a memory area to store atoms, clauses, records, flags, etc. This area is dynamically enlarged at runtime on all versions of SWI-Prolog.

2.13.2 Other Limits

Clauses Currently the following limitations apply to clauses. The arity may not be more than 1024 and the number of variables should be less than 65536.

Atoms and Strings SWI-Prolog has no limits on the sizes of atoms and strings. `read/1` and its derivatives however normally limit the number of newlines in an atom or string to 5 to improve error detection and recovery. This can be switched off with `style_check/1`.

Address space SWI-Prolog data is packed in a 32-bit word, which contains both type and value information. The size of the various memory areas is limited to 128 Mb for each of the areas. With some redesign, the program area could be split into data that should be within this range and the rest of the data, virtually unlimiting the program size.

Integers Integers are 32-bit to the user, but integers upto the value of the `max_tagged_integer` feature is represented more efficiently.

Floats Floating point numbers are represented as native double precision floats, 64 bit IEEE on most machines.

2.13.3 Reserved Names

The boot compiler (see `-b` option) does not support the module system (yet). As large parts of the system are written in Prolog itself we need some way to avoid name clashes with the user's predicates, database keys, etc. Like Edinburgh C-Prolog [Pereira, 1986] all predicates, database keys, etc. that should be hidden from the user start with a dollar (`$`) sign (see `style_check/2`).

The compiler uses the special functor `$VAR$/1` while analysing the clause to compile. Using this functor in a program causes unpredictable behaviour of the compiler and resulting program.

Option	Default[a]	Area name	Description
-L	2M	**local stack**	The local stack is used to store the execution environments of procedure invocations. The space for an environment is reclaimed when it fails, exits without leaving choice points, the alternatives are cut of with the ! predicate or no choice points have been created since the invocation and the last subclause is started (tail recursion optimisation).
-G	4M	**global stack**	The global stack is used to store terms created during Prolog's execution. Terms on this stack will be reclaimed by backtracking to a point before the term was created or by garbage collection (provided the term is no longer referenced).
-T	4M	**trail stack**	The trail stack is used to store assignments during execution. Entries on this stack remain alive until backtracking before the point of creation or the garbage collector determines they are nor needed any longer.
-A	1M	**argument stack**	The argument stack is used to store one of the intermediate code interpreter's registers. The amount of space needed on this stack is determined entirely by the depth in which terms are nested in the clauses that constitute the program. Overflow is most likely when using long strings in a clause.

[a] Defaults may depend on local installation.

Table 2.3: Memory areas

Chapter 3

Built-In Predicates

3.1 Notation of Predicate Descriptions

We have tried to keep the predicate descriptions clear and concise. First the predicate name is printed in bold face, followed by the arguments in italics. Arguments are preceded by a '+', '−' or '?' sign. '+' indicates the argument is input to the predicate, '−' denotes output and '?' denotes 'either input or output'.[1] Constructs like 'op/3' refer to the predicate 'op' with arity '3'.

3.2 Consulting Prolog Source files

SWI-Prolog source files normally have a suffix '.pl'. Specifying the suffix is optional. All predicates that handle source files first check whether a file with suffix '.pl' exists. If not the plain file name is checked for existence. Library files are specified by embedding the file name using the functor library/1. Thus 'foo' refers to 'foo.pl' or 'foo' in the current directory, 'library(foo)' refers to 'foo.pl' or 'foo' in one of the library directories specified by the dynamic predicate library_directory/1. The user may specify other 'aliases' than library using the predicate file_search_path/2. This is strongly encouraged for managing complex applications. See also absolute_file_name/[2,3].

SWI-Prolog recognises grammar rules as defined in [Clocksin & Mellish, 1981]. The user may define additional compilation of the source file by defining the dynamic predicate term_expansion/2. Transformations by this predicate overrule the systems grammar rule transformations. It is not allowed to use assert/1, retract/1 or any other database predicate in term_expansion/2 other than for local computational purposes.[2]

Directives may be placed anywhere in a source file, invoking any predicate. They are executed when encountered. If the directive fails, a warning is printed. Directives are specified by :-/1 or ?-/1. There is no difference between the two.

SWI-Prolog does not have a separate reconsult/1 predicate. Reconsulting is implied automatically by the fact that a file is consulted which is already loaded.

load_files(*+Files, +Options*)

[1] These marks do NOT suggest instantiation (e.g. var(+Var)).

[2] It does work for consult, but makes it impossible to compile programs into a stand alone executable (see section 2.7)

The predicate load_files/2 is the parent of all the other loading predicates. It currently supports a subset of the options of Quintus load_files/2. *Files* is either specifies a single, or a list of source-files. The specification for a source-file is handled absolute_file_name/2. See this predicate for the supported expansions. *Options* is a list of options using the format

OptionName(*OptionValue*)

The following options are currently supported:

if(*Condition*)	Load the file only if the specified condition is satisfied. The value true loads the file unconditionally, changed loads the file if it was not loaded before, or has been modified since it was loaded the last time, not_loaded loads the file if it was not loaded before.
must_be_module(*Bool*)	If true, raise an error if the file is not a module file. Used by use_module/[1,2].
imports(*List*|all)	If all and the file is a module file, import all public predicates. Otherwise import only the named predicates. No effect if the file is not a module file.
silent(*Bool*)	If true, load the file without printing a message.

consult(*+File*)

Read *File* as a Prolog source file. *File* may be a list of files, in which case all members are consulted in turn. *File* may start with the csh(1) special sequences ~, ~<user> and $<var>. *File* may also be library(Name), in which case the libraries are searched for a file with the specified name. See also library_directory/1 and file_search_path/2. consult/1 may be abbreviated by just typing a number of file names in a list. Examples:

```
?- consult(load).          % consult 'load' or 'load.pl'
?- [library(quintus)].     % load Quintus compatibility library
```

Equivalent to load_files(Files, []).

ensure_loaded(*+File*)

If the file is not already loaded, this is equivalent to consult/1. Otherwise, if the file defines a module, import all public predicates. Finally, if the file is already loaded, is not a module file and the context module is not the global user module, ensure_loaded/1 will call consult/1.

With the semantics, we hope to get as closely possible to the clear semantics without the presence of a module system. Applications using modules should consider using use_module/[1,2].

Equivalent to load_files(Files, [if(changed)]).

require(*+ListOfNameAndArity*)

Declare that this file/module requires the specified predicates to be defined "with their commonly accepted definition". This predicate originates from the Prolog portability layer for XPCE. It is intended to provide a portable mechanism for specifying that this module requires the specified predicates.

The implementation normally first verifies whether the predicate is already defined. If not, it will search the libraries and load the required library.

SWI-Prolog, having autoloading, does **not** load the library. Instead it creates a procedure header for the predicate if this does not exist. This will flag the predicate as 'undefined'. See also check/0 and autoload/0.

make
Consult all source files that have been changed since they were consulted. It checks *all* loaded source files: files loaded into a compiled state using `pl -c ...` and files loaded using consult or one of its derivatives. `make/0` is normally invoked by the `edit/[0,1]` and `ed/[0,1]` predicates. `make/0` can be combined with the compiler to speed up the development of large packages. In this case compile the package using

```
sun% pl -g make -o my_program -c file ...
```

If 'my_program' is started it will first reconsult all source files that have changed since the compilation.

library_directory(*?Atom*)
Dynamic predicate used to specify library directories. Default `.`, `./lib`, `~/lib/prolog` and the system's library (in this order) are defined. The user may add library directories using `assert/1`, `asserta/1` or remove system defaults using `retract/1`.

file_search_path(*+Alias, ?Path*)
Dynamic predicate used to specify 'path-aliases'. This feature is best described using an example. Given the definition

```
file_search_path(demo, '~/demo').
```

the file specification `demo(myfile)` will be expanded to `~/demo/myfile`. The second argument of `file_search_path/2` may be another alias.

Below is the initial definition of the file search path. This path implies `swi(Path)` refers to a file in the SWI-Prolog home directory. The alias `foreign(Path)` is intended for storing shared libraries (`.so` or `.dll` files). See also `load_foreign_library/[1,2]`.

```
user:file_search_path(library, X) :-
        library_directory(X).
user:file_search_path(swi, Home) :-
        feature(home, Home).
user:file_search_path(foreign, swi(ArchLib)) :-
        feature(arch, Arch),
        concat('lib/', Arch, ArchLib).
user:file_search_path(foreign, swi(lib)).
```

The `file_search_path/2` expansion is used by all loading predicates as well as by `absolute_file_name/2`.

source_file(*?File*)
Succeeds if *File* was loaded using `consult/1` or `ensure_loaded/1`. *File* refers to the full path name of the file (see `expand_file_name/2`). `Source_file/1` backtracks over all loaded source files.

source_file(*?Pred, ?File*)
Is true if the predicate specified by *Pred* was loaded from file *File*, where *File* is an absolute path name (see `expand_file_name/2`). Can be used with any instantiation pattern, but the database only maintains the source file for each predicate. Predicates declared *multifile* (see `multifile/1`) cannot be found this way.

prolog_load_context(*?Key, ?Value*)
Determine loading context. The following keys are defined:

Key	Description
`module`	Module into which file is loaded
`file`	File loaded
`stream`	Stream identifier (see `current_stream/1`)
`directory`	Directory in which *File* lives.
`term_position`	Position of last term read. Term of the form '$stream_position'(0,Line,0,0,0)

Quintus compatibility predicate. See also `source_location/2`.

source_location(*-File, -Line*)
If the last term has been read from a physical file (i.e. not from the file `user` or a string), unify *File* with an absolute path to the file and *Line* with the line-number in the file. New code should use `prolog_load_context/2`.

term_expansion(*+Term1, -Term2*)
Dynamic predicate, normally not defined. When defined by the user all terms read during consulting that are given to this predicate. If the predicate succeeds Prolog will assert *Term2* in the database rather then the read term (*Term1*). *Term2* may be a term of a the form '?- *Goal*' or ':- *Goal*'. *Goal* is then treated as a directive. If *Term2* is a list all terms of the list are stored in the database or called (for directives). If *Term2* is of the form below, the system will assert *Clause* and record the indicated source-location with it.

'$source_location'(*File, Line*):*Clause*

When compiling a module (see chapter 4 and `:- module/2`), `term_expand/2` will first try `term_expansion/2` in the module being compiled to allow for term-expansion rules that are local to a module. If there is no local definition, or the local definition fails to translate the term, `expand_term/2` will try user:`term_expansion/2`. For compatibility with SICStus and Quintus Prolog, this feature should not be used. See also `expand_term/2`.

expand_term(*+Term1, -Term2*)
This predicate is normally called by the compiler to perform preprocessing. First it calls `term_expansion/2`. If this predicate fails it performs a grammar-rule translation. If this fails it returns the first argument.

at_initialization(*+Goal*)
Register *Goal* to be ran when the system initialises. Initialisation takes place after reloading a .qlf (formerly .wic) file as well as after reloading a saved-state. The hooks are run in the order they were registered. A warning message is issued if *Goal* fails, but execution continues. See also `at_halt/1`

at_halt(*+Goal*)
Register *Goal* to be ran when the system halts. The hooks are run in the order they were registered. Success or failure executing a hook is ignored. These hooks may not call `halt/[0,1]`.

initialization(*+Goal*)
Call *Goal* and register it using `at_initialization/1`. Directives that do other things that creating clauses, records, flags or setting predicate attributes should normally be written using this tag to ensure the initialisation is executed when a saved system starts. See also `qsave_program/[1,2]`.

compiling
Succeeds if the system is compiling source files with the `-c` option into an intermediate code file. Can be used to perform code optimisations in `expand_term/2` under this condition.

preprocessor(*-Old, +New*)
Read the input file via a Unix process that acts as preprocessor. A preprocessor is specified as an atom. The first occurrence of the string '`%f`' is replaced by the name of the file to be loaded. The resulting atom is called as a Unix command and the standard output of this command is loaded. To use the Unix C preprocessor one should define:

```
?- preprocessor(Old, '/lib/cpp -C -P %f'), consult(...).

Old = none
```

3.2.1 Quick Load Files

The features described in this section should be regarded **alpha**.

As of version 2.0.0, SWI-Prolog supports compilation of individual or multiple Prolog sourcefiles into 'Quick Load Files'. A 'Quick Load Files' (`.qlf` file) stores the contents of the file in a precompiled format very similar to compiled files created using the `-b` and `-c` flags (see section 2.7).

These files load considerably faster than sourcefiles and are normally more compact. They are machine independent and may thus be loaded on any implementation of SWI-Prolog. Note however that clauses are stored as virtual machine instructions. Changes to the compiler will generally make old compiled files unusable.

Quick Load Files are created using `qcompile/1`. They may be loaded explicitly using `qload/1` or implicitly using `consult/1` or one of the other file-loading predicates described in section 3.2. If consult is given the explicit `.pl` file, it will load the Prolog source. When given the `.qlf` file, it will call `qload/1` to load the file. When no extension is specified, it will load the `.qlf` file when present and the `.pl` file otherwise.

qcompile(*+File*)
Takes a single file specification like `consult/1` (i.e. accepts constructs like `library(LibFile)` and creates a Quick Load File from *File*. The file-extension of this file is `.qlf`. The base name of the Quick Load File is the same as the input file.

If the file contains '`:- consult(`*+File*`)`' or '`:- [`*+File*`]`' statements, the referred files are compiled into the same `.qlf` file. Other directives will be stored in the `.qlf` file and executed in the same fashion as when loading the `.pl` file.

For `term_expansion/2`, the same rules as described in section 2.7 apply.

Source references (`source_file/2`) in the Quick Load File refer to the Prolog source file from which the compiled code originates.

qload(*+File*)
Loads the 'Quick Load File'. It has the same semantics as `consult/1` for a normal sourcefile. Equivalent to `consult(`*File*`)` iff *File* refers to a 'Quick Load File'.

3.3 Listing Predicates and Editor Interface

SWI-Prolog offers an interface to the Unix *vi* editor (vi(1)) and the GNU Emacs invocations `emacs` and `emacsclient`. Which editor is used is determined by the Unix environment variable `EDITOR`, which should hold the full pathname of the editor. If this variable is not defined, vi(1) is used.[3]

[3] When using XPCE, you may wish to load library('`emacs/swi_prolog`') to use XPCE/Prolog's built-in editor.

After the user quits the editor, `make/0` is invoked to reload all modified source files using `consult/1`. If the editor can be quit such that an exit status non-equal to 0 is returned `make/0` will not be invoked. *top* can do this by typing control-C, *vi* cannot do this.

A predicate specification is either a term with the same functor and arity as the predicate wanted, a term of the form `Functor/Arity` or a single atom. In the latter case the database is searched for a predicate of this name and arbitrary arity (see `current_predicate/2`). When more than one such predicate exists the system will prompt for confirmation on each of the matched predicates. Predicates specifications are given to the 'Do What I Mean' system (see `dwim_predicate/2`) if the requested predicate does not exist.

ed(*+Pred*)
Invoke the user's preferred editor on the source file of *Pred*, providing a search specification which searches for the predicate at the start of a line.

ed
Invoke `ed/1` on the predicate last edited using `ed/1`. Asks the user to confirm before starting the editor.

edit(*+File*)
Invoke the user's preferred editor on *File*. *File* is a file specification as for `consult/1` (but not a list). Note that the file should exist.

edit
Invoke `edit/1` on the file last edited using `edit/1`. Asks the user to confirm before starting the editor.

listing(*+Pred*)
List specified predicates (when an atom is given all predicates with this name will be listed). The listing is produced on the basis of the internal representation, thus loosing user's layout and variable name information. See also `portray_clause/1`.

listing
List all predicates of the database using `listing/1`.

portray_clause(*+Clause*)
Pretty print a clause as good as we can. A clause should be specified as a term '`Head :- Body`' (put brackets around it to avoid operator precedence problems). Facts are represented as '`Head :- true`'.

3.4 Verify Type of a Term

var(*+Term*)
Succeeds if *Term* currently is a free variable.

nonvar(*+Term*)
Succeeds if *Term* currently is not a free variable.

integer(*+Term*)
Succeeds if *Term* is bound to an integer.

float(*+Term*)
Succeeds if *Term* is bound to a floating point number.

number(*+Term*)
Succeeds if *Term* is bound to an integer or a floating point number.

atom(*+Term*)
Succeeds if *Term* is bound to an atom.

string(*+Term*)
Succeeds if *Term* is bound to a string.

atomic(*+Term*)
Succeeds if *Term* is bound to an atom, string, integer or floating point number.

compound(*+Term*)
Succeeds if *Term* is bound to a compound term. See also `functor/3` and =../2.

ground(*+Term*)
Succeeds if *Term* holds no free variables.

3.5 Comparison and Unification or Terms

3.5.1 Standard Order of Terms

Comparison and unification of arbitrary terms. Terms are ordered in the so called "standard order". This order is defined as follows:

1. *Variables* < *Atoms* < *Strings*[4] < *Numbers* < *Terms*
2. *Old Variable* < *New Variable*[5]
3. *Atoms* are compared alphabetically.
4. *Strings* are compared alphabetically.
5. *Numbers* are compared by value. Integers and floats are treated identically.
6. *Terms* are first checked on their functor (alphabetically), then on their arity and finally recursively on their arguments, leftmost argument first.

+Term1 `==` *+Term2*
Succeeds if *Term1* is equivalent to *Term2*. A variable is only identical to a sharing variable.

+Term1 `\==` *+Term2*
Equivalent to '`\+ Term1 == Term2`'.

+Term1 `=` *+Term2*
Unify *Term1* with *Term2*. Succeeds if the unification succeeds.

+Term1 `\=` *+Term2*
Equivalent to '`\+ Term1 = Term2`'.

+Term1 `=@=` *+Term2*
Succeeds if *Term1* is 'structurally equal' to *Term2*. Structural equivalence is weaker than equivalence (==/2), but stronger than unification (=/2). Two terms are structurally equal if their tree representation is identical and they have the same 'pattern' of variables. Examples:

[4] Strings might be considered atoms in future versions. See also section 3.19
[5] In fact the variables are compared on their (dereferenced) addresses. Variables living on the global stack are always < than variables on the local stack. Programs should not rely on the order in which variables are sorted.


```
        a =@= A          false
        A =@= B          true
  x(A,A) =@= x(B,C)      false
  x(A,A) =@= x(B,B)      true
  x(A,B) =@= x(C,D)      true
```

+Term1 `\=@=` *+Term2*
Equivalent to `` `\+ Term1 =@= Term2´ ``.

+Term1 `@<` *+Term2*
Succeeds if *Term1* is before *Term2* in the standard order of terms.

+Term1 `@=<` *+Term2*
Succeeds if both terms are equal (`==`) or *Term1* is before *Term2* in the standard order of terms.

+Term1 `@>` *+Term2*
Succeeds if *Term1* is after *Term2* in the standard order of terms.

+Term1 `@>=` *+Term2*
Succeeds if both terms are equal (`==`) or *Term1* is after *Term2* in the standard order of terms.

3.6 Control Predicates

The predicates of this section implement control structures. Normally these constructs are translated into virtual machine instructions by the compiler. It is still necessary to implement these constructs as true predicates to support meta-calls, as demonstrated in the example below. The predicate finds all currently defined atoms of 1 character long. Note that the cut has no effect when called via one of these predicates (see !/0).

```
one_character_atoms(As) :-
        findall(A, (current_atom(A), atom_length(A, 1)), As).
```

fail
Always fail. The predicate `fail/0` is translated into a single virtual machine instruction.

true
Always succeed. The predicate `true/0` is translated into a single virtual machine instruction.

repeat
Always succeed, provide an infinite number of choice points.

!
Cut. Discard choice points of parent frame and frames created after the parent frame. Note that the control structures `;/2`, `|/2` `->/2` and `\+/1` are normally handled by the compiler and do not create a frame, which implies the cut operates through these predicates. Some examples are given below. Note the difference between `t3/1` and `t4/1`. Also note the effect of `call/1` in `t5/0`. As the argument of `call/1` is evaluated by predicates rather than the compiler the cut has no effect.

```
t1 :- (a, !, fail ; b).          % cuts a/0 and t1/0
t2 :- (a -> b, !  ; c).          % cuts b/0 and t2/0
t3(G) :- a, G, fail.             % if 'G = !' cuts a/0 and t1/1
t4(G) :- a, call(G), fail.       % if 'G = !' cut has no effect
t5 :- call((a, !, fail ; b)).    % Cut has no effect
t6 :- \+ (a, !, fail ; b).       % cuts a/0 and t6/0
```

+Goal1 , *+Goal2*
: Conjunction. Succeeds if both 'Goal1' and 'Goal2' can be proved. It is defined as (this definition does not lead to a loop as the second comma is handled by the compiler):

```
Goal1, Goal2 :- Goal1, Goal2.
```

+Goal1 ; *+Goal2*
: The 'or' predicate is defined as:

```
Goal1 ; _Goal2 :- Goal1.
_Goal1 ; Goal2 :- Goal2.
```

+Goal1 | *+Goal2*
: Equivalent to `;/2`. Retained for compatibility only. New code should use `;/2`. Still nice though for grammar rules.

+Condition `->` *+Action*
: If-then and If-Then-Else. Implemented as:

```
If -> Then; _Else :- If, !, Then.
If -> _Then; Else :- !, Else.
If -> Then :- If, !, Then.
```

+Condition `*->` `+Action` ; *+Else*
: This construct implements the so-called 'soft-cut'. The control is defined as follows: If *Condition* succeeds at least once, the semantics is the same as (*Condition*, *Action*). If *Condition* does not succeed, the semantics is that of (*Condition*, *Else*). In other words, If *Condition* succeeds at least once, simply behave as the conjunction of *Condition* and *Action*, otherwise execute *Else*.

`\+` *+Goal*
: Succeeds if 'Goal' cannot be proven (mnemonic: + refers to *provable* and the backslash is normally used to indicate negation).

3.7 Meta-Call Predicates

Meta call predicates are used to call terms constructed at run time. The basic meta-call mechanism offered by SWI-Prolog is to use variables as a subclause (which should of course be bound to a valid goal at runtime). A meta-call is slower than a normal call as it involves actually searching the database at runtime for the predicate, while for normal calls this search is done at compile time.

call(*+Goal*)
: Invoke *Goal* as a goal. Note that clauses may have variables as subclauses, which is identical to `call/1`, except when the argument is bound to the cut. See !/0. .C call [2..] +Goal, +ExtraArg1, ...Append *ExtraArg1, ExtraArg2, ...* to the argument list of *Goal* and call the result. For example, `call(plus(1), 2, X)` will call `plus/3`, binding *X* to 3.

  The `call/[2..]` construct is handled by the compiler, which implies that redefinition as a predicate has no effect. The predicates `call/[2-6]` are defined as true predicates, so they can be handled by interpreted code.

apply(*+Term, +List*)
: Append the members of *List* to the arguments of *Term* and call the resulting term. For example: '`apply(plus(1), [2, X])`' will call '`plus(1, 2, X)`'. `Apply/2` is incorporated in the virtual machine of SWI-Prolog. This implies that the overhead can be compared to the overhead of `call/1`.

not *+Goal*
: Succeeds when *Goal* cannot be proven. Retained for compatibility only. New code should use `\+/1`.

once(*+Goal*)
: Defined as:

```
once(Goal) :-
        Goal, !.
```

  `Once/1` can in many cases be replaced with `->/2`. The only difference is how the cut behaves (see !/0). The following two clauses are identical:

```
1) a :- once((b, c)), d.
2) a :- b, c -> d.
```

ignore(*+Goal*)
: Calls *Goal* as `once/1`, but succeeds, regardless of whether *Goal* succeeded or not. Defined as:

```
ignore(Goal) :-
        Goal, !.
ignore(_).
```

3.8 Advanced control-structures: blocks

The predicates of this section form a tightly related set for realising premature successfull or failing exits from a *block*. These predicates are first of all useful for error-recovery. They were primarily implemented for compatibility reasons.

block(*+Label, +Goal, -ExitValue*)
: Execute *Goal* in a *block*. *Label* is the name of the block. *Label* is normally an atom, but the system imposes no type constraints and may even be a variable. *ExitValue* is normally unified to the second argument of an `exit/2` call invoked by *Goal*.

exit(*+Label, +Value*)
Calling `exit/2` makes the innermost *block* which *Label* unifies exit. The block's *ExitValue* is unified with *Value*. If this unification fails the block fails.

fail(*+Label*)
Calling `fail/1` makes the innermost *block* which *Label* unifies fail immediately. Implemented as

```
fail(Label) :- !(Label), fail.
```

!(*+Label*)
Cut all choice-points created since the entry of the innermost *block* which *Label* unifies.

The example below illustrate these constructs to immediately report a syntax-error from a 'deep-down' procedure to the outside world without passing it as an argument 'all-over-the-place'.

```
parse(RuleSet, InputList, Rest) :-
        block(syntaxerror, phrase(RuleSet, InputList, Rest), Error),
        (   var(Error)
        ->  true
        ;   format(´Syntax-error: ~w~n´, Error),
            fail
        ).

integer(N) -->
        digit(D1), !, digits(Ds),
        { name(N, [D1|Ds]) }.

digits([D|R]) --> digit(D), digits(R).
digits(_) --> letter(_), !, { exit(syntaxerror, ´Illegal number´) }.
digits([]) --> [].

digit(D, [D|R], R)  :- between(0´0, 0´9, D).
letter(D, [D|R], R) :- between(0´a, 0´z, D).
```

3.9 Grammar rule interface (phrase)

The predicates below may be called to activate a grammar-rule set:

phrase(*+RuleSet, +InputList*)
Equivalent to `phrase(RuleSet, InputList, [])`.

phrase(*+RuleSet, +InputList, -Rest*)
Activate the rule-set with given name. 'InputList' is the list of tokens to parse, 'Rest' is unified with the remaining tokens if the sentence is parsed correctly.

3.10 Database

SWI-Prolog offers three different database mechanisms. The first one is the common assert/retract mechanism for manipulating the clause database. As facts and clauses asserted using `assert/1` or one of its derivatives become part of the program these predicates compile the term given to them. `Retract/1` and `retractall/1` have to unify a term and therefore have to decompile the program. For these reasons the assert/retract mechanism is expensive. On the other hand, once compiled, queries to the database are faster than querying the recorded database discussed below. See also `dynamic/1`.

The second way of storing arbitrary terms in the database is using the "recorded database". In this database terms are associated with a *key*. A key can be an atom, integer or term. In the last case only the functor and arity determine the key. Each key has a chain of terms associated with it. New terms can be added either at the head or at the tail of this chain. This mechanism is considerably faster than the assert/retract mechanism as terms are not compiled, but just copied into the heap.

The third mechanism is a special purpose one. It associates an integer or atom with a key, which is an atom, integer or term. Each key can only have one atom or integer associated with it. It again is considerably faster than the mechanisms described above, but can only be used to store simple status information like counters, etc.

abolish(*+Functor, +Arity*)
Removes all clauses of a predicate with functor *Functor* and arity *Arity* from the database. Unlike version 1.2, all predicate attributes (dynamic, multifile, index, etc.) are reset to their defaults. Abolishing an imported predicate only removes the import link; the predicate will keep its old definition in its definition module. For 'cleanup' of the dynamic database, one should use `retractall/1` rather than `abolish/2`.

redefine_system_predicate(*+Head*)
This directive may be used both in module `user` and in normal modules to redefine any system predicate. If the system definition is redefined in module `user`, the new definition is the default definition for all sub-modules. Otherwise the redefinition is local to the module. The system definition remains in the module `system`.

Redefining system predicate facilitates the definition of compatibility packages. Use in other context is discouraged.

retract(*+Term*)
When *Term* is an atom or a term it is unified with the first unifying fact or clause in the database. The fact or clause is removed from the database.

retractall(*+Head*)
All facts or clauses in the database for which the *head* unifies with *Head* are removed.[6]

assert(*+Term*)
Assert a fact or clause in the database. *Term* is asserted as the last fact or clause of the corresponding predicate.

asserta(*+Term*)
Equivalent to `assert/1`, but *Term* is asserted as first clause or fact of the predicate.

assertz(*+Term*)
Equivalent to `assert/1`.

[6] Note that the definition has changed since version 2.0.6. See release notes.

assert(*+Term, -Reference*)
Equivalent to `assert/1`, but *Reference* is unified with a unique reference to the asserted clause. This key can later be used with `clause/3` or `erase/1`.

asserta(*+Term, -Reference*)
Equivalent to `assert/2`, but *Term* is asserted as first clause or fact of the predicate.

assertz(*+Term, -Reference*)
Equivalent to `assert/2`.

recorda(*+Key, +Term, -Reference*)
Assert *Term* in the recorded database under key *Key*. *Key* is an integer, atom or term. *Reference* is unified with a unique reference to the record (see `erase/1`).

recorda(*+Key, +Term*)
Equivalent to `recorda(Key, Value, _)`.

recordz(*+Key, +Term, -Reference*)
Equivalent to `recorda/3`, but puts the *Term* at the tail of the terms recorded under *Key*.

recordz(*+Key, +Term*)
Equivalent to `recordz(Key, Value, _)`.

recorded(*+Key, -Value, -Reference*)
Unify *Value* with the first term recorded under *Key* which does unify. *Reference* is unified with the memory location of the record.

recorded(*+Key, -Value*)
Equivalent to `recorded(Key, Value, _)`.

erase(*+Reference*)
Erase a record or clause from the database. *Reference* is an integer returned by `recorda/3` or `recorded/3`, `clause/3`, `assert/2`, `asserta/2` or `assertz/2`. Other integers might conflict with the internal consistency of the system. Erase can only be called once on a record or clause. A second call also might conflict with the internal consistency of the system.[7]

flag(*+Key, -Old, +New*)
Key is an atom, integer or term. Unify *Old* with the old value associated with *Key*. If the key is used for the first time *Old* is unified with the integer 0. Then store the value of *New*, which should be an integer, float, atom or arithmetic expression, under *Key*. `flag/3` is a very fast mechanism for storing simple facts in the database. Example:

```
:- module_transparent succeeds_n_times/2.

succeeds_n_times(Goal, Times) :-
        flag(succeeds_n_times, Old, 0),
        Goal,
        flag(succeeds_n_times, N, N+1),
        fail ; flag(succeeds_n_times, Times, Old).
```

[7] BUG: The system should have a special type for pointers, thus avoiding the Prolog user having to worry about consistency matters. Currently some simple heuristics are used to determine whether a reference is valid.

3.10.1 Indexing databases

By default, SWI-Prolog, as most other implementations, indexes predicates on their first argument. SWI-Prolog allows indexing on other and multiple arguments using the declaration `index/1`.

For advanced database indexing, it defines `hash_term/2`:

hash_term(*+Term, -HashKey*)
If *Term* is a ground term (see `ground/1`), *HashKey* is unified with a positive integer value that may be used as a hash-key to the value. If *Term* is not ground, the predicate succeeds immediately, leaving *HashKey* an unbound variable.

This predicate may be used to build hash-tables as well as to exploit argument-indexing to find complex terms more quickly.

The hash-key does not rely on temporary information like addresses of atoms and may be assumed constant over different invocations of SWI-Prolog.

3.11 Declaring Properties of Predicates

This section describes directives which manipulate attributes of predicate definitions. The functors `dynamic/1`, `multifile/1` and `discontiguous/1` are operators of priority 1150 (see `op/3`), which implies the list of predicates they involve can just be a comma separated list:

```
:- dynamic
        foo/0,
        baz/2.
```

On SWI-Prolog all these directives are just predicates. This implies they can also be called by a program. Do not rely on this feature if you want to maintain portability to other Prolog implementations.

dynamic *+Functor/+Arity, ...*
Informs the interpreter that the definition of the predicate(s) may change during execution (using `assert/1` and/or `retract/1`). Currently `dynamic/1` only stops the interpreter from complaining about undefined predicates (see `unknown/2`). Future releases might prohibit `assert/1` and `retract/1` for not-dynamic declared procedures.

multifile *+Functor/+Arity, ...*
Informs the system that the specified predicate(s) may be defined over more than one file. This stops `consult/1` from redefining a predicate when a new definition is found.

discontiguous *+Functor/+Arity, ...*
Informs the system that the clauses of the specified predicate(s) might not be together in the source file. See also `style_check/1`.

index(*+Head*)
Index the clauses of the predicate with the same name and arity as *Head* on the specified arguments. *Head* is a term of which all arguments are either '1' (denoting 'index this argument') or '0' (denoting 'do not index this argument'). Indexing has no implications for the semantics of a predicate, only on its performance. If indexing is enabled on a predicate a special purpose algorithm is used to select candidate clauses based on the actual arguments of the goal. This

algorithm checks whether indexed arguments might unify in the clause head. Only atoms, integers and functors (e.g. name and arity of a term) are considered. Indexing is very useful for predicates with many clauses representing facts.

Due to the representation technique used at most 4 arguments can be indexed. All indexed arguments should be in the first 32 arguments of the predicate. If more than 4 arguments are specified for indexing only the first 4 will be accepted. Arguments above 32 are ignored for indexing.

By default all predicates with arity ≥ 1 are indexed on their first argument. It is possible to redefine indexing on predicates that already have clauses attached to them. This will initiate a scan through the predicates clause list to update the index summary information stored with each clause.

If—for example—one wants to represents sub-types using a fact list 'sub_type(Sub, Super)' that should be used both to determine sub- and super types one should declare `sub_type/2` as follows:

```
:- index(sub_type(1, 1)).

sub_type(horse, animal).
...
...
```

3.12 Examining the Program

current_atom(*-Atom*)
Successively unifies *Atom* with all atoms known to the system. Note that `current_atom/1` always succeeds if *Atom* is instantiated to an atom.

current_functor(*?Name, ?Arity*)
Successively unifies *Name* with the name and *Arity* with the arity of functors known to the system.

current_flag(*-FlagKey*)
Successively unifies *FlagKey* with all keys used for flags (see `flag/3`).

current_key(*-Key*)
Successively unifies *Key* with all keys used for records (see `recorda/3`, etc.).

current_predicate(*?Name, ?Head*)
Successively unifies *Name* with the name of predicates currently defined and *Head* with the most general term built from *Name* and the arity of the predicate. This predicate succeeds for all predicates defined in the specified module, imported to it, or in one of the modules from which the predicate will be imported if it is called.

predicate_property(*?Head, ?Property*)
Succeeds if *Head* refers to a predicate that has property *Property*. Can be used to test whether a predicate has a certain property, obtain all properties known for *Head*, find all predicates having *property* or even obtaining all information available about the current program. *Property* is one of:

interpreted
Is true if the predicate is defined in Prolog. We return true on this because, although the code is actually compiled, it is completely transparent, just like interpreted code.

built_in
Is true if the predicate is locked as a built-in predicate. This implies it cannot be redefined in its definition module and it can normally not be seen in the tracer.

foreign
Is true if the predicate is defined in the C language.

dynamic
Is true if the predicate is declared dynamic using the `dynamic/1` declaration.

multifile
Is true if the predicate is declared multifile using the `multifile/1` declaration.

undefined
Is true if a procedure definition block for the predicate exists, but there are no clauses in it and it is not declared dynamic. This is true if the predicate occurs in the body of a loaded predicate, an attempt to call it has been made via one of the meta-call predicates or the predicate had a definition in the past. See the library package *check* for example usage.

transparent
Is true if the predicate is declared transparent using the `module_transparent/1` declaration.

exported
Is true if the predicate is in the public list of the context module.

imported_from(*Module*)
Is true if the predicate is imported into the context module from module *Module*.

indexed(*Head*)
Predicate is indexed (see `index/1`) according to *Head*. *Head* is a term whose name and arity are identical to the predicate. The arguments are unified with '1' for indexed arguments, '0' otherwise.

file(*FileName*)
Unify *FileName* with the name of the sourcefile in which the predicate is defined. See also `source_file/2`.

line_count(*LineNumber*)
Unify *LineNumber* with the line number of the first clause of the predicate. Fails if the predicate is not associated with a file. See also `source_file/2`.

dwim_predicate(*+Term, -Dwim*)
'Do What I Mean' ('dwim') support predicate. *Term* is a term, which name and arity are used as a predicate specification. *Dwim* is instantiated with the most general term built from *Name* and the arity of a defined predicate that matches the predicate specified by *Term* in the 'Do What I Mean' sense. See `dwim_match/2` for 'Do What I Mean' string matching. Internal system predicates are not generated, unless `style_check(+dollar)` is active. Backtracking provides all alternative matches.

clause(*?Head, ?Body*)
Succeeds when *Head* can be unified with a clause head and *Body* with the corresponding clause body. Gives alternative clauses on backtracking. For facts *Body* is unified with the atom *true*. Normally `clause/2` is used to find clause definitions for a predicate, but it can also be used to find clause heads for some body template.

clause(*?Head, ?Body, ?Reference*)
Equivalent to `clause/2`, but unifies *Reference* with a unique reference to the clause (see also `assert/2`, `erase/1`). If *Reference* is instantiated to a reference the clause's head and body will be unified with *Head* and *Body*.

nth_clause(*?Pred, ?Index, ?Reference*)
Provides access to the clauses of a predicate using their index number. Counting starts at 1. If *Reference* is specified it unifies *Pred* with the most general term with the same name/arity as the predicate and *Index* with the index-number of the clause. Otherwise the name and arity of *Pred* are used to determine the predicate. If *Index* is provided *Reference* will be unified with the clause reference. If *Index* is unbound, backtracking will yield both the indices and the references of all clauses of the predicate. The following example finds the 2nd clause of `member/2`:

```
?- nth_clause(member(_,_), 2, Ref), clause(Head, Body, Ref).

Ref = 160088
Head = system : member(G575, [G578|G579])
Body = member(G575, G579)
```

clause_property(*+ClauseRef, -Property*)
Queries properties of a clause. *ClauseRef* is a reference to a clause as produced by `clause/3`, `nth_clause/3` or `prolog_frame_attribute/3`. *Property* is one of the following:

file(*FileName*)
Unify *FileName* with the name of the sourcefile in which the clause is defined. Fails if the clause is not associated to a file.

line_count(*LineNumber*)
Unify *LineNumber* with the line number of the clause. Fails if the clause is not associated to a file.

3.13 Input and Output

SWI-Prolog provides two different packages for input and output. One confirms to the Edinburgh standard. This package has a notion of 'current-input' and 'current-output'. The reading and writing predicates implicitly refer to these streams. In the second package, streams are opened explicitly and the resulting handle is used as an argument to the reading and writing predicate to specify the source or destination. Both packages are fully integrated; the user may switch freely between them.

3.13.1 Input and Output Using Implicit Source and Destination

The package for implicit input and output destination is upwards compatible to DEC-10 and C-Prolog. The reading and writing predicates refer to resp. the current input- and output stream. Initially these streams are connected to the terminal. The current output stream is changed using `tell/1` or `append/1`. The current input stream is changed using `see/1`. The streams current value can be obtained using `telling/1` for output- and `seeing/1` for input streams. The table below shows the valid stream specifications. The reserved names `user_input`, `user_output` and `user_error` are for neat integration with the explicit streams.

`user`	This reserved name refers to the terminal
`user_input`	Input from the terminal
`user_output`	Output to the terminal
`stderr or user_error`	Unix error stream (output only)
Atom	Name of a Unix file
`pipe`(*Atom*)	Name of a Unix command

Source and destination are either a file, one of the reserved words above, or a term 'pipe(*Command*)'. In the predicate descriptions below we will call the source/destination argument '*SrcDest*'. Below are some examples of source/destination specifications.

```
?- see(data).          % Start reading from file 'data'.
?- tell(stderr).       % Start writing on the error stream.
?- tell(pipe(lpr)).    % Start writing to the printer.
```

Another example of using the `pipe/1` construct is shown on in figure 3.1. Note that the `pipe/1` construct is not part of Prolog's standard I/O repertoire.

```
getwd(Wd) :-
        seeing(Old), see(pipe(pwd)),
        collect_wd(String),
        seen, see(Old),
        name(Wd, String).

collect_wd([C|R]) :-
        get0(C), C \== -1, !,
        collect_wd(R).
collect_wd([]).
```

Figure 3.1: Get the working directory

see(*+SrcDest*)
Make *SrcDest* the current input stream. If *SrcDest* was already opened for reading with `see/1` and has not been closed since, reading will be resumed. Otherwise *SrcDest* will be opened and the file pointer is positioned at the start of the file.

tell(*+SrcDest*)
Make *SrcDest* the current output stream. If *SrcDest* was already opened for writing with `tell/1` or `append/1` and has not been closed since, writing will be resumed. Otherwise the file is created or—when existing—truncated. See also `append/1`.

append(*+File*)
Similar to `tell/1`, but positions the file pointer at the end of *File* rather than truncating an existing file. The pipe construct is not accepted by this predicate.

seeing(*?SrcDest*)
Unify the name of the current input stream with *SrcDest*.

telling(*?SrcDest*)
Unify the name of the current output stream with *SrcDest*.

seen
Close the current input stream. The new input stream becomes *user*.

told
Close the current output stream. The new output stream becomes *user*.

3.13.2 Explicit Input and Output Streams

The predicates below are part of the Quintus compatible stream-based I/O package. In this package streams are explicitly created using the predicate `open/3`. The resulting stream identifier is then passed as a parameter to the reading and writing predicates to specify the source or destination of the data.

open(*+SrcDest, +Mode, -Stream, +Options*)
ISO compliant predicate to open a stream. *SrcDes* is either an atom, specifying a Unix file, or a term '`pipe`(*Command*)', just like `see/1` and `tell/1`. *Mode* is one of `read`, `write`, `append` or `update`. Mode `append` opens the file for writing, positioning the file-pointer at the end. Mode `update` opens the file for writing, positioning the file-pointer at the beginning of the file without truncating the file. See also `stream_position/3`. *Stream* is either a variable, in which case it is bound to an integer identifying the stream, or an atom, in which case this atom will be the stream identifier. The *Options* list can contain the following options:

- `type(Type)`
  . Using type `text` (default), Prolog will write a text-file in an operating-system compatible way. Using type `binary` the bytes will be read or written without any translation. Note there is no difference between the two on Unix systems.
- `alias(Atom)`
  gives the stream a name. The following two calls are identical, but only the latter is allowed in ISO Prolog.

```
?- open(foo, read, in, []).
?- open(foo, read, S, [alias(in)]).
```

- `eof_action(Action)`
  defines what happens if the end of the input stream is reached. Action `eof_code` makes `get0/1` and friends return -1 and `read/1` and friends return the atom `end_of_file`. Repetitive reading keeps yielding the same result. Action `error` is like `eof_code`, but repetitive reading will raise an error. With action *reset*, Prolog will examine the file again and return more data if the file has grown.

The option `reposition` is not supported in SWI-Prolog. All streams connected to a file may be repositioned.

open(*+SrcDest, +Mode, ?Stream*)
Equivalent to `open/4` with an empty option-list.

open_null_stream(*?Stream*)
Open a stream that produces no output. All counting functions are enabled on such a stream. An attempt to read from a null-stream will immediately signal end-of-file. Similar to Unix `/dev/null`.

close(*+Stream*)
Close the specified stream. If *Stream* is not open an error message is displayed. If the closed stream is the current input or output stream the terminal is made the current input or output.

current_stream(*?File, ?Mode, ?Stream*)
Is true if a stream with file specification *File*, mode *Mode* and stream identifier *Stream* is open. The reserved streams *user* and *user_error* are not generated by this predicate. If a stream has been opened with mode `append` this predicate will generate mode *write*.

stream_position(*+Stream, -Old, +New*)
Unify the position parameters of *Stream* with *Old* and set them to *New*. A position is represented by the following term:

```
'$stream_position'(CharNo, LineNo, LinePos).
```

It is only possible to change the position parameters if the stream is connected to a disk file. If the position is changed, the *CharNo* field determines the new position in the file. The *LineNo* and *LinePos* are copied in the stream administration.

3.13.3 Switching Between Implicit and Explicit I/O

The predicates below can be used for switching between the implicit- and the explicit stream based I/O predicates.

set_input(*+Stream*)
Set the current input stream to become *Stream*. Thus, open(file, read, Stream), set_input(Stream) is equivalent to see(file).

set_output(*+Stream*)
Set the current output stream to become *Stream*.

current_input(*-Stream*)
Get the current input stream. Useful to get access to the status predicates associated with streams.

current_output(*-Stream*)
Get the current output stream.

3.14 Status of Input and Output Streams

wait_for_input(*+ListOfStreams, -ReadyList, +TimeOut*)
Wait for input on one of the streams in *ListOfStreams* and return a list of streams on which input is available in *ReadyList*. `wait_for_input/3` waits for at most *TimeOut* seconds. *Timeout* may be specified as a floating point number to specify fractions of a second. If *Timeout* equals 0, `wait_for_input/3` waits indefinitely. This predicate can be used to implement timeout while reading and to handle input from multiple sources. The following example will wait for input from the user and an explicitly opened second terminal. On return, *Inputs* may hold `user` or *P4* or both.

```
?- open('/dev/ttyp4', read, P4),
   wait_for_input([user, P4], Inputs, 0).
```

character_count(*+Stream, -Count*)
Unify *Count* with the current character index. For input streams this is the number of characters read since the open, for output streams this is the number of characters written. Counting starts at 0.

line_count(*+Stream, -Count*)
Unify *Count* with the number of lines read or written. Counting starts at 1.

line_position(*+Stream, -Count*)
Unify *Count* with the position on the current line. Note that this assumes the position is 0 after the open. Tabs are assumed to be defined on each 8-th character and backspaces are assumed to reduce the count by one, provided it is positive.

fileerrors(*-Old, +New*)
Define error behaviour on errors when opening a file for reading or writing. Valid values are the atoms `on` (default) and `off`. First *Old* is unified with the current value. Then the new value is set to *New*.[8]

3.15 Primitive Character Input and Output

nl
Write a newline character to the current output stream. On Unix systems `nl/0` is equivalent to `put(10)`.

nl(*+Stream*)
Write a newline to *Stream*.

put(*+Char*)
Write *Char* to the current output stream, *Char* is either an integer-expression evaluating to an ASCII value ($0 \leq Char \leq 255$) or an atom of one character.

put(*+Stream, +Char*)
Write *Char* to *Stream*.

tab(*+Amount*)
Writes *Amount* spaces on the current output stream. *Amount* should be an expression that evaluates to a positive integer (see section 3.21).

tab(*+Stream, +Amount*)
Writes *Amount* spaces to *Stream*.

flush
Flush pending output on current output stream. `flush/0` is automatically generated by `read/1` and derivatives if the current input stream is *user* and the cursor is not at the left margin.

flush_output(*+Stream*)
Flush output on the specified stream. The stream must be open for writing.

ttyflush
Flush pending output on stream *user*. See also `flush/0`.

[8] Note that Edinburgh Prolog defines `fileerrors/0` and `nofileerrors/0`. As this does not allow you to switch back to the old mode I think this definition is better.

get0(*-Char*)
Read the current input stream and unify the next character with *Char*. *Char* is unified with -1 on end of file.

get0(*+Stream, -Char*)
Read the next character from *Stream*.

get(*-Char*)
Read the current input stream and unify the next non-blank character with *Char*. *Char* is unified with -1 on end of file.

get(*+Stream, -Char*)
Read the next non-blank character from *Stream*.

peek_byte(*-Char*)
Reads the next input character like `get0/1`, but does not remove it from the input stream. This predicate is ISO compliant.

peek_byte(*+Stream, -Char*)
Reads the next input character like `get0/2`, but does not remove it from the stream. This predicate is ISO compliant.

skip(*+Char*)
Read the input until *Char* or the end of the file is encountered. A subsequent call to `get0/1` will read the first character after *Char*.

skip(*+Stream, +Char*)
Skip input (as `skip/1`) on *Stream*.

get_single_char(*-Char*)
Get a single character from input stream 'user' (regardless of the current input stream). Unlike `get0/1` this predicate does not wait for a return. The character is not echoed to the user's terminal. This predicate is meant for keyboard menu selection etc.. If SWI-Prolog was started with the `-tty` flag this predicate reads an entire line of input and returns the first non-blank character on this line, or the ASCII code of the newline (10) if the entire line consisted of blank characters.

at_end_of_stream
Succeeds after the last character of the current input stream has been read. Also succeeds if there is no valid current input stream.

at_end_of_stream(*+Stream*)
Succeeds after the last character of the named stream is read, or *Stream* is not a valid input stream.

3.16 Term Reading and Writing

This section describes the basic term reading and writing predicates. The predicates `term_to_atom/2` and `atom_to_term/3` provide means for translating atoms and strings to terms. The predicates `format/[1,2]` and `writef/2` provide formatted output.

There are two ways to manipulate the output format. The predicate `print/[1,2]` may be programmed using `portray/1`. The format of floating point numbers may be manipulated using the feature (see `feature/2`) `float_format`.

Reading is sensitive to the feature `character_escapes`, which controls the interpretation of the \ character in quoted atoms and strings.

display(+*Term*)
Write *Term* on the current output stream using standard parenthesised prefix notation (i.e. ignoring operator declarations). Display is normally used to examine the internal representation for terms holding operators.

display(+*Stream*, +*Term*)
Display *Term* on *Stream*.

displayq(+*Term*)
Write *Term* on the current output stream using standard parenthesised prefix notation (i.e. ignoring operator declarations). Atoms that need quotes are quoted. Terms written with this predicate can always be read back, regardless of current operator declarations.

displayq(+*Stream*, +*Term*)
Display *Term* on *Stream*. Equivalent to Quintus `write_canonical/2`.

write(+*Term*)
Write *Term* to the current output, using brackets and operators where appropriate. See `feature/2` for controlling floating point output format.

write(+*Stream*, +*Term*)
Write *Term* to *Stream*.

writeq(+*Term*)
Write *Term* to the current output, using brackets and operators where appropriate. Atoms that need quotes are quoted. Terms written with this predicate can be read back with `read/1` provided the currently active operator declarations are identical.

writeq(+*Stream*, +*Term*)
Write *Term* to *Stream*, inserting quotes.

print(+*Term*)
Prints *Term* on the current output stream similar to `write/1`, but for each (sub)term of *Term* first the dynamic predicate `portray/1` is called. If this predicate succeeds *print* assumes the (sub)term has been written. This allows for user defined term writing.

print(+*Stream*, +*Term*)
Print *Term* to *Stream*.

portray(+*Term*)
A dynamic predicate, which can be defined by the user to change the behaviour of `print/1` on (sub)terms. For each subterm encountered that is not a variable `print/1` first calls `portray/1` using the term as argument. For lists only the list as a whole is given to `portray/1`. If portray succeeds `print/1` assumes the term has been written.

read(-*Term*)
Read the next Prolog term from the current input stream and unify it with *Term*. On a syntax error `read/1` displays an error message, attempts to skip the erroneous term and fails. On reaching end-of-file *Term* is unified with the atom `end_of_file`.

read(+*Stream*, -*Term*)
Read *Term* from *Stream*.

read_clause(-*Term*)
Equivalent to `read/1`, but warns the user for variables only occurring once in a term (singleton variables) which do not start with an underscore if `style_check(singleton)` is active (default). Used to read Prolog source files (see `consult/1`). New code should use `read_term/2` with the option `singletons(warning)`.

read_clause(+*Stream*, -*Term*)
Read a clause from *Stream*. See `read_clause/1`.

read_variables(-*Term*, -*Bindings*)
Similar to `read/1`, but *Bindings* is unified with a list of '*Name* = *Var*' tuples, thus providing access to the actual variable names. New code should use `read_term/2` using the option `variables(X)`.

read_variables(+*Stream*, -*Term*, -*Bindings*)
Read, returning term and bindings from *Stream*. See `read_variables/2`.

read_term(-*Term*, +*Options*)
Read a term from the current input stream and unify the term with *Term*. The reading is controlled by options from the list of *Options*. If this list is empty, the behaviour is the same as for `read/1`. The options are upward compatible to Quintus Prolog. The argument order is according to the ISO standard. Options:

`syntax_errors`(*atom or variable*)
Define the behaviour for when a syntax error occurs. The possible values are:

`fail`
Default behaviour. The error is reported as a warning and the predicate fails.

`quiet`
Quietly fails if a syntax error has occurred.

`Variable`
If no error occurs, the variable is unified with `none`, otherwise *Variable* is unified with a term of the form

```
´$stream_position´(CharNo, LineNo, LinePos):Message
```

This behaviour is a SWI-Prolog extension.

`variable_names`(*Vars*)
Unify *Vars* with a list of '*Name* = *Var*', where *Name* is an atom describing the variable name and *Var* is a variable that shares with the corresponding variable in *Term*.

`singletons`(*Vars*)
As `variable_names`, but only reports the variables occurring only once in the *Term* read. Variables starting with an underscore ('_') are not included in this list.

`term_position`(*Pos*)
Unifies *Pos* with the starting position of the term read. *Pos* if of the same format as use by `stream_position/2`.

`subterm_positions`(*TermPos*)
Describes the detailed layout of the term. The formats for the various types of terms if given below. All positions are character positions. If the input is related to a normal stream, these positions are relative to the start of the input, when reading from the terminal, they are relative to the start of the term.

From-*To*
Used for primitive types (atoms, numbers, variables).

`string_position`(*From*, *To*)
Used to indicate the position of a string enclosed in double quotes (").

`brace_term_position`(*From*, *To*, *Arg*)
Term of the form `{ ... }`, as used in DCG rules. *Arg* describes the argument.

`list_position`(*From*, *To*, *Elms*, *Tail*)
A list. *Elms* describes the positions of the elements. If the list specifies the tail as `|TailTerm`, *Tail* is unified with the term-position of the tail, otherwise with the atom `none`.

`term_position`(*From*, *To*, *FFrom*, *FTo*, *SubPos*)
Used for a compound term not matching one of the above. *FFrom* and *FTo* describe the position of the functor. *SubPos* is a list, each element of which describes the term-position of the corresponding subterm.

read_term(*+Stream, -Term, +Options*)
Read term with options from *Stream*. See `read_term/2`.

read_history(*+Show, +Help, +Special, +Prompt, -Term, -Bindings*)
Similar to `read_variables/2`, but allows for history substitutions. `history_read/6` is used by the top level to read the user's actions. *Show* is the command the user should type to show the saved events. *Help* is the command to get an overview of the capabilities. *Special* is a list of commands that are not saved in the history. *Prompt* is the first prompt given. Continuation prompts for more lines are determined by `prompt/2`. A `%w` in the prompt is substituted by the event number. See section 2.4 for available substitutions.

SWI-Prolog calls `history_read/6` as follows:

```
read_history(h, '!h', [trace], '%w ?- ', Goal, Bindings)
```

history_depth(*-Int*)
Dynamic predicate, normally not defined. The user can define this predicate to set the history depth. It should unify the argument with a positive integer. When not defined 15 is used as the default.

prompt(*-Old, +New*)
Set prompt associated with `read/1` and its derivatives. *Old* is first unified with the current prompt. On success the prompt will be set to *New* if this is an atom. Otherwise an error message is displayed. A prompt is printed if one of the read predicates is called and the cursor is at the left margin. It is also printed whenever a newline is given and the term has not been terminated. Prompts are only printed when the current input stream is *user*.

3.17 Analysing and Constructing Terms

functor(*?Term, ?Functor, ?Arity*)
Succeeds if *Term* is a term with functor *Functor* and arity *Arity*. If *Term* is a variable it is unified with a new term holding only variables. `functor/3` silently fails on instantiation faults[9] If *Term* is an atom or number, *Functor* will be unified with *Term* and arity will be unified with the integer 0 (zero).

[9] In version 1.2 instantiation faults led to error messages. The new version can be used to do type testing without the need to catch illegal instantiations first.

arg(*?Arg, ?Term, ?Value*)
Term should be instantiated to a term, *Arg* to an integer between 1 and the arity of *Term*. *Value* is unified with the *Arg*-th argument of *Term*. *Arg* may also be unbound. In this *Value* will be unified with the successive arguments of the term. On successful unification, *Arg* is unified with the argument number. Backtracking yields alternative solutions.[10]

setarg(*+Arg, +Term, +Value*)
Extra-logical predicate. Assigns the *Arg*-th argument of the compound term *Term* with the given *Value*. The assignment is undone if backtracking brings the state back into a position before the `setarg/3` call.

This predicate may be used for destructive assignment to terms, using them as and extra-logical storage bin.

?Term `=..` *?List*
List is a list which head is the functor of *Term* and the remaining arguments are the arguments of the term. Each of the arguments may be a variable, but not both. This predicate is called 'Univ'. Examples:

```
?- foo(hello, X) =.. List.

List = [foo, hello, X]

?- Term =.. [baz, foo(1)]

Term = baz(foo(1))
```

numbervars(*+Term, +Functor, +Start, -End*)
Unify the free variables of *Term* with a term constructed from the atom *Functor* with one argument. The argument is the number of the variable. Counting starts at *Start*. *End* is unified with the number that should be given to the next variable. Example:

```
?- numbervars(foo(A, B, A), this_is_a_variable, 0, End).

A = this_is_a_variable(0)
B = this_is_a_variable(1)
End = 2
```

In Edinburgh Prolog the second argument is missing. It is fixed to be `'$VAR'`.

free_variables(*+Term, -List*)
Unify *List* with a list of variables, each sharing with a unique variable of *Term*. For example:

```
?- free_variables(a(X, b(Y, X), Z), L).

L = [G367, G366, G371]
X = G367
Y = G366
Z = G371
```

[10] The instantiation pattern (-, +, ?) is an extension to 'standard' Prolog.

copy_term(*+In, -Out*)
Make a copy of term *In* and unify the result with *Out*. Ground parts of *In* are shared by *Out*. Provided *In* and *Out* have no sharing variables before this call they will have no sharing variables afterwards. `copy_term/2` is semantically equivalent to:

```
copy_term(In, Out) :-
        recorda(copy_key, In, Ref),
        recorded(copy_key, Out, Ref),
        erase(Ref).
```

3.18 Analysing and Constructing Atoms

These predicates convert between Prolog constants and lists of ASCII values. The predicates `atom_chars/2`, `number_chars/2` and `number/2` behave the same when converting from a constant to a list of ASCII values. When converting the other way around, `atom_chars/2` will generate an atom, number_chars will generate a number or fail and `name/2` will return a number if possible and an atom otherwise.

atom_chars(*?Atom, ?String*)
Convert between an atom and a list of ASCII values. If *Atom* is instantiated, if will be translated into a list of ASCII values and the result is unified with *String*. If *Atom* is unbound and *String* is a list of ASCII values, it will *Atom* will be unified with an atom constructed from this list.

atom_char(*?Atom, ?ASCII*)
Convert between character and ASCII value for a single character.

number_chars(*?Number, ?String*)
Similar to `atom_chars/2`, but converts between a number and its representation as a list of ASCII values. Fails silently if *Atom* is unbound and *String* does not describe a number.

name(*?AtomOrInt, ?String*)
String is a list of ASCII values describing *Atom*. Each of the arguments may be a variable, but not both. When *String* is bound to an ASCII value list describing an integer and *Atom* is a variable *Atom* will be unified with the integer value described by *String* (e.g. '`name(N, "300"), 400 is N + 100`' succeeds).

int_to_atom(*+Int, +Base, -Atom*)
Convert *Int* to an ASCII representation using base *Base* and unify the result with *Atom*. If $Base \neq 10$ the base will be prepended to *Atom*. $Base = 0$ will try to interpret *Int* as an ASCII value and return `0'c`. Otherwise $2 \leq Base \leq 36$. Some examples are given below.

$$\begin{array}{lcl} \text{int_to_atom}(45,\ 2,\ \text{A}) & \longrightarrow & A = 2'101101 \\ \text{int_to_atom}(97,\ 0,\ \text{A}) & \longrightarrow & A = 0'a \\ \text{int_to_atom}(56,\ 10,\ \text{A}) & \longrightarrow & A = 56 \end{array}$$

int_to_atom(*+Int, -Atom*)
Equivalent to `int_to_atom(Int, 10, Atom)`.

term_to_atom(*?Term, ?Atom*)
Succeeds if *Atom* describes a term that unifies with *Term*. When *Atom* is instantiated *Atom* is converted and then unified with *Term*. Otherwise *Term* is "written" on *Atom* using `write/1`.

atom_to_term(*+Atom, -Term, -Bindings*)
Use *Atom* as input to `read_variables/2` and return the read term in *Term* and the variable bindings in *Bindings*. *Bindings* is a list of *Name* = *Var* couples, thus providing access to the actual variable names. See also `read_variables/2`.

concat(*?Atom1, ?Atom2, ?Atom3*)
Atom3 forms the concatenation of *Atom1* and *Atom2*. At least two of the arguments must be instantiated to atoms, integers or floating point numbers.

concat_atom(*+List, -Atom*)
List is a list of atoms, integers or floating point numbers. Succeeds if *Atom* can be unified with the concatenated elements of *List*. If *List* has exactly 2 elements it is equivalent to `concat/3`, allowing for variables in the list.

concat_atom(*+List, +Separator, -Atom*)
Creates an atom just like `concat_atom/2`, but inserts *Separator* between each pair of atoms. For example:

```
?- concat_atom([gnu, gnat], ´, ´, A).

A = ´gnu, gnat´
```

atom_length(*+Atom, -Length*)
Succeeds if *Atom* is an atom of *Length* characters long. This predicate also works for integers and floats, expressing the number of characters output when given to `write/1`.

atom_prefix(*+Atom, +Prefix*)
Succeeds if *Atom* starts with the characters from *Prefix*. Its behaviour is equivalent to `?- concat(`*Prefix*`, _,` *Atom*`)`, but avoids the construction of an atom for the 'remainder'.

3.19 Representing Text in Strings

SWI-Prolog supports the data type *string*. Strings are a time and space efficient mechanism to handle text in Prolog. Atoms are under some circumstances not suitable because garbage collection on them is next to impossible (Although it is possible: BIM_prolog does it). Representing text as a list of ASCII values is, from the logical point of view, the cleanest solution. It however has two drawbacks: 1) they cannot be distinguished from a list of (small) integers; and 2) they consume (in SWI-Prolog) 12 bytes for each character stored.

Within strings each character only requires 1 byte storage. Strings live on the global stack and their storage is thus reclaimed on backtracking. Garbage collection can easily deal with strings.

The ISO standard proposes `"..."` is transformed into a string object by `read/1` and derivatives. This poses problems as in the old convention `"..."` is transformed into a list of ASCII characters. For this reason the style check option '`string`' is available (see `style_check/2`).

The set of predicates associated with strings is incomplete and tentative. Names and definitions might change in the future to confirm to the emerging standard.

string_to_atom(*?String, ?Atom*)
Logical conversion between a string and an atom. At least one of the two arguments must be instantiated. *Atom* can also be an integer or floating point number.

string_to_list(*?String, ?List*)
Logical conversion between a string and a list of ASCII characters. At least one of the two arguments must be instantiated.

string_length(*+String, -Length*)
Unify *Length* with the number of characters in *String*. This predicate is functionally equivalent to `atom_length/2` and also accepts atoms, integers and floats as its first argument.

string_concat(*?String1, ?String2, ?String3*)
Similar to `concat/3`, but the unbound argument will be unified with a string object rather than an atom. Also, if both *String1* and *String2* are unbound and *String3* is bound to text, it breaks *String3*, unifying the start with *String1* and the end with *String2* as append does with lists. Note that this is not particularly fast on long strings as for each redo the system has to create two entirely new strings, while the list equivalent only creates a single new list-cell and moves some pointers around.

substring(*+String, +Start, +Length, -Sub*)
Create a substring of *String* that starts at character *Start* (1 base) and has *Length* characters. Unify this substring with *Sub*.[11]

3.20 Operators

op(*+Precedence, +Type, +Name*)
Declare *Name* to be an operator of type *Type* with precedence *Precedence*. *Name* can also be a list of names, in which case all elements of the list are declared to be identical operators. *Precedence* is an integer between 0 and 1200. Precedence 0 removes the declaration. *Type* is one of: `xf`, `yf`, `xfx`, `xfy`, `yfx`, `yfy`, `fy` or `fx`. The '`f`' indicates the position of the functor, while `x` and `y` indicate the position of the arguments. '`y`' should be interpreted as "on this position a term with precedence lower or equal to the precedence of the functor should occur". For '`x`' the precedence of the argument must be strictly lower. The precedence of a term is 0, unless its principal functor is an operator, in which case the precedence is the precedence of this operator. A term enclosed in brackets (`(...)`) has precedence 0.

The predefined operators are shown in table 3.1. Note that all operators can be redefined by the user.

current_op(*?Precedence, ?Type, ?Name*)
Succeeds when *Name* is currently defined as an operator of type *Type* with precedence *Precedence*. See also `op/3`.

3.21 Arithmetic

Arithmetic can be divided into some special purpose integer predicates and a series of general predicates for floating point and integer arithmetic as appropriate. The integer predicates are as "logical" as possible. Their usage is recommended whenever applicable, resulting in faster and more "logical" programs.

The general arithmetic predicates are optionally compiled now (see `please/3` and the `-O` command line option). Compiled arithmetic reduces global stack requirements and improves performance. Unfortunately compiled arithmetic cannot be traced, which is why it is optional.

[11] Future versions probably will provide a more logical variant of this predicate.

1200	xfx	`-->`, `:-`
1200	fx	`:-`, `?-`
1150	fx	`dynamic`, `multifile`, `module_transparent`, `discontiguous`, `volatile`, `initialization`
1100	xfy	`;`, `|`
1050	xfy	`->`
1000	xfy	`,`
954	xfy	`\\`
900	fy	`\+`, `not`
900	fx	`~`
700	xfx	`<`, `=`, `=..`, `=@=`, `=:=`, `=<`, `==`, `=\=`, `>`, `>=`, `@<`, `@=<`, `@>`, `@>=`, `\=`, `\==`, `is`
600	xfy	`:`
500	yfx	`+`, `-`, `/\`, `\/`, `xor`
500	fx	`+`, `-`, `?`, `\`
400	yfx	`*`, `/`, `//`, `<<`, `>>`, `mod`, `rem`
200	xfx	`**`
200	xfy	`^`

Table 3.1: System operators

The general arithmetic predicates all handle *expressions*. An expression is either a simple number or a *function*. The arguments of a function are expressions. The functions are described in section 3.22.

between(*+Low, +High, ?Value*)
Low and *High* are integers, $High \geq Low$. If *Value* is an integer, $Low \leq Value \leq High$. When *Value* is a variable it is successively bound to all integers between *Low* and *High*.

succ(*?Int1, ?Int2*)
Succeeds if $Int2 = Int1 + 1$. At least one of the arguments must be instantiated to an integer.

plus(*?Int1, ?Int2, ?Int3*)
Succeeds if $Int3 = Int1 + Int2$. At least two of the three arguments must be instantiated to integers.

+Expr1 `>` *+Expr2*
Succeeds when expression *Expr1* evaluates to a larger number than *Expr2*.

+Expr1 `<` *+Expr2*
Succeeds when expression *Expr1* evaluates to a smaller number than *Expr2*.

+Expr1 `=<` *+Expr2*
Succeeds when expression *Expr1* evaluates to a smaller or equal number to *Expr2*.

+Expr1 `>=` *+Expr2*
Succeeds when expression *Expr1* evaluates to a larger or equal number to *Expr2*.

+Expr1 `=\=` *+Expr2*
Succeeds when expression *Expr1* evaluates to a number non-equal to *Expr2*.

+Expr1 `=:=` *+Expr2*
Succeeds when expression *Expr1* evaluates to a number equal to *Expr2*.

-Number **is** *+Expr*
Succeeds when *Number* has successfully been unified with the number *Expr* evaluates to. If *Expr* evaluates to a float that can be represented using an integer (i.e. the value is integer and within the range that can be described by Prolog's integer representation), *Expr* is unified with the integer value.

Note that normally, `is/2` will be used with unbound left operand. If equality is to be tested, `=:=/2` should be used. For example:

`?- 1.0 is sin(pi/2).`	Fails!. `sin(pi/2)` evaluates to 1.0, but `is/2` will represent this as the integer 1, after which unify will fail.
`?- 1.0 is float(sin(pi/2)).`	Succeeds, as the `float/1` function forces the result to be float.
`?- 1.0 =:= sin(pi/2).`	Succeeds as expected.

3.22 Arithmetic Functions

Arithmetic functions are terms which are evaluated by the arithmetic predicates described above. SWI-Prolog tries to hide the difference between integer arithmetic and floating point arithmetic from the Prolog user. Arithmetic is done as integer arithmetic as long as possible and converted to floating point arithmetic whenever one of the arguments or the combination of them requires it. If a function returns a floating point value which is whole it is automatically transformed into an integer. There are three types of arguments to functions:

Expr	Arbitrary expression, returning either a floating point value or an integer.
IntExpr	Arbitrary expression that should evaluate into an integer.
Int	An integer.

In case integer addition, subtraction and multiplication would lead to an integer overflow the operands are automatically converted to floating point numbers. The floating point functions (`sin/1`, `exp/1`, etc.) form a direct interface to the corresponding C library functions used to compile SWI-Prolog. Please refer to the C library documentation for details on precision, error handling, etc.

- +Expr
Result $= -Expr$

+Expr1 `+` *+Expr2*
Result $= Expr1 + Expr2$

+Expr1 `-` *+Expr2*
Result $= Expr1 - Expr2$

+Expr1 `*` *+Expr2*
Result $= Expr1 \times Expr2$

+Expr1 / +Expr2
Result $= \frac{Expr1}{Expr2}$

+IntExpr1 **mod** *+IntExpr2*
Result $=$ *Expr1* mod *Expr2* (remainder of division).

+IntExpr1 **rem** *+IntExpr2*
Result $=$ *Expr1* rem *Expr2* (remainder of division).

+IntExpr1 // +IntExpr2
Result $=$ *Expr1* div *Expr2* (integer division).

abs(*+Expr*)
Evaluate *Expr* and return the absolute value of it.

sign(*+Expr*)
Evaluate to -1 if $Expr < 0$, 1 if $Expr > 0$ and 0 if $Expr = 0$.

max(*+Expr1, +Expr2*)
Evaluates to the largest of both *Expr1* and *Expr2*.

min(*+Expr1, +Expr2*)
Evaluates to the smallest of both *Expr1* and *Expr2*.

.(*+Int*, [])
A list of one element evaluates to the element. This implies `"a"` evaluates to the ASCII value of the letter `a` (97). This option is available for compatibility only. It will not work if '`style_check(+string)`' is active as `"a"` will then be transformed into a string object. The recommended way to specify the ASCII value of the letter 'a' is `0'a`.

random(*+Int*)
Evaluates to a random integer i for which $0 \leq i < Int$. The seed of this random generator is determined by the system clock when SWI-Prolog was started.

round(*+Expr*)
Evaluates *Expr* and rounds the result to the nearest integer.

integer(*+Expr*)
Same as `round/1` (backward compatibility).

float(*+Expr*)
Translate the result to a floating point number. Normally, Prolog will use integers whenever possible. When used around the 2nd argument of `is/2`, the result will be returned as a floating point number. In other contexts, the operation has no effect.

float_fractional_part(*+Expr*)
Fractional part of a floating-point number. Negative if *Expr* is negative, 0 if *Expr* is integer.

float_integer_part(*+Expr*)
Integer part of floating-point number. Negative if *Expr* is negative, *Expr* if *Expr* is integer.

truncate(*+Expr*)
Truncate *Expr* to an integer. Same as `float_integer_part/1`.

floor(*+Expr*)
Evaluates *Expr* and returns the largest integer smaller or equal to the result of the evaluation.

ceiling(*+Expr*)
Evaluates *Expr* and returns the smallest integer larger or equal to the result of the evaluation.

ceil(*+Expr*)
Same as `ceiling/1` (backward compatibility).

+IntExpr >> *+IntExpr*
Bitwise shift *IntExpr1* by *IntExpr2* bits to the right. Note that integers are only 27 bits.

+IntExpr << *+IntExpr*
Bitwise shift *IntExpr1* by *IntExpr2* bits to the left.

+IntExpr \/ *+IntExpr*
Bitwise 'or' *IntExpr1* and *IntExpr2*.

+IntExpr /\ *+IntExpr*
Bitwise 'and' *IntExpr1* and *IntExpr2*.

+IntExpr **xor** *+IntExpr*
Bitwise 'exclusive or' *IntExpr1* and *IntExpr2*.

\ *+IntExpr*
Bitwise negation.

sqrt(*+Expr*)
Result = $\sqrt{Expr}$

sin(*+Expr*)
Result = sin *Expr*. *Expr* is the angle in radians.

cos(*+Expr*)
Result = cos *Expr*. *Expr* is the angle in radians.

tan(*+Expr*)
Result = tan *Expr*. *Expr* is the angle in radians.

asin(*+Expr*)
Result = arcsin *Expr*. *Result* is the angle in radians.

acos(*+Expr*)
Result = arccos *Expr*. *Result* is the angle in radians.

atan(*+Expr*)
Result = arctan *Expr*. *Result* is the angle in radians.

atan(*+YExpr, +XExpr*)
Result = $\arctan \frac{YExpr}{XExpr}$. *Result* is the angle in radians. The return value is in the range $[-\pi \ldots \pi]$. Used to convert between rectangular and polar coordinate system.

log(*+Expr*)
Result = ln *Expr*

log10(*+Expr*)
Result = lg *Expr*

exp(*+Expr*)
Result = e^{Expr}

+Expr1 ** *+Expr2*
Result = $Expr1^{Expr2}$

+Expr1 ^ *+Expr2*
Same as **/2. (backward compatibility).

pi
Evaluates to the mathematical constant π (3.141593).

e
Evaluates to the mathematical constant e (2.718282).

cputime
Evaluates to a floating point number expressing the CPU time (in seconds) used by Prolog up till now. See also `statistics/2` and `time/1`.

3.23 Adding Arithmetic Functions

Prolog predicates can be given the role of arithmetic function. The last argument is used to return the result, the arguments before the last are the inputs. Arithmetic functions are added using the predicate `arithmetic_function/1`, which takes the head as its argument. Arithmetic functions are module sensitive, that is they are only visible from the module in which the function is defined and declared. Global arithmetic functions should be defined and registered from module `user`. Global definitions can be overruled locally in modules. The builtin functions described above can be redefined as well.

arithmetic_function(*+Head*)
Register a Prolog predicate as an arithmetic function (see `is/2`, `>/2`, etc.). The Prolog predicate should have one more argument than specified by *Head*, which it either a term *Name/Arity*, an atom or a complex term. This last argument is an unbound variable at call time and should be instantiated to an integer or floating point number. The other arguments are the parameters. This predicate is module sensitive and will declare the arithmetic function only for the context module, unless declared from module `user`. Example:

```
1 ?- [user].
:- arithmetic_function(mean/2).

mean(A, B, C) :-
        C is (A+B)/2.
user compiled, 0.07 sec, 440 bytes.

Yes
2 ?- A is mean(4, 5).

A = 4.500000
```

current_arithmetic_function(*?Head*)
Successively unifies all arithmetic functions that are visible from the context module with *Head*.

3.24 List Manipulation

is_list(*+Term*)
Succeeds if *Term* is bound to the empty list (`[]`) or a term with functor '.' and arity 2.

proper_list(*+Term*)
Equivalent to `is_list/1`, but also requires the tail of the list to be a list (recursively). Examples:

```
is_list([x|A])          % true
proper_list([x|A])      % false
```

append(*?List1, ?List2, ?List3*)
Succeeds when *List3* unifies with the concatenation of *List1* and *List2*. The predicate can be used with any instantiation pattern (even three variables).

member(*?Elem, ?List*)
Succeeds when *Elem* can be unified with one of the members of *List*. The predicate can be used with any instantiation pattern.

memberchk(*?Elem, +List*)
Equivalent to `member/2`, but leaves no choice point.

delete(*+List1, ?Elem, ?List2*)
Delete all members of *List1* that simultaneously unify with *Elem* and unify the result with *List2*.

select(*?List1, ?Elem, ?List2*)
Select an element of *List1* that unifies with *Elem*. *List2* is unified with the list remaining from *List1* after deleting the selected element. Normally used with the instantiation pattern *+List1, -Elem, -List2*, but can also be used to insert an element in a list using *-List1, +Elem, +List2*.

nth0(*?Index, ?List, ?Elem*)
Succeeds when the *Index*-th element of *List* unifies with *Elem*. Counting starts at 0.

nth1(*?Index, ?List, ?Elem*)
Succeeds when the *Index*-th element of *List* unifies with *Elem*. Counting starts at 1.

last(*?Elem, ?List*)
Succeeds if *Elem* unifies with the last element of *List*.

reverse(*+List1, -List2*)
Reverse the order of the elements in *List1* and unify the result with the elements of *List2*.

flatten(*+List1, -List2*)
Transform *List1*, possibly holding lists as elements into a 'flat' list by replacing each list with its elements (recursively). Unify the resulting flat list with *List2*. Example:

```
?- flatten([a, [b, [c, d], e]], X).

X = [a, b, c, d, e]
```

length(*?List, ?Int*)
Succeeds if *Int* represents the number of elements of list *List*. Can be used to create a list holding only variables.

merge(*+List1, +List2, -List3*)
List1 and *List2* are lists, sorted to the standard order of terms (see section 3.5). *List3* will be unified with an ordered list holding both the elements of *List1* and *List2*. Duplicates are **not** removed.

3.25 Set Manipulation

is_set(*+Set*)
Succeeds if *Set* is a proper list (see `proper_list/1`) without duplicates.

list_to_set(*+List, -Set*)
Succeeds if *Set* holds the same elements as *List* in the same order, but has no duplicates. See also `sort/2`.

intersection(*+Set1, +Set2, -Set3*)
Succeeds if *Set3* unifies with the intersection of *Set1* and *Set2*. *Set1* and *Set2* are lists without duplicates. They need not be ordered.

subtract(*+Set, +Delete, -Result*)
Delete all elements of set 'Delete' from 'Set' and unify the resulting set with 'Result'.

union(*+Set1, +Set2, -Set3*)
Succeeds if *Set3* unifies with the union of *Set1* and *Set2*. *Set1* and *Set2* are lists without duplicates. They need not be ordered.

subset(*+Subset, +Set*)
Succeeds if all elements of *Subset* are elements of *Set* as well.

merge_set(*+Set1, +Set2, -Set3*)
Set1 and *Set2* are lists without duplicates, sorted to the standard order of terms. *Set3* is unified with an ordered list without duplicates holding the union of the elements of *Set1* and *Set2*.

3.26 Sorting Lists

sort(*+List, -Sorted*)
Succeeds if *Sorted* can be unified with a list holding the elements of *List*, sorted to the standard order of terms (see section 3.5). Duplicates are removed.

msort(*+List, -Sorted*)
Equivalent to `sort/2`, but does not remove duplicates.

keysort(*+List, -Sorted*)
List is a list of `Key-Value` pairs (e.g. terms of the functor '-' with arity 2). `keysort/2` sorts *List* like `msort/2`, but only compares the keys. Can be used to sort terms not on standard order, but on any criterion that can be expressed on a multi-dimensional scale. Sorting on more than one criterion can be done using terms as keys, putting the first criterion as argument 1, the second as argument 2, etc.

predsort(*+Pred, +List, -Sorted*)
Sorts similar to `msort/2`, but determines the order of two terms by applying *Pred* to pairs of elements from *List* (see `apply/2`). The predicate should succeed if the first element should be before the second.

3.27 Finding all Solutions to a Goal

findall(*+Var, +Goal, -Bag*)
Creates a list of the instantiations *Var* gets successively on backtracking over *Goal* and unifies

the result with *Bag*. Succeeds with an empty list if *Goal* has no solutions. `findall/3` is equivalent to `bagof/3` with all free variables bound with the existence operator (`^`), except that `bagof/3` fails when goal has no solutions.

bagof(*+Var, +Goal, -Bag*)
Unify *Bag* with the alternatives of *Var*, if *Goal* has free variables besides the one sharing with *Var* bagof will backtrack over the alternatives of these free variables, unifying *Bag* with the corresponding alternatives of *Var*. The construct `Var^Goal` tells bagof not to bind *Var* in *Goal*. `bagof/3` fails if *Goal* has no solutions.

The example below illustrates `bagof/3` and the `^` operator. The variable bindings are printed together on one line to save paper.

```
2 ?- listing(foo).

foo(a, b, c).
foo(a, b, d).
foo(b, c, e).
foo(b, c, f).
foo(c, c, g).

Yes
3 ?- bagof(C, foo(A, B, C), Cs).

A = a, B = b, C = G308, Cs = [c, d] ;
A = b, B = c, C = G308, Cs = [e, f] ;
A = c, B = c, C = G308, Cs = [g] ;

No
4 ?- bagof(C, A^foo(A, B, C), Cs).

A = G324, B = b, C = G326, Cs = [c, d] ;
A = G324, B = c, C = G326, Cs = [e, f, g] ;

No
5 ?-
```

setof(*+Var, +Goal, -Set*)
Equivalent to `bagof/3`, but sorts the result using `sort/2` to get a sorted list of alternatives without duplicates.

3.28 Invoking Predicates on all Members of a List

All the predicates in this section call a predicate on all members of a list or until the predicate called fails. The predicate is called via `apply/2`, which implies common arguments can be put in front of the arguments obtained from the list(s). For example:

```
?- maplist(plus(1), [0, 1, 2], X).

X = [1, 2, 3]
```


we will phrase this as "*Predicate* is applied on ..."

checklist(*+Pred, +List*)
Pred is applied successively on each element of *List* until the end of the list or *Pred* fails. In the latter case the `checklist/2` fails.

maplist(*+Pred, ?List1, ?List2*)
Apply *Pred* on all successive pairs of elements from *List1* and *List2*. Fails if *Pred* can not be applied to a pair. See the example above.

sublist(*+Pred, +List1, ?List2*)
Unify *List2* with a list of all elements of *List1* to which *Pred* applies.

3.29 Forall

forall(*+Cond, +Action*)
For all alternative bindings of *Cond* *Action* can be proven. The example verifies that all arithmetic statements in the list *L* are correct. It does not say which is wrong if one proves wrong.

```
?- forall(member(Result = Formula, [2 = 1 + 1, 4 = 2 * 2]),
                  Result =:= Formula).
```

3.30 Formatted Write

The current version of SWI-Prolog provides two formatted write predicates. The first is `writef/[1,2]`, which is compatible with Edinburgh C-Prolog. The second is `format/[1,2]`, which is compatible with Quintus Prolog. We hope the Prolog community will once define a standard formatted write predicate. If you want performance use `format/[1,2]` as this predicate is defined in C. Otherwise compatibility reasons might tell you which predicate to use.

3.30.1 Writef

write_ln(*+Term*)
Equivalent to `write(Term), nl.`

writef(*+Atom*)
Equivalent to `writef(Atom, []).`

writef(*+Format, +Arguments*)
Formatted write. *Format* is an atom whose characters will be printed. *Format* may contain certain special character sequences which specify certain formatting and substitution actions. *Arguments* then provides all the terms required to be output.

Escape sequences to generate a single special character:

\n	<NL> is output
\l	<LF> is output
\r	<CR> is output
\t	<TAB> is output
\\	The character '\' is output
\%	The character '%' is output
\nnn	where nnn is an integer (1-3 digits) the character with ASCII code nnn is output (NB : nnn is read as DECIMAL)

Note that \l, \nnn and \\ are interpreted differently when character-escapes are in effect. See section 2.12.1.

Escape sequences to include arguments from *Arguments*. Each time a % escape sequence is found in *Format* the next argument from *Arguments* is formatted according to the specification.

%t	print/1 the next item (mnemonic: term)
%w	write/1 the next item
%q	writeq/1 the next item
%d	display/1 the next item
%p	print/1 the next item (identical to %t)
%n	put the next item as a character (i.e. it is an ASCII value)
%r	write the next item N times where N is the second item (an integer)
%s	write the next item as a String (so it must be a list of characters)
%f	perform a ttyflush/0 (no items used)
%Nc	write the next item Centered in N columns.
%Nl	write the next item Left justified in N columns.
%Nr	write the next item Right justified in N columns. N is a decimal number with at least one digit. The item must be an atom, integer, float or string.

swritef(-*String*, +*Format*, +*Arguments*)
Equivalent to writef/3, but "writes" the result on *String* instead of the current output stream. Example:

```
?- swritef(S, '%15L%w', ['Hello', 'World']).

S = "Hello          World"
```

swritef(-*String*, +*Format*)
Equivalent to swritef(String, Format, []).

3.30.2 Format

format(+*Format*)
Defined as 'format(Format) :- format(Format, []).'

format(+*Format*, +*Arguments*)
Format is an atom, list of ASCII values, or a Prolog string. *Arguments* provides the arguments required by the format specification. If only one argument is required and this is not a list of

ASCII values the argument need not be put in a list. Otherwise the arguments are put in a list.

Special sequences start with the tilde (~), followed by an optional numeric argument, followed by a character describing the action to be undertaken. A numeric argument is either a sequence of digits, representing a positive decimal number, a sequence `<character>, representing the ASCII value of the character (only useful for ~t) or a asterisk (*), in when the numeric argument is taken from the next argument of the argument list, which should be a positive integer. Actions are:

~ Output the tilde itself.

a Output the next argument, which should be an atom. This option is equivalent to **w**. Compatibility reasons only.

c Output the next argument as an ASCII value. This argument should be an integer in the range [0, ..., 255] (including 0 and 255).

d Output next argument as a decimal number. It should be an integer. If a numeric argument is specified a dot is inserted *argument* positions from the right (useful for doing fixed point arithmetic with integers, such as handling amounts of money).

D Same as **d**, but makes large values easier to read by inserting a comma every three digits left to the dot or right.

e Output next argument as a floating point number in exponential notation. The numeric argument specifies the precision. Default is 6 digits. Exact representation depends on the C library function printf(). This function is invoked with the format %.<precision>e.

E Equivalent to **e**, but outputs a capital E to indicate the exponent.

f Floating point in non-exponential notation. See C library function printf().

g Floating point in **e** or **f** notation, whichever is shorter.

G Floating point in **E** or **f** notation, whichever is shorter.

i Ignore next argument of the argument list. Produces no output.

k Give the next argument to displayq/1 (canonical write).

n Output a newline character.

N Only output a newline if the last character output on this stream was not a newline. Not properly implemented yet.

p Give the next argument to print/1.

q Give the next argument to writeq/1.

r Print integer in radix the numeric argument notation. Thus ~16r prints its argument hexadecimal. The argument should be in the range [2, ..., 36]. Lower case letters are used for digits above 9.

R Same as **r**, but uses upper case letters for digits above 9.

s Output a string of ASCII characters from the next argument.

t All remaining space between 2 tabs tops is distributed equally over ~t statements between the tabs tops. This space is padded with spaces by default. If an argument is supplied this is taken to be the ASCII value of the character used for padding. This can be used to do left or right alignment, centering, distributing, etc. See also ~| and ~+ to set tab stops. A tabs top is assumed at the start of each line.

| Set a tabs top on the current position. If an argument is supplied set a tabs top on the position of that argument. This will cause all ~t's to be distributed between the previous and this tabs top.

+ Set a tabs top relative to the current position. Further the same as `~|`.

w Give the next argument to `write/1`.

Example:

```
simple_statistics :-
    <obtain statistics>         % left to the user
    format(´~tStatistics~t~72|~n~n´),
    format(´Runtime: ~`.t ~2f~34|  Inferences: ~`.t ~D~72|~n´,
                                        [RunT, Inf]),
    ....
```

Will output

```
                              Statistics

Runtime: .................. 3.45  Inferences: .......... 60,345
```

sformat(*-String, +Format, +Arguments*)
Equivalent to `format/3`, but "writes" the result on *String* instead of the current output stream. Example:

```
?- sformat(S, ´~w~t~15|~w´, [´Hello´, ´World´]).

S = "Hello          World"
```

sformat(*-String, +Format*)
Equivalent to '`sformat(String, Format, []).`'

3.30.3 Programming Format

format_predicate(*+Char, +Head*)
If a sequence `~c` (tilde, followed by some character) is found, the format derivatives will first check whether the user has defined a predicate to handle the format. If not, the built in formatting rules described above are used. *Char* is either an ASCII value, or a one character atom, specifying the letter to be (re)defined. *Head* is a term, whose name and arity are used to determine the predicate to call for the redefined formatting character. The first argument to the predicate is the numeric argument of the format command, or the atom `default` if no argument is specified. The remaining arguments are filled from the argument list. The example below redefines `~n` to produce *Arg* times return followed by linefeed (so a (Grr.) DOS machine is happy with the output).

```
:- format_predicate(n, dos_newline(_Arg)).

dos_newline(Arg) :-
        between(1, Ar, _), put(13), put(10), fail ; true.
```


3.31 Terminal Control

The following predicates form a simple access mechanism to the Unix termcap library to provide terminal independent I/O for screen terminals. The library package `tty` builds on top of these predicates.

tty_get_capability(*+Name, +Type, -Result*)
Get the capability named *Name* from the termcap library. See termcap(5) for the capability names. *Type* specifies the type of the expected result, and is one of `string`, `number` or `bool`. String results are returned as an atom, number result as an integer and bool results as the atom `on` or `off`. If an option cannot be found this predicate fails silently. The results are only computed once. Successive queries on the same capability are fast.

tty_goto(*+X, +Y*)
Goto position *(X, Y)* on the screen. Note that the predicates `line_count/2` and `line_position/2` will not have a well defined behaviour while using this predicate.

tty_put(*+Atom, +Lines*)
Put an atom via the termcap library function tputs(). This function decodes padding information in the strings returned by `tty_get_capability/3` and should be used to output these strings. *Lines* is the number of lines affected by the operation, or 1 if not applicable (as in almost all cases).

set_tty(*-OldStream, +NewStream*)
Set the output stream, used by `tty_put/2` and `tty_goto/2` to a specific stream. Default is user_output.

3.32 Operating System Interaction

shell(*+Command, -Status*)
Execute *Command* on the operating system. *Command* is given to the Bourne shell (/bin/sh). *Status* is unified with the exit status of the command.

On *Win32* systems, `shell/[1,2]` executes the command using the CreateProcess() API and waits for the command to terminate. This does not work under Win32s (Windows 3.1), which does not support this call. If the command ends with a `&` sign, the command is handed to the WinExec() API, which does not wait for the new task to terminate and also works for Win32s. See also `win_exec/2`.

shell(*+Command*)
Equivalent to '`shell(Command, 0)`'.

shell
Start an interactive Unix shell. Default is `/bin/sh`, the environment variable `SHELL` overrides this default. Not available for Win32 platforms.

win_exec(*+Command, +Show*)
Win32 systems only. Spawns a Windows task without waiting for its completion. *Show* is either `iconic` or `normal` and dictates the initial status of the window. The `iconic` option is notably handy to start (DDE) servers.

getenv(*+Name, -Value*)
Get Unix environment variable (see csh(1) and sh(1)). Fails if the variable does not exist.

setenv(*+Name, +Value*)
Set Unix environment variable. *Name* and *Value* should be instantiated to atoms or integers. The environment variable will be passed to `shell/[0-2]` and can be requested using `getenv/2`.

unsetenv(*+Name*)
Remove Unix environment variable from the environment.

get_time(*-Time*)
Return the number of seconds that elapsed since the epoch of Unix, 1 January 1970, 0 hours. *Time* is a floating point number. Its granularity is system dependent. On SUN, this is 1/60 of a second.

convert_time(*+Time, -Year, -Month, -Day, -Hour, -Minute, -Second, -MilliSeconds*)
Convert a time stamp, provided by `get_time/1`, `time_file/2`, etc. *Year* is unified with the year, *Month* with the month number (January is 1), *Day* with the day of the month (starting with 1), *Hour* with the hour of the day (0–23), *Minute* with the minute (0–59). *Second* with the second (0–59) and *MilliSecond* with the milliseconds (0–999). Note that the latter might not be accurate or might always be 0, depending on the timing capabilities of the system.

3.33 File System Interaction

access_file(*+File, +Mode*)
Succeeds if *File* exists and can be accessed by this prolog process under mode *Mode*. *Mode* is one of the atoms `read`, `write`, `append`, `exist`, `none` or `execute`. *File* may also be the name of a directory. Fails silently otherwise. `access_file(File, none)` simply succeeds without testing anything.

If 'Mode' is `write` or `append`, this predicate also succeeds if the file does not exist and the user has write-access to the directory of the specified location.

exists_file(*+File*)
Succeeds when *File* exists. This does not imply the user has read and/or write permission for the file.

file_directory_name(*+File, -Directory*)
Extracts the directory-part of *File*. The resulting *Directory* name ends with the directory separator character `/`. If *File* is an atom that does not contain any directory separator characters, the empty atom `''` is returned. See also `file_base_name/2`.

file_base_name(*+File, -BaseName*)
Extracts the filename part from a path specification. If *File* does not contain any directory separators, *File* is returned.

same_file(*+File1, +File2*)
Succeeds if both filenames refer to the same physical file. That is, if *File1* and *File2* are the same string or both names exist and point to the same file (due to hard or symbolic links and/or relative vs. absolute paths).

exists_directory(*+Directory*)
Succeeds if *Directory* exists. This does not imply the user has read, search and or write permission for the directory.

delete_file(*+File*)
Unlink *File* from the Unix file system.

rename_file(*+File1, +File2*)
Rename *File1* into *File2*. Currently files cannot be moved across devices.

size_file(*+File, -Size*)
Unify *Size* with the size of *File* in characters.

time_file(*+File, -Time*)
Unify the last modification time of *File* with *Time*. *Time* is a floating point number expressing the seconds elapsed since Jan 1, 1970.

absolute_file_name(*+File, -Absolute*)
Expand Unix file specification into an absolute path. User home directory expansion (`~` and `~user`) and variable expansion is done. The absolute path is canonised: references to '.' and '..' are deleted. SWI-Prolog uses absolute file names to register source files independent of the current working directory. See also `absolute_file_name/3`.

absolute_file_name(*+Spec, +Options, -Absolute*)
Converts the given file specification into an absolute path. *Option* is a list of options to guide the conformation process:

`extensions(ListOfExtensions)`
List of file-extensions to try. Default is `['']`. For each extension, `absolute_file_name/3` will first add the extension and then verify the conditions imposed by the other options. If the condition fails, the next extension of the list is tried. Extensions may be specified both as `'.ext'` or plain `'ext'`.
`access(Mode)`
Imposes the condition access_file(*File, Mode*). *Mode* is on of `read`, `write`, `append`, `exist` or `none`. See also `access_file/2`.
`file_type(Type)`
Defines extensions. Current mapping: `txt` implies `['']`, `prolog` implies `['.pl', '']`, `executable` implies `['.so', '']`, `qlf` implies `['.qlf', '']` and `directory` implies `['']`.
`file_errors(fail/true)`
Report if the path cannot be resolved or be silent. The default is to stay silent.
`solutions(first/all)`
If `first` (default), the predicates leaves no choice-point. Otherwise a choice-point will be left and backtracking may yield more solutions.

is_absolute_file_name(*+File*)
True if *File* specifies and absolute path-name. On Unix systems, this implies the path starts with a '/'. For Microsoft based systems this implies the path starts with <letter>:. This predicate is intended to provide platform-independent checking for absolute paths. See also `absolute_file_name/2` and `prolog_to_os_filename/2`.

file_name_extension(*?Base, ?Extension, ?Name*)
This predicate is used to add, remove or test filename extensions. The main reason for its introduction is to deal with different filename properties in a portable manner. If the file system is case-insensitive, testing for an extension will be done case-insensitive too. *Extension* may be specified with or without a leading dot (`.`). If an *Extension* is generated, it will not have a leading dot.

expand_file_name(*+WildCard, -List*)
Unify *List* with a sorted list of files or directories matching *WildCard*. The normal Unix wildcard constructs '`?`', '`*`', '`[...]`' and '`{...}`' are recognised. The interpretation of '`{...}`'

is interpreted slightly different from the C shell (csh(1)). The comma separated argument can be arbitrary patterns, including '`{...}`' patterns. The empty pattern is legal as well: '`{.pl,}`' matches either '`.pl`' or the empty string.

prolog_to_os_filename(*?PrologPath, ?OsPath*)
Converts between the internal Prolog pathname conventions and the operating-system pathname conventions. The internal conventions are Unix and this predicates is equivalent to =/2 (unify) on Unix systems. On DOS systems it will change the directory-separator, limit the filename length map dots, except for the last one, onto underscores.

read_link(*+File, -Link, -Target*)
If *File* points to a symbolic link, unify *Link* with the value of the link and *Target* to the file the link is pointing to. *Target* points to a file, directory or non-existing entry in the file system, but never to a link. Fails if *File* is not a link. Fails always on systems that do not support symbolic links.

tmp_file(*+Base, -TmpName*)
Create a name for a temporary file. *Base* is an identifier for the category of file. The *TmpName* is guaranteed to be unique. If the system halts, it will automatically remove all created temporary files.

chdir(*+Path*)
Change working directory to *Path*.

3.34 User Toplevel Manipulation

break
Recursively start a new Prolog top level. This Prolog top level has its own stacks, but shares the heap with all break environments and the top level. Debugging is switched off on entering a break and restored on leaving one. The break environment is terminated by typing the system's end-of-file character (control-D). If the `-t` *toplevel* command line option is given this goal is started instead of entering the default interactive top level (`prolog/0`).

abort
Abort the Prolog execution and start a new top level. If the `-t` *toplevel* command line options is given this goal is started instead of entering the default interactive top level. Break environments are aborted as well. All open files except for the terminal related files are closed. The input- and output stream again refers to *user*.[12]

halt
Terminate Prolog execution. Open files are closed and if the command line option `-tty` is not active the terminal status (see Unix stty(1)) is restored. Hooks may be registered both in Prolog and in foreign code. Prolog hooks are registered using `at_halt/1`. `halt/0` is equivalent to `halt(0)`.

halt(*+Status*)
Terminate Prolog execution with given status. Status is an integer. See also `halt/0`.

prolog
This goal starts the default interactive top level. `prolog/0` is terminated (succeeds) by typing control-D.

[12] BUG: Erased clauses which could not actually be removed from the database, because they are active in the interpreter, will never be garbage collected after an abort.

3.35 Creating a Protocol of the User Interaction

SWI-Prolog offers the possibility to log the interaction with the user on a file.[13] All Prolog interaction, including warnings and tracer output, are written on the protocol file.

protocol(*+File*)
Start protocolling on file *File*. If there is already a protocol file open then close it first. If *File* exists it is truncated.

protocola(*+File*)
Equivalent to `protocol/1`, but does not truncate the *File* if it exists.

noprotocol
Stop making a protocol of the user interaction. Pending output is flushed on the file.

protocolling(*-File*)
Succeeds if a protocol was started with `protocol/1` or `protocola/1` and unifies *File* with the current protocol output file.

3.36 Debugging and Tracing Programs

trace
Start the tracer. `trace/0` itself cannot be seen in the tracer. Note that the Prolog toplevel treats `trace/0` special; it means 'trace the next goal'.

tracing
Succeeds when the tracer is currently switched on. `tracing/0` itself can not be seen in the tracer.

notrace
Stop the tracer. `notrace/0` itself cannot be seen in the tracer.

trace(*+Pred*)
Equivalent to `trace(`*Pred*`, +all)`.

trace(*+Pred, +Ports*)
Put a trace-point on all predicates meeting the predicate specification *Pred*. *Ports* is a list of portnames (`call, redo, exit, fail`). The atom `all` refers to all ports. If the port is preceded by a '-' sign the trace-point is cleared for the port. If it is preceded by a '+' the trace-point is set.

The predicate `trace/2` activates debug mode (see `debug/0`). Each time a port (of the 4-port model) is passed that has a trace-point set the goal is printed as with `trace/0`. Unlike `trace/0` however, the execution is continued without asking for further information. Examples:

`?- trace(hello).`	Trace all ports of hello with any arity in any module.
`?- trace(foo/2, +fail)`	Trace failures of `foo/2` in any module.
`?- trace(bar/1, -all)`	Stop tracing `bar/1`.

The predicate `debugging/0` shows all currently defined trace-points.

[13] A similar facility was added to Edinburgh C-Prolog by Wouter Jansweijer.

notrace(*+Goal*)
Call *Goal*, but suspend the debugger while *Goal* is executing. The current implementation cuts the choicepoints of *Goal* after successful completion. See `once/1`. Later implementations may have the same semantics as `call/1`.

debug
Start debugger (stop at spy points).

nodebug
Stop debugger (do not trace, nor stop at spy points).

debugging
Print debug status and spy points on current output stream.

spy(*+Pred*)
Put a spy point on all predicates meeting the predicate specification *Pred*. See section 3.3.

nospy(*+Pred*)
Remove spy point from all predicates meeting the predicate specification *Pred*.

nospyall
Remove all spy points from the entire program.

leash(*?Ports*)
Set/query leashing (ports which allow for user interaction). *Ports* is one of `+Name`, `-Name`, `?Name` or a list of these. `+Name` enables leashing on that port, `-Name` disables it and `?Name` succeeds or fails according to the current setting. Recognised ports are: `call`, `redo`, `exit`, `fail` and `unify`. The special shorthand `all` refers to all ports, `full` refers to all ports except for the unify port (default). `half` refers to the `call`, `redo` and `fail` port.

visible(*+Ports*)
Set the ports shown by the debugger. See `leash/1` for a description of the port specification. Default is `full`.

unknown(*-Old, +New*)
Unify *Old* with the current value of the unknown system flag. On success *New* will be used to specify the new value. *New* should be instantiated to either `fail` or `trace` and determines the interpreters action when an undefined predicate which is not declared dynamic is encountered (see `dynamic/1`). `fail` implies the predicate just fails silently. `trace` implies the tracer is started. Default is `trace`. The unknown flag is local to each module and `unknown/2` is module transparent. Using it as a directive in a module file will only change the unknown flag for that module. Using the :/2 construct the behaviour on trapping an undefined predicate can be changed for any module. Note that if the unknown flag for a module equals `fail` the system will not call `exception/3` and will **not** try to resolve the predicate via the dynamic library system. The system will still try to import the predicate from the public module.

style_check(*+Spec*)
Set style checking options. *Spec* is either `+<option>`, `-<option>`, `?<option>` or a list of such options. `+<option>` sets a style checking option, `-<option>` clears it and `?<option>` succeeds or fails according to the current setting. `consult/1` and derivatives resets the style checking options to their value before loading the file. If—for example—a file containing long atoms should be loaded the user can start the file with:

```
:- style_check(-atom).
```

Currently available options are:

Name	Default	Description
`singleton`	on	`read_clause/1` (used by `consult/1`) warns on variables only appearing once in a term (clause) which have a name not starting with an underscore.
`atom`	on	`read/1` and derivatives will produce an error message on quoted atoms or strings longer than 5 lines.
`dollar`	off	Accept dollar as a lower case character, thus avoiding the need for quoting atoms with dollar signs. System maintenance use only.
`discontiguous`	on	Warn if the clauses for a predicate are not together in the same source file.
`string`	off	Read and derivatives transform `"..."` into a prolog string instead of a list of ASCII characters.

3.37 Obtaining Runtime Statistics

statistics(*+Key, -Value*)
Unify system statistics determined by *Key* with *Value*. The possible keys are given in the table 3.2.

cputime	(User) CPU time since Prolog was started in seconds
inferences	Total number of passes via the call and redo ports since Prolog was started.
heapused	Bytes heap in use.
local	Allocated size of the local stack in bytes.
localused	Number of bytes in use on the local stack.
locallimit	Size to which the local stack is allowed to grow
global	Allocated size of the global stack in bytes.
globalused	Number of bytes in use on the global stack.
globallimit	Size to which the global stack is allowed to grow
trail	Allocated size of the trail stack in bytes.
trailused	Number of bytes in use on the trail stack.
traillimit	Size to which the trail stack is allowed to grow
atoms	Total number of defined atoms.
functors	Total number of defined name/arity pairs.
predicates	Total number of predicate definitions.
modules	Total number of module definitions.
externals	Total number of *external references* in all clauses.
codes	Total amount of byte codes in all clauses.

Table 3.2: Keys for `statistics/2`

statistics
Display a table of system statistics on the current output stream.

time(*+Goal*)
Execute *Goal* just like `once/1` (i.e. leaving no choice points), but print used time, number of logical inferences and the average number of *lips* (logical inferences per second). Note that

SWI-Prolog counts the actual executed number of inferences rather than the number of passes through the call- and redo ports of the theoretical 4-port model.

3.38 Finding Performance Bottlenecks

SWI-Prolog offers a statistical program profiler similar to Unix prof(1) for C and some other languages. A profiler is used as an aid to find performance pigs in programs. It provides information on the time spent in the various Prolog predicates.

The profiler is based on the assumption that if we monitor the functions on the execution stack on time intervals not correlated to the program's execution the number of times we find a procedure on the environment stack is a measure of the time spent in this procedure. It is implemented by calling a procedure each time slice Prolog is active. This procedure scans the local stack and either just counts the procedure on top of this stack (`plain` profiling) or all procedures on the stack (`cumulative` profiling). To get accurate results each procedure one is interested in should have a reasonable number of counts. Typically a minute runtime will suffice to get a rough overview of the most expensive procedures.

profile(*+Goal, +Style, +Number*)
Execute *Goal* just like `time/1`. Collect profiling statistics according to style (see `profiler/2`) and show the top *Number* procedures on the current output stream (see `show_profile/1`). The results are kept in the database until `reset_profiler/0` or `profile/3` is called and can be displayed again with `show_profile/1`. `profile/3` is the normal way to invoke the profiler. The predicates below are low-level predicates that can be used for special cases.

show_profile(*+Number*)
Show the collected results of the profiler. Stops the profiler first to avoid interference from `show_profile/1`. It shows the top *Number* predicates according the percentage CPU-time used.[14]

profiler(*-Old, +New*)
Query or change the status of the profiler. The status is one of `off`, `plain` or `cumulative`. `plain` implies the time used by children of a predicate is not added to the time of the predicate. For status `cumulative` the time of children is added (except for recursive calls). Cumulative profiling implies the stack is scanned up to the top on each time slice to find all active predicates. This implies the overhead grows with the number of active frames on the stack. Cumulative profiling starts debugging mode to disable tail recursion optimisation, which would otherwise remove the necessary parent environments. Switching status from `plain` to `cumulative` resets the profiler. Switching to and from status `off` does not reset the collected statistics, thus allowing to suspend profiling for certain parts of the program.

reset_profiler
Switches the profiler to `off` and clears all collected statistics.

profile_count(*+Head, -Calls, -Promilage*)
Obtain profile statistics of the predicate specified by *Head*. *Head* is an atom for predicates with arity 0 or a term with the same name and arity as the predicate required (see `current_predicate/2`). *Calls* is unified with the number of 'calls' and 'redos' while the profiler was active. *Promilage* is unified with the relative number of counts the predicate was active (`cumulative`) or on top of the stack (`plain`). *Promilage* is an integer between 0 and 1000.

[14] `show_profile/1` is defined in Prolog and takes a considerable amount of memory.

3.39 Memory Management

Note: `limit_stack/2` and `trim_stacks/0` have no effect on machines that do not offer dynamic stack expansion. On these machines these predicates simply succeed to improve portability.

garbage_collect
Invoke the global- and trail stack garbage collector. Normally the garbage collector is invoked automatically if necessary. Explicit invocation might be useful to reduce the need for garbage collections in time critical segments of the code. After the garbage collection `trim_stacks/0` is invoked to release the collected memory resources.

limit_stack(*+Key, +Kbytes*)
Limit one of the stack areas to the specified value. *Key* is one of `local`, `global` or `trail`. The limit is an integer, expressing the desired stack limit in K bytes. If the desired limit is smaller than the currently used value, the limit is set to the nearest legal value above the currently used value. If the desired value is larger than the maximum, the maximum is taken. Finally, if the desired value is either 0 or the atom `unlimited` the limit is set to its maximum. The maximum and initial limit is determined by the command line options `-L`, `-G` and `-T`.

trim_stacks
Release stack memory resources that are not in use at this moment, returning them to the operating system. Trim stack is a relatively cheap call. It can be used to release memory resources in a backtracking loop, where the iterations require typically seconds of execution time and very different, potentially large, amounts of stack space. Such a loop should be written as follows:

```
loop :-
        generator,
            trim_stacks,
            potentially_expensive_operation,
        stop_condition, !.
```

The prolog top level loop is written this way, reclaiming memory resources after every user query.

stack_parameter(*+Stack, +Key, -Old, +New*)
Query/set a parameter for the runtime stacks. *Stack* is one of `local`, `global`, `trail`, `argument` or `lock`. The table below describes the *Key*/Value pairs. Old is first unified with the current value.

`limit`	Maximum size of the stack in bytes
`min_free`	Minimum free space at entry of foreign predicate

This predicate is currently only available on versions that use the stack-shifter to enlarge the runtime stacks when necessary. It's definition is subject to change.

3.40 Windows DDE interface

The predicates in this section deal with MS-Windows 'Dynamic Data Exchange' or DDE protocol.[15] A Windows DDE conversation is a form of interprocess communication based on sending reserved window-events between the communicating processes.

[15] This interface is contributed by Don Dwiggins.

See also section 5.4 for loading Windows DLL's into SWI-Prolog.

3.40.1 DDE client interface

The DDE client interface allows Prolog to talk to DDE server programs. We will demonstrate the use of the DDE interface using the Windows PROGMAN (Program Manager) application:

```
1 ?- open_dde_conversation(progman, progman, C).

C = 0
2 ?- dde_request(0, groups, X)

--> Unifies X with description of groups

3 ?- dde_execute(0, '[CreateGroup("DDE Demo")]').

Yes

4 ?- close_dde_conversation(0).

Yes
```

For details on interacting with PROGMAN, use the SDK online manual section on the Shell DDE interface. See also the Prolog library progman.pl, which may be used to write simple Windows setup scripts in Prolog.

open_dde_conversation(*+Service, +Topic, -Handle*)
Open a conversation with a server supporting the given service name and topic (atoms). If successful, *Handle* may be used to send transactions to the server. If no willing server is found this predicate fails silently.

close_dde_conversation(*+Handle*)
Close the conversation associated with *Handle*. All opened conversations should be closed when they're no longer needed, although the system will close any that remain open on process termination.

dde_request(*+Handle, +Item, -Value*)
Request a value from the server. *Item* is an atom that identifies the requested data, and *Value* will be a string (`CF_TEXT` data in DDE parlance) representing that data, if the request is successful. If unsuccessful, *Value* will be unified with a term of form `error`(*Reason*), identifying the problem. This call uses SWI-Prolog string objects to return the value rather then atoms to reduce the load on the atom-space. See section 3.19 for a discussion on this data type.

dde_execute(*+Handle, +Command*)
Request the DDE server to execute the given command-string. Succeeds if the command could be executed and fails with error message otherwise.

dde_poke(*+Handle, +Item, +Command*)
Issue a `POKE` command to the server on the specified *Item*. Command is passed as data of type `CF_TEXT`.

3.40.2 DDE server mode

The (autoload) library `dde.pl` defines primitives to realise simple DDE server applications in SWI-Prolog. These features are provided as of version 2.0.6 and should be regarded prototypes. The C-part of the DDE server can handle some more primitives, so if you need features not provided by this interface, please study the library `dde.pl`.

dde_register_service(*+Template, +Goal*)
Register a server to handle DDE request or DDE execute requests from other applications. To register a service for a DDE request, *Template* is of the form:

+Service(+Topic, +Item, +Value)

Service is the name of the DDE service provided (like `progman` in the client example above). *Topic* is either an atom, indicating *Goal* only handles requests on this topic or a variable that also appears in *Goal*. *Item* and *Value* are variables that also appear in *Goal*.

The example below registers the Prolog `feature/2` predicate to be accessible from other applications. The request may be given from the same Prolog as well as from another application.

```
?- dde_register_service(prolog(feature, F, V),
                        feature(F, V)).

?- open_dde_conversation(prolog, feature, Handle),
   dde_request(Handle, home, Home),
   close_dde_conversation(Handle).

Home = '/usr/local/lib/pl-2.0.6/'
```

Handling DDE `execute` requests is very similar. In this case the template is of the form:

+Service(+Topic, +Item)

Passing a *Value* argument is not needed as execute requests either succeed or fail. If *Goal* fails, a 'not processed' is passed back to the caller of the DDE request.

dde_unregister_service(*+Service*)
Stop responding to *Service*. If Prolog is halted, it will automatically call this on all open services.

dde_current_service(*-Service, -Topic*)
Find currently registered services and the topics served on them.

dde_current_connection(*-Service, -Topic*)
Find currently open conversations.

3.41 Miscellaneous

dwim_match(*+Atom1, +Atom2*)
Succeeds if *Atom1* matches *Atom2* in 'Do What I Mean' sense. Both *Atom1* and *Atom2* may also be integers or floats. The two atoms match if:

- They are identical

- They differ by one character (spy ≡ spu)
- One character is inserted/deleted (debug ≡ deug)
- Two characters are transposed (trace ≡ tarce)
- 'Sub-words' are glued differently (existsfile ≡ existsFile ≡ exists_file)
- Two adjacent sub words are transposed (existsFile ≡ fileExists)

dwim_match(*+Atom1, +Atom2, -Difference*)
Equivalent to `dwim_match/2`, but unifies *Difference* with an atom identifying the the difference between *Atom1* and *Atom2*. The return values are (in the same order as above): `equal`, `mismatched_char`, `inserted_char`, `transposed_char`, `separated` and `transposed_word`.

wildcard_match(*+Pattern, +String*)
Succeeds if *String* matches the wildcard pattern *Pattern*. *Pattern* is very similar the the Unix csh pattern matcher. The patterns are given below:

`?`	Matches one arbitrary character.
`*`	Matches any number of arbitrary characters.
`[...]`	Matches one of the characters specified between the brackets. `<char>-<char>` indicates a range.
{...}	Matches any of the patterns of the comma separated list between the braces.

Example:

```
?- wildcard_match(´[a-z]*.{pro,pl}[%~]´, ´a_hello.pl%´).

Yes.
```

gensym(*+Base, -Unique*)
Generate a unique atom from base *Base* and unify it with *Unique*. *Base* should be an atom. The first call will return `<base>1`, the next `<base>2`, etc. Note that this is no warrant that the atom is unique in the system.[16]

sleep(*+Time*)
Suspend execution *Time* seconds. *Time* is either a floating point number or an integer. Granularity is dependent on the system's timer granularity (1/60 seconds on most Unix systems). A negative time causes the timer to return immediately. As Unix is a multi-tasking environment we can only ensure execution is suspended for **at least** *Time* seconds.

[16] BUG: I plan to supply a real `gensym/2` which does give this warrant for future versions.

Chapter 4

Using Modules

4.1 Why Using Modules?

In traditional Prolog systems the predicate space was flat. This approach is not very suitable for the development of large applications, certainly not if these applications are developed by more than one programmer. In many cases, the definition of a Prolog predicate requires sub-predicates that are intended only to complete the definition of the main predicate. With a flat and global predicate space these support predicates will be visible from the entire program.

For this reason, it is desirable that each source module has it's own predicate space. A module consists of a declaration for it's name, it's *public* predicates and the predicates themselves. This approach allow the programmer to use short (local) names for support predicates without worrying about name conflicts with the support predicates of other modules. The module declaration also makes explicit which predicates are meant for public usage and which for private purposes. Finally, using the module information, cross reference programs can indicate possible problems much better.

4.2 Name-based versus Predicate-based Modules

Two approaches to realize a module system are commonly used in Prolog and other languages. The first one is the *name based* module system. In these systems, each atom read is tagged (normally prefixed) with the module name, with the exception of those atoms that are defined *public*. In the second approach, each module actually implements its own predicate space.

A critical problem with using modules in Prolog is introduced by the meta-predicates that transform between Prolog data and Prolog predicates. Consider the case where we write:

```
:- module(extend, [add_extension/3]).

add_extension(Extension, Plain, Extended) :-
        maplist(extend_atom(Extension), Plain, Extended).

extend_atom(Extension, Plain, Extended) :-
        concat(Plain, Extension, Extended).
```


In this case we would like maplist to call `extend_atom/3` in the module `extend`. A name based module system will do this correctly. It will tag the atom `extend_atom` with the module and maplist will use this to construct the tagged term `extend_atom/3`. A name based module however, will not only tag the atoms that will eventually be used to refer to a predicate, but *all* atoms that are not declared public. So, with a name based module system also data is local to the module. This introduces another serious problem:

```
:- module(action, [action/3]).

action(Object, sleep, Arg) :- ....
action(Object, awake, Arg) :- ....

:- module(process, [awake_process/2]).

awake_process(Process, Arg) :-
        action(Process, awake, Arg).
```

This code uses a simple object-oriented implementation technique were atoms are used as method selectors. Using a name based module system, this code will not work, unless we declare the selectors public atoms in all modules that use them. Predicate based module systems do not require particular precautions for handling this case.

It appears we have to choose either to have local data, or to have trouble with meta-predicates. Probably it is best to choose for the predicate based approach as novice users will not often write generic meta-predicates that have to be used across multiple modules, but are likely to write programs that pass data around across modules. Experienced Prolog programmers should be able to deal with the complexities of meta-predicates in a predicate based module system.

4.3 Defining a Module

Modules normally are created by loading a *module file*. A module file is a file holding a `module/2` directive as its first term. The `module/2` directive declares the name and the public (i.e. externally visible) predicates of the module. The rest of the file is loaded into the module. Below is an example of a module file, defining `reverse/2`.

```
:- module(reverse, [reverse/2]).

reverse(List1, List2) :-
        rev(List1, [], List2).

rev([], List, List).
rev([Head|List1], List2, List3) :-
        rev(List1, [Head|List2], List3).
```

4.4 Importing Predicates into a Module

As explained before, in the predicate based approach adapted by SWI-Prolog, each module has it's own predicate space. In SWI-Prolog, a module initially is completely empty. Predicates can be added to a module by loading a module file as demonstrated in the previous section, using assert or by *importing* them from another module.

Two mechanisms for importing predicates explicitly from another module exist. The `use_module/[1,2]` predicates load a module file and import (part of the) public predicates of the file. The `import/1` predicate imports any predicate from any module.

use_module(*+File*)
: Load the file(s) specified with *File* just like `ensure_loaded/1`. The files should all be module files. All exported predicates from the loaded files are imported into the context module. The difference between this predicate and `ensure_loaded/1` becomes apparent if the file is already loaded into another module. In this case `ensure_loaded/1` does nothing; use_module will import all public predicates of the module into the current context module.

use_module(*+File, +ImportList*)
: Load the file specified with *File* (only one file is accepted). *File* should be a module file. *ImportList* is a list of name/arity pairs specifying the predicates that should be imported from the loaded module. If a predicate is specified that is not exported from the loaded module a warning will be printed. The predicate will nevertheless be imported to simplify debugging.

import(*+Head*)
: Import predicate *Head* into the current context module. *Head* should specify the source module using the <*module*>:<*term*> construct. Note that predicates are normally imported using one of the directives `use_module/[1,2]`. `import/1` is meant for handling imports into dynamically created modules.

It would be rather inconvenient to have to import each predicate referred to by the module, including the system predicates. For this reason each module is assigned a *default* module. All predicates in the default module are available without extra declarations. Their definition however can be overruled in the local module. This schedule is implemented by the exception handling mechanism of SWI-Prolog: if an undefined predicate exception is raised for a predicate in some module, the exception handler first tries to import the predicate from the module's default module. On success, normal execution is resumed.

4.4.1 Reserved Modules

SWI-Prolog contains two special modules. The first one is the module `system`. This module contains all built-in predicates described in this manual. Module `system` has no default module assigned to it. The second special module is the module `user`. This module forms the initial working space of the user. Initially it is empty. The default module of module `user` is `system`, making all built-in predicate definitions available as defaults. Built-in predicates thus can be overruled by defining them in module `user` before they are used.

All other modules default to module `user`. This implies they can use all predicates imported into `user` without explicitly importing them.

4.5 Using the Module System

The current structure of the module system has been designed with some specific organisations for large programs in mind. Many large programs define a basic library layer on top of which the actual program itself is defined. The module *user*, acting as the default module for all other modules of the program can be used to distribute these definitions over all program module without introducing the need to import this common layer each time explicitly. It can also be used to redefine built-in predicates if this is required to maintain compatibility to some other Prolog implementation. Typically, the loadfile of a large application looks like this:

```
:- use_module(compatibility).   % load XYZ prolog compatibility

:- use_module(                  % load generic parts
        [ error                 % errors and warnings
        , goodies               % general goodies (library extensions)
        , debug                 % application specific debugging
        , virtual_machine       % virtual machine of application
        , ...                   % more generic stuff
        ]).

:- ensure_loaded(
        [ ...                   % the application itself
        ]).
```

The 'use_module' declarations will import the public predicates from the generic modules into the `user` module. The 'ensure_loaded' directive loads the modules that constitute the actual application. It is assumed these modules import predicates from each other using `use_module/[1,2]` as far as necessary.

In combination with the object-oriented schema described below it is possible to define a neat modular architecture. The generic code defines general utilities and the message passing predicates (`invoke/3` in the example below). The application modules define classes that communicate using the message passing predicates.

4.5.1 Object Oriented Programming

Another typical way to use the module system is for defining classes within an object oriented paradigm. The class structure and the methods of a class can be defined in a module and the explicit module-boundary overruling describes in section 4.6.2 can by used by the message passing code to invoke the behaviour. An outline of this mechanism is given below.

```
%       Define class point

:- module(point, []).           % class point, no exports

%        name           type,           default access
%                                       value

variable(x,             integer,        0,      both).
variable(y,             integer,        0,      both).

%         method name   predicate name  arguments

behaviour(mirror,       mirror,         []).

mirror(P) :-
        fetch(P, x, X),
        fetch(P, y, Y),
        store(P, y, X),
        store(P, x, Y).
```

The predicates `fetch/3` and `store/3` are predicates that change instance variables of instances. The figure below indicates how message passing can easily be implemented:

```
%       invoke(+Instance, +Selector, ?ArgumentList)
%       send a message to an instance

invoke(I, S, Args) :-
        class_of_instance(I, Class),
        Class:behaviour(S, P, ArgCheck), !,
        convert_arguments(ArgCheck, Args, ConvArgs),
        Goal =.. [P|ConvArgs],
        Class:Goal.
```

The construct *'Module:Goal'* explicitly calls *Goal* in module *Module*. It is discussed in more detail in section 3.7.

4.6 Meta-Predicates in Modules

As indicated in the introduction, the problem with a predicate based module system lies in the difficulty to find the correct predicate from a Prolog term. The predicate 'solution(Solution)' can exist in more than one module, but 'assert(solution(4))' in some module is supposed to refer to the correct version of `solution/1`.

Various approaches are possible to solve this problem. One is to add an extra argument to all predicates (e.g. 'assert(Module, Term)'). Another is to tag the term somehow to indicate which module is desired (e.g. 'assert(Module:Term)'). Both approaches are not very attractive as they make the user responsible for choosing the correct module, inviting unclear programming by asserting in

other modules. The predicate `assert/1` is supposed to assert in the module it is called from and should do so without being told explicitly. For this reason, the notion *context module* has been introduced.

4.6.1 Definition and Context Module

Each predicate of the program is assigned a module, called it's *definition module*. The definition module of a predicate is always the module in which the predicate was originally defined. Each active goal in the Prolog system has a *context module* assigned to it.

The context module is used to find predicates from a Prolog term. By default, this module is the definition module of the predicate running the goal. For meta-predicates however, this is the context module of the goal that invoked them. We call this *module_transparent* in SWI-Prolog. In the 'using maplist' example above, the predicate `maplist/3` is declared module_transparent. This implies the context module remains `extend`, the context module of `add_extension/3`. This way `maplist/3` can decide to call extend_atom in module `extend` rather than in it's own definition module.

All built-in predicates that refer to predicates via a Prolog term are declared module_transparent. Below is the code defining maplist.

```
:- module(maplist, maplist/3).

:- module_transparent maplist/3.

%       maplist(+Goal, +List1, ?List2)
%       True if Goal can successfully be applied to all successive pairs
%       of elements of List1 and List2.

maplist(_, [], []).
maplist(Goal, [Elem1|Tail1], [Elem2|Tail2]) :-
        apply(Goal, [Elem1, Elem2]),
        maplist(Goal, Tail1, Tail2).
```

4.6.2 Overruling Module Boundaries

The mechanism above is sufficient to create an acceptable module system. There are however cases in which we would like to be able to overrule this schema and explicitly call a predicate in some module or assert explicitly in some module. The first is useful to invoke goals in some module from the user's toplevel or to implement a object-oriented system (see above). The latter is useful to create and modify *dynamic* modules (see section 4.7).

For this purpose, the reserved term `:/2` has been introduced. All built-in predicates that transform a term into a predicate reference will check whether this term is of the form '<Module>:<Term>'. If so, the predicate is searched for in *Module* instead of the goal's context module. The `:/2` operator may be nested, in which case the inner-most module is used.

The special calling construct <Module>:<Goal> pretends *Goal* is called from *Module* instead of the context module. Examples:

```
?- assert(world:done).  % asserts done/0 into module world
?- world:assert(done).  % the same
```

```
?- world:done.          % calls done/0 in module world
```

4.7 Dynamic Modules

So far, we discussed modules that were created by loading a module-file. These modules have been introduced on facilitate the development of large applications. The modules are fully defined at load-time of the application and normally will not change during execution. Having the notion of a set of predicates as a self-contained world can be attractive for other purposes as well. For example, assume an application that can reason about multiple worlds. It is attractive to store the data of a particular world in a module, so we extract information from a world simply by invoking goals in this world.

Dynamic modules can easily be created. Any built-in predicate that tries to locate a predicate in a specific module will create this module as a side-effect if it did not yet exist. Example:

```
?- assert(world_a, consistent),
   world_a:unknown(_, fail).
```

These calls create a module called 'world_a' and make the call 'world_a:consistent' succeed. Undefined predicates will not start the tracer or autoloader for this module (see `unknown/2`).

Import and export from dynamically created world is arranged via the predicates `import/1` and `export/1`:

```
?- world_b:export(solve(_,_)).          % exports solve/2 from world_b
?- world_c:import(world_b:solve(_,_)).  % and import it to world_c
```

4.8 Module Handling Predicates

This section gives the predicate definitions for the remaining built-in predicates that handle modules.

:- module(*+Module, +PublicList*)
: This directive can only be used as the first term of a source file. It declares the file to be a *module file*, defining *Module* and exporting the predicates of *PublicList*. *PublicList* is a list of name/arity pairs.

module_transparent *+Preds*
: *Preds* is a comma separated list of name/arity pairs (like `dynamic/1`). Each goal associated with a transparent declared predicate will inherit the *context module* from its parent goal.

context_module(*-Module*)
: Unify *Module* with the context module of the current goal. `context_module/1` itself is transparent.

export(*+Head*)
: Add a predicate to the public list of the context module. This implies the predicate will be imported into another module if this module is imported with `use_module/[1,2]`. Note that predicates are normally exported using the directive `module/2`. `export/1` is meant to handle export from dynamically created modules.

export_list(*+Module, ?Exports*)
: Unifies *Exports* with a list of terms. Each term has the name and arity of a public predicate of *Module*. The order of the terms in *Exports* is not defined. See also `predicate_property/2`.

4.9 Compatibility of the Module System

The principles behind the module system of SWI-Prolog differ in a number of aspects from the Quintus Prolog module system.

- The SWI-Prolog module system allows the user to redefine system predicates.
- All predicates that are available in the *system* and *user* modules are visible in all other modules as well.
- Quintus has the '`meta_predicate/1`' declaration were SWI-Prolog has the `module_transparent/1` declaration.

The `meta_predicate/1` declaration causes the compiler to tag arguments that pass module sensitive information with the module using the `:/2` operator. This approach has some disadvantages:

- Changing a meta_predicate declaration implies all predicates *calling* the predicate need to be reloaded. This can cause serious consistency problems.
- It does not help for dynamically defined predicates calling module sensitive predicates.
- It slows down the compiler (at least in the SWI-Prolog architecture).
- At least within the SWI-Prolog architecture the run-time overhead is larger than the overhead introduced by the transparent mechanism.

Unfortunately the transparent predicate approach also has some disadvantages. If a predicate A passes module sensitive information to a predicate B, passing the same information to a module sensitive system predicate both A and B should be declared transparent. Using the Quintus approach only A needs to be treated special (i.e. declared with `meta_predicate/1`)[1]. A second problem arises if the body of a transparent predicate uses module sensitive predicates for which it wants to refer to its own module. Suppose we want to define `findall/3` using `assert/1` and `retract/1`[2]. The example in figure 4.1 gives the solution.

The Quintus `meta_predicate/1` directive can in many cases be replaced by the transparent declaration. Figure 4.2 gives a definition of `meta_predicate/1` as available from the 'quintus' library package.

The discussion above about the problems with the transparent mechanism show the two cases in which this simple transformation does not work.

[1] Although this would make it impossible to call B directly.
[2] The system version uses `recordz/2` and `recorded/3`.

```
:- module(findall, [findall/3]).

:- dynamic
        solution/1.

:- module_transparent
        findall/3,
        store/2.

findall(Var, Goal, Bag) :-
        assert(findall:solution(´$mark´)),
        store(Var, Goal),
        collect(Bag).

store(Var, Goal) :-
        Goal,                   % refers to context module of
                                % caller of findall/3
        assert(findall:solution(Var)),
        fail.
store(_, _).

collect(Bag) :-
        ...,
```

Figure 4.1: `findall` using modules

```
:- op(1150, fx, (meta_predicate)).

meta_predicate((Head, More)) :- !,
        meta_predicate1(Head),
        meta_predicate(More).
meta_predicate(Head) :-
        meta_predicate1(Head).

meta_predicate1(Head) :-
        Head =.. [Name|Arguments],
        member(Arg, Arguments),
        module_expansion_argument(Arg), !,
        functor(Head, Name, Arity),
        module_transparent(Name/Arity).
meta_predicate1(_).             % just a mode declaration

module_expansion_argument(:).
module_expansion_argument(N) :- integer(N).
```

Figure 4.2: Definition of `meta_predicate/1`

Chapter 5

Foreign Language Interface

SWI-Prolog offers a powerful interface to C [Kernighan & Ritchie, 1978]. The main design objectives of the foreign language interface are flexibility and performance. A foreign predicate is a C-function that has the same number of arguments as the predicate represented. C-functions are provided to analyse the passed terms, convert them to basic C-types as well as to instantiate arguments using unification. Non-deterministic foreign predicates are supported, providing the foreign function with a handle to control backtracking.

C can call Prolog predicates, providing both an query interface and an interface to extract multiple solutions from an non-deterministic Prolog predicate. There is no limit to the nesting of Prolog calling C, calling Prolog, etc. It is also possible to write the 'main' in C and use Prolog as an embedded logical engine.

5.1 Overview of the Interface

A special include file called <SWI-Prolog.h> should be included with each C-source file that is to be loaded via the foreign interface. The installation process installs this file in the directory `include` in the SWI-Prolog home directory (`?- feature(home, Home).`). This C-header file defines various data types, macros and functions that can be used to communicate with SWI-Prolog. Functions and macros can be divided into the following categories:

- Analysing Prolog terms
- Constructing new terms
- Unifying terms
- Returning control information to Prolog
- Registering foreign predicates with Prolog
- Calling Prolog from C
- Global actions on Prolog (halt, break, abort, etc.)

5.2 Linking Foreign Modules

Foreign modules may be linked to Prolog in three ways. Using *static* linking, the extensions, a small description file and the basic SWI-Prolog object file are linked together to form a new executable.

Using *dynamic* linking, the extensions are linked to a shared library (`.so` file on most Unix systems) or dynamic-link library (`.DLL` file on Microsoft platforms) and loaded into the the running Prolog process.[1].

5.2.1 What linking is provided?

The *static* linking schema can be used on all versions of SWI-Prolog. The `feature/2` predicate may be used to find out what other linking methods are provided for this version.

- *feature(open_shared_object, true)*
  If this succeeds the system provides the `open_shared_object/2` and related predicates that allow for handling Unix shared object files based on the Unix library functions dlopen() and friends. See section 5.4.
- *feature(dll, true)*
  If this succeeds the system provides an interface for loading `.DLL` files by means of `open_dll/2` and friends. See section 5.4.

If either the feature *open_shared_object* or *dll* is true, the library `library(shlib)` provides a common interface for loading foreign files from Prolog.

5.2.2 What kind of loading should I be using?

All described approaches have their advantages and disadvantages. Static linking is portable and allows for debugging on all platforms. It is relatively cumbersome and the libraries you need to pass to the linker may vary from system to system.

Loading shared objects or DLL files provides sharing and protection and is generally the best choice. The old (and also badly portable) `save/[1,2] and save_program/[1,2]` do not cooperate with this mechanism, but the more recent `qsave_program/[1,2]` can be used to created programs that load the appropriate library at startup.

Note that the definition of the foreign predicates is the same, regardless of the linking type used.

5.3 Dynamic Linking of shared libraries

The interface defined in this section allows the user to load shared libraries (`.so` files on most Unix systems). This interface is portable to all machines providing the function dlopen() or an equivalent, normally from the library -ldl. These functions provide the basic interface layer. It is advised to use the predicates from section 5.4 in your application.

open_shared_object(*+File, -Handle*)
File is the name of a `.so` file (see your C programmers documentation on how to create a `.so` file). This file is attached to the current process and *Handle* is unified with a handle to the shared object. Equivalent to `open_shared_object(File, [global], Handle)`. See also `load_foreign_library/[1,2]`.

[1] The system also contains code to load .o files directly for some operating systems, notably Unix systems using the BSD a.out executable format. As the number of Unix platforms supporting this gets quickly smaller and this interface is difficult to port and slow, it is no longer described in this manual. The best alternatively would be to use the dld package on machines do not have shared libraries

open_shared_object(*+File, +Options, -Handle*)
As `open_shared_object/2`, but allows for additional flags to be passed. *Options* is a list of atoms. `now` implies the symbols are resolved immediately rather than lazy (default). `global` implies symbols of the loaded object are visible while loading other shared objects (by default they are local). Note that these flags may not be supported by your operating system. Check the documentation of dlopen() or equivalent on your operating system.

close_shared_object(*+Handle*)
Detach the shared object identified by *Handle*.

call_shared_object_function(*+Handle, +Function*)
Call the named function in the loaded shared library. The function is called without arguments and the return-value is ignored. Normally this function installs foreign language predicates using calls to PL_register_foreign().

5.4 Using the library shlib for .DLL and .so files

This section discusses the functionality of the (autoload) library `shlib.pl`, providing an interface to shared libraries. Currently it supports MS-Windows DLL (`.DLL`) libraries and Unix `.so` (shared object) files.

load_foreign_library(*+Lib*)
Equivalent to load_foreign_library(Lib, install).

load_foreign_library(*+Lib, +Entry*)
Search for the given foreign library and link it to the current SWI-Prolog instance. The library may be specified with or without the extension. First, `absolute_file_name/3` is used to locate the file. If this succeeds, the full path is passed to the low-level function to open the library. Otherwise, the plain library name is passed, exploiting the operating-system defined search mechanism for the shared library. The `file_search_path/2` alias mechanism defines the alias `foreign`, which refers to the directories ¡plhome¿`/lib/`¡arch¿ and ¡plhome¿`/lib`, in this order.

If the library can be loaded, the function called *Entry* will be called without arguments. The return value of the function is ignored.

The *Entry* function will normally call PL_register_foreign() to declare functions in the library as foreign predicates.

unload_foreign_library(*+Lib*)
If the foreign library defines the function `uninstall`, this function will be called without arguments and its return value is ignored. Next, `abolish/2` is used to remove all known foreign predicates defined in the library. Finally the library itself is detached from the process.

current_foreign_library(*-Lib, -Predicates*)
Query the currently loaded foreign libraries and their predicates. *Predicates* is a list with elements of the form *Module:Head*, indicating the predicates installed with PL_register_foreign() when the entry-point of the library was called.

Figure 5.1 connects a Windows message-box using a foreign function. This example was tested using Windows NT and Microsoft Visual C++ 2.0.


```
#include <windows.h>
#include <SWI-Prolog.h>

static foreign_t
pl_say_hello(term_t to)
{ char *a;

  if ( PL_get_atom_chars(to, &a) )
  { MessageBox(NULL, a, "DLL test", MB_OK|MB_TASKMODAL);

    PL_succeed;
  }

  PL_fail;
}

install_t
install()
{ PL_register_foreign("say_hello", 1, pl_say_hello, 0);
}
```

Figure 5.1: MessageBox() example in Windows NT

5.4.1 Static Linking

Below is an outline of the files structure required for statically linking SWI-Prolog with foreign extensions. `.../pl` refers to the SWI-Prolog home directory (see `feature/2`). `<arch>` refers to the architecture identifier that may be obtained using `feature/2`.

`.../pl/runtime/<arch>/libpl.a`	SWI-Library
`.../pl/include/SWI-Prolog.h`	Include file
`.../pl/include/SWI-Stream.h`	Stream I/O include file
`.../pl/include/SWI-Exports`	Export declarations (AIX only)
`.../pl/include/stub.c`	Extension stub

The definition of the foreign predicates is the same as for dynamic linking. Unlike with dynamic linking however, there is no initialisation function. Instead, the file `.../pl/include/stub.c` may be copied to your project and modified to define the foreign extensions. Below is stub.c, modified to link the lowercase example described later in this chapter:

```
/*  Copyright (c) 1991 Jan Wielemaker. All rights reserved.
    jan@swi.psy.uva.nl

    Purpose: Skeleton for extensions
*/

#include <stdio.h>
#include <SWI-Prolog.h>

extern foreign_t pl_lowercase(term, term);

PL_extension PL_extensions [] =
{
/*{ "name",      arity,  function,      PL_FA_<flags> },*/

  { "lowercase", 2       pl_lowercase,  0 },
  { NULL,        0,      NULL,          0 }     /* terminating line */
};


int
main(int argc, char **argv, char **env)
{ if ( !PL_initialise(argc, argv, env) )
    PL_halt(1);

  PL_install_readline();                /* delete if not required */

  PL_halt(PL_toplevel() ? 0 : 1);
}
```

Now, a new executable may be created by compiling this file and linking it to libpl.a from the runtime directory and the libraries required by both the extensions and the SWI-Prolog kernel. This may be done by hand, or using the `plld` utility described in section 5.7.

5.4.2 Dynamic Linking based on `load_foreign/[2,5]`

The predicates below are considered obsolete. They are briefly described here for compatibility purposes. New code should use the predicates from the library `shlib`.

load_foreign(*+File, +Entry*)
Load a foreign file or list of files specified by *File*. The files are searched for similar to `consult/1`. Except that the '`.o`' extension is used rather than '`.pl`'.

Entry defines the entry point of the resulting executable. The entry point will be called by Prolog to install the foreign predicates.

load_foreign(*+File, +Entry, +Options, +Libraries, +Size*)
The first two arguments are identical to those of `load_foreign/2`. *Options* is (a list of) additional option to be given to the loader. The options are inserted just before the files. *Libraries* is (a list of) libraries to be passed to the loader. They are inserted just after the files.

If *Size* is specified Prolog first assumes that the resulting executable will fit in *Size* bytes and do the loading in one pass.

foreign_file(*?File*)
Is true if *File* is the absolute path name of a file loaded as foreign file.

5.5 Interface Data types

5.5.1 Type `term_t`: a reference to a Prolog term

The principal data-type is `term_t`. Type `term_t` is what Quintus calls `QP_term_ref`. This name indicates better what the type represents: it is a *handle* for a term rather than the term itself. Terms can only be represented and manipulated using this type, as this is the only safe way to ensure the Prolog kernel is aware of all terms referenced by foreign code and thus allows the kernel to perform garbage-collection and/or stack-shifts while foreign code is active, for example during a callback from C.

A term reference is a C unsigned long, representing the offset of a variable on the Prolog environment-stack. A foreign function is passed term references for the predicate-arguments, one for each argument. If references for intermediate results are needed, such references may be created using PL_new_term_ref() or PL_new_term_refs(). These references normally live till the foreign function returns control back to Prolog. Their scope can be explicitly limited using PL_open_foreign_frame() and PL_close_foreign_frame()/PL_discard_foreign_frame().

A term_t always refers to a valid Prolog term (variable, atom, integer, float or compound term). A term lives either until backtracking takes us back to a point before the term was created, the garbage collector has collected the term or the term was created after a PL_open_foreign_frame() and PL_discard_foreign_frame() has been called.

The foreign-interface functions can either *read*, *unify* or *write* to term-references. In the this document we use the following notation for arguments of type term_t:

`term_t +t`	Accessed in read-mode. The '+' indicates the argument is 'input'.
`term_t -t`	Accessed in write-mode.
`term_t ?t`	Accessed in unify-mode.

Term references are obtained in any of the following ways.

- *Passed as argument*
  The C-functions implementing foreign predicates are passed their arguments as term-references. These references may be read or unified. Writing to these variables causes undefined behaviour.
- *Created by PL_new_term_ref()*
  A term created by PL_new_term_ref() is normally used to build temporary terms or be written by one of the interface functions. For example, PL_get_arg() writes a reference to the term-argument in its last argument.
- *Created by PL_new_term_refs(int n)*
  This function returns a set of term refs with the same characteristics as PL_new_term_ref(). See PL_open_query().
- *Created by PL_copy_term_ref(term_t t)*
  Creates a new term-reference to the same term as the argument. The term may be written to. See figure 5.3.

Term-references can safely be copied to other C-variables of type term_t, but all copies will always refer to the same term.

term_t **PL_new_term_ref**()
Return a fresh reference to a term. The reference is allocated on the *local* stack. Allocating a term-reference may trigger a stack-shift on machines that cannot use sparse-memory management for allocation the Prolog stacks. The returned reference describes a variable.

term_t **PL_new_term_refs**(*int n*)
Return *n* new term references. The first term-reference is returned. The others are *t*+1, *t*+2, etc. There are two reasons for using this function. PL_open_query() expects the arguments as a set of consecutive term references and *very* time-critical code requiring a number of term-references can be written as:

```
pl_mypredicate(term_t a0, term_t a1)
{ term_t t0 = PL_new_term_refs(2);
  term_t t1 = t0+1;

  ...
}
```

term_t **PL_copy_term_ref**(*term_t from*)
Create a new term reference and make it point initially to the same term as *from*. This function is commonly used to copy a predicate argument to a term reference that may be written.

Interaction with the garbage collector and stack-shifter

Prolog implements two mechanisms for avoiding stack overflow: garbage collection and stack expansion. On machines that allow for it, Prolog will use virtual memory management to detect stack overflow and expand the runtime stacks. On other machines Prolog will reallocate the stacks and update all pointers to them. To do so, Prolog needs to know which data is referenced by C-code. As all Prolog data known by C is referenced through term references (`term_t`), Prolog has all information necessary to perform its memory management without special precautions from the C-programmer.

5.5.2 Other foreign interface types

atom_t An atom in Prologs internal representation. Atoms are pointers to an opaque structure. They are a unique representation for represented text, which implies that atom *A* represents the same text as atom *B* if-and-only-if *A* and *B* are the same pointer.

Atoms are the central representation for textual constants in Prolog The transformation of C a character string to an atom implies a hash-table lookup. If the same atom is needed often, it is advised to store its reference in a global variable to avoid repeated lookup.

functor_t A functor is the internal representation of a name/arity pair. They are used to find the name and arity of a compound term as well as to construct new compound terms. Like atoms they live for the whole Prolog session and are unique.

predicate_t Handle to a Prolog predicate. Predicate handles live forever (although they can loose their definition).

qid_t Query Identifier. Used by PL_open_query()/PL_next_solution()/PL_close_query() to handle backtracking from C.

fid_t Frame Identifier. Used by PL_open_foreign_frame()/PL_close_foreign_frame().

module_t A module is a unique handle to a Prolog module. Modules are used only to call predicates in a specific module.

foreign_t Return type for a C-function implementing a Prolog predicate.

control_t Passed as additional argument to non-deterministic foreign functions. See PL_retry*() and PL_foreign_context*().

install_t Type for the `install()` and `uninstall()` functions of shared or dynamic link libraries. See section 5.4.

5.6 The Foreign Include File

5.6.1 Argument Passing and Control

If Prolog encounters a foreign predicate at run time it will call a function specified in the predicate definition of the foreign predicate. The arguments (1, ..., arity) pass the Prolog arguments to the goal as Prolog terms. Foreign functions should be declared of type `foreign_t`. Deterministic foreign functions have two alternatives to return control back to Prolog:

void **PL_succeed**
Succeed deterministically. PL_succeed is defined as "return TRUE".

void **PL_fail**
Fail and start Prolog backtracking. PL_fail is defined as "return FALSE".

Non-deterministic Foreign Predicates

By default foreign predicates are deterministic. Using the `PL_FA_NONDETERMINISTIC` attribute (see PL_register_foreign()) it is possible to register a predicate as a non-deterministic predicate. Writing non-deterministic foreign predicates is slightly more complicated as the foreign function needs context information for generating the next solution. Note that the same foreign function should be prepared to be simultaneously active in more than one goal. Suppose the `natural_number_below_n/2` is a non-deterministic foreign predicate, backtracking over all natural numbers lower than the first argument. Now consider the following predicate:

```
quotient_below_n(Q, N) :-
        natural_number_below_n(N, N1),
        natural_number_below_n(N, N2),
        Q =:= N1 / N2, !.
```

In this predicate the function `natural_number_below_n/2` simultaneously generates solutions for both its invocations.

Non-deterministic foreign functions should be prepared to handle three different calls from Prolog:

Initial call (`PL_FIRST_CALL`)
Prolog has just created a frame for the foreign function and asks it to produce the first answer.

Redo call (`PL_REDO`)
The previous invocation of the foreign function associated with the current goal indicated it was possible to backtrack. The foreign function should produce the next solution.

Terminate call (`PL_CUTTED`)
The choice point left by the foreign function has been destroyed by a cut. The foreign function is given the opportunity to clean the environment.

Both the context information and the type of call is provided by an argument of type `control_t` appended to the argument list for deterministic foreign functions. The macro PL_foreign_control() extracts the type of call from the control argument. The foreign function can pass a context handle using the PL_retry*() macros and extract the handle from the extra argument using the PL_foreign_context*() macro.

void **PL_retry**(*long*)
The foreign function succeeds while leaving a choice point. On backtracking over this goal the foreign function will be called again, but the control argument now indicates it is a 'Redo' call and the macro PL_foreign_context() will return the handle passed via PL_retry(). This handle is a 30 bits signed value (two bits are used for status indication).

void **PL_retry_address**(*void **)
As PL_retry(), but ensures an address as returned by malloc() is correctly recovered by PL_foreign_context_address().

int **PL_foreign_control**(*control_t*)
Extracts the type of call from the control argument. The return values are described above. Note that the function should be prepared to handle the `PL_CUTTED` case and should be aware that the other arguments are not valid in this case.

long **PL_foreign_context**(*control_t*)
Extracts the context from the context argument. In the call type is `PL_FIRST_CALL` the context value is 0L. Otherwise it is the value returned by the last PL_retry() associated with this goal (both if the call type is `PL_REDO` as `PL_CUTTED`).

*void ** **PL_foreign_context_address**(*control_t*)
Extracts an address as passed in by PL_retry_address().

Note: If a non-deterministic foreign function returns using PL_succeed or PL_fail, Prolog assumes the foreign function has cleaned its environment. **No** call with control argument `PL_CUTTED` will follow.

The code of figure 5.2 shows a skeleton for a non-deterministic foreign predicate definition.

5.6.2 Atoms and functors

The following functions provide for communication using atoms and functors.

atom_t **PL_new_atom**(*const char **)
Return an atom handle for the given C-string. This function always succeeds. The returned handle is valid for the entire session.


```
typedef struct                  /* define a context structure */
{ ...
} context;

foreign_t
my_function(term_t a0, term_t a1, foreign_t handle)
{ struct context * ctxt;

  switch( PL_foreign_control(handle) )
  { case PL_FIRST_CALL:
        ctxt = malloc(sizeof(struct context));
        ...
        PL_retry_address(ctxt);
    case PL_REDO:
        ctxt = PL_foreign_context_address(handle);
        ...
        PL_retry_address(ctxt);
    case PL_CUTTED:
        free(ctxt);
        PL_succeed;
  }
}
```

Figure 5.2: Skeleton for non-deterministic foreign functions

*char ** **PL_atom_chars**(*atom_t atom*)
Return a C-string for the text represented by the given atom. The returned text will not be changed by Prolog. It is not allowed to modify the contents, not even 'temporary' as the string may reside in read-only memory.

functor_t **PL_new_functor**(*atom_t name, int arity*)
Returns a *functor identifier*, a handle for the name/arity pair. The returned handle is valid for the entire Prolog session. .F atom_t PL_functor_name functor_t f Return an atom representing the name of the given functor. .F int PL_functor_arity functor_t f Return the arity of the given functor.

5.6.3 Analysing Terms via the Foreign Interface

Each argument of a foreign function (except for the control argument) is of type *term_t*, an opaque handle to a Prolog term. Three groups of functions are available for the analysis of terms. The first just validates the type, like the Prolog predicates `var/1`, `atom/1`, etc and are called `PL_is_*()`. The second group attempts to translate the argument into a C primitive type. These predicates take a `term_t` and a pointer to the appropriate C-type and return `TRUE` or `FALSE` depending on successful or unsuccessful translation. If the translation fails, the pointed-to data is never modified.

Testing the type of a term

int **PL_term_type**(*term_t*)
Obtain the type of a term, which should be a term returned by one of the other interface predicates or passed as an argument. The function returns the type of the Prolog term. The type identifiers are listed below. Note that the extraction functions `PL_ge_t*()` also validate the type and thus the two sections below are equivalent.

```
if ( PL_is_atom(t) )
{ char *s;

  PL_get_atom_chars(t, &s);
  ...;
}
```

or

```
char *s;
if ( PL_get_atom_chars(t, &s) )
{ ...;
}
```

`PL_VARIABLE`	An unbound variable. The value of term as such is a unique identifier for the variable.
`PL_ATOM`	A Prolog atom.
`PL_STRING`	A Prolog string.
`PL_INTEGER`	A Prolog integer.
`PL_FLOAT`	A Prolog floating point number.
`PL_TERM`	A compound term. Note that a list is a compound term with name '.' and arity 2.

The functions PL_is_<type> are an alternative to PL_term_type(). The test "PL_is_var(term)" is equivalent to "PL_term_type(term) == PL_VARIABLE", but the first is considerably faster. On the other hand, using a switch over PL_term_type() is faster and more readable then using an if-then-else using the functions below. All these functions return either `TRUE` or `FALSE`.

int **PL_is_variable**(*term_t*)
Returns non-zero if *term* is a variable.

int **PL_is_atom**(*term_t*)
Returns non-zero if *term* is an atom.

int **PL_is_string**(*term_t*)
Returns non-zero if *term* is a string.

int **PL_is_integer**(*term_t*)
Returns non-zero if *term* is an integer.

int **PL_is_float**(*term_t*)
Returns non-zero if *term* is a float.

int **PL_is_compound**(*term_t*)
Returns non-zero if *term* is a compound term.

int **PL_is_functor**(*term_t*, *functor_t*)
Returns non-zero if *term* is compound and its functor is *functor*. This test is equivalent to PL_get_functor(), followed by testing the functor, but easier to write and faster.

int **PL_is_list**(*term_t*)
Returns non-zero if *term* is a compound term with functor ./2 or the atom `[]`.

int **PL_is_atomic**(*term_t*)
Returns non-zero if *term* is atomic (not variable or compound).

int **PL_is_number**(*term_t*)
Returns non-zero if *term* is an integer or float.

Reading data from a term

The functions `PL_get_*()` read information from a Prolog term. Most of them take two arguments. The first is the input term and the second is a pointer to the output value or a term-reference.

int **PL_get_atom**(*term_t +t, atom_t *a*)
If *t* is an atom, store the unique atom identifier over *a*. See also PL_string_from_atom() and PL_new_atom(). If there is no need to access the data (characters) of an atom, it is advised to manipulate atoms using their handle.

int **PL_get_atom_chars**(*term_t +t, char **s*)
If *t* is an atom, store a pointer to a 0-terminated C-string in *s*. It is explicitly **not** allows to modify the contents of this string. Some built-in atoms may have the string allocated in read-only memory, so 'temporary manipulation' can cause an error.

int **PL_get_string**(*term_t +t, char **s, int *len*)
If *t* is a string object, store a pointer to a 0-terminated C-string in *s* and the length of the string in *len*. Note that this pointer is invalidated by backtracking, garbage-collection and stack-shifts, so generally the only save operations are to pass it immediately to a C-function that doesn't involve Prolog.

int **PL_get_chars**(*term_t +t, char **s, unsigned flags*)
Convert the argument term *t* to a 0-terminated C-string. *flags* is a bitwise disjunction from two groups of constants. The first specifies which term-types should converted and the second how the argument is stored. Below is a specification of these constants. `BUF_RING` implies, if the data is not static (as from an atom), the data is copied to the next buffer from a ring of four (4) buffers. This is a convenient way of converting multiple arguments passed to a foreign predicate to C-strings. If BUF_MALLOC is used, the data must be freed using free() when not needed any longer.

CVT_ATOM	Convert if term is an atom
CVT_STRING	Convert if term is a string
CVT_LIST	Convert if term is a list of integers between 1 and 255
CVT_INTEGER	Convert if term is an integer (using %d)
CVT_FLOAT	Convert if term is a float (using %f)
CVT_NUMBER	Convert if term is a integer or float
CVT_ATOMIC	Convert if term is atomic
CVT_VARIABLE	Convert variable to print-name
CVT_ALL	Convert if term is any of the above, except for variables
BUF_DISCARDABLE	Data must copied immediately
BUF_RING	Data is stored in a ring of buffers
BUF_MALLOC	Data is copied to a new buffer returned by malloc()

int **PL_get_list_chars**(*+term_t l, char **s, unsigned flags*)
Same as `PL_get_chars(`*l*`, s, CVT_LIST|`*flags*`)`, provided *flags* contains no of the `CVT_*` flags.

int **PL_get_integer**(*+term_t t, int *i*)
If *t* is a Prolog integer, assign its value over *i*. On 32-bit machines, this is the same as PL_get_long(), but avoids a warning from the compiler. See also PL_get_long().

int **PL_get_long**(*term_t +t, long *i*)
If *t* is a Prolog integer, assign its value over *i*. Note that Prolog integers have limited value-range. If *t* is a floating point number that can be represented as a long, this function succeeds as well.

int **PL_get_pointer**(*term_t +t, void **ptr*)
In the current system, pointers are represented by Prolog integers, but need some manipulation to make sure they do not get truncated due to the limited Prolog integer range. PL_put_pointer()/PL_get_pointer() guarantees pointers in the range of malloc() are handled without truncating.

int **PL_get_float**(*term_t +t, double *f*)
If *t* is a float or integer, its value is assigned over *f*.

int **PL_get_functor**(*term_t +t, functor_t *f*)
If *t* is compound or an atom, the Prolog representation of the name-arity pair will be assigned over *f*. See also PL_get_name_arity() and PL_is_functor().

int **PL_get_name_arity**(*term_t +t, atom_t *name, int *arity*)
If *t* is compound or an atom, the functor-name will be assigned over *name* and the arity over *arity*. See also PL_get_functor() and PL_is_functor().

int **PL_get_module**(*term_t +t, module_t *module*)
If *t* is an atom, the system will lookup or create the corresponding module and assign an opaque pointer to it over *module*,.

int **PL_get_arg**(*int index, term_t +t, term_t -a*)
If *t* is compound and index is between 1 and arity (including), assign *a* with a term-reference to the argument.

Reading a list

The functions from this section are intended to read a Prolog list from C. Suppose we expect a list of atoms, the following code will print the atoms, each on a line:


```
foreign_t
pl_write_atoms(term_t l)
{ term_t head = PL_new_term_ref();      /* variable for the elements */
  term_t list = PL_copy_term_ref();     /* copy as we need to write */

  while( PL_get_list(list, head, list) )
  { char *s;

    if ( PL_get_atom_chars(head, &s) )
      Sprintf("%s\n", s);
    else
      PL_fail;
  }

  return PL_get_nil(list);              /* test end for [] */
}
```

int **PL_get_list**(*term_t +l, term_t -h, term_t -t*)
If *l* is a list and not [] assign a term-reference to the head to *h* and to the tail to *t*.

int **PL_get_head**(*term_t +l, term_t -h*)
If *l* is a list and not [] assign a term-reference to the head to *h*.

int **PL_get_tail**(*term_t +l, term_t -t*)
If *l* is a list and not [] assign a term-reference to the tail to *t*.

int **PL_get_nil**(*term_t +l*)
Succeeds if represents the atom [].

An example: defining `display/1` in C

Figure 5.3 shows a definition of `display/1` to illustrate the described functions.

5.6.4 Constructing Terms

Terms can be constructed using functions from the `PL_put_*()` and `PL_cons_*()` families. This approach builds the term 'inside-out', starting at the leaves and subsequently creating compound terms. Alternatively, terms may be created 'top-down', first creating a compound holding only variables and subsequently unifying the arguments. This section discusses functions for the first approach. This approach is generally used for creating arguments for PL_call() and PL_open_query.

void **PL_put_variable**(*term_t -t*)
Put a fresh variable in the term. The new variable lives on the global stack. Note that the initial variable lives on the local stack and is lost after a write to the term-references. After using this function, the variable will continue to live.

void **PL_put_atom**(*term_t -t, atom_t a*)
Put an atom in the term reference from a handle. See also PL_new_atom() and PL_string_from_atom().

```
foreign_t
pl_display(term_t t)
{ functor_t functor;
  int arity, len, n;
  char *s;

  switch( PL_term_type(t) )
  { case PL_VARIABLE:
    case PL_ATOM:
    case PL_INTEGER:
    case PL_FLOAT:
      PL_get_chars(t, &s, CVT_ALL);
      Sprintf("%s", s);
      break;
    case PL_STRING:
      PL_get_string_chars(t, &s, &len);
      Sprintf("\"%s\"", s);
      break;
    case PL_TERM:
    { term_t a = PL_new_term_ref();

      PL_get_name_arity(t, &name, &arity);
      Sprintf("%s(", PL_string_from_atom(name));
      for(n=1; n<=arity; n++)
      { PL_get_arg(n, t, a);
        if ( n > 1 )
          Sprintf(", ");
        pl_display(a);
      }
      Sprintf(")");
      break;
    default:
      PL_fail;                          /* should not happen */
  }

  PL_succeed;
}
```

Figure 5.3: A Foreign definition of `display/1`

void **PL_put_atom_chars**(*term_t -t, const char *chars*)
Put an atom in the term-reference constructed from the 0-terminated string. The string itself will never be references by Prolog after this function.

void **PL_put_string_chars**(*term_t -t, const char *chars*)
Put a string in the term-reference. The data will be copied.

void **PL_put_list_chars**(*term_t -t, const char *chars*)
Put a list of ASCII values in the term-reference.

void **PL_put_integer**(*term_t -t, long i*)
Put a Prolog integer in the term reference.

void **PL_put_pointer**(*term_t -t, void *ptr*)
Put a Prolog integer in the term-reference. Provided ptr is in the 'malloc()-area', PL_get_pointer() will get the pointer back.

void **PL_put_float**(*term_t -t, double f*)
Put a floating-point value in the term-reference.

void **PL_put_functor**(*term_t -t, functor_t functor*)
Create a new compound term from *functor* and bind *t* to this term. All arguments of the term will be variables. To create a term with instantiated arguments, either instantiate the arguments using the `PL_unify_*()` functions or use PL_cons_functor().

void **PL_put_list**(*term_t -l*)
Same as `PL_put_functor(l, PL_new_functor(PL_new_atom("."), 2))`.

void **PL_put_nil**(*term_t -l*)
Same as `PL_put_atom_chars("[]")`.

void **PL_put_term**(*term_t -t1, term_t +t2*)
Make *t1* point to the same term as *t2*.

void **PL_cons_functor**(*term_t -h, functor_t f, ...*)
Create a term, whose arguments are filled from variable argument list holding the same number of term_t objects as the arity of the functor. To create the term `animal(gnu, 50)`, use:

```
term_t a1 = PL_new_term_ref();
term_t a2 = PL_new_term_ref();
term_t t;

PL_put_atom_chars(a1, "gnu");
PL_put_integer(a2, 50);
PL_cons_functor(t, PL_new_functor(PL_new_atom("animal"), 2),
                a1, a2);
```

After this sequence, the term-references *a1* and *a2* may be used for other purposes.

void **PL_cons_list**(*term_t -l, term_t +h, term_t +t*)
Create a list (cons-) cell in *l* from the head and tail. The code below creates a list of atoms from a `char **`. The list is built tail-to-head. The `PL_unify_*()` functions can be used to build a list head-to-tail.

```
void
put_list(term_t l, int n, char **words)
{ term_t a = PL_new_term_ref();

  PL_put_nil(l);
  while( --n >= 0 )
  { PL_put_atom_chars(a, words[n]);
    PL_put_list(l, a, l);
  }
}
```

5.6.5 Unifying data

The functions of this sections *unify* terms with other terms or translated C-data structures. Except for PL_unify(), the functions of this section are specific to SWI-Prolog. They have been introduced to make translation of old code easier, but also because they provide for a faster mechanism for returning data to Prolog that requires less term-references. Consider the case where we want a foreign function to return the host name of the machine Prolog is running on. Using the `PL_get_*()` and `PL_put_*()` functions, the code becomes:

```
foreign_t
pl_hostname(term_t name)
{ char buf[100];

  if ( gethostname(buf, sizeof(buf)) )
  { term_t tmp = PL_new_term_ref();

    PL_put_atom_chars(tmp, buf);
    return PL_unify(name, buf);
  }

  PL_fail;
}
```

Using PL_unify_atom_chars(), this becomes:

```
foreign_t
pl_hostname(term_t name)
{ char buf[100];

  if ( gethostname(buf, sizeof(buf)) )
    return PL_unify_atom_chars(name, buf);

  PL_fail;
}
```

int **PL_unify**(*term_t ?t1, term_t ?t2*)
Unify two Prolog terms and return non-zero on success.

int **PL_unify_atom**(*term_t ?t, atom_t a*)
Unify *t* with the atom *a* and return non-zero on success.

int **PL_unify_atom_chars**(*term_t ?t, const char *chars*)
Unify *t* with an atom created from *chars* and return non-zero on success.

int **PL_unify_list_chars**(*term_t ?t, const char *chars*)
Unify *t* with a list of ASCII characters constructed from *chars*.

int **PL_unify_string_chars**(*term_t ?t, const char *chars*)
Unify *t* with a Prolog string object created from *chars*.

int **PL_unify_integer**(*term_t ?t, long n*)
Unify *t* with a Prolog integer from *n*.

int **PL_unify_float**(*term_t ?t, double f*)
Unify *t* with a Prolog float from *f*.

int **PL_unify_pointer**(*term_t ?t, void *ptr*)
Unify *t* with a Prolog integer describing the pointer. See also PL_put_pointer() and PL_get_pointer().

int **PL_unify_functor**(*term_t ?t, functor_t f*)
If *t* is a compound term with the given functor, just succeed. If it is unbound, create a term and bind the variable, else fails. Not that this function does not create a term if the argument is already instantiated.

int **PL_unify_list**(*term_t ?l, term_t -h, term_t -t*)
Unify *l* with a list-cell (`./2`). If successful, write a reference to the head of the list to *h* and a reference to the tail of the list in *t*. This reference may be used for subsequent calls to this function. Suppose we want to return a list of atoms from a `char **`. We could use the example described by PL_put_list(), followed by a call to PL_unify(), or we can use the code below. If the predicate argument is unbound, the difference is minimal (the code based on PL_put_list() is probably slightly faster). If the argument is bound, the code below may fail before reaching the end of the word-list, but even if the unification succeeds, this code avoids a duplicate (garbage) list and a deep unification.

```
foreign_t
pl_get_environ(term_t env)
{ term_t l = PL_copy_term_ref(env);
  term_t a = PL_new_term_ref();
  extern char **environ;

  while(*environ)
  { if ( !PL_unify_list(l, a, l) ||
         !PL_unify_atom_chars(a, *environ) )
      PL_fail;
  }

  return PL_unify_nil(l);
}
```

int **PL_unify_nil**(*term_t ?l*)
Unify *l* with the atom `[]`.

int **PL_unify_arg**(*int index, term_t ?t, term_t ?a*)
Unifies the *index-th* argument (1-based) of *t* with *a*.

int **PL_unify_term**(*term_t ?t, ...*)
Unify *t* with a (normally) compound term. The remaining arguments is a sequence of a type identifier, followed by the required arguments. This predicate is an extension to the Quintus and SICStus foreign interface from which the SWI-Prolog foreign interface has been derived, but has proved to be a powerful and comfortable way to create compound terms from C. Due to the vararg packing/unpacking and the required type-switching this interface is slightly slower than using the primitives. Please note that some bad C-compilers have fairly low limits on the number of arguments that may be passed to a function.

The type identifiers are:

`PL_VARIABLE` *none*
: No op. Used in arguments of `PL_FUNCTOR`.

`PL_ATOM` *atom_t*
: Unify the argument with an atom, as in PL_unify_atom().

`PL_INTEGER` *long*
: Unify the argument with an integer, as in PL_unify_integer().

`PL_FLOAT` *double*
: Unify the argument with a float, as in PL_unify_float(). Note that, as the argument is passed using the C vararg conventions, a float must be casted to a double explicitly.

`PL_STRING` *const char **
: Unify the argument with a string object, as in PL_unify_string_chars().

`PL_TERM` *term_t*
: Unify a subterm. Note this may the return value of a PL_new_term_ref() call to get access to a variable.

`PL_CHARS` *const char **
: Unify the argument with an atom, constructed from the C `char *`, as in PL_unify_atom_chars().

`PL_FUNCTOR` *functor_t, ...*
: Unify the argument with a compound term. This specification should be followed by exactly as many specifications as the number of arguments of the compound term.

`PL_LIST` *int length, ...*
: Create a list of the indicated length. The following arguments contain the elements of the list.

For example, to unify an argument with the term `language(dutch)`, the following skeleton may be used:

```
static functor_t FUNCTOR_language1;

static void
init_constants()
{ FUNCTOR_language1 = PL_new_functor(PL_new_atom("language"), 1);
}

foreign_t
pl_get_lang(term_t r)
{ return PL_unify_term(r,
                       PL_FUNCTOR, FUNCTOR_language1,
                           PL_CHARS, "dutch");
}

install_t
install()
{ PL_register_foreign("get_lang", 1, pl_get_lang, 0);
  init_constants();
}
```


5.6.6 Calling Prolog from C

The Prolog engine can be called from C. There are to interfaces for this. For the first, a term is created that could be used as an argument to `call/1` and next PL_call() is used to call Prolog. This system is simple, but does not allow to inspect the different answers to a non-deterministic goal and is relatively slow as the runtime system needs to find the predicate. The other interface is based on PL_open_query(), PL_next_solution() and PL_cut_query() or PL_close_query(). This mechanism is more powerful, but also more complicated to use.

Predicate references

This section discusses the functions used to communicate about predicates. Though a Prolog predicate may defined or not, redefined, etc., a Prolog predicate has a handle that is not destroyed, nor moved. This handle is known by the type `predicate_t`.

predicate_t **PL_pred**(*functor_t f, module_t m*)
: Return a handle to a predicate for the specified name/arity in the given module. This function always succeeds, creating a handle for an undefined predicate if no handle was available.

predicate_t **PL_predicate**(*const char *name, int arity, const char* module*)
: Same a PL_pred(), but provides a more convenient interface to the C-programmer.

void **PL_predicate_info**(*predicate_t p, atom_t *n, int *a, module_t *m*)
: Return information on the predicate *p*. The name is stored over *n*, the arity over *a*, while *m* receives the definition module. Note that the latter need not be the same as specified with PL_predicate(). If the predicate was imported into the module given to PL_predicate(), this function will return the module where the predicate was defined.

Initiating a query from C

This section discusses the functions for creating and manipulating queries from C. Note that a foreign context can have at most one active query. This implies it is allowed to make strictly nested calls between C and Prolog (Prolog calls C, calls Prolog, calls C, etc., but it is *not* allowed to open multiple queries and start generating solutions for each of them by calling PL_next_solution(). Be sure to call PL_cut_query() or PL_close_query() on any query you opened before opening the next or returning control back to Prolog.

qid_t **PL_open_query**(*module_t ctx, int debug, predicate_t p, term_t +t0*)
: Opens a query and returns an identifier for it. This function always succeeds, regardless whether the predicate is defined or not. *ctx* is the *context module* of the goal. When `NULL`, the context module of the calling context will be used, or `user` if there is no calling context (as may happen in embedded systems). Note that the context module only matters for *module_transparent* predicates. See `context_module/1` and `module_transparent/1`. The *debug* argument is normally `TRUE`. If *FALSE* is specified, the goal is run in 'nodebug' mode, regardless of the current debug mode. The *p* argument specifies the predicate, and should be the result of a call to PL_pred() or PL_predicate(). Note that it is allowed to store this handle as global data and reuse it for future queries. The term-reference *t0* is the first of a vector of term-references as returned by PL_new_term_refs(n).

  The example below opens a query to the predicate `is_a/2` to find the ancestor of for some name.

```
char *
ancestor(const char *me)
{ term_t a0 = PL_new_term_refs(2);
  static predicate_t p;

  if ( !p )
    p = PL_predicate("is_a", 2, "database");

  PL_put_atom_chars(a0, me);
  PL_open_query(NULL, TRUE, p, a0);
  ...
}
```

int **PL_next_solution**(*qid_t qid*)
Generate the first (next) solution for the given query. The return value is *TRUE* if a solution was found, or *FALSE* to indicate the query could not be proven. This function may be called repeatedly until it fails to generate all solutions to the query.

void **PL_cut_query**(*qid*)
Discards the query, but does not delete any of the data created by the query. It just invalidate *qid*, allowing for a new call to PL_open_query() in this context.

void **PL_close_query**(*qid*)
As PL_cut_query(), but all data and bindings created by the query are destroyed.

int **PL_call_predicate**(*module_t m, int debug, predicate_t pred, term_t +t0*)
Shorthand for PL_open_query(), PL_next_solution(), PL_cut_query(), generating a single solution. The arguments are the same as for PL_open_query(), the return value is the same as PL_next_solution().

int **PL_call**(*term_t, module_t*)
Call term just like the Prolog predicate `once/1`. *Term* is called in the specified module, or in the context module if module_t = NULL. Returns `TRUE` if the call succeeds, `FALSE` otherwise. Figure 5.4 shows an example to obtain the number of defined atoms. All checks are omitted to improve readability.

5.6.7 Discarding Data

The Prolog data created and term-references needed to setup the call and/or analyse the result can in most cases be discarded right after the call. PL_close_query() allows for destructing the data, while leaving the term-references. The calls below may be used to destroy term-references and data. See figure 5.4 for an example.

fid_t **PL_open_foreign_frame**()
Created a foreign frame, holding a mark that allows the system to undo bindings and destroy data created after it as well as providing the environment for creating term-references. This function is called by the kernel before calling a foreign predicate.

void **PL_close_foreign_frame**(*fid_t id*)
Discard all term-references created after the frame was opened. All other Prolog data is retained. This function is called by the kernel whenever a foreign function returns control back to Prolog.

void **PL_discard_foreign_frame**(*fid_t id*)
Same as PL_close_foreign_frame(), but also undo all bindings made since the open and destroy all Prolog data.

It is obligatory to call either of the two closing functions to discard a foreign frame. Foreign frames may be nested.

```
int
count_atoms()
{ fid_t fid = PL_open_foreign_frame();
  term_t goal  = PL_new_term_ref();
  term_t a1    = PL_new_term_ref();
  term_t a2    = PL_new_term_ref();
  functor_t s2 = PL_new_functor(PL_new_atom("statistics"), 2);
  int atoms;

  PL_put_atom_chars(a1, "atoms");
  PL_cons_functor(goal, s2, a1, a2);
  PL_call(t, NULL);         /* call it in current module */

  PL_get_integer(a2, &atoms);
  PL_discard_foreign_frame(fid);

  return atoms;
}
```

Figure 5.4: Calling Prolog

5.6.8 Foreign Code and Modules

Modules are identified via a unique handle. The following functions are available to query and manipulate modules.

module_t **PL_context**()
Return the module identifier of the context module of the currently active foreign predicate. .F PL_strip_module 3 term_t +raw, module_t *m, term_t -plain Utility function. If *term_t* is a term, possibly holding the module construct *module:rest* this function will make *plain* a reference to *rest* and fill *module ** with *module*. For further nested module constructs the inner most module is returned via *module **. If *term* is not a module construct *term* will simply be put in *plain*. If *module ** is `NULL` it will be set to the context module. Otherwise it will be left untouched. The following example shows how to obtain the plain term and module if the default module is the user module:

```
{ module m = PL_new_module(PL_new_atom("user"));
  term_t plain = PL_new_term_ref();

  PL_strip_module(term, &m, plain);
  ...
```

atom_t **PL_module_name**(*module_t*)
Return the name of *module* as an atom.

module_t **PL_new_module**(*atom_t*)
Find an existing or create a new module with name specified by the atom *atomic*.

5.6.9 Miscellaneous

int **PL_compare**(*term_t t1, term_t t2*)
Compares two terms using the standard order of terms and returns -1, 0 or 1. See also `compare/3`.

5.6.10 Catching Signals (Software Interrupts)

SWI-Prolog catches the Unix signals SIGINT, SIGFPE and SIGSEGV. To avoid problems with foreign code attempting to catch these signals foreign code should call PL_signal() to install signal handlers rather than the Unix library function signal(). SWI-Prolog will always handle SIGINT itself. SIGFPE and SIGSEGV are passed to the foreign code handlers if Prolog did not expect that signal.

void (***PL_signal**(*sig, func*))()
This function should be used to install signal handlers rather than the Unix library function signal(). It ensures consistent signal handling between SWI-Prolog and the foreign code and reinstalls signal handlers if a state created with `save_program/1` is restarted.

5.6.11 Errors and warnings

Two standard functions are available to print standard Prolog errors to the standard error stream.

int **PL_warning**(*format, a1, ...*)
Print an error message starting with '`[WARNING: `', followed by the output from *format*, followed by a '`]`' and a newline. Then start the tracer. *format* and the arguments are the same as for printf(2). Always returns FALSE.

5.6.12 Environment Control from Foreign Code

int **PL_action**(*int, C_type*)
Perform some action on the Prolog system. *int* describes the action, *C_type* provides the argument if necessary. The actions are listed in table 5.1.

5.6.13 Querying Prolog

C_type **PL_query**(*int*)
Obtain status information on the Prolog system. The actual argument type depends on the information required. *int* describes what information is wanted. The options are given in table 5.2.

`PL_ACTION_TRACE`	Start Prolog tracer
`PL_ACTION_DEBUG`	Switch on Prolog debug mode
`PL_ACTION_BACKTRACE`	Print backtrace on current output stream. The argument (an int) is the number of frames printed.
`PL_ACTION_HALT`	Halt Prolog execution. This action should be called rather than Unix exit() to give Prolog the opportunity to clean up. This call does not return.
`PL_ACTION_ABORT`	Generate a Prolog abort. This call does not return.
`PL_ACTION_BREAK`	Create a standard Prolog break environment. Returns after the user types control-D.
`PL_ACTION_SYMBOLFILE`	The argument (a char *) is considered to be hold the symbolfile for further incremental loading. Should be called by user applications that perform incremental loading as well and want to inform Prolog of the new symbol table.

Table 5.1: PL_action() options

`PL_QUERY_ARGC`	Return an integer holding the number of arguments given to Prolog from Unix.
`PL_QUERY_ARGV`	Return a char ** holding the argument vector given to Prolog from Unix.
`PL_QUERY_SYMBOLFILE`	Return a char * holding the current symbol file of the running process.
`PL_QUERY_ORGSYMBOLFILE`	Return the initial symbol file (before loading) of Prolog. By setting the symbol file to this value no name clashes can occur with previously loaded foreign files (but no symbols can be shared with earlier loaded modules as well).
`PL_MAX_INTEGER`	Return a long, representing the maximal integer value represented by Prolog's tagged integers.
`PL_MIN_INTEGER`	Return a long, represented the minimal integer value.
`PL_QUERY_VERSION`	Return a long, representing the version as $10,000 \times M + 100 \times m + p$, where M is the major, m the minor version number and p the patch-level. For example, the current version yields `207070`.

Table 5.2: PL_query() options

5.6.14 Registering Foreign Predicates

int **PL_register_foreign**(*name, arity, function, flags*)
Register a C-function to implement a Prolog predicate. After this call returns successfully a predicate with name *name* (a char *) and arity *arity* (a C int) is created. When called in Prolog, Prolog will call *function*. *flags* forms bitwise or'ed list of options for the installation. These are:

`PL_FA_NOTRACE`	Predicate cannot be seen in the tracer
`PL_FA_TRANSPARENT`	Predicate is module transparent
`PL_FA_NONDETERMINISTIC`	Predicate is non-deterministic. This attribute is currently ignored, but will probably be used in future versions.

5.6.15 Foreign Code Hooks

For various specific applications some hooks re provided.

PL_dispatch_hook_t **PL_dispatch_hook**(*PL_dispatch_hook_t*)
If this hook is not NULL, this function is called when reading from the terminal. It is supposed to dispatch events when SWI-Prolog is connected to a window environment. It can return two values: `PL_DISPATCH_INPUT` indicates Prolog input is available on file descriptor 0 or `PL_DISPATCH_TIMEOUT` to indicate a timeout. The old hook is returned. The type `PL_dispatch_hook_t` is defined as:

```
typedef int  (*PL_dispatch_hook_t)(void);
```

void **PL_abort_hook**(*PL_abort_hook_t*)
Install a hook when `abort/0` is executed. SWI-Prolog `abort/0` is implemented using C setjmp()/longjmp() construct. The hooks are executed in the reverse order of their registration after the longjmp() took place and before the Prolog toplevel is reinvoked. The type `PL_abort_hook_t` is defined as:

```
typedef void (*PL_abort_hook_t)(void);
```

int **PL_abort_unhook**(*PL_abort_hook_t*)
Remove a hook installed with PL_abort_hook(). Returns `FALSE` if no such hook is found, `TRUE` otherwise.

void **PL_reinit_hook**(*PL_reinit_hook_t*)
Install a hook that is called when a saved program (using `save_program/[1,2]`) is restored. The hooks are called in reverse order. The type `PL_reinit_hook_t` is defined as:

```
typedef void (*PL_reinit_hook_t)(int argc, char **argv);
```

int **PL_reinit_unhook**(*PL_reinit_hook_t*)
Remove a hook installed with PL_reinit_hook(). Returns `FALSE` if no such hook is found, `TRUE` otherwise.

5.6.16 Embedding SWI-Prolog in a C-program

As of version 2.1.0, SWI-Prolog may be embedded in a C-program. To reach at a compiled C-program with SWI-Prolog as an embedded application is very similar to creating a statically linked SWI-Prolog executable as described in section 5.4.1.

The file `.../pl/include/stub.c` defines SWI-Prologs default main program:


```
int
main(int argc, char **argv, char **env)
{ if ( !PL_initialise(argc, argv, env) )
    PL_halt(1);

  PL_install_readline();        /* delete if you don't want readline */

  PL_halt(PL_toplevel() ? 0 : 1);
}
```

This may be replaced with your own main C-program. The interface function PL_initialise() **must** be called before any of the other SWI-Prolog foreign language functions described in this chapter. PL_initialise() interprets all the command-line arguments, except for the `-t`*toplevel* flag that is interpreted by PL_toplevel().

int **PL_initialise**(*int argc, char **argv, char **environ*)
Initialises the SWI-Prolog heap and stacks, restores the boot QLF file, loads the system and personal initialisation files, runs the `at_initialisation/1` hooks and finally runs the `-g goal` hook.

PL_initialise() returns 1 if all initialisation succeeded and 0 otherwise. Various fatal errors may cause PL_initialise to call PL_halt(1), preventing it from returning at all.

void **PL_install_readline**()
Installs the GNU-readline line-editor. Embedded applications that do not use the Prolog toplevel should normally delete this line, shrinking the Prolog kernel significantly.

int **PL_toplevel**()
Runs the goal of the `-t`*toplevel* switch (default `prolog/0`) and returns 1 if successful, 0 otherwise.

void **PL_halt**(*int status*)
Cleanup the Prolog environment and calls exit() with the status argument.

5.7 Linking embedded applications using plld

The utility program `plld` may be used to link a combination of C-files and Prolog files into a standalone executable. It is a simple Bourne-shell script that automates most of the steps outlined in the previous sections.

In the normal usage, a copy is made of the default embedding template `.../pl/include/stub.c`. Additional foreign predicates are defined and added to the extension table `PL_extensions`. The main() routine is modified to suit your application. PL_initialise() **must** be passed the program-name (`argv[0]`). The other elements of the command-line may be modified. Next, `plld` is typically invoked as:

```
plld -o output stubfile.c [other-c-or-o-files] [plfiles]
```

`plld` will first split the options into various groups for both the C-compiler and the Prolog compiler. Next, it will add various default options to the C-compiler and call it to create an executable holding

the user's C-code and the Prolog kernel. Then, it will call the SWI-Prolog compiler to create a saved state from the provided Prolog files and finally, it will attach this saved state to the created emulator to create the requested executable.

Below, it is described how the options are split and which additional options are passed.

`-help`
: Print brief synopsis.

`-pl` *prolog*
: Select the prolog to use. This prolog is used for two purposes: get the home-directory as well as the compiler/linker options and create a saved state of the Prolog code.

`-v`
: Select verbose operation, showing the various programs and their options.

`-o` *outfile*
: Reserved to specify the final output file.

`-l`*library*
: Specifies a library for the C-compiler. By default, `-lpl` and the libraries needed by the Prolog kernel are given.

`-L`*library-directory*
: Specifies a library directory for the C-compiler. By default the directory containing -lpl for the current architecture is passed.

`-g` or `-I`*include-directory* or `-D`*definition*
: These options are passed to the C-compiler. By default, the include directory containing `<SWI-Prolog.h>` is passed. `plld` adds two additional `-D`*def* flags:

  `-D__SWI_PROLOG__` Indicates the code is to be connected to SWI-Prolog.

  `-D__SWI_EMBEDDED__` Indicates the creation of an embedded program.

`*.o` or `*.c` or `*.C` or `*.cxx` or `*.cpp`
: Passed as input files to the C-compiler

`*.pl` or `*.qlf`
: Passed as input files to the Prolog compiler to create the saved-state.

`*`
: I.e. all other options. These are passed as linker options to the C-compiler.

5.7.1 A simple example

The following is a very simple example going through all the steps outlined above. It provides an arithmetic expression evaluator. We will call the application `calc` and define it in the files `calc.c` and `calc.pl`. The Prolog file is simple:

```
calc(Atom) :-
        term_to_atom(Expr, Atom),
        A is Expr,
        write(A),
        nl.
```


The C-part of the application parses the command-line options, initialises the Prolog engine, locates the `calc/1` predicate and calls it. The coder is in figure 5.5.

The application is now created using the following command-line:

```
% plld -o calc calc.c calc.pl
```

The following indicates the usage of the application:

```
% calc pi/2
1.5708
```

5.8 Example of Using the Foreign Interface

Below is an example showing all stages of the declaration of a foreign predicate that transforms atoms possibly holding uppercase letters into an atom only holding lower case letters. Figure 5.6 shows the C-source file, figure 5.7 illustrates compiling and loading of foreign code.

```
#include <stdio.h>
#include <SWI-Prolog.h>

PL_extension PL_extensions [] =
{
/*{ "name",     arity,  function,       PL_FA_<flags> },*/

  { NULL,       0,      NULL,           0 }     /* terminating line */
};


#define MAXLINE 1024

int
main(int argc, char **argv, char **env)
{ char expression[MAXLINE];
  char *e = expression;
  char *program = argv[0];
  char *plav[2];
  int n;

  /* combine all the arguments in a single string */

  for(n=1; n<argc; n++)
  { if ( n != 1 )
      *e++ = ´ ´;
    strcpy(e, argv[n]);
    e += strlen(e);
  }

  /* make the argument vector for Prolog */

  plav[0] = program;
  plav[1] = NULL;

  /* initialise Prolog */

  if ( !PL_initialise(1, plav, env) )
    PL_halt(1);

  /* Lookup calc/1 and make the arguments and call */

  { predicate_t pred = PL_predicate("calc", 1, "user");
    term_t h0 = PL_new_term_refs(1);
    int rval;

    PL_put_atom_chars(h0, expression);
    rval = PL_call_predicate(NULL, FALSE, pred, h0);

    PL_halt(rval ? 0 : 1);
  }

  return 0;
}
```


Figure 5.5: C-source for the calc application


```
/*  Include file depends on local installation */
#include <SWI-Prolog.h>
#include <stdlib.h>
#include <ctype.h>

foreign_t
pl_lowercase(term_t u, term_t l)
{ char *copy;
  char *s, *q;
  int rval;

  if ( !PL_get_atom_chars(u, &s) )
    return PL_warning("lowercase/2: instantiation fault");
  copy = malloc(strlen(s)+1);

  for( q=copy; *s; q++, s++)
    *q = (isupper(*s) ? tolower(*s) : *s);
  *q = ´\0´;

  rval = PL_unify_atom_chars(l, copy);
  free(copy);

  return rval;
}

install_t
install()
{ PL_register_foreign("lowercase", 2, pl_lowercase, 0);
}
```

Figure 5.6: Lowercase source file

```
% gcc -I/usr/local/lib/pl-2.2.0/include -fpic -c lowercase.c
% gcc -shared -o lowercase.so lowercase.o
% pl
Welcome to SWI-Prolog (version 2.1.11)
Copyright (c) 1993-1995 University of Amsterdam.  All rights reserved.

1 ?- load_foreign_library(lowercase).

Yes
2 ?- lowercase(´Hello World!´, L).

L = ´hello world!´

Yes
```

Figure 5.7: Compiling the C-source and loading the object file

5.9 Notes on Using Foreign Code

5.9.1 Memory Allocation

SWI-Prolog's memory allocation is based on the malloc() library routines. Foreign applications can safely use malloc(), realloc() and free(). Memory allocation using brk() or sbrk() is not allowed as these calls conflict with malloc().

5.9.2 Debugging Foreign Code

Statically linked foreign code or embedded systems can be debugged normally. Most modern environments provide debugging tools for dynamically loaded shared objects or dynamic load libraries. The following example traces the code of lowercase using gdb(1) in a Unix environment.

```
% gcc -I/usr/local/lib/pl-2.2.0/include -fpic -c -g lowercase.c
% gcc -shared -o lowercase.so lowercase.o
% gdb pl
(gdb) r
Welcome to SWI-Prolog (version 2.1.11)
Copyright (c) 1993-1995 University of Amsterdam.  All rights reserved.
?- load_foreign_library(lowercase).
<type Control-C>
(gdb) shared                    % loads symbols for shared objects
(gdb) break pl_lowercase
(gdb) continue
?- lowercase(´HELLO´, X).
```

5.9.3 Name Conflicts in C modules

In the current version of the system all public C functions of SWI-Prolog are in the symbol table. This can lead to name clashes with foreign code. Someday I should write a program to strip all these symbols from the symbol table (why does Unix not have that?). For now I can only suggest to give your function another name. You can do this using the C preprocessor. If –for example– your foreign package uses a function warning(), which happens to exist in SWI-Prolog as well, the following macro should fix the problem.

```
#define warning warning_
```

Note that shared libraries do not have this problem as the shared library loader will only look for symbols in the main executable for symbols that are not defined in the library itself.

5.9.4 Compatibility of the Foreign Interface

The term-reference mechanism was first used by Quintus Prolog version 3. SICStus Prolog version 3 is strongly based on the Quintus interface. The described SWI-Prolog interface is similar to using the Quintus or SICStus interfaces, defining all foreign-predicate arguments of type `+term`. SWI-Prolog explicitly uses type `functor_t`, while Quintus and SICStus uses name + arity. As the names of the

functions differ from Prolog to Prolog, a simple macro layer dealing with the names can also deal with this detail. For example:

```
#define QP_put_functor(t, n, a) PL_put_functor(t, PL_new_functor(n, a))
```

The `PL_unify_*()` functions are lacking from the Quintus and SICStus interface. They can easily be emulated or the put/unify approach should be used to write compatible code.

The PL_open_foreign_frame()/PL_close_foreign_frame() combination is lacking from both other Prologs. SICStus has PL_new_term_refs(0), followed by PL_reset_term_refs() that allows for discarding term references.

The Prolog interface for the graphical user interface package XPCE shares about 90% of the code using a simple macro layer to deal with different naming and calling conventions of the interfaces.

Chapter 6

Generating Runtime Applications

This chapter describes the features of SWI-Prolog for delivering applications that can run without the development version of the system installed.

A SWI-Prolog built application consists of at least two parts: the emulator and the compiled application. The latter is in the same format as a SWI-Prolog boot-file and SWI-Prolog pre-compiled (QLF) file. This format is fast loadable and abstracted just far enough to be machine independent. This implies an application delivered in binary format can run on any computer for which an emulator is available without modification.

qsave_program(*+File, +ListOfOptions*)
Saves the current state of the program to the file 'File'. The result is an executable shell-script, that will start the emulator. *ListOfOptions* is a list of *Key = Value* pairs. The available keys are described in table 6.1.

Key	Option	Type	Description
local	**-L**	K-bytes	Size (Limit) of local stack
global	**-G**	K-bytes	Size (Limit) of global stack
trail	**-T**	K-bytes	Size (Limit) of trail stack
argument	**-A**	K-bytes	Size (Limit) of argument stack
goal	**-g**	atom	Initialisation goal
toplevel	**-t**	atom	Prolog toplevel goal
init_file	**-f**	atom	Personal initialisation file
autoload		bool	If true, run `autoload/0` first
map		atom	File containing info on dump
op		`save/standard`	Save operator declarations?
stand_alone		bool	Include the emulator in the state

Table 6.1: Key = Value pairs for `qsave_program/2`

The `/bin/sh` script contains the following data:

1. The **shell script header** starts as:

```
#!/bin/sh
#SAVE-VERSION=<num>
#PROLOG-VERSION=<num>
exec ${SWIPL-/path-to-emulator} -x $0 "$@"
```


2. The **settings** section contains the default values for the various command line options.
3. The **predicates** section contains all predicates from the currently running system. Clauses of predicates defined as *volatile* (see `volatile/1`) are **not** saved. Neither are foreign predicates (see also below).
4. The **record** section contains the database records saved with `recorda/3` and friends. The current version saves records using directives.
5. The **flag** section contains the global flags saved using the `flag/3` predicate. Flags are saved as directives.
6. The **feature** section contains all features that do not originate from the emulator itself. See `set_feature/1`.
7. The **import** section contains the imports as far as they are not handled by the auto-import system. That is, an import is stored if the module is `user` or the module `user` contains a different definition as the one imported in the target module.'

Before writing the data to file, `qsave_program/2` will run `autoload/0` to all required autoloading the system can discover. See `autoload/0`.

Provided the application does not require any of the Prolog libraries to be loaded at runtime, the only file from the SWI-Prolog development environment required is the emulator itself. The emulator may be built in two flavours. The default is the *development* emulator. The *runtime* emulator is similar, but lacks the tracer. The stand-alone program `chpl` may be used to change the default path to the emulator.

If the option `stand_alone(on)` is present, the emulator is prepended for the state. If the emulator is started and no state is specified using the `-x` flag, it will test whether a boot-file (state) is attached to the emulator itself and load this state. Provided the application has all libraries loaded, the resulting file may be started anywhere.

qsave_program(*+File*)
Equivalent to `qsave_program(File, [])`.

autoload
Check the current Prolog program for predicates that are referred to, are undefined and have a definition in the Prolog library. Load the appropriate libraries.

This predicate is used by `qsave_program/[1,2]` to ensure the saved state will not depend on one of the libraries. `Autoload/0` will find all *direct* references to predicates. It does not find predicates referenced via meta-predicates. The predicate `log/2` is defined in the library(quintus) to provide a quintus compatible means to compute the natural logarithm of a number. The following program will behave correctly if its state is executed in an environment where the library(quintus) is not available:

```
logtable(From, To) :-
        From > To, !.
logtable(From, To) :-
        log(From, Value),
        format(´~d~t~8|~2f~n´, [From, Value]),
        F is From + 1,
        logtable(F, To).
```

However, the following implementation refers to `log/2` through the meta-predicate `maplist/2`. Autoload will not be able to find the reference. This problem may be fixed either by loading the module libtary(quintus) explicitly or use `require/1` to tell the system that the predicate `log/2` is required by this module.

```
logtable(From, To) :-
        findall(X, between(From, To, X), Xlist),
        maplist(log, Xlist, SineList),
        write_table(Xlist, SineList).

write_table([], []).
write_table([I|IT], [V|VT]) :-
        format(´~d~t~8|~2f~n´, [I, V]),
        write_table(IT, VT).
```

volatile *+Name/Arity, ...*
Declare that the clauses of specified predicates should **not** be saved to the program. The volatile declaration is normally used to avoid that the clauses of dynamic predicates that represent data for the current session is saved in the state file.

6.1 Limitations of qsave_program

There are three areas that require special attention when using `qsave_program/[1,2]`.

- If the program is an embedded Prolog application or uses the foreign language interface, care has to be taken to restore the appropriate foreign context. See section 6.2 for details.
- If the program uses directives (`:- goal.` lines) that perform other actions then setting predicate attributes (dynamic, volatile, etc.) or loading files (consult, etc.), the directive may need to be prefixed with `initialization/1`.
- 'Database references as returned by `clause/3`, `recorded/3`, etc. are not preserved and may thus not be part of the database when saved.

6.2 Runtimes and Foreign Code

Some applications may need to use the foreign language interface. Object code is by definition machine-dependent and thus cannot be part of the saved program file.

To complicate the matter even further there are various ways of loading foreign code:

- *Using the library(shlib) predicates*
  This is the preferred way of dealing with foreign code. It loads quickly and ensures an acceptable level of independence between the versions of the emulator and the foreign code loaded. It works on Unix machines supporting shared libraries and library functions to load them. Most modern Unixes satisfy this constraint.[1]. It also works on the Win32 platform: Windows-NT, '95 and Windows 3.1 running win32s.

[1] Linux with the old a.out format does **not**

- *Static linking*
  This mechanism works on all machines, but generally requires the same C-compiler and linker to be used for the external code as is used to build SWI-Prolog itself. This mechanism is the preferred way if shared libraries are not supported.
- *Using* `load_foreign/2`*,5]*
  Basically only works on Unix system supporting the a.out format executables. This mechanism is slow and non-portable. It should be avoided whenever possible.

To make a runtime executable that can run on multiple platforms one must make runtime checks to find the correct way of linking. Suppose we have a source-file `myextension` defining the installation function `install`.

If this file is compiled to a shared library, `load_foreign_library/1` will load this library and call the installation function to initialise the foreign code. If it is loaded as a static extension, define install() as the predicate `install/0`:

```
static foreign_t
pl_install()
{ install();

  PL_succeed;
}

PL_extension PL_extensions [] =
{
/*{ "name",     arity,  function,       PL_FA_<flags> },*/

  { "install",  0,      pl_install,     0 },
  { NULL,       0,      NULL,           0 }     /* terminating line */
};
```

Now, use the following Prolog code to load the foreign library:

```
load_foreign_extensions :-
        current_predicate(install, install), !, % static loaded
        install.
load_foreign_extensions :-                      % shared library
        load_foreign_library(foreign(myextension)).

:- initialization load_foreign_extensions.
```

The path alias `foreign` is defined by `file_search_path/2`. By default it searches the directories <home>/lib/<arch> and <home>/lib. The application can specify additional rules for `file_search_path/2`.

6.3 Finding Application files

If your application uses files that are not part of the saved program such as database files, configuration files, etc., the runtime version has to be able to locate these files. The `file_search_path/2`

mechanism in combination with the -p command-line argument is the preferred way to locate runtime files. The first step is to define an alias for the toplevel directory of your application. We will call this directory gnatdir in our examples.

A good place for storing data associated with SWI-Prolog runtime systems is below the emulator's home-directory. swi is a predefined alias for this directory. The following is a useful default definition for the search path.

```
user:file_search_path(gnatdir, swi(gnat)).
```

The application should locate all files using absolute_file_name. Suppose gnatdir contains a file config.pl to define local configuration. Then use the code below to load this file:

```
configure_gnat :-
        (   absolute_file_name(gnatdir(´config.pl´), ConfigFile)
        ->  consult(ConfigFile)
        ;   format(user_error, ´gnat: Cannot locate config.pl~n´),
            halt(1)
        ).
```

6.4 Using chpl for Configuration Information

6.4.1 Changing the emulator of a runtime application

The program chpl, may be used to manipulate the header of a SWI-Prolog bootfile or state created with qsave_program/[1,2].

It will be used most commonly by the installer of a SWI-Prolog runtime application to specify the path to the emulator. If the end-user decided to install the SWI-Prolog runtime environment in

```
/usr/local/lib/rt-pl-2.1.4
```

the gnat application can be told to use this emulator using:

```
% /usr/local/lib/rtpl-2.1.4/bin/chpl -e /usr/local/lib/rt-pl-2.1.4/bin/pl gnat
```

Now, gnat may be installed in any public or private directory for binaries.

6.4.2 Passing a path to the application

Suppose the system administrator has installed the SWI-Prolog runtime environment in /usr/local/lib/rt-pl-2.:
A user wants to install gnat, but gnat will look for its configuration in /usr/local/lib/rt-pl-2.1.4/gnat
where the user cannot write.

The user decides to install the gnat runtime files in /users/bob/lib/gnat. For one-time usage, the user may decide to start gnat using the command:

```
% gnat -p gnatdir=/users/bob/lib/gnat
```


For a more widely used executable, this is not very comfortable. The user may decide to edit the shell-script part of gnat. Upto the line holding

```
# End Header
```

gnat is a simple /bin/sh script. After this line, the file is binary and may contain long lines. Most editors are not capable of editing such files.[2] Instead of editing the file directly, the program chpl may be used to extract and replace the header of gnat. The following editing sequence will work with any editor capable of editing ASCII files.

```
% chpl -x gnat > gnat.hdr
% emacs gnat.hdr
% chpl -h gnat.hdr gnat
```

The header may be changed to the following to install gnat properly:

```
#!/bin/sh
# SWI-Prolog version: 2.1.4
# SWI-Prolog save-version: 25
exec ${SWIPL-/usr/local/lib/rt-pl-2.1.4/bin/pl} -x $0 \
     -p gnatdir=/users/bob/lib/gnat "$@"
```

6.5 The Runtime Environment

6.5.1 The Runtime Emulator

The sources may be used to built two versions of the emulator. By default, the *development* emulator is built. This emulator contains all features for interactive development of Prolog applications. If the system is configured using --enable-runtime, make will create a *runtime* version of the emulator. This emulator is equivalent to the development version, except for the following features:

- *No input editing*
  The GNU library -lreadline that provides EMACS compatible editing of input lines will never be linked to the system.
- *No tracer*
  The tracer and all its options are removed, making the system a little bit faster too.
- *No profiler*
  profile/3 and friends are not supported. This saves some space and provides a bit better performance.
- *No interrupt*
  Keyboard interrupt (Control-C normally) is not rebound and will normally terminate the application.

[2] If you use GNU-Emacs, make sure require-final-newline is set to nil

- *feature(runtime, true) succeeds*
  This may be used to verify your application is running in the runtime environment rather than the development environment.

- `clause/[2,3]` *do not work on static predicates*
  This feature inhibits listing your program. It is only a very limited protection however.

The following fragment is an example for building the runtime environment in `$HOME/lib/rt-pl-2.1.4`. If possible, the shared-library interface should be configured to ensure it can serve a large number of applications.

```
% cd pl-2.1.4
% mkdir runtime
% cd runtime
% ../src/configure --enable-runtime --prefix=$HOME
% make
% make rt-install
```

The runtime directory contains the components listed below. This directory may be tar'ed and shipped with your application.

`README.RT`	Info on the runtime environment
`bin/pl` `bin/chpl`	The emulator itself The utility to change the runtime
`man/chpl.1` `man/pl.1`	Manual page for chpl Manual page for pl
`swipl`	pointer to the home directory (.)
`lib/` `lib/<arch>/`	directory for shared libraries machine-specific shared libraries

Appendix A

Hackers corner

This appendix describes a number of predicates which enable the Prolog user to inspect the Prolog environment and manipulate (or even redefine) the debugger. They can be used as entry points for experiments with debugging tools for Prolog. The predicates described here should be handled with some care as it is easy to corrupt the consistency of the Prolog system by misusing them.

A.1 Examining the Environment Stack

prolog_current_frame(*-Frame*)
Unify *Frame* with an integer providing a reference to the parent of the current local stack frame. A pointer to the current local frame cannot be provided as the predicate succeeds deterministically and therefore its frame is destroyed immediately after succeeding.

prolog_frame_attribute(*+Frame, +Key, -Value*)
Obtain information about the local stack frame *Frame*. *Frame* is a frame reference as obtained through `prolog_current_frame/1`, `prolog_trace_interception/4` or this predicate. The key values are described in table A.1.

A.2 Intercepting the Tracer

prolog_trace_interception(*+Port, +Frame, +PC, -Action*)
Dynamic predicate, normally not defined. This predicate is called from the SWI-Prolog debugger just before it would show a port. If this predicate succeeds the debugger assumes the trace action has been taken care of and continues execution as described by *Action*. Otherwise the normal Prolog debugger actions are performed.

Port is one of `call`, `redo`, `exit`, `fail` or `unify`. *Frame* is an integer reference to the current local stack frame. *PC* is the current value of the program-counter, relative to the start of the current clause, or 0 if it is invalid, for example because the current frame runs a foreign predicate, or no clause has been selected yet. *Action* should be unified with one of the atoms `continue` (just continue execution), `retry` (retry the current goal) or `fail` (force the current goal to fail). Leaving it a variable is identical to `continue`.

Together with the predicates described in section 3.36 and the other predicates of this chapter this predicate enables the Prolog user to define a complete new debugger in Prolog. Besides

Key	Value
alternative	*Value* is unified with an integer reference to the local stack frame in which execution is resumed if the goal associated with *Frame* fails. Fails if the frame has no alternative frame.
has_alternatives	*Value* is unified with `true` if *Frame* still is a candidate for backtracking. `false` otherwise.
goal	*Value* is unified with the goal associated with *Frame*. If the definition module of the active predicate is not `user` the goal is represented as *module:goal*. Do not instantiate variables in this goal unless you *know* what you are doing!
clause	*Value* is unified with a reference to the currently running clause. Fails if the current goal is associated with a foreign (C) defined predicate. See also `nth_clause/3` and `clause_property/2`.
level	*Value* is unified with the recursion level of *Frame*. The top level frame is at level '0'.
parent	*Value* is unified with an integer reference to the parent local stack frame of *Frame*. Fails if *Frame* is the top frame.
context_module	*Value* is unified with the name of the context module of the environment.
top	*Value* is unified with `true` if *Frame* is the top Prolog goal from a recursive call back from the foreign language. `false` otherwise.
hidden	*Value* is unified with `true` if the frame is hidden from the user, either because a parent has the hide-childs attribute (all system predicates), or the system has no trace-me attribute.
pc	*Value* is unified with the program-pointer saved on behalve of the parent-goal if the parent-goal is not owned by a foreign predicate.
argument(N)	*Value* is unified with the *N*-th slot of the frame. Argument `1` is the first argument of the goal. Arguments above the arity refer to local variables. Fails silently if *N* is out of range.

Table A.1: Key values of `prolog_current_frame/1`

this it enables the Prolog programmer monitor the execution of a program. The example shown in figure A.1 records all goals trapped by the tracer in the database. To trace the execution of 'go' this way the following query should be given:

```
?- trace, go, notrace.
```

prolog_skip_level(*-Old, +New*)
Unify *Old* with the old value of 'skip level' and than set this level according to *New*. New is an integer, or the special atom `very_deep` (meaning don't skip). The 'skip level' is a global variable of the Prolog system that disables the debugger on all recursion levels deeper than the level of the variable. Used to implement the trace options 'skip' (sets skip level to the level of the frame) and 'up' (sets skip level to the level of the parent frame (i.e. the level of this frame

```
prolog_trace_interception(Port, Frame, _PC, continue) :-
        prolog_frame_attribute(Frame, goal, Goal),
        prolog_frame_attribute(Frame, level, Level),
        recordz(trace, trace(Port, Level, Goal)).
```

Figure A.1: Record a trace in the database

minus 1).

A.3 Exception Handling

A start has been made to make exception handling available to the Prolog user. On exceptions a dynamic and multifile defined predicate `exception/3` is called. If this user defined predicate succeeds Prolog assumes the exception has been taken care of. Otherwise the system default exception handler is called.

exception(*+Exception, +Context, -Action*)
Dynamic predicate, normally not defined. Called by the Prolog system on run-time exceptions. Currently `exception/3` is only used for trapping undefined predicates. Future versions might handle signal handling, floating exceptions and other runtime errors via this mechanism. The values for *Exception* are described below.

undefined_predicate
If *Exception* is `undefined_predicate` *Context* is instantiated to a term *Name/Arity*. *Name* refers to the name and *Arity* to the arity of the undefined predicate. If the definition module of the predicate is not *user*, *Context* will be of the form *Module:Name/Arity*. If the predicate fails Prolog will print the default error warning and start the tracer. If the predicate succeeds it should instantiate the last argument either to the atom `fail` to tell Prolog to fail the predicate or the atom `retry` to tell Prolog to retry the predicate. This only makes sense if the exception handler has defined the predicate. Otherwise it will lead to a loop.

warning
If prolog wants to give a warning while reading a file, it will first raise the exception *warning*. The context argument is a term of the form *warning(Path, LineNo, Message)*, where *Path* is the absolute filename of the file prolog is reading; *LineNo* is an estimate of the line number where the error occurred and *Message* is a Prolog string indicating the message. The *Action* argument is ignored. The error is supposed to be presented to the user if the exception handler succeeds. Otherwise the standard Prolog warning message is printed.
This exception is used by the library `emacs_interface`, that integrates error handling with GNU Emacs.

A.4 Readline Interaction

The following predicates are available if `feature(readline, true)` succeeds. They allow for direct interaction with the GNU readline library. See also `readline(3)`.

rl_read_init_file(*+File*)
Read a readline initialisation file. Readline by default reads `~/.inputrc`. This predicate may be used to read alternative readline initialisation files.

rl_add_history(*+Line*)
Add a line to the Control-P/Control-N history system of the readline library.

Appendix B

Summary

B.1 Predicates

`! /0`	Cut (discard choicepoints)
`! /1`	Cut block. See `block/3`
`,  /2{xfy 1000}`	Conjunction of goals
`->  /2{xfy 1050}`	If-then-else
`*->  /2{xfy 1050}`	Soft-cut
`. /2`	Consult. Also list constructor
`;  /2{xfy 1100}`	Disjunction of goals. Same as `| /2`
`<  /2{xfx 700}`	Arithmetic smaller
`=  /2{xfx 700}`	Unification
`=..  /2{xfx 700}`	"Univ." Term to list conversion
`=:=  /2{xfx 700}`	Arithmetic equal
`=<  /2{xfx 700}`	Arithmetic smaller or equal
`==  /2{xfx 700}`	Identical
`=@=  /2{xfx 700}`	Structural identical
`=\=  /2{xfx 700}`	Arithmetic not equal
`>  /2{xfx 700}`	Arithmetic larger
`>=  /2{xfx 700}`	Arithmetic larger or equal
`@<  /2{xfx 700}`	Standard order smaller
`@=<  /2{xfx 700}`	Standard order smaller or equal
`@>  /2{xfx 700}`	Standard order larger
`@>=  /2{xfx 700}`	Standard order larger or equal
`\+  /1{ fy 900}`	Negation by failure (argument not provable). Same as `not/1`
`\=  /2{xfx 700}`	Not unifyable
`\==  /2{xfx 700}`	Not identical
`\=@=  /2{xfx 700}`	Not structural identical
`^  /2{xfy 200}`	Existential quantification (`bagof/3`, `setof/3`)
`|  /2{xfy 1100}`	Disjunction of goals. Same as `; /2`

`abolish/2`	Remove predicate definition from the database
`abort/0`	Abort execution, return to top level
`absolute_file_name/2`	Get absolute path name
`absolute_file_name/3`	Get absolute path name with options

`access_file/2`	Check access permissions of a file
`append/1`	Append to a file
`append/3`	Concatenate lists
`apply/2`	Call goal with additional arguments
`apropos/1`	library(`online_help`): Show related predicates and manual sections
`arg/3`	Access argument of a term
`arithmetic_function/1`	Register an evaluable function
`assert/1`	Add a clause to the database
`assert/2`	Add a clause to the database, give reference
`asserta/1`	Add a clause to the database (first)
`asserta/2`	Add a clause to the database (first)
`assertz/1`	Add a clause to the database (last)
`assertz/2`	Add a clause to the database (last)
`at_end_of_stream/0`	Test for end of file on input
`at_end_of_stream/1`	Test for end of file on stream
`at_halt/1`	Register goal to run at `halt/1`
`at_initialization/1`	Register goal to run at start-up
`atom/1`	Type check for an atom
`atom_char/2`	Convert between atom and ASCII value
`atom_chars/2`	Convert between atom and list of ASCII values
`atom_length/2`	Determine length of an atom
`atom_prefix/2`	Test for start of atom
`atom_to_term/3`	Convert between atom and term
`atomic/1`	Type check for primitive
`autoload/0`	Autoload all predicates now

`bagof/3`	Find all solutions to a goal
`between/3`	Integer range checking/generating
`block/3`	Start a block ('catch'/'throw')
`break/0`	Start interactive toplevel

`call/1`	Call a goal
`call/[2..]`	Call with additional arguments
`call_dll_function/2`	Win32: Call function in dynamic link library (.dll file)
`call_shared_object_function/2`	UNIX: Call C-function in shared (.so) file
`character_count/2`	Get character index on a stream
`chdir/1`	Change working directory
`checklist/2`	Invoke goal on all members of a list
`clause/2`	Get clauses of a predicate
`clause/3`	Get clauses of a predicate
`clause_property/2`	Get properties of a clause
`close/1`	Close stream
`close_dde_conversation/1`	Win32: Close DDE channel
`close_dll/1`	Win32: Close dynamic link library (.dll file)
`close_shared_object/1`	UNIX: Close shared library (.so file)
`compare/3`	Compare, using a predicate to determine the order
`compiling/0`	Is this a compilation run?
`compound/1`	Test for compound term
`concat/3`	Append two atoms
`concat_atom/2`	Append a list of atoms
`concat_atom/3`	Append a list of atoms with separator

consult/1	Read (compile) a Prolog source file
context_module/1	Get context module of current goal
convert_time/8	Convert time stamp
copy_term/2	Make a copy of a term
current_arithmetic_function/1	Examine evaluable functions
current_atom/1	Examine existing atoms
current_flag/1	Examine existing flags
current_foreign_library/2	library(shlib): Examine loaded shared libraries (.so files)
current_functor/2	Examine existing name/arity pairs
current_input/1	Get current input stream
current_key/1	Examine existing database keys
current_module/1	Examine existing modules
current_module/2	Examine existing modules
current_op/3	Examine current operator declarations
current_output/1	Get the current output stream
current_predicate/2	Examine existing predicates
current_stream/3	Examine open streams
dde_current_connection/2	Win32: Examine open DDE connections
dde_current_service/2	Win32: Examine DDE services provided
dde_execute/2	Win32: Execute command on DDE server
dde_register_service/2	Win32: Become a DDE server
dde_request/3	Win32: Make a DDE request
dde_poke/3	Win32: POKE operation on DDE server
dde_unregister_service/1	Win32: Terminate a DDE service
debug/0	Test for debugging mode
debugging/0	Show debugger status
default_module/2	Get the default modules of a module
delete/3	Delete all matching members from a list
delete_file/1	Remove a file from the file system
discontiguous/1{fx 1150}	Indicate distributed definition of a predicate
display/1	Write a term, ignore operators
display/2	Write a term, ignore operators on a stream
displayq/1	Write a term with quotes, ignore operators
displayq/2	Write a term with quotes, ignore operators on a stream
dwim_match/2	Atoms match in "Do What I Mean" sense
dwim_match/3	Atoms match in "Do What I Mean" sense
dwim_predicate/2	Find predicate in "Do What I Mean" sense
dynamic/1{fx 1150}	Indicate predicate definition may change
ed/0	Edit last edited predicate
ed/1	Edit a predicate
edit/0	Edit last edited file
edit/1	Edit a file
edit_source/1	(hook) Intercept editing
ensure_loaded/1	Consult a file if that has not yet been done
erase/1	Erase a database record or clause
exception/3	(hook) Handle runtime exceptions
exists_directory/1	Check existence of directory
exists_file/1	Check existence of file
exit/2	Exit from named block. See block/3

expand_file_name/2	Wildcard expansion of file names
expand_file_search_path/2	Wildcard expansion of file paths
expand_term/2	Compiler: expand read term into clause(s)
explain/1	library(explain): Explain argument
explain/2	library(explain): 2nd argument is explanation of first
export/1	Export a predicate from a module
export_list/2	List of public predicates of a module
fail/0	Always false
fail/1	Immediately fail named block. See block/3
feature/2	Get system configuration parameters
file_base_name/2	Get file part of path
file_directory_name/2	Get directory part of path
file_name_extension/3	Add, remove or test file extensions
file_search_path/2	Define path-aliases for locating files
fileerrors/2	Do/Don't warn on file errors
findall/3	Find all solutions to a goal
flag/3	Simple global variable system
flatten/2	Transform nested list into flat list
float/1	Type check for a floating point number
flush/0	Output pending characters on current stream
flush_output/1	Output pending characters on specified stream
forall/2	Prove goal for all solutions of another goal
foreign_file/1	Examine loaded foreign files
format/1	Formatted output
format/2	Formatted output with arguments
format/3	Formatted output on a stream
format_predicate/2	Program format/[1,2]
free_variables/2	Find unbound variables in a term
functor/3	Get name and arity of a term or construct a term
garbage_collect/0	Invoke the garbage collector
gensym/2	Generate unique atoms from a base
get/1	Read first non-blank character
get/2	Read first non-blank character from a stream
get0/1	Read next character
get0/2	Read next character from a stream
get_single_char/1	Read next character from the terminal
get_time/1	Get current time
getenv/2	Get shell environment variable
ground/1	Verify term holds no unbound variables
halt/0	Exit from Prolog
halt/1	Exit from Prolog with status
hash_term/2	Hash-value of ground term
help/0	Give help on help
help/1	Give help on predicates and show parts of manual
history_depth/1	Number of remembered queries
ignore/1	Call the argument, but always succeed
import/1	Import a predicate from a module

index/1	Change clause indexing
initialization/1	Initialization directive
int_to_atom/2	Convert from integer to atom
int_to_atom/3	Convert from integer to atom (non-decimal)
integer/1	Type check for integer
intersection/3	Set intersection
is/2{xfx 700}	Evaluate arithmetic expression
is_absolute_file_name/1	True if arg defines an absolute path
is_list/1	Type check for a list
is_set/1	Type check for a set
keysort/2	Sort, using a key
last/2	Last element of a list
leash/1	Change ports visited by the tracer
length/2	Length of a list
library_directory/1	(hook) Directories holding Prolog libraries
limit_stack/2	Limit stack expansion
line_count/2	Line number on stream
line_position/2	Character position in line on stream
list_to_set/2	Remove duplicates
listing/0	List program in current module
listing/1	List predicate
load_files/2	Load source files with options
load_foreign/2	Load foreign (C) module
load_foreign/5	Load foreign (C) module
load_foreign_library/1	library(shlib): Load shared library (.so file)
load_foreign_library/2	library(shlib): Load shared library (.so file)
make/0	Reconsult all changed source files
make_fat_filemap/1	Win32: Create file containing non-FAT filenames
make_library_index/1	Create autoload file INDEX.pl
maplist/3	Transform all elements of a list
member/2	Element is member of a list
memberchk/2	Deterministic member/2
merge/3	Merge two sorted lists
merge_set/3	Merge two sorted sets
module/1	Query/set current type-in module
module/2	Declare a module
module_transparent/1{fx 1150}	Indicate module based meta predicate
msort/2	Sort, do not remove duplicates
multifile/1{fx 1150}	Indicate distributed definition of predicate
name/2	Convert between atom and list of ASCII characters
nl/0	Generate a newline
nl/1	Generate a newline on a stream
nodebug/0	Disable debugging
nonvar/1	Type check for bound term
noprotocol/0	Disable logging of user interaction
nospy/1	Remove spy point
nospyall/0	Remove all spy points

not/1{fy 900}	Negation by failure (argument not provable). Same as \+ /1
notrace/0	Stop tracing
notrace/1	Do not debug argument goal
nth0/3	N-th element of a list (0-based)
nth1/3	N-th element of a list (1-based)
nth_clause/3	N-th clause of a predicate
number/1	Type check for integer or float
number_chars/2	Convert between number and atom
numbervars/4	Enumerate unbound variables of a term using a given base
once/1	Call a goal deterministically
op/3	Declare an operator
open/3	Open a file (creating a stream)
open/4	Open a file (creating a stream)
open_dde_conversation/3	Win32: Open DDE channel
open_null_stream/1	Open a stream to discard output
open_shared_object/2	UNIX: Open shared library (.so file)
open_shared_object/3	UNIX: Open shared library (.so file)
peek_byte/1	Read character without removing
peek_byte/2	Read character without removing
phrase/2	Activate grammar-rule set
phrase/3	Activate grammar-rule set (returning rest)
please/3	Query/change environment parameters
plus/3	Logical integer addition
portray/1	(hook) Modify behaviour of print/1
portray_clause/1	Pretty print a clause
predicate_property/2	Query predicate attributes
predsort/3	Sort, using a predicate to determine the order
preprocessor/2	Install a preprocessor before the compiler
print/1	Print a term
print/2	Print a term on a stream
profile/3	Obtain execution statistics
profile_count/3	Obtain profile results on a predicate
profiler/2	Obtain/change status of the profiler
prolog/0	Run interactive toplevel
prolog_current_frame/1	Reference to goal's environment stack
prolog_frame_attribute/3	Obtain information on a goal environment
prolog_load_context/2	Context information for directives
prolog_skip_level/2	Indicate deepest recursion to trace
prolog_to_os_filename/2	Convert between Prolog and OS filenames
prolog_trace_interception/4	library(user): Intercept the Prolog tracer
prompt1/1	Change prompt for 1 line
prompt/2	Change the prompt used by read/1
proper_list/1	Type check for list
protocol/1	Make a log of the user interaction
protocola/1	Append log of the user interaction to file
protocolling/1	On what file is user interaction logged
put/1	Write a character
put/2	Write a character on a stream

qcompile/1	Compile source to Quick Load File
qload/1	Load Quick Load File as consult/1
qsave_program/1	Create runtime application
qsave_program/2	Create runtime application
read/1	Read Prolog term
read/2	Read Prolog term from stream
read_clause/1	Read clause
read_clause/2	Read clause from stream
read_history/6	Read using history substitution
read_link/3	Read a symbolic link
read_term/2	Read term with options
read_term/3	Read term with options from stream
read_variables/2	Read clause including variable names
read_variables/3	Read clause including variable names from stream
recorda/2	Record term in the database (first)
recorda/3	Record term in the database (first)
recorded/2	Obtain term from the database
recorded/3	Obtain term from the database
recordz/2	Record term in the database (last)
recordz/3	Record term in the database (last)
redefine_system_predicate/1	Abolish system definition
rename_file/2	Change name of file
repeat/0	Succeed, leaving infinite backtrack points
require/1	This file requires these predicates
reset_profiler/0	Clear statistics obtained by the profiler
restore/1	Restore saved-state (save/1, save_program/1)
retract/1	Remove clause from the database
retractall/1	Remove unifying clauses from the database
reverse/2	Inverse the order of the elements in a list
same_file/2	Succeeds if arguments refer to same file
save/1	Save program including current goal
save/2	Save program including current goal
save_program/1	Save the current program on a file
save_program/2	Save the current program on a file
see/1	Change the current input stream
seeing/1	Query the current input stream
seen/0	Close the current input stream
select/3	Select element of a list
set_feature/2	Define a system feature
set_input/1	Set current input stream from a stream
set_output/1	Set current output stream from a stream
set_tty/2	Set 'tty' stream
setarg/3	Destructive assignment on term
setenv/2	Set shell environment variable
setof/3	Find all unique solutions to a goal
sformat/2	Format on a string
sformat/3	Format on a string
shell/0	Execute interactive subshell
shell/1	Execute OS command
shell/2	Execute OS command

show_profile/1	Show results of the profiler
size_file/2	Get size of a file in characters
skip/1	Skip to character in current input
skip/2	Skip to character on stream
rl_add_history/1	Add line to readline(3) history
rl_read_init_file/1	Read readline(3) init file
sleep/1	Suspend execution for specified time
sort/2	Sort elements in a list
source_file/1	Examine currently loaded source files
source_file/2	Obtain source file of predicate
source_location/2	Location of last read term
spy/1	Force tracer on specified predicate
stack_parameter/4	Some systems: Query/Set runtime stack parameter
statistics/0	Show execution statistics
statistics/2	Obtain collected statistics
stream_position/3	Get/seek to position in file
string/1	Type check for string
string_concat/3	concat/3 for strings (non-deterministic)
string_length/2	Determine length of a string
string_to_atom/2	Conversion between string and atom
string_to_list/2	Conversion between string and list of ASCII
style_check/1	Change level of warnings
sublist/3	Determine elements that meet condition
subset/2	Generate/check subset relation
substring/4	Get part of a string
subtract/3	Delete elements that do not meet condition
succ/2	Logical integer successor relation
swritef/2	Formatted write on a string
swritef/3	Formatted write on a string
tab/1	Output number of spaces
tab/2	Output number of spaces on a stream
tell/1	Change current output stream
telling/1	Query current output stream
term_expansion/2	(hook) Convert term before compilation
term_to_atom/2	Convert between term and atom
time/1	Determine time needed to execute goal
time_file/2	Get last modification time of file
tmp_file/2	Create a temporary filename
told/0	Close current output
trace/0	Start the tracer
trace/1	Set trace-point on predicate
trace/2	Set/Clear trace-point on ports
tracing/0	Query status of the tracer
trim_stacks/0	Release unused memory resources
true/0	Succeed
tty_get_capability/3	Get terminal parameter
tty_goto/2	Goto position on screen
tty_put/2	Write control string to terminal
ttyflush/0	Flush output on terminal

union/3	Union of two sets
unknown/2	Trap undefined predicates
unload_foreign_library/1	library(shlib): Detach shared library (.so file)
unsetenv/1	Delete shell environment variable
use_module/1	Import a module
use_module/2	Import predicates from a module
var/1	Type check for unbound variable
visible/1	Ports that are visible in the tracer
volatile/1{fx 1150}	Predicates that are not saved
wait_for_input/3	Wait for input with optional timeout
wildcard_match/2	Csh(1) style wildcard match
win_exec/2	Win32: spawn Windows task
write/1	Write term
write/2	Write term to stream
write_ln/1	Write term, followed by a newline
writef/1	Formatted write
writef/2	Formatted write on stream
writeq/1	Write term, insert quotes
writeq/2	Write term, insert quotes on stream

B.2 Arithmetic Functions

* /2{yfx 400}	Multiplication
** /2{xfx 200}	Power function
+ /2{yfx 500}	Addition
- /1{ fx 500}	Unary minus
- /2{yfx 500}	Subtraction
/ /2{yfx 400}	Division
// /2{yfx 400}	Integer division
/\ /2{yfx 500}	Bitwise and
<< /2{yfx 400}	Bitwise left shift
>> /2{yfx 400}	Bitwise right shift
"C"/1 (list of one character)	Character code
\ /1{ fx 500}	Bitwise negation
\/ /2{yfx 500}	Bitwise or
^ /2{xfy 200}	Power function
abs/1	Absolute value
acos/1	Inverse (arc) cosine
asin/1	Inverse (arc) sine
atan/1	Inverse (arc) tangent
atan/2	Rectangular to polar conversion
ceil/1	Smallest integer larger than arg
ceiling/1	Smallest integer larger than arg
cos/1	Cosine
cputime/0	Get CPU time
e/0	Mathematical constant
exp/1	Exponent (base e)
float/1	Explicitly convert to float

float_fractional_part/1	Fractional part of a float
float_integer_part/1	Integer part of a float
floor/1	Largest integer below argument
integer/1	Round to nearest integer
log/1	Natural logarithm
log10/1	10 base logarithm
max/2	Maximum of two numbers
min/2	Minimum of two numbers
mod/2{xfx 300}	Remainder of division
random/1	Generate random number
rem/2	Remainder of division
round/1	Round to nearest integer
truncate/1	Truncate float to integer
pi/0	Mathematical constant
sign/1	Extract sign of value
sin/1	Sine
sqrt/1	Square root
tan/1	Tangent
xor/2{yfx 400}	Bitwise exclusive or

B.3 Operators

1	fx	$	Bind toplevel variable
200	xfy	^	(1) Predicate
200	xfy	^	(2) Arithmetic function
300	xfx	mod	Arithmetic function
400	yfx	*	Arithmetic function
400	yfx	/	Arithmetic function
400	yfx	//	Arithmetic function
400	yfx	<<	Arithmetic function
400	yfx	>>	Arithmetic function
400	yfx	xor	Arithmetic function
500	fx	+	Arithmetic function
500	fx	-	Arithmetic function
500	fx	?	XPCE: obtainer
500	fx	\	Arithmetic function
500	yfx	+	Arithmetic function
500	yfx	-	Arithmetic function
500	yfx	/\	Arithmetic function
500	yfx	\/	Arithmetic function
600	xfy	:	module:term separator
700	xfx	<	Predicate
700	xfx	=	Predicate
700	xfx	=..	Predicate
700	xfx	=:=	Predicate
700	xfx	=<	Predicate
700	xfx	==	Predicate
700	xfx	=@=	Predicate
700	xfx	=\=	Predicate
700	xfx	>	Predicate

700	xfx	>=	Predicate
700	xfx	@<	Predicate
700	xfx	@=<	Predicate
700	xfx	@>	Predicate
700	xfx	@>=	Predicate
700	xfx	is	Predicate
700	xfx	\=	Predicate
700	xfx	\==	Predicate
700	xfx	\=@=	Predicate
900	fy	not	Predicate
900	fy	\+	Predicate
1000	xfy	,	Predicate
1050	xfy	->	Predicate
1100	xfy	;	Predicate
1100	xfy	|	Predicate
1150	fx	discontiguous	Predicate
1150	fx	dynamic	Predicate
1150	fx	module_transparent	Predicate
1150	fx	multifile	Predicate
1150	fx	volatile	Predicate
1150	fx	initialization	Predicate
1200	fx	:-	Introduces a directive
1200	fx	?-	Introduces a directive
1200	xfx	-->	DCGrammar: rewrite
1200	xfx	:-	head :- body. separator

Bibliography

[Anjewierden & Wielemaker, 1989] A. Anjewierden and J. Wielemaker. Extensible objects. ESPRIT Project 1098 Technical Report UvA-C1-TR-006a, University of Amsterdam, March 1989.

[BIM, 1989] *BIM_Prolog release 2.4.* Everberg, Belgium, 1989.

[Bowen & Byrd, 1983] D. L. Bowen and L. M. Byrd. A portable Prolog compiler. In L. M. Pereira, ed., *Proceedings of the Logic Programming Workshop 1983*, Lisabon, Portugal, 1983. Universidade nova de Lisboa.

[Bratko, 1986] I. Bratko. *Prolog Programming for Artificial Intelligence.* Addison-Wesley, Reading MA, 1986.

[Clocksin & Mellish, 1981] W. F. Clocksin and C. S. Mellish. *Programming in Prolog.* Springer-Verlag, New York, 1981. (4th ed. 1994)

[Kernighan & Ritchie, 1978] B. W. Kernighan and D. M. Ritchie. *The C Programming Language.* Prentice-Hall, Englewood Cliffs NJ, 1978.

[O'Keefe, 1990] R. A. O'Keefe. *The Craft of Prolog.* MIT Press, Cambridge MA, 1990.

[Pereira, 1986] F. Pereira. *C-Prolog User's Manual*, 1986.

[Qui, 1987] *Quintus Prolog, User Guide and Reference Manual.* Mountain View CA, 1987.

[Sterling & Shapiro, 1986] L. Sterling and E. Shapiro. *The Art of Prolog.* MIT Press, Cambridge MA, 1986. (2nd ed. 1994)

[Warren, 1983] D. H. D. Warren. The runtime environment for a Prolog compiler using a copy algorithm. Technical Report 83/052, SUNY at Stony Brook, New York, 1983. Major revision March 1984.