

# Algorithms in grid classes

Ruth Hoffmann

University of St Andrews, School of Computer Science

Permutation Patterns 2013  
Université Paris Diderot  
2nd July 2013



University of  
St Andrews

600  
YEARS

Introduction

Background

Geometric Grid Class

Theorem

Original Proof

Alternative Proof (Concept)

- ▶ Different, computationally efficient representation of permutation pattern classes.
- ▶ Solved questions can be constructive, but some are not, yet.
- ▶ Want to add more language theoretic aspects to permutation pattern classes.
- ▶ This approach could introduce some more constructive approaches to answered or open questions.

## Definition

A **transducer** is a six-tuple  $(Q, \Sigma, \Gamma, i, A, \theta)$  where:

$Q$  - set of states;

$\Sigma$  - input alphabet;

$\Gamma$  - output alphabet;

$i \in Q$  - start state;

$A \subseteq Q$  - set of accept states;

$\theta : Q \times (\Sigma \cup \{\epsilon\}) \rightarrow Q \times (\Gamma \cup \{\epsilon\})$  - transition function, where:

$\epsilon$  - empty string.

## Definition (Classic permutation pattern inclusion)

$\sigma \in S_n$  **contains** or **involves**  $\pi \in S_k$ ,  $\pi \leq \sigma$ , if  $\sigma$  contains a subsequence of length  $k$  order isomorphic to  $\pi$ .

## Definition (Classic permutation pattern classes)

A **permutation class**  $C$  is a down set of permutations under the containment or involvement order. So if  $\sigma \in C$  and  $\pi \leq \sigma$  then  $\pi \in C$ .

## Definition (Antichain or Basis)

For any permutation class  $C$ , the **antichain** or **basis**  $B$  is the set of minimal permutations not in  $C$ . So

$$C = Av(B) = \{\sigma : \beta \not\leq \sigma \text{ for all } \beta \in B\}.$$

## Definition (Partial well-order)

A poset is said to be **partially well-ordered** (pwo) if it contains neither an infinite strict descending chain nor an infinite antichain.

Matrices  $M$  are indexed with columns (Left  $\rightarrow$  Right), rows (Bottom  $\rightarrow$  Top).

$M$  is an  $s \times t$  matrix with  $0, +1, -1$  as its entries.

## Definition (Partial Multiplication Matrix)

$M$  is said to be a **partial multiplication matrix** (pmm) if there are column signs  $c_1, \dots, c_s \in \{\pm 1\}$  and row signs  $r_1, \dots, r_t \in \{\pm 1\}$  such that for all  $k, \ell$ ,  $M_{k,\ell}$  is equal to either  $c_k * r_\ell$  or  $0$ .

## Definition (Gridding of a permutation)

An  **$M$ -gridding** of a permutation  $\sigma \in S_n$  is a pair of sequences  $0 = x_1 \leq \dots \leq x_{s+1} = n$  (column divisors) and  $0 = y_1 \leq \dots \leq y_{t+1} = n$  (row divisors) such that the  $\sigma((x_k, x_{k+1}]) \in (y_\ell, y_{\ell+1}]$  are increasing if  $M_{k,\ell} = 1$ , decreasing if  $M_{k,\ell} = -1$  and empty if  $M_{k,\ell} = 0$ .

## Definition (Monotone Grid Class)

The **monotone grid class** or **grid class** of  $M$ ,  $\text{Grid}(M)$ , contains all permutations which possess an  $M$ -gridding.


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

with

$$c_1 = -1, c_2 = c_3 = 1;$$

$$r_1 = 1, r_2 = -1.$$



567213984 possesses an  
 $M$ -gridding.

## Definition (Standard Figure)

The **standard figure** of  $M$  is the point set in  $\mathbb{R}^2$  consisting of the increasing line segment from  $(k-1, \ell-1)$  to  $(k, \ell)$  if  $M_{k,\ell} = 1$  or the decreasing line segment from  $(k-1, \ell)$  to  $(k, \ell-1)$  if  $M_{k,\ell} = -1$ .

## Definition (Geometric Grid Class)

The **geometric grid class** of  $M$ ,  $\text{Geom}(M)$ , is the set of all permutations that can be drawn on the standard figure of  $M$  as follows:

Choose  $n$  points in the figure, no two on a common horizontal or vertical line. Then label the points from 1 to  $n$  bottom  $\rightarrow$  top and record the labels left  $\rightarrow$  right.

## Definition (The Grid Language)

Let  $M$  be pmm with column signs  $c_1, \dots, c_s$  and row signs,  $r_1, \dots, r_t$  and let  $\Sigma = \{(k, \ell) : M_{k, \ell} \neq 0\}$ . The map  $\varphi : \Sigma^* \rightarrow \text{Grid}(M)$  describes how to create an  $M$ -gridded permutation  $\pi = \varphi(w)$ , for each word  $w \in \Sigma^*$ , in which the letter  $(k, \ell)$  corresponds to an entry in the  $(k, \ell)$  cell.  $\pi$  is build by reading  $w$  left to right inserting the elements as follows:

$c_k$	$r_\ell$	order
1	1	L→R & B→T ↗
1	-1	L→R & T→B ↘
1	1	R→L & B→T ↖
-1	-1	R→L & T→B ↙


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

$$c_1 = -1, c_2 = c_3 = 1;$$

$$r_1 = 1, r_2 = -1.$$

$$\Sigma = \{(1, 1), (1, 2), (2, 1), (3, 2)\}$$



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

$$c_1 = -1, c_2 = c_3 = 1;$$

$$r_1 = 1, r_2 = -1.$$

$$\Sigma = \{(1, 1), (1, 2), (2, 1), (3, 2)\}$$



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

$$c_1 = -1, c_2 = c_3 = 1;$$

$$r_1 = 1, r_2 = -1.$$

$$\Sigma = \{(1, 1), (1, 2), (2, 1), (3, 2)\}$$



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

$$c_1 = -1, c_2 = c_3 = 1;$$

$$r_1 = 1, r_2 = -1.$$

$$\Sigma = \{(1, 1), (1, 2), (2, 1), (3, 2)\}$$



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

$$c_1 = -1, c_2 = c_3 = 1;$$

$$r_1 = 1, r_2 = -1.$$

$$\Sigma = \{(1, 1), (1, 2), (2, 1), (3, 2)\}$$



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

$$c_1 = -1, c_2 = c_3 = 1;$$

$$r_1 = 1, r_2 = -1.$$

$$\Sigma = \{(1, 1), (1, 2), (2, 1), (3, 2)\}$$



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

$$c_1 = -1, c_2 = c_3 = 1;$$

$$r_1 = 1, r_2 = -1.$$

$$\Sigma = \{(1, 1), (1, 2), (2, 1), (3, 2)\}$$



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$


# Example

$$M = \begin{pmatrix} 1 & 0 & -1 \\ -1 & 1 & 0 \end{pmatrix}$$

$$c_1 = -1, c_2 = c_3 = 1;$$



$$r_1 = 1, r_2 = -1.$$

$$\Sigma = \{(1, 1), (1, 2), (2, 1), (3, 2)\}$$



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$

# Example



$$w = (1, 1)(2, 1)(1, 1)(1, 2)(3, 2)(3, 2)(2, 1)$$

$$\varphi(w) = 7312465$$

## Theorem

*Every geometrically griddable class is finitely based.*

See (Albert, Atkinson, Bouvel, Ruškuc, Vatter 2011) for details.

## Proposition

*If the class  $C$  is geometrically griddable, then the class  $C^{+1}$  (one point extension) is also geometrically griddable.*

## Theorem

*Every geometrically griddable class is pwo.*

## Theorem (Higman's Theorem)

*The set of words over any finite alphabet is pwo under the subword order.*

Subword-closed languages are regular languages.

# Alternative Proof (Concept)

## Outline

### Proposition

*If the class  $C$  is geometrically griddable, then the class  $C^{+1}$  (one point extension) is also geometrically griddable.*

Take  $C$  with  $M$  and alphabet  $\Sigma$ . Find  $C^{+1}$  with  $M^{+1}$  and alphabet  $\Sigma^{+1}$  using transducers.

1. Expand  $M$  to  $M^{\times 3}$ .
2. Find all (finite number) points off the line segments.

# Alternative Proof (Concept)

Transducer 1  $M \rightarrow M^{\times 3}$

$$M_{k,\ell} = 0 \Rightarrow M_{[3*k-2,3*k],[3*\ell-2,3*\ell]}^{\times 3} = \begin{matrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{matrix}$$

As  $\Sigma = \{(k, \ell) : M_{k,\ell} \neq 0\}$  nothing changes in  $\Sigma^{\times 3}$ .

# Alternative Proof (Concept)

Transducer 1  $M \rightarrow M^{\times 3}$

$$M_{k,\ell} = 1 \Rightarrow M_{[3*k-2,3*k],[3*\ell-2,3*\ell]}^{\times 3} = \begin{matrix} & 0 & 0 & 1 \\ & 0 & 1 & 0 \\ & 1 & 0 & 0 \end{matrix}$$

$(k, \ell) \in \Sigma \Rightarrow$

$\{(3 * k - 2, 3 * \ell - 2), (3 * k - 1, 3 * \ell - 1), (3 * k, 3 * \ell)\} \in \Sigma^{\times 3}$

# Alternative Proof (Concept)

Transducer 1  $M \rightarrow M^{\times 3}$

$$M_{k,\ell} = -1 \Rightarrow M_{[3*k-2,3*k],[3*\ell-2,3*\ell]}^{\times 3} = \begin{matrix} & -1 & 0 & 0 \\ & 0 & -1 & 0 \\ & 0 & 0 & -1 \end{matrix}$$

$(k, \ell) \in \Sigma \Rightarrow$

$\{(3 * k - 2, 3 * \ell), (3 * k - 1, 3 * \ell - 1), (3 * k, 3 * \ell - 2)\} \in \Sigma^{\times 3}$



# Alternative Proof (Concept)

## One-Point-Deletion Transducer

- ▶ Based on (Albert, Atkinson, Ruškuc, 2003).
- ▶ This transducer,  $\mathcal{D}$ , read words  $w$  (representing permutation  $\pi$ ), deletes a letter and returns  $w'$  which represents the permutation that is missing the entry corresponding to the deleted letter.
- ▶ Applying  $\mathcal{D}$  to the language of  $M^{+1}$  should result in the language of the basis.

# Furthermore

## Multiple-Point-Deletion Transducer

- ▶ This transducer,  $\mathcal{P}$ , deletes multiple letters of the word  $w$  (representing  $\pi$ ), and returns  $w'$  which represents the permutation missing the entries corresponding to the deleted letters.
- ▶ In (Albert, Atkinson, Ruškuc, 2003) this transducer is then transposed (reversed), so it adds multiple letters and is used to find the language of the class from the language of the basis.

Thank you

-  Michael H. Albert, M. D. Atkinson, Mathilde Bouvel, Nik Ruškuc, and Vincent Vatter, *Geometric grid classes of permutations*, ArXiv e-prints (2011), 1–28.
-  M H Albert, M D Atkinson, and N Ruškuc, *Regular closed sets of permutations*, Theoretical Computer Science **306** (2003), no. 1–3, 85–100.
-  Robert Brignall, *Grid classes and Partial Well Order*, Journal of Combinatorial Theory, Series A **119** (2012), no. 1, 99–116.
-  Vincent Vatter and Steve Waton, *On partial well-order for monotone grid classes of permutations*, Order **28** (2011), no. 2, 193–199.
-  Stephen D Waton, *On Permutation Classes Defined by Token Passing Networks, Gridding Matrices and Pictures: Three Flavours of Involvement*, Ph.D. thesis, University of St Andrews, 2007.