On the Occur-check Free Prolog Programs

Krzysztof R. Apt
CWI and University of Amsterdam
and
Alessandro Pellegrini
Università di Padova

In most Prolog implementations for the efficiency reasons so-called occur-check is omitted from the unification algorithm. We provide here natural syntactic conditions which allow the occur-check to be safely omitted. The established results apply to most well-known Prolog programs, including those that use difference-lists, and seem to explain why this omission does not lead in practice to any complications. When applying these results to general programs we show their usefulness for proving absence of floundering. Finally, we propose a program transformation which transforms every program into a program for which only the calls to the built-in unification predicate need to be resolved by a unification algorithm with the occur-check.

Categories and Subject Descriptors: D.2.4 [**Software engineering**]: Program verification—*correctness proofs*; D.3.4 [**Programming languages**]: Processors—*preprocessors*; I.2.3 [**Artificial intelligence**]: Deduction and theorem proving—*logic programming*

General terms: Languages

Additional Key Words and Phrases: unification algorithm, Prolog programs, occur-check problem, moded programs

1. INTRODUCTION

The occur-check is a special test used in the unification algorithm. In most Prolog implementations it is omitted for the efficiency reasons. This omission affects the unification algorithm and introduces a possibility of divergence or may yield incorrect results. This is obviously an undesired situation. This problem was studied in the literature under the name of the *occur-check problem* (see e.g. Plaisted [22] and Deransart and Maluszynski [14]).

The aim of this paper is to provide easy to check syntactic conditions which ensure that for Prolog programs the occur-check can be safely omitted. We use here a result of Deransart, Ferrand and Téguia [13] and build upon it within the context of moded programs. This allows us to extend the results of Deransart and Maluszynski [14], to simplify the arguments of Chadha and Plaisted [8] and to offer a uniform presentation. Additionally, the results of the former paper needed here are proved directly, without resorting to the techniques of the attribute grammars theory,

The work of the first author was partly supported by ESPRIT Basic Research Action 6810 (Compulog 2). This research carried out partly during the second author's stay at Centre for Mathematics and Computer Science, Amsterdam. His stay was supported by the 2060^{th} District of the Rotary Foundation, Italy. A shorter version of this paper appeared as [3].
Authors' current addresses: Krzysztof R. Apt CWI P.O. Box 94079, 1090 GB Amsterdam, The Netherlands and Faculty of Mathematics and Computer Science University of Amsterdam, Plantage Muidergracht 24 1018 TV Amsterdam, The Netherlands; Alessandro Pellegrini Dipartimento di Matematica Pura ed Applicata Università di Padova Via Belzoni 7, 35131 Padova, Italy.

and the results of the latter paper are supplied with a needed justification. We also consider here general programs and show the usefulness of our approach for proving absence of floundering. Finally, we show how the problem of inserting occur-checks in a program execution can be taken care of by means of a program transformation which inserts calls of the built-in unification predicate into the program text. The obtained results apply to most well-known Prolog programs.

In this paper we need a slightly more liberal definition of an SLD-derivation according to which the selection of the atom in the current goal is combined with the selection of the input clause used to resolve this atom. Then an SLD-derivation fails if the selected atom does not unify with the head of the input clause selected to resolve it.

To see the difference with the customary definition, consider the program $\{p(0) \leftarrow , p(x) \leftarrow \}$. According to our definition, the goal $\leftarrow p(s(0))$ is not only the root of an SLD-refutation, but also a root of an immediately failing SLD-derivation (when the first clause is selected).

In what follows we study logic programs executed by means of the *LD-resolution*, which consists of the SLD-resolution combined with the leftmost selection rule. An SLD-derivation in which the leftmost selection rule is used is called an *LD-derivation*. We allow in programs various first-order built-in's, like $=$, $\leq$, $>$, etc, and assume that they are resolved in the way conforming to their interpretation.

Throughout the paper we use the standard notation of Lloyd [18] and Apt [2]. In particular, given a syntactic construct E (so for example, a term, an atom or a set of equations) we denote by $Var(E)$ the set of the variables appearing in E. Given a substitution $\theta = \{x_1/t_1, ..., x_n/t_n\}$ we denote by $Dom(\theta)$ the set of variables $\{x_1, \ldots, x_n\}$, by $Range(\theta)$ the set of terms $\{t_1, \ldots, t_n\}$, and by $Ran(\theta)$ the set of variables appearing in $\{t_1, \ldots, t_n\}$. Finally, we define $Var(\theta) = Dom(\theta) \cup Ran(\theta)$.

Recall that a substitution θ is called *grounding* if $Ran(\theta)$ is empty, and is called a *renaming* if it is a permutation of the variables in $Dom(\theta)$. Given a substitution θ and a set of variables V, we denote by $\theta|V$ the substitution obtained from θ by restricting its domain to V.

2. OCCUR-CHECK FREE PROGRAMS

We start our considerations by recalling a unification algorithm due to Martelli and Montanari [20]. We use below the notions of sets and of systems of equations interchangingly. Two atoms can unify only if they have the same relation symbol. With two atoms $p(s_1, ..., s_n)$ and $p(t_1, ..., t_n)$ to be unified we associate the set of equations

$$\{s_1 = t_1, ..., s_n = t_n\}.$$

In the applications we often refer to this set as $p(s_1, ..., s_n) = p(t_1, ..., t_n)$. The algorithm operates on such finite sets of equations. A substitution θ such that $s_1\theta = t_1\theta, \ldots, s_n\theta = t_n\theta$ is called a *unifier* of the set of equations $\{s_1 = t_1, ..., s_n = t_n\}$. Thus the set of equations $E = \{s_1 = t_1, ..., s_n = t_n\}$ has the same unifiers as the atoms $p(s_1, ..., s_n)$ and $p(t_1, ..., t_n)$.

A unifier θ of a set of equations E is called a *most general unifier* (in short *mgu*) of E if it is more general than all unifiers of E. An mgu θ of a set of equations E is called *relevant* if $Var(\theta) \subseteq Var(E)$.

Two sets of equations are called *equivalent* if they have the same set of unifiers,

and a set of equations is called *solved* if it is of the form $\{x_1 = t_1, ..., x_n = t_n\}$ where the x_i's are distinct variables and none of them occurs in a term t_j. The interest in solved sets of equations is revealed by the following lemma.

LEMMA 2.1. *If $E = \{x_1 = t_1, ..., x_n = t_n\}$ is solved, then $\theta = \{x_1/t_1, ..., x_n/t_n\}$ is a relevant mgu of E.* □

We call θ the *unifier determined by* E. Thus to find an *mgu* of two atoms it suffices to transform the associated set of equations into an equivalent one which is solved. The following algorithm does it if this is possible and otherwise halts with failure.

MARTELLI-MONTANARI ALGORITHM

Nondeterministically choose from the set of equations an equation of a form below and perform the associated action.

(1) $f(s_1, ..., s_n) = f(t_1, ..., t_n)$	*replace by the equations* $s_1 = t_1, ..., s_n = t_n$,
(2) $f(s_1, ..., s_n) = g(t_1, ..., t_m)$ where $f \not\equiv g$	*halt with failure*,
(3) $x = x$	*delete the equation*,
(4) $t = x$ where t is not a variable	*replace by the equation* $x = t$,
(5) $x = t$ where $x \not\equiv t$, x does not occur in t and x occurs elsewhere	*perform the substitution* $\{x/t\}$ *in every other equation*,
(6) $x = t$ where $x \not\equiv t$ and x occurs in t	*halt with failure.*

The algorithm terminates when no action can be performed or when failure arises. To keep the formulation of the algorithm concise we identified here constants with 0-ary functions. Thus action (2) includes the case of two different constants. The following theorem holds (see Martelli and Montanari [20]).

THEOREM UNIFICATION. *The Martelli-Montanari algorithm always terminates. If the ori-ginal set of equations E has a unifier, then the algorithm successfully terminates and produces a solved set of equations determining a relevant mgu of E, and otherwise it terminates with failure.* □

The Martelli-Montanari algorithm does not generate all relevant mgu's of a set of equations E but the following lemma, proved in Lassez, Marriot and Maher [17], will allow us to cope with this peculiarity.

LEMMA 2.3. *Let θ_1 and θ_2 be mgu's of a set of equations. Then for some renaming η we have $\theta_2 = \theta_1\eta$.* □

Finally, the following lemma allows us to search for mgu's in an iterative fashion.

LEMMA 2.4. *Let E_1, E_2 be two sets of equations. Suppose that θ_1 is a relevant mgu of E_1 and θ_2 is a relevant mgu of $E_2\theta_1$. Then $\theta_1\theta_2$ is a relevant mgu of $E_1 \cup E_2$. Moreover, if $E_1 \cup E_2$ is unifiable then θ_1 exists and for any such θ_1 an appropriate θ_2 exists, as well.*

Proof. If e is an equation of E_1, then it is unified by θ_1, so a fortiori by $\theta_1\theta_2$. If e is an equation of E_2, then $e\theta_1$ is an equation of $E_2\theta_1$. Thus $e\theta_1$ is unified by θ_2 and consequently e is unified by $\theta_1\theta_2$. This proves that $\theta_1\theta_2$ is a unifier of $E_1 \cup E_2$. Moreover, $Var(\theta_1\theta_2) \subseteq Var(\theta_1) \cup Var(\theta_2) \subseteq Var(E_1) \cup Var(E_2\theta_1) \subseteq Var(E_1) \cup Var(E_2) \cup Var(\theta_1) \subseteq Var(E_1 \cup E_2)$, so $\theta_1\theta_2$ is relevant.

Let now η be a unifier of $E_1 \cup E_2$. By the choice of θ_1 there exists a substitution λ_1 such that $\eta = \theta_1\lambda_1$. Thus λ_1 is a unifier of $(E_1 \cup E_2)\theta_1$, and a fortiori of $E_2\theta_1$. By the choice of θ_2 for some λ_2 we have $\lambda_1 = \theta_2\lambda_2$. Thus $\eta = \theta_1\lambda_1 = \theta_1\theta_2\lambda_2$. This proves that $\theta_1\theta_2$ is an mgu of $E_1 \cup E_2$.

Finally, note that if $E_1 \cup E_2$ is unifiable, then a fortiori E_1 is unifiable and the Unification Theorem 2.2 tells us that a relevant mgu θ_1 for E_1 is produced by the Martelli-Montanari algorithm. The previously inferred existence of λ_1 implies that for such a θ_1 $E_2\theta_1$ is unifiable and again the Martelli-Montanari algorithm can be used to produce for this set a relevant mgu θ_2. □

Let us return now to the Martelli-Montanari algorithm. The test "x does not occur in t" in action (5) is called the *occur-check*. In most Prolog implementations the occur-check is omitted. Let us recall that this omission can in some cases bring the cost of unification from linear time down to constant time. An example is the concatenation of the lists by means of the difference-list representation. (For a thorough analysis of the time complexity of the unification algorithm with and without the occur-check see Albert, Casas and Fages [1].) By omitting the occur-check in (5) and deleting action (6) from the Martelli-Montanari algorithm we are still left with two options depending on whether the substitution $\{x/t\}$ is performed in t itself. If it is, then divergence can result, because x occurs in t implies that x occurs in $t\{x/t\}$. If it is not (as in the case of the modified version of the algorithm just mentioned), then an incorrect result can be produced, as in the case of the single equation $x = f(x)$ which yields the substitution $\{x/f(x)\}$.

None of these alternatives is desirable. It is natural then to seek conditions which guarantee that, in absence of the occur-check, in all Prolog evaluations of a given goal w.r.t. a given program unification is correctly performed. This leads us to the following notion due to Deransart, Ferrand and Téguia [13].

DEFINITION 2.5. A set of equations E is called *not subject to occur-check* (NSTO in short) if in no execution of the Martelli-Montanari algorithm started with E action (6) can be performed. □

We now introduce the key definition of the paper.

DEFINITION 2.6.

—Let ξ be an LD-derivation. Let A be an atom selected in ξ and H the head of the input clause selected to resolve A in ξ. Suppose that A and H have the same relation symbol. Then we say that the system $A = H$ *is considered in* ξ.

—Suppose that all systems of equations considered in the LD-derivations of $P \cup \{G\}$ are NSTO. Then we say that $P \cup \{G\}$ is *occur-check free*. □

This definition assumes a specific unification algorithm but allows us to derive precise results. Moreover, the nondeterminism built into the Martelli-Montanari algorithm allows us to model executions of various other unification algorithms,

including Robinson's algorithm (see e.g. Albert, Casas and Fages [1]). In contrast, no specific unification algorithm in the definition of the LD-resolution is assumed.

By Theorem 2.2 if a considered system of equations is unifiable, then it is NSTO, as well. Thus the property of being occur-check free rests exclusively upon those considered systems which are not unifiable. As in the definition of the occur-check freedom *all* LD-derivations of $P \cup \{G\}$ are considered, all systems of equations that can be considered in a possibly backtracking Prolog evaluation of a goal G w.r.t. the program P are taken into account.

In Deransart, Ferrand and Téguia [13] a related concept of an NSTO program is studied which essentially states that, independently of the selection rule and the resolution strategy chosen, all considered systems are NSTO. The definition of the occur-check freedom refers to the leftmost selection rule, and the results we obtain usually cannot be extended to those dealing with NSTO programs.

The aim of this paper is to offer simple syntactic conditions which imply that $P \cup \{G\}$ is occur-check free. As expected, the property of being occur-check free is undecidable (see Deransart and Maluszynski [14] and for a strengthened version the appendix). On the other hand, the problem whether a set of equations is NSTO, is decidable. In fact, Apt, van Emde Boas and Welling [5] recently proved that this problem is CoNP-complete.

For further analysis we need the following concepts.

DEFINITION 2.7.

—We call a family of terms (resp. an atom) *linear* if every variable occurs at most once in it.

—We call a set of equations *left linear* (resp. *right linear*) if the family of terms formed by their left-hand (resp. right-hand) sides is linear. □

Thus a family of terms is linear iff no variable has two distinct occurrences in any term and no two terms have a variable in common.

DEFINITION 2.8. Let E be a set of equations. We denote by $\rightarrow_E$ the following relation defined on the elements of E:
$e_1 \rightarrow_E e_2$ iff the left-hand side of e_1 and the right-hand side of e_2 have a variable in common. □

In particular, if a variable occurs both in the left-hand and right-hand side of an equation e of E, then $e \rightarrow_E e$. The following result due to Deransart, Ferrand and Téguia [13] will be helpful in the sequel.

LEMMA NSTO. *Suppose that the equations in E can be oriented in such a way that the resulting system F is left linear and the relation $\rightarrow_F$ is cycle-free. Then E is NSTO.* □

Note that the converse of this lemma is not true – just take $E = \{f(x) = g(x)\}$. The original formulation of this lemma is slightly stronger, but for our purposes the above version is sufficient.

3. MODED PROGRAMS

For a further analysis we introduce modes, first considered in Mellish [21], and more extensively studied in Reddy [23] and Dembinski and Maluszynski [12].

DEFINITION 3.1. Consider an n-ary relation symbol p. By a *mode* for p we mean a function d_p from $\{1, \ldots, n\}$ to the set $\{+, -\}$. If $d_p(i) = \text{'+'}$, we call i an *input position* of p and if $d_p(i) = \text{'-'}$, we call i an *output position* of p (both w.r.t. d_p).

We write d_p in a more suggestive form $p(d_p(1), \ldots, d_p(n))$. By a *moding* we mean a collection of modes, each for a different relation symbol. □

Intuitively, the modes indicate how the arguments of a relation should be used, though the distinction between the input and output positions is not clear when all positions in an atom of a goal are filled in by compound terms.

The definition of moding assumes one mode per relation in a program. Multiple modes may be obtained by simply renaming the relations. From now on we assume that *every considered relation* has a mode associated with it. This will allow us to talk about input positions and output positions of an atom.

We now introduce the following concepts.

DEFINITION 3.2.

—An atom is called *input* (resp. *output*) *linear* if the family of terms occurring in its input (resp. output) positions is linear.

—An atom is called *input-output disjoint* if the family of terms occurring in its input positions has no variable in common with the family of terms occurring in its output positions. □

The following lemma is crucial.

LEMMA NSTO VIA MODES. *Consider two atoms A and H with the same relation symbol. Suppose that*

—*they have no variable in common,*

—*one of them is input-output disjoint,*

—*one of them is input linear and the other is output linear.*

Then $A = H$ is NSTO.

Proof. Suppose first that A is input-output disjoint and input linear and H is output linear. Let $i_1^A, \ldots, i_m^A$ (resp. $i_1^H, \ldots, i_m^H$) be the terms filling in the input positions of A (resp. H) and $o_1^A, \ldots, o_n^A$ (resp. $o_1^H, \ldots, o_n^H$) the terms filling in the output positions of A (resp. H).

The system under consideration is

$$E = \{i_1^A = i_1^H, \ldots, i_m^A = i_m^H, o_1^A = o_1^H, \ldots, o_n^A = o_n^H\}.$$

Reorient it as follows:

$$F = \{i_1^A = i_1^H, \ldots, i_m^A = i_m^H, o_1^H = o_1^A, \ldots, o_n^H = o_n^A\}.$$

By assumption A and H have no variable in common. This implies that

—F is left-linear (because additionally A is input linear and H is output linear),

—the equations $i_j^A = i_j^H$ have no successor in the $\rightarrow_F$ relation and the equations $o_j^H = o_j^A$ have no predecessor (because additionally A is input-output disjoint).

Thus by the NSTO Lemma 2.9 $A = H$ is NSTO. The proofs for the remaining three cases are analogous and omitted. □

We now prove two results allowing us to conclude that $P \cup \{G\}$ is occur-check free. The first one uses the following notion introduced in Dembinski and Maluszynski [12].

DEFINITION 3.4. We call an LD-derivation *data driven* if all atoms selected in it are ground in their input positions. □

THEOREM 3.5. *Suppose that*

—the head of every clause of P is output linear,
—all LD-derivations of $P \cup \{G\}$ are data driven.

Then $P \cup \{G\}$ is occur-check free.

Proof. Consider an LD-derivation of $P \cup \{G\}$. Let A be an atom selected in it and suppose that H is the head of an input clause such that A and H have the same relation symbol. By assumption A is ground in its input positions, so it is input-output disjoint and input linear. By assumption H is output linear and A and H have no variable in common. So by the NSTO via Modes Lemma 3.3 $A = H$ is NSTO. □

The second result uses the following notion.

DEFINITION 3.6. We call an LD-derivation *output driven* if all atoms selected in it are output linear and input-output disjoint. □

THEOREM 3.7. *Suppose that*

—the head of every clause of P is input linear,
—all LD-derivations of $P \cup \{G\}$ are output driven.

Then $P \cup \{G\}$ is occur-check free.

Proof. Let A and H be as in the proof of Theorem 3.5. The NSTO via Modes Lemma 3.3 applies and yields that $A = H$ is NSTO. □

This theorem is implicit in Chadha and Plaisted [8] (see the proof of their Theorem 2.2). Clearly, through different "distributions" of the conditions of the NSTO via Modes Lemma 3.3 other applications can be obtained. We found the above two least restrictive.

It is useful to note that the theorems established above generalize the following well-known result stated in Clark [9, page 15] and established in Deransart, Ferrand and Téguia [13] as a direct consequence of the NSTO Lemma 2.9.

COROLLARY 3.8. *Suppose that*

—the head of every clause of P is linear.

Then $P \cup \{G\}$ is occur-check free for every goal G.

Proof. By Theorem 3.5 by moding every relation completely output or by Theorem 3.7 by moding every relation completely input. □

This corollary can be applied to some well-known Prolog programs, for example to the unification program (see page 150 in the book of Sterling and Shapiro [28])

and — paradoxically — to the unification with occur-check program (see page 152). However, to most programs this corollary does not apply. The subsequent sections provide some other options.

So far we isolated two properties of LD-derivations, each of which implies occur-check freedom. In both cases we had to impose some restrictions on the heads of the clauses. When we combine these two properties we get occur-check freedom directly.

THEOREM 3.9. *Suppose that*

—all LD-derivations of $P \cup \{G\}$ are both data and output driven.

Then $P \cup \{G\}$ is occur-check free.

Proof. Let A and H be as in the proof of Theorem 3.5. By assumption the system $A = H$ is left linear. Moreover, A and H have no variable in common, so the relation $\rightarrow_{A=H}$ is empty and a fortiori cycle-free. So by the NSTO Lemma 2.9 $A = H$ is NSTO. □

4. WELL-MODED PROGRAMS

The obvious problem with Theorems 3.5, 3.7 and 3.9 is that is is not easy to check their conditions. In fact, one can show that in general it is undecidable whether for a given program P and goal G the conditions of Theorem 3.5, 3.7 or 3.9 hold (see the appendix).

The aim of this section is to propose some simple syntactic restrictions that imply the conditions of Theorem 3.5. We then show that these restrictions are satisfied by a number of well-known programs.

We use here the notion of a well-moded program. The concept is due to Dembinski and Maluszynski [12]; we use here an elegant formulation due to Rosenblueth [25] (which is equivalent to that of Drabent [15] where well-moded programs are called simple). The definition of a well-moded program constrains the "flow of data" through the clauses of the programs. To simplify the notation, when writing an atom as $p(\mathbf{u}, \mathbf{v})$, we now assume that $\mathbf{u}$ is a sequence of terms filling in the input positions of p and that $\mathbf{v}$ is a sequence of terms filling in the output positions of p.

DEFINITION 4.1.

—A goal $\leftarrow p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$ is called *well-moded* if for $i \in [1, n]$

$$Var(\mathbf{s_i}) \subseteq \bigcup_{j=1}^{i-1} Var(\mathbf{t_j}).$$

—A clause

$$p_0(\mathbf{t_0}, \mathbf{s_{n+1}}) \leftarrow p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$$

is called *well-moded* if for $i \in [1, n+1]$

$$Var(\mathbf{s_i}) \subseteq \bigcup_{j=0}^{i-1} Var(\mathbf{t_j}).$$

—A program is called *well-moded* if every clause of it is. □

Thus, a goal is well-moded if

—every variable occurring in an input position of an atom ($i \in [1, n]$) occurs in an output position of an earlier ($j \in [1, i-1]$) atom.

And a clause is well-moded if

—($i \in [1, n]$) every variable occurring in an input position of a body atom occurs either in an input position of the head ($j = 0$), or in an output position of an earlier ($j \in [1, i-1]$) body atom,

—($i = n + 1$) every variable occurring in an output position of the head occurs in an input position of the head ($j = 0$), or in an output position of a body atom ($j \in [1, n]$).

A test whether a goal or clause is well-moded can be efficiently performed by noting that a goal G is well-moded iff every first from the left occurrence of a variable in G is within an output position. And a clause $p(\mathbf{s}, \mathbf{t}) \leftarrow \mathbf{B}$ is well-moded iff every first from the left occurrence of a variable in the sequence $\mathbf{s}, \mathbf{B}, \mathbf{t}$ is within the input position of $p(\mathbf{s}, \mathbf{t})$ or within an output position in $\mathbf{B}$. (We assume in this description that in every atom the input positions occur first.)

Note that a goal with only one atom is well-moded iff this atom is ground in its input positions. The definition of a well-moded program is designed in such a way that the following theorem due to Dembinski and Maluszynski [12] holds.

THEOREM 4.2. *Let P and G be well-moded. Then all LD-derivations of $P \cup \{G\}$ are data driven.*

In Dembinski and Maluszynski [12] a different formulation of well-modedness is given and the above theorem is actually presented without a proof. So we allow ourselves to give a proof here.

Note that the first atom of a well-moded goal is ground in its input positions and a variant of a well-moded clause is well-moded. Thus it suffices to prove the following lemma which shows the "persistence" of the notion of well-modedness.

LEMMA 4.3. *An LD-resolvent of a well-moded goal and a well-moded clause that is variable-disjoint with it, is well-moded.*

Proof. An LD-resolvent of a goal and a clause is obtained by means of the following three operations:

—instantiation of a goal,

—instantiation of a clause,

—replacement of the first atom, say H, of a goal by the body of a clause whose head is H.

So we only need to prove the following two claims.

CLAIM 1. *An instance of a well-moded goal (resp. clause) is well-moded.*

Proof. It suffices to note that for any sequences of terms $\mathbf{s}, \mathbf{t_1}, \ldots, \mathbf{t_n}$ and a substitution σ,
$Var(\mathbf{s}) \subseteq \bigcup_{j=1}^{n} Var(\mathbf{t_j})$ implies $Var(\mathbf{s}\sigma) \subseteq \bigcup_{j=1}^{n} Var(\mathbf{t_j}\sigma)$. □

CLAIM 2. *Suppose $\leftarrow H, \mathbf{A}$ is a well-moded goal and $H \leftarrow \mathbf{B}$ is a well-moded clause. Then $\leftarrow \mathbf{B}, \mathbf{A}$ is a well-moded goal.*

Proof. Let $H = p(\mathbf{s}, \mathbf{t})$ and $\mathbf{B} = p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$. We have $Var(\mathbf{s}) = \emptyset$ since H is the first atom of a well-moded goal. Thus $\leftarrow \mathbf{B}$ is well-moded. Moreover, $Var(\mathbf{t}) \subseteq \bigcup_{j=1}^{n} Var(\mathbf{t_j})$, since $H \leftarrow \mathbf{B}$ is a well-moded clause and $Var(\mathbf{s}) = \emptyset$. These two observations imply the claim. □

□

As a digression let us recall the following immediate and well-known conclusion of this theorem.

COROLLARY 4.4. *Let P and G be well-moded. Then for every computed answer substitution σ, $G\sigma$ is ground.*

Proof. Let $\mathbf{x}$ stand for the sequence of all variables that appear in G. Let p be a new relation of arity equal to the length of $\mathbf{x}$ and with all positions moded as input. Then $\leftarrow \mathbf{A}, p(\mathbf{x})$ is a well-moded goal, where $G = \leftarrow \mathbf{A}$.

Now, σ is a computed answer substitution for $P \cup \{G\}$ iff $p(\mathbf{x})\sigma$ is a selected atom in an LD-derivation of $P \cup \{\leftarrow \mathbf{A}, p(\mathbf{x})\}$. The conclusion now follows by Theorem 4.2. □

We shall see in Section 7 that there are natural Prolog programs for which data drivedness cannot be established using the concept of well-modedness. Still, the above theorem brings us to the following conclusion which can be easily applied to a number of well-known Prolog programs.

COROLLARY 4.5. *Let P and G be well-moded. Suppose that*

—the head of every clause of P is output linear.

Then $P \cup \{G\}$ is occur-check free.

Proof. By Theorems 3.5 and 4.2. □

EXAMPLE 4.6. When presenting the programs we adhere to the usual syntactic conventions of Prolog with the exception that Prolog's ":-" is replaced by the logic programming " $\leftarrow$ ".
(i) Consider the program `append`:

```
app([X | Xs], Ys, [X | Zs]) ← app(Xs, Ys, Zs).
app([], Ys, Ys).
```

with the mode `app(+,+,-)`. It is easy to check that `append` is then well-moded and that the head of every clause is output linear. By Corollary 4.5 we conclude that for `s` and `t` ground, `append` $\cup$ $\{\leftarrow$ `app(s, t, u)`$\}$ is occur-check free.

(ii) Examine now the program `append` with the mode `app(-,-,+)`. Again, by Corollary 4.5, we conclude that for `u` ground, `append` $\cup$ $\{\leftarrow$ `app(s, t, u)`$\}$ is occur-check free.

(iii) Consider the program `permutation` which consists of the clauses

```
perm(Xs, [X | Ys]) ←
   app(X1s, [X | X2s], Xs),
   app(X1s, X2s, Zs),
```

```
   perm(Zs, Ys).
perm([], []).
```

augmented by the **append** program.

We use here the following moding: `perm(+,-)`, `app(-,-,+)` for the first call to **append** and `app(+,+,-)` for the second call to **append**.

It is easy to check that `permutation` is then well-moded and that the heads of all clauses are output linear. By Corollary 4.5 we get that for `s` ground, `permutation` $\cup \{\leftarrow$ `perm(s, t)`$\}$ is occur-check free.

(iv) Examine now the program `quicksort` which consists of the clauses

```
qs([X | Xs], Ys) ←
   partition(X, Xs, Littles, Bigs),
   qs(Littles, Ls),
   qs(Bigs, Bs),
   app(Ls, [X | Bs], Ys).
qs([], []).

partition(X, [Y | Xs], [Y | Ls], Bs) ←
   X > Y,
   partition(X, Xs, Ls, Bs).
partition(X, [Y | Xs], Ls, [Y | Bs]) ←
   X ≤ Y,
   partition(X, Xs, Ls, Bs).
partition(X, [], [], []).
```

augmented by the **append** program.

We mode it as follows: `qs(+,-)`, `partition(+,+,-,-)`, `app(+,+,-)`. Again, it is easy to check that `quicksort` is then well-moded and that the heads of all clauses are output linear. By Corollary 4.5 we conclude that for `s` ground, `quicksort` $\cup$ $\{\leftarrow$ `qs(s, t)`$\}$ is occur-check free.

(v) Finally, consider the program `palindrome`:

```
palindrome(Xs) ← reverse(Xs, Xs).
reverse(X1s, X2s) ← reverse(X1s, [], X2s).
reverse([X | X1s], X2s, Ys) ← reverse(X1s, [X | X2s], Ys).
reverse([], Xs, Xs).
```

We mode it as follows: `palindrome(+)`, `reverse(+,-)`, `reverse(+,+,-)`. Then `palindrome` is well-moded and the heads of all clauses are output linear. By Corollary 4.5 we conclude that for `s` ground, `palindrome` $\cup \{\leftarrow$ `palindrome(s)`$\}$ is occur-check free.

Note that to none of these programs Corollary 3.8 can be applied. □

5. NICELY MODED PROGRAMS

The above conclusions are still of a restrictive kind, because in each case we had to assume that the input positions of the one atom goals are ground. To alleviate this

restriction we now consider some syntactic restrictions that imply the conditions of Theorem 3.7.

The following notion was introduced in Chadha and Plaisted [8]. (We found essentially the same concept independently, though later; the name and formulation are ours.)

DEFINITION 5.1.

—A goal $\leftarrow p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$ is called *nicely moded* if $\mathbf{t_1}, \ldots, \mathbf{t_n}$ is a linear family of terms and for $i \in [1, n]$

$$Var(\mathbf{s_i}) \cap (\bigcup_{j=i}^{n} Var(\mathbf{t_j})) = \emptyset. \tag{1}$$

—A clause

$$p_0(\mathbf{s_0}, \mathbf{t_0}) \leftarrow p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$$

is called *nicely moded* if $\leftarrow p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$ is nicely moded and

$$Var(\mathbf{s_0}) \cap (\bigcup_{j=1}^{n} Var(\mathbf{t_j})) = \emptyset. \tag{2}$$

In particular, every unit clause is nicely-moded.

—A program is called *nicely moded* if every clause of it is. □

Thus, assuming that in every atom the input positions occur first, a goal is nicely moded if

—every variable occurring in an output position of an atom does not occur earlier in the goal.

And a clause is nicely moded if

—every variable occurring in an output position of a body atom occurs neither earlier in the body nor in an input position of the head.

So, intuitively, the concept of being nicely moded prevents a "speculative binding" of the variables which occur in output positions — these variables are required to be "fresh". Note that a goal with only one atom is nicely moded iff it is output linear and input-output disjoint. The following theorem clarifies our interest in nicely moded programs.

THEOREM 5.2. *Let P and G be nicely moded. Then all LD-derivations of $P \cup \{G\}$ are output driven.*

Note that the first atom of a nicely moded goal is output linear and input-output disjoint, and a variant of a nicely moded clause is nicely moded. Thus to prove Theorem 5.2 it suffices to prove the following lemma which shows the "persistence" of the notion of being nicely moded.

LEMMA 5.3. *An LD-resolvent of a nicely moded goal and a nicely moded clause that is variable-disjoint with it, is nicely moded.*

Proof. The proof is quite long and can be found in the appendix. □

This lemma leads us to the following conclusion.

COROLLARY 5.4. *Let P and G be nicely moded. Suppose that*

—the head of every clause of P is input linear.

Then $P \cup \{G\}$ is occur-check free.

Proof. By Theorems 3.7 and 5.2. □

This corollary is stated in Chadha and Plaisted [8] as a direct consequence of Theorem 3.7 without mentioning Theorem 5.2. In our opinion the latter theorem is necessary to draw the above conclusion. Pierre Deransart (private communication) pointed out to us that this corollary is a consequence of Theorem 4.1 in Deransart, Ferrand and Téguia [13] whose conditions are satisfied for a nicely moded program P and a nicely moded goal G. This suggests a stronger result, namely that such a P and G is NSTO. On the other hand, our proof establishes Lemma 5.3 which will allow us to deal in Section 7 with programs that use difference-lists and in Section 10 with programs that do require the use of unification with the occur-check.

It is worthwhile to note that to prove Corollary 5.4 it is actually sufficient to prove Lemma 5.3 under the assumption that the head of every clause of P is input linear. The proof is considerably simpler than that of Lemma 5.3.

To apply Corollary 4.5 it is natural to start by moding the relations used in the goal so that this goal becomes well-moded. Then one should try to mode other relations used in the program, so that the remaining conditions of this Corollary are satisfied. The important clue comes from the fact that the input positions of the first atom of a well-moded goal are filled in by ground terms. This is not the case for the nicely moded goals, so for example it is not clear how to mode the relation app when considering the goal $\leftarrow$ `app([X,2], [Y,U], [3,Z,0,Z])` (which succeeds with the c.a.s. $\{\mathtt{X}/3, \mathtt{Z}/2, \mathtt{Y}/0, \mathtt{U}/2\}$). We shall see later that in presence of difference-lists there is no clear intuition either about the modes of certain positions in the relations.

Consequently, as noted by Chadha and Plaisted [8], to apply Corollary 5.4 it is probably more natural to investigate first all the modings for which the program is nicely moded and the heads of all clauses are input linear. Then one should check for which modings the given goal is nicely moded. To this end Chadha and Plaisted [8] proposed two efficient algorithms for generating modings with the minimal number of input positions, for which the program is nicely moded. These algorithms were implemented and applied to a number of well-known Prolog programs.

In the case of the append program out of 8 modes only for 5 of them the conditions of Corollary 5.4 are satisfied. Out of these 5 only the mode `app(-,-,+)` can be used to deal with the goal $\leftarrow$ `app([X,2], [Y,U], [3,Z,0,Z])`.

Let us see now how this corollary can be applied to the previously studied programs.

EXAMPLE 5.5.

(i) Consider again the program append with the moding `app(+,+,-)`. Clearly, append is nicely moded and that the head of every clause is input linear. By Corollary 5.4 we conclude that when u is linear and $Var(\mathtt{s}, \mathtt{t}) \cap Var(\mathtt{u}) = \emptyset$, append $\cup \{\leftarrow$ `app(s, t, u)`$\}$ is occur-check free.

(ii) With the moding `app(-,-,+)` the program append is nicely moded, as well,

and the head of every clause is input linear. Again, by Corollary 5.4 we conclude that when $\mathtt{s,t}$ is a linear family of terms and $Var(\mathtt{s},\mathtt{t}) \cap Var(\mathtt{u}) = \emptyset$, $\mathtt{append} \cup \{\leftarrow \mathtt{app(s,\ t,\ u)}\}$ is occur-check free.

(iii) Reconsider now the program `permutation` with the modings as before. Again, it is easy to check that `permutation` is nicely moded and that the heads of all clauses are input linear. By Corollary 5.4 we get that when $\mathtt{t}$ is linear and $Var(\mathtt{s}) \cap Var(\mathtt{t}) = \emptyset$, $\mathtt{permutation} \cup \{\leftarrow \mathtt{perm(s,\ t)}\}$ is occur-check free.

(iv) Examine again the program `quicksort` with the modings as before. Again, Corollary 5.4 applies and we conclude that when $\mathtt{t}$ is linear and $Var(\mathtt{s}) \cap Var(\mathtt{t}) = \emptyset$, $\mathtt{quicksort} \cup \{\leftarrow \mathtt{qs(s,\ t)}\}$ is occur-check free.

(v) So far it seems that Corollary 5.4 allows us to draw more useful conclusions that Corollary 4.5. However, reconsider the program `palindrome`. In Chadha and Plaisted [8] it is shown that no moding exists in which `palindrome` is nicely moded with the heads of all clauses being input linear. Thus Corollary 5.4 cannot be applied to this program. □

6. STRICTLY MODED PROGRAMS

Next, we consider syntactic restrictions that imply the condition of Theorem 3.9. To this end it is sufficient to combine the properties of being well-moded and nicely moded. Indeed, we have the following observation.

COROLLARY 6.1. *Let P and G be well-moded and nicely moded. Then $P \cup \{G\}$ is occur-check free.*

Proof. By Theorems 4.2, 5.2 and 3.9. □

In the remainder of this section we show that the conditions of this corollary can be weakened. First, note that when a goal $\leftarrow p_1(\mathtt{s_1},\mathtt{t_1}),\ldots,p_n(\mathtt{s_n},\mathtt{t_n})$ is well-moded and the family $\mathtt{t_1},\ldots,\mathtt{t_n}$ is linear, condition (1) of Definition 5.1 is satisfied and thus the goal is nicely moded. A similar observation can be made about a clause $p_0(\mathtt{s_0},\mathtt{t_0}) \leftarrow p_1(\mathtt{s_1},\mathtt{t_1}),\ldots,p_n(\mathtt{s_n},\mathtt{t_n})$.

Thus the assumptions of the above corollary can be simplified. We now show that a further simplification is possible, namely condition (2) of Definition 5.1 can be omitted, as well.

DEFINITION 6.2.

—A goal $\leftarrow p_1(\mathtt{s_1},\mathtt{t_1}),\ldots,p_n(\mathtt{s_n},\mathtt{t_n})$ is called *strict* if $\mathtt{t_1},\ldots,\mathtt{t_n}$ is a linear family of terms.

—A clause $H \leftarrow \mathbf{B}$ is called *strict* if $\leftarrow \mathbf{B}$ is strict.

—A program is called *strict* if every clause of it is.

—A goal (clause) (program) is called *strictly moded* if it is both strict and well-moded. □

THEOREM 6.3. *Let P and G be strictly moded. Then all LD-derivations of $P \cup \{G\}$ are both data and output driven.*

Note that the first atom of a strictly moded goal is ground in its input positions, output linear and input-output disjoint, and a variant of a strictly moded clause

is strictly moded. Thus to prove this theorem it suffices to show, as in the case of the notions of well-modedness and being nicely moded, that the notion of strict modedness is "persistent".

LEMMA 6.4. *An LD-resolvent of a strictly moded goal and a strictly moded clause that is variable-disjoint with it, is strictly moded.*

Proof. Consider a strictly moded goal $\leftarrow A, \mathbf{A}$ and a disjoint with it strictly moded clause $H \leftarrow \mathbf{B}$. We start by proving three claims that appropriately refine those of Lemma 4.3.

Suppose $A = p(\mathrm{s}_A, \mathrm{t}_A)$ and $H = p(\mathrm{s}_H, \mathrm{t}_H)$. Assume that $A = H$ is unifiable. Take as E_1 the system of equations $\mathrm{s}_A = \mathrm{s}_H$ and as E_2 the system of equations $\mathrm{t}_A = \mathrm{t}_H$. Let θ_1 be a relevant mgu of E_1 and θ_2 a relevant mgu of $E_2\theta_1$. The existence of these substitutions is assured by Lemma 2.4 which also gives that $\theta_1\theta_2$ is a relevant mgu of $A = H$.

Let p^- be a new relation symbol of arity equal to the cardinality of t_A (and t_H) with all positions moded as output. Note that θ_1 is grounding, so by the definition of a nicely moded goal and clause, $\leftarrow (p^-(\mathrm{t}_A), \mathbf{A})\theta_1$ and $p^-(\mathrm{t}_H\theta_1) \leftarrow \mathbf{B}\theta_1$ are both nicely moded and have no variables in common. By Lemma 5.3 their resolvent $\leftarrow (\mathbf{B}\theta_1, \mathbf{A}\theta_1)\theta_2$ is nicely moded, as well.

This and Lemma 4.3 allow us to conclude that the LD-resolvent $\leftarrow (\mathbf{B}, \mathbf{A})\theta_1\theta_2$ of the goal $\leftarrow A, \mathbf{A}$ and the clause $H \leftarrow \mathbf{B}$ is both well-moded and nicely moded, thus strictly moded.

$\theta = \theta_1\theta_2$ is just one specific mgu of $A = H$. By Lemma 2.3 every other mgu of $A = H$ is of the form $\theta\eta$ for a renaming η. But a renaming of a strictly moded goal is strictly moded, so we conclude that every LD-resolvent of $\leftarrow A, \mathbf{A}$ and $H \leftarrow \mathbf{B}$ is strictly moded. □

The following result improves upon Corollary 6.1.

COROLLARY 6.5. *Let P and G be strictly moded. Then $P \cup \{G\}$ is occur-check free.*

Proof. By Theorems 6.3 and 3.9. □

EXAMPLE 6.6. In contrast to the case of well-moded and nicely moded programs it is difficult to come up with a natural example to which the notion of a strictly moded program could be applied. Still, consider the program `derivative` from Sterling and Shapiro [28, page 63]) which computes a derivative of an expression w.r.t. a variable. To save space we only reproduce here a couple of crucial clauses. The used function symbols are written in an infix form and for simplicity unary notation for natural numbers is used.

```
der(X, X, s(0)).
der(X↑s(N), X, s(N)* X↑N).
der(F+G, X, DF + DG) ← der(F, X, DF), der(G, X, DG).
der(F*G, X, F*DG + DF*G) ← der(F, X, DF), der(G, X, DG).
```

To compute the derivative of an expression `e`, say `x↑s(0) + x*y + y↑s(s(s(0)))`, w.r.t. a variable, say `x`, one uses the goal ← `der(e, x, Y)`. In the mode `der(+,+,-)` this program is both well-moded and nicely moded, and consequently also strictly

moded. By Corollary 6.5 we conclude that when `e` and `t` are ground and `u` is linear, `derivative` $\cup$ { $\leftarrow$ `der(e, t, u)`} is occur-check free.

Note that the head of the first clause is not input linear and the head of the second clause is not output linear. Consequently neither Corollary 4.5 nor 5.4 can be applied here. □

7. DIFFERENCE-LISTS

It is well-known that programs with difference-lists easily lead to complications in absence of the occur-check. For example, the program `empty`

```
empty(L \ L).
```

when executed with the goal $\leftarrow$ `empty([a | X] \ X)` leads to the consideration of the system { `[a | X] = L, X = L` } which is subject to the occur-check. It is wortwhile to note that programs which use difference-lists can be handled by the methods proposed. For example, Corollary 5.4 immediately implies that for `s` and `t` linear and disjoint, `empty` $\cup$ { $\leftarrow$ `empty(s, t)`} is occur-check free.

However, we did found two programs in the book of Sterling and Shapiro [28] that use difference-lists and to which we could not apply the results so far established. These are `flatten_dl` (program 15.2 on page 241):

```
flatten(Xs, Ys) ← flatten_dl(Xs, Ys \ []).

flatten_dl([X | Xs], Ys \ Zs) ←
   flatten_dl(X, Ys \ Ys1),
   flatten_dl(Xs, Ys1 \ Zs).
flatten_dl(X, [X | Xs] \ Xs) ←
   constant(X), X ≠ [].
flatten_dl([], Xs \ Xs).
```

and `quicksort_dl` (program 15.4 on page 244):

```
qs(Xs, Ys) ← qs_dl(Xs, Ys \ []).

qs_dl([X | Xs], Ys \ Zs) ←
   partition(X, Xs, Littles, Bigs),
   qs_dl(Littles, Ys \ [X | Ys1]),
   qs_dl(Bigs, Ys1 \ Zs).
qs_dl([], Xs \ Xs).
```

augmented by the `partition` program.

These programs are customarily used in the modes `flatten(+,-)` and `qs(+,-)`. It is easy to check that for both programs no completion of the moding exists for which the program is well-moded, or nicely moded and with the heads of all clauses being input linear.

For example, for `flatten_dl` the attempt to get it well-moded fails as follows. Assume the mode `flatten(+,-)`. For the first clause we have to use a mode of the form `flatten_dl(?,-,?)`. Now due to the last clause we actually have to use a mode of the form `flatten_dl(?,-,+)`. But then in the recursive clause for `flatten_dl` we cannot satisfy the requirement of well-modedness concerning the variable `Y1s`.

However, it is possible to modify the results on well-moded and nicely moded programs in such a way that the occur-check freedom of the above two programs used in the discussed modes still can be established. The idea is quite simple, though some work is needed to make it precise. Suppose that we know that some program atoms when selected in a derivation are ground in specific input positions. Then these input positions do not need to be considered when proving that the program is occur-check free.

To formalize this idea we consider a program and goal in two different modings. First we prove that when an atom is selected in a derivation, its input positions, which are "shared" in both modes, are ground. Then we consider a derived program obtained by removing from each atom these shared input positions and apply to it the previous results on the nicely moded programs.

To avoid confusion we write below m-well-moded (resp. m-nicely moded, etc.) when a given goal (clause) (program) is well-moded (resp. nicely moded, etc.) with respect to the moding m. Assume now two modings m_1 and m_2. Fix a relation symbol p. Some positions in p are both m_1-input and m_2-input. We associate now with p a new relation symbol p^- in which these shared input positions are removed and the remaining positions are moded as in m_2. The moding so obtained for the relation symbols of the form p^- is denoted by $m_2 - m_1$.

For example, if m_2 is `flatten_dl(+,+,-)` and m_1 is `flatten_dl(+,-,-)`, then $m_2 - m_1$ is `flatten_dl`$^-$`(+,-)`. These new relation symbols allow us to associate with any atom A written in the mode m_2 as $p(\mathbf{u}, \mathbf{v})$, an atom A^- written in the mode $m_2 - m_1$ as $p^-(\mathbf{u}^-, \mathbf{v})$, where $\mathbf{u}^-$ is obtained by removing from $\mathbf{u}$ the terms which are in m_1-input positions. For example, for the above two modes m_1 and m_2 and $A =$ `flatten_dl([X | Xs], Ys, Zs)` we get A^- = `flatten_dl`$^-$`(Ys, Zs)`.

Given now a sequence of atoms $\mathbf{A}$, we associate with it a sequence $\mathbf{A}^-$ obtained by replacing in $\mathbf{A}$ every atom A by A^-.

DEFINITION 7.1.

—A goal $\leftarrow \mathbf{A}$ is called *m_2-nicely moded w.r.t. m_1* (*$m_2|m_1$-nice* in short) if the goal $\leftarrow \mathbf{A}^-$ is $(m_2 - m_1)$-nicely moded.

—A clause $H \leftarrow \mathbf{B}$ is called *$m_2|m_1$-nice* if the clause $H^- \leftarrow \mathbf{B}^-$ is $m_2|m_1$-nice.

—A program is called *$m_2|m_1$-nice* if every clause of it is. □

Thus a goal (clause) (program) is $m_2|m_1$-nice if its "$^-$" version is $(m_2 - m_1)$-nicely moded. Note that the notion of $m_2|m_1$-nice goal (clause) (program) extends that of nice goal (clause) (program). Indeed, if a goal (clause) (program) is m_2-nice then it is $m_2|m_1$-nice for every m_1. Also, a goal (clause) (program) is $m_1|m_1$-nice and m_1-well-moded iff it is m_1-strictly moded.

The following theorem explains the usefulness of this concept.

THEOREM 7.2. *Suppose that*

—*all LD-derivations of $P \cup \{G\}$ are m_1-data driven,*

—*P and G are $m_2|m_1$-nice.*

Then all LD-derivations of $P \cup \{G\}$ are m_2-output driven.

Proof. First we prove that all goals appearing in an LD-derivation of $P \cup \{G\}$ are $m_2|m_1$-nice. To this end, due to the assumption of m_1-data drivedness, it suffices

to prove that for A m_1-input ground an LD-resolvent of a $m_2|m_1$-nice goal $\leftarrow A, \mathbf{A}$ and a disjoint with it variant $H \leftarrow \mathbf{B}$ of a $m_2|m_1$-nice clause is $m_2|m_1$-nice, as well.

Assume that A and H are unifiable. $A = H$ equals $E \cup (A^- = H^-)$ where the left-hand sides of the equations from E are ground. Let θ_1 be a relevant mgu of E and θ_2 a relevant mgu of $(A^- = H^-)\theta_1$. The existence of these substitutions is assured by Lemma 2.4 which also gives that $\theta_1\theta_2$ is a relevant mgu of $A = H$.

θ_1 is grounding, so by the definition of a nicely moded goal and clause, both $\leftarrow (A^-, \mathbf{A}^-)\theta_1$ and $(H^- \leftarrow \mathbf{B}^-)\theta_1$ are $(m_2 - m_1)$-nicely moded. By Lemma 5.3 their LD-resolvent $\leftarrow (\mathbf{B}^-, \mathbf{A}^-)\theta_1\theta_2$ is $(m_2 - m_1)$-nicely moded, i.e. $\leftarrow (\mathbf{B}, \mathbf{A})\theta_1\theta_2$, the resolvent of $\leftarrow A, \mathbf{A}$ and $H \leftarrow \mathbf{B}$, is $m_2|m_1$-nice. To draw the same conclusion for an arbitrary LD-resolvent of $\leftarrow A, \mathbf{A}$ and $H \leftarrow \mathbf{B}$ it suffices now to use Lemma 2.3.

Consider now a goal appearing in an LD-derivation of $P \cup \{G\}$. We just established that it is $m_2|m_1$-nice, so its first atom A is such that A^- is $(m_2 - m_1)$-output linear and $(m_2 - m_1)$-input-output disjoint. By assumption A is also m_1-input ground, so A is actually m_2-output linear and m_2-input-output disjoint. This proves the claim. □

This brings us to the following conclusion.

COROLLARY 7.3. *Suppose that*

—*all LD-derivations of* $P \cup \{G\}$ *are* m_1*-data driven,*

—P *and* G *are* $m_2|m_1$*-nice,*

—*for a head* H*, of a clause of* P*,* H^- *is* $(m_2 - m_1)$*-input linear.*

Then $P \cup \{G\}$ *is occur-check free.*

Note that the last assumption is weaker than the statement that the head of every clause of P is m_2-input linear.

Proof. Let A be an atom selected in an LD-derivation of $P \cup \{G\}$ and suppose that H is a head of an input clause such that A and H have the same relation symbol. By Theorem 7.2 A is m_2-output linear and m_2 input-output disjoint. Let m_3 be the mode obtained from m_2 by reversing the m_1-input positions to output positions. By assumption the m_1-input positions of A are ground, so A is m_3-output linear and m_3-input-output disjoint. Moreover, by assumption H is m_3-input linear. Now the NSTO via Modes Lemma 3.3 applies and yields that $A = H$ is NSTO. □

We noticed already that neither `flatten_dl` nor `quicksort_dl` is well-moded when the relation `flatten` (resp. `qs`) is moded `(+,-)`. Thus to be able to apply this corollary we need another method for establishing data-drivedness than proving well-modedness. Our idea is to weaken the latter notion by assuming that only part of the program is well-moded, and by requiring that the previous inclusions referring to the output variables refer now to the output variables of the atoms defined in this well-moded part. We begin with some definitions.

DEFINITION 7.4. Let P be a program and p, q relations.

—We say that p *refers to* q iff there is a clause in P that uses p in its head and q in its body.

—We say that p *depends on* q iff (p, q) is in the reflexive, transitive closure of the relation *refers to*.

—We say that a clause of P *defines the relation* p if p is used in its head. □

DEFINITION 7.5. Consider a program P and an atom A in a given moding.

—We denote by P_A the set of clauses of P that define the relation p of A and the relations on which p depends.

—We say that A is *well-moded in* P if P_A is. □

For example, in the moding `qs(+,-), qs_dl(+,+,-), partition(+,+,-,-)`, for $A =$
`partition(X, Xs, Littles, Bigs)` we have $\texttt{quicksort_dl}_A = \texttt{partition}$, so A is well-moded in `quicksort_dl`.

We now introduce the following modification of the notion of a well-moded program and goal.

DEFINITION 7.6. Let P be a program.

—A goal $\leftarrow p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$ is called *weakly moded w.r.t.* P if for $i \in [1, n]$

$$Var(\mathbf{s_i}) \subseteq \bigcup_{j=1}^{k} Var(\mathbf{t_{i_j}}),$$

where $p_{i_1}(\mathbf{s_{i_1}}, \mathbf{t_{i_1}}), \ldots, p_{i_k}(\mathbf{s_{i_k}}, \mathbf{t_{i_k}})$ are all the atoms among $p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_{i-1}(\mathbf{s_{i-1}}, \mathbf{t_{i-1}})$ which are well-moded in P. (Here and below k depends on i.)

—A clause

$$p_0(\mathbf{s_0}, \mathbf{t_0}) \leftarrow p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$$

is called *weakly moded w.r.t.* P if for $i \in [1, n]$

$$Var(\mathbf{s_i}) \subseteq Var(\mathbf{s_0}) \cup \bigcup_{j=1}^{k} Var(\mathbf{t_{i_j}}),$$

where $p_{i_1}(\mathbf{s_{i_1}}, \mathbf{t_{i_1}}), \ldots, p_{i_k}(\mathbf{s_{i_k}}, \mathbf{t_{i_k}})$ are all the atoms among $p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_{i-1}(\mathbf{s_{i-1}}, \mathbf{t_{i-1}})$ which are well-moded in P.
In particular, every unit clause is weakly moded w.r.t. P.

—A program is called *weakly moded* if every clause of it is weakly moded w.r.t. it. □

Thus, a goal is weakly moded w.r.t. P if

—every variable occurring in an input position of an atom occurs in an output position of an earlier, well-moded in P, atom.

And a clause is weakly moded w.r.t. P if

—($i \in [1, n]$) every variable occurring in an input position of a body atom occurs either in an input position of the head, or in an output position of an earlier body atom, which is well-moded in P.

Observe that a goal with only one atom is weakly moded w.r.t. a program P iff this atom is ground in its input positions. The notion of being weakly moded is obviously related to that of being well-moded. In fact, if a program P is well-moded, then it is weakly moded. Next, assuming that P is well-moded, if a goal is well-moded, then it is weakly moded w.r.t. P. Thus the following theorem generalizes Theorem 4.2.

THEOREM 7.7. *Let P be weakly moded and G weakly moded w.r.t. P. Then all LD-derivations of $P \cup \{G\}$ are data driven.*

Note that the first atom of a weakly moded goal is ground in its input positions and a variant of a weakly moded clause is weakly moded (all w.r.t. a program P). Thus, as in the case of Theorem 4.2 it suffices to prove the following lemma showing the persistence of the notion of being weakly modedness.

LEMMA 7.8. *An LD-resolvent of a weakly moded goal and a weakly moded clause that is variable-disjoint with it, is weakly moded, all w.r.t. a program P.*

Proof. The proof is analogous to that of Lemma 4.3. We prove two claims.

CLAIM 1. *An instance of a weakly moded goal (resp. clause) is weakly moded, both w.r.t. a program P.*

Proof. As the proof of Claim 1 of Lemma 4.3. □

CLAIM 2. *Suppose $\leftarrow H, \mathbf{A}$ is a weakly moded goal and $H \leftarrow \mathbf{B}$ is a weakly moded clause. Then $\leftarrow \mathbf{B}, \mathbf{A}$ is a weakly moded goal, all w.r.t. a program P.*

Proof. Let $H = p(\mathrm{s}, \mathrm{t})$ and $\mathbf{B} = p_1(\mathrm{s_1}, \mathrm{t_1}), \ldots, p_n(\mathrm{s_n}, \mathrm{t_n})$. We have $Var(\mathrm{s}) = \emptyset$ since H is the first atom of a weakly moded goal. Thus $\leftarrow \mathbf{B}$ is weakly moded.

Now, if H is well-moded in P, then $H \leftarrow \mathbf{B}$ is a well-moded clause, and consequently $Var(\mathrm{t}) \subseteq \bigcup_{j=1}^{n} Var(\mathrm{t_j})$, since $Var(\mathrm{s}) = \emptyset$. Moreover, all atoms in $\mathbf{B}$ are then well-moded. So $\leftarrow \mathbf{B}, \mathbf{A}$ is weakly moded.

If H is not well-moded in P, then by assumption $\leftarrow \mathbf{A}$ is weakly moded and so $\leftarrow \mathbf{B}, \mathbf{A}$ is, as well. □

□

In contrast, Corollary 4.4 does not generalize to the case of weak modedness. Indeed, consider $P = \{p(x) \leftarrow\}$ and $G = \leftarrow p(y)$, where the relation p is moded $p(-)$.

Combining now Theorem 7.7 with Corollary 7.3 we obtain the generalization of Corollaries 5.4 and 6.5 we aimed at.

COROLLARY 7.9. *Suppose that*

—*P is m_1-weakly moded and G m_1-weakly moded w.r.t. P,*

—*P and G are $m_2|m_1$-nice,*

—*for a head H, of a clause of P, H^- is $(m_2 - m_1)$-input linear.*

Then $P \cup \{G\}$ is occur-check free. □

The conditions of this corollary look quite elaborate, but it is easy to check them for specific programs.

EXAMPLE 7.10.
(i) Consider the `flatten_dl` program with "\" replaced by ",". Choose m_2 = `flatten(+,-), flatten_dl(+,+,-), constant(+),` $\neq$`(+,+)`. It is easy to see that in this moding `flatten_dl` is nicely moded, so it is $m_2|m_1$-nice for any moding m_1. However, in the moding m_2 the head of the third clause is not input linear, so we cannot apply here Corollary 5.4.

On the other hand, by choosing m_1 with `flatten_dl(+,-,-)` and all other modes as in m_2, we get for a head H of a clause of `flatten_dl` that H^- is $(m_2 - m_1)$-input linear. Additionally, `flatten_dl` is m_1-weakly moded.

We can now apply Corollary 7.9 and conclude that when `xs` is ground and `ys` is linear, `flatten_dl` $\cup$ { $\leftarrow$ `flatten(xs, ys)`} is occur-check free.

(ii) Let us examine now the program `quicksort_dl`, again with "\" replaced by ",". Choose m_2 = `qs(+,-), qs_dl(+,+,-), partition(+,+,-,-)`. In this mode `quicksort_dl` is not nicely moded since in the second clause the variable `X` occurs both in an input position of the head and in an output position of a body atom.

However, by choosing m_1 with `qs_dl(+,-,-)` and all other modes as in m_2, we get that `quicksort_dl` is $m_2|m_1$-nice. Additionally, `quicksort_dl` is m_1-weakly moded since, as we already noted, `partition(X, Xs, Littles, Bigs)` is well-moded in `quicksort_dl`. Also, for a head H, of a clause of `quicksort_dl`, H^- is $(m_2 - m_1)$-input linear.

By Corollary 7.9 we get that when `xs` is ground and `ys` is linear, `quicksort_dl` $\cup$ { $\leftarrow$ `qs(xs, ys)`} is occur-check free.

(iii) Finally, consider the following program `normalize` from Sterling and Shapiro [28, page 248], in which we replaced the binary infix symbol "++" (symbolizing the sum still to be performed) by ",":

```
normalize(Exp, Norm) ← normalize_ds(Exp, Norm, 0).

normalize_ds(A+B, Norm, Space) ←
   normalize_ds(A, Norm, NormB)
   normalize_ds(B, NormB, Space).
normalize_ds(A, (A+Space), Space) ← constant(A).
```

`normalize` converts a sum `Exp` into a normalized form `Norm` that is bracketed to the right. For example $(a + b) + (c + d)$ is normalized to $(a + (b + (c + d)))$.

Assume the mode `normalize(+,-)`. We leave to the reader the task of checking that Corollaries 4.5, 5.4 or 6.5 cannot be applied here. Consider now m_2 = `normalize(+,-), normalize_ds(+,+,-), constant(+)`, and let m_1 consist of `normalize_ds(+,-,-)` and all other modes as in m_2. The same reasoning as in the case of `flatten_dl` applies and yields that for `exp` ground and `norm` linear, `normalize` $\cup$ { $\leftarrow$`normalize(exp, norm)`} is occur-check free.

8. GENERAL PROGRAMS

We now consider an extension of these results to the case of general programs, i.e. programs in which negative literals in the clause bodies are allowed. We also show here that the concept of well-modedness can be used to prove absence of floundering, i.e. selection of a negative, non-ground literal in a derivation.

First, we need to extend the basic definitions. By the *LDNF-resolution* we mean the SLDNF-resolution of Clark [9] with the leftmost selection rule. When studying

the occur-check problem we need to use a definition of SLDNF-resolution which guarantees that for every general program P and a general goal G the SLDNF-tree, which comprises all SLDNF-derivations exists. (The definition provided in Lloyd [18] is for this purpose too restrictive — for example for the program $P = \{p \leftarrow p\}$ and the general goal $G = \leftarrow \neg p$ no SLDNF-derivation or tree exists.) Such a definition was recently given in Apt and Doets [4].

Here we only need to know what are the general goals which can appear in an LDNF-derivation of $P \cup \{G\}$. This leads us to the following definition, where for a general goal H and a literal L, $H - \{L\}$ stands for the result of removing L from H.

DEFINITION 8.1. Consider an LDNF-derivation of $P \cup \{G\}$. Let $\mathcal{G}_{P,G}$ be the least set of general goals such that

(i) $G \in \mathcal{G}_{P,G}$,

(ii) if $H \in \mathcal{G}_{P,G}$, the first literal of H is positive and H' is an LDNF-resolvent of H and a general clause of P that is variable-disjoint with it, then $H' \in \mathcal{G}_{P,G}$,

(iii) if $H \in \mathcal{G}_{P,G}$ and the first literal, L, of H is negative and ground, then $H - \{L\} \in \mathcal{G}_{P,G}$,

(iv) if H is ground, then $H \in \mathcal{G}_{P,G}$. □

Using the definition of SLDNF-resolution provided in Apt and Doets [4] it is straightforward to prove the following lemma whose proof we omit.

LEMMA 8.2. *Consider an LDNF-derivation ξ of $P \cup \{G\}$. Every general goal which appears in ξ belongs to $\mathcal{G}_{P,G}$.* □

When computing with general programs one of the complications is so-called floundering. We study it here for the case of the LDNF-resolution.

DEFINITION 8.3. Let P be a general program and G a general goal. We say that $P \cup \{G\}$ *flounders* if in the LDNF-tree of $P \cup \{G\}$ a general goal appears with the first literal negative and non-ground. □

Next, when considering the notion of the occur-check freedom for general programs and general goals, we simply reuse the original Definition 2.6. In this way, we ignore the selection of negative literals but this does not matter as the choice of a negative literal $\neg A$ either leads to floundering or to the consideration of the goal $\leftarrow A$ whose selected literal is positive. In both cases no unification is performed.

The concepts of data and output driven derivations extend to LDNF-derivations in a straightforward way by considering selected literals instead of selected atoms.

Now, we generalize the notion of well-modedness to general programs and general goals by simply allowing in Definition 4.1 the negation symbol to occur in front of any atom $p_i(\mathbf{s_i}, \mathbf{t_i})$, where $i \in [1, n]$. Theorem 4.2 easily generalizes to general programs and general goals. More precisely, we have the following result.

THEOREM 8.4. *Consider a general program P and a general goal G. Let P and G be well-moded. Then all LDNF-derivations of $P \cup \{G\}$ are data driven.*

Proof. First we prove that every general goal in $\mathcal{G}_{P,G}$ is well-moded. Lemma 4.3 generalizes to LDNF-resolvents, so clause (ii) of Definition 8.1 preserves well-modedness. Obviously so does clause (iii), and clauses (i) and (iv) admit only

well-moded general goals in $\mathcal{G}_{P,G}$. The desired conclusion now follows from Lemma 8.2 and the fact that the first literal of a well-moded general goal is ground in its input positions. □

Consequently, Corollary 4.5 holds for general programs and general goals, this time by virtue of Theorems 3.5 and 8.4.

The following simple result shows that the concept of well-modedness is also very helpful for the study of floundering. It was independently discovered by Stroetman [29].

THEOREM 8.5. *Consider a general program P and a general goal G. Suppose that P and G are well-moded and that all relations which appear in negative literals of P and G are moded completely input. Then $P \cup \{G\}$ does not flounder.*

Proof. Using the inductive definition of $\mathcal{G}_{P,G}$ it is straightforward to show that every negative literal L occurring in a general goal $H \in \mathcal{G}_{P,G}$ is an instance of a negative literal occurring in P or G. So by assumption the relation appearing in such L is moded completely input. The claim now follows by Lemma 8.2 and by Theorem 8.4. □

Note that also Theorem 7.7 easily generalizes to general goals and general programs. Consequently, Theorem 8.5 can be strengthened to the case of (appropriately defined) weakly moded general goals and general programs. The above generalization of Corollary 4.5, and Theorem 8.5 are easily applicable.

EXAMPLE 8.6. All general programs below are understood to be augmented by the following program `member`:

```
member(X, [Y | Xs]) ← member(X, Xs).
member(X, [X | Xs]).
```

(i) Consider the following general program `disjoint`:

```
disjoint(X, Y) ← ¬ overlap(X, Y).
overlap(X, Y) ← member(Z, X), member(Z, Y).
```

with the moding `disjoint(+,+)`, `overlap(+,+)`, `member(-,+)`. Of course, `disjoint` checks whether two lists are disjoint.

`disjoint` is clearly well-moded and the heads of all general clauses are output linear, so for `s` and `t` ground, `disjoint` $\cup$ { ← `disjoint(s, t)`} is occur-check free, and by virtue of Theorem 8.5 it does not flounder.

(ii) The following well-known general program `trans` computes the transitive closure of a binary relation:

```
trans(X, Y, E, V) ← member([X, Y], E).
trans(X, Z, E, V) ←
   member([X, Y], E),
   ¬ member(Y, V),
   trans(Y, Z, E, [Y | V]).
```

In a typical use of this program in order to check that `[x, y]` is in the transitive closure of the binary relation `e`, one evaluates the goal ← `trans(x, y, e, [x])`.

With the moding `trans(-,-,+,+)`, `member(+,+)` for the occurrence of `member` in the negative literal ¬ `member(Y, V)`, and `member(-,+)` for the other occurrences of `member`, `trans` is well-moded and the heads of all general clauses are output linear. So we conclude that for `e,v` ground, `trans` ∪ { ← `trans(s, t, e, v)`} is occur-check free and by Theorem 8.5 it does not flounder. The mode `member(+,+)` is needed here only to draw the latter conclusion.

(iii) Finally, consider the following general program `sink`:

```
sink(X, E) ← ¬ interior(X, E).
interior(X, E) ← member([X, Y], E).
```

with the moding `sink(+,+)`, `interior(+,+)`, `member(-,+)`. For a binary relation `e`, the goal ← `sink(a, e)` succeeds if `a` is a sink point in `e`. `sink` is well-moded and the heads of all general clauses are output linear, so for `a,e` ground, `sink` ∪ { ← `sink(a, e)`} is occur-check free and does not flounder. □

The usual approach to prove absence of floundering by syntactic means concentrates on SLDNF-resolution and is based on various generalizations of the concept of allowedness (see Decker [11] for the strongest results in this direction). However, these techniques in general cannot be applied LDNF-resolution which employs a more specific notion of flounderning.

Using Lemma 8.2 it is also possible to generalize the results on nicely and strictly moded programs (viz. Corollaries 5.4 and 6.5) to the case of general programs. However, the concept of a strictly moded general program is rarely needed and that of a nicely moded general program does not prevent the use of non-ground input positions in the goals. As a result general programs to which the results on nicely moded general programs can be applied usually flounder. So — in the framework of LDNF-resolution — these generalizations are of limited interest and consequently are omitted.

9. DISCUSSION

To apply the established results to a (general) program and a (general) goal, one needs to find appropriate modings for the considered relations such that the conditions of one of the established Corollaries are satisfied. In the table below several programs taken from the book of Sterling and Shapiro [28] are listed. (A similar analysis of the notion of a well-moded program was carried in Drabent [15]). Corollary 3.8 can be applied to none of them. For each program it is indicated which of the relevant conditions for a given moding are satisfied. All built-in's are moded completely input.

In programs which use difference-lists we replaced "\" by ",", thus splitting a position filled in by a difference-list into two positions. Because of this change in some relations additional arguments are introduced, and so certain clauses have to be modified in an obvious way. For example, in the parsing program on page 258 each clause of the form `p(X)` ← `r(X)` has to be replaced by `p(X,Y)` ← `r(X,Y)`. Such changes are purely syntactic and they allow us to draw conclusions about the occur-check freedom of the original program.

The modings considered are usually intuitive and at least one of the Corollaries 4.5, 5.4 or 6.5 applies.

program	page	moding	well-moded	heads out. lin.	nicely moded	heads in. lin.	strictly moded
member	45	(–,+)	yes	yes	yes	yes	yes
member	45	(+,+)	yes	yes	yes	no	yes
prefix	45	(–,+)	yes	yes	yes	yes	yes
prefix	45	(+,+)	yes	yes	yes	no	yes
suffix	45	(–,+)	yes	yes	yes	yes	yes
suffix	45	(+,+)	yes	yes	yes	no	yes
naive reverse	48	r(+,–) a(+,+,–)	yes	yes	yes	yes	yes
reverse-acc.	48	r(+,–) r(+,+,-)	yes	yes	yes	yes	yes
delete	53	(+,+,–)	yes	yes	yes	no	yes
select	53	(+,+,–)	yes	yes	yes	no	yes
insertion sort	55	s(+,–) i(+,+,–)	yes	yes	yes	yes	yes
tree-member	58	(–,+)	yes	yes	yes	yes	yes
tree-member	58	(+,+)	yes	yes	yes	no	yes
isotree	58	(+,+)	yes	yes	yes	no	yes
substitute	60	(+,+,+,–)	yes	yes	yes	no	yes
pre-order	60	p(+,–) a(+,+,–)	yes	yes	yes	yes	yes
in-order	60	i(+,–) a(+,+,–)	yes	yes	yes	yes	yes
post-order	60	p(+,–) a(+,+,–)	yes	yes	yes	yes	yes
polynomial	62	(+,+)	yes	yes	yes	no	yes
derivative	63	(+,+,–)	yes	no	yes	no	yes
hanoi	64	h(+,+,+,–) a(+,+,–)	yes	yes	yes	yes	yes

append_dl	241	(+,−,+,+,−,−)	yes	yes	yes	yes	yes
append_dl	241	(+,−,+,−,−,−)	no	no	yes	yes	no
flatten_dl	241	f(+,+) f_dl(+,+,−)	yes	yes	yes	no	yes
flatten	243	f(+,−) f(+,+,−)	yes	yes	yes	yes	yes
reverse_dl	244	r(+,−) r_dl(+,−,+)	yes	yes	yes	yes	yes
quicksort_dl	244	q(+,+) q_dl(+,+,−) p(+,+,−,−)	yes	yes	no	yes	yes
dutch	246	dutch(+,−) di(+,−,−,−)	yes	yes	yes	yes	yes
dutch_dl	246	dutch(+,−) di(+,−,+,−,+,−,+)	yes	yes	yes	yes	yes
parsing	258	all (+,−)	yes	yes	yes	yes	yes

The appropriate entry in the table above indicates that, after replacing "\" by ",", in the mode `flatten(+,+)` and `flatten_dl(+,+,-)`, `flatten_dl` is well-moded and the heads of the clauses are output linear. Thus by virtue of Corollary 4.5 for `s` and `t` ground, all LD-derivations of `flatten_dl` $\cup$ { $\leftarrow$ `flatten(s,t)`} are occur-check free. Similar conclusion can be drawn about `quicksort_dl` moded `qs(+,+)`, `qs_dl(+,+,-)`, `partition(+,+,-,-)`. Thus for a restricted class of goals the occur-check freedom of these two programs can be established by means of the elementary techniques presented in Chapter 4.

10. WHEN THE OCCUR-CHECK IS NEEDED

Still, the results of this paper should be interpreted with caution. When Corollary 5.4 cannot be applied to a given program, the only alternative are Corollaries 4.5, 6.5 or 7.9. In such cases well- or weak-modedness is required and thus groundness of the inputs of the one atom goal has to be assumed. Thus no conclusion about the occur-check freedom for one atom goals with non-ground inputs can be drawn. For example, for the `member` program of Exercise 8.6 no conclusion can be drawn for the goal $\leftarrow$ `member(Y1s, Y2s)` when `Y1s` and `Y2s` are not ground. And indeed, when `Y2s = [f(Y1s)]` one of the considered systems is { `Y1s = X, f(Y1s) = X, [] = Xs` } which *is* subject to occur-check. Thus, after all, even for simple programs the occur-check problem can very easily creep in.

In view of this discussion it is easy to interpret the obtained results as a statement that the occur-check problem can arise only when considering some "ill-designed programs" or "ill-posed goals". The following delightful example offered to us by

Dino Pedreschi (private communication) shows that it is not so.

Consider the typed lambda calculus and Curry's system of type assignment (see Curry and Feys [10]). It involves statements of the form $x : t$ which should be read as "term x has type t". Finite sequences of such statements are denoted below by R. The following three rules allow us to assign types to lambda terms:

$$\frac{x : t \in R}{R \vdash x : t}$$

$$\frac{R \vdash m : s \to t \ , \quad R \vdash n : s}{R \vdash (m\ n) : t}$$

$$\frac{R \ , \ x : s \vdash m : t}{R \vdash (\lambda x.\, m) : s \to t}$$

These rules translate directly into the following Prolog program `curry` which can be used to compute a type assignment to a lambda term, if such an assignment exists (see e.g. Reddy [24]):

```
curry(R, var(X), T) ← in([X, T], R).
curry(R, apply(M, N), T) ← curry(R, M, S → T), curry(R, N, S).
curry(R, lambda(X, M), S → T) ← curry([[X, S] | R], M, T).

in(X, [Y | Xs]) ← X ≠ Y, in(X, Xs).
in(X, [X | Xs]).
```

In the first clause the function symbol `var` is used to enforce the interpretation of `X` as a variable and consequently to prevent the instantiations of the clause to statements about the application and lambda abstraction. $\to$ is a binary function symbol written in an infix form.

Consider now the lambda term $\lambda x.\ (x\ x)$ to which no type can be assigned, and its Prolog representation `m = lambda(X, apply(var(X), var(X)))`. Then it is easy to prove that the goal $\leftarrow$`curry([], m, T)` finitely fails. However, when the unification without the occur-check is used, then, if the substitution $\{x/t\}$ is performed in t, the goal $\leftarrow$`curry([], m, T)` diverges, and otherwise it succeeds! Thus for the above program it is essential that a unification algorithm with the occur-check is used.

To deal with such programs we propose to use a program transformation. The following strengthening of Corollary 5.4 is essential.

THEOREM 10.1. *Let P and G be nicely moded. All systems of equations which are considered in the LD-derivations of $P \cup \{G\}$ and are obtained using a clause whose head is input linear, are NSTO.*

Proof. By Lemma 5.3 all goals which appear in the LD-derivations of $P \cup \{G\}$ are nicely moded. But the first atom of a nicely moded goal is output linear and input-output disjoint. So when the head of the input clause used is input linear, by the NSTO via Modes Lemma 3.3 the corresponding system of equations is NSTO. □

To use this result we transform a program and a goal into a nicely moded program and a nicely moded goal using the relation "$=_{oc}$" which is defined by the single clause $\mathtt{X} =_{oc} \mathtt{X}$ moded completely input. In the transformed program only this relation will be evaluated by the unification algorithm with the occur-check. The subscript $_{oc}$ was added to distinguish it from the Prolog built-in "=" which performs unification without the occur-check.

The idea is to replace the variables which "contradict nice modedness" by "fresh" variables. Consider a clause $H \leftarrow \mathbf{B}$. Assume for simplicity that in every atom input positions occur first. We say that a given occurrence of a variable x in $\mathbf{B}$ *contradicts nicety* of $H \leftarrow \mathbf{B}$ if x occurs in an output position of an atom in $\mathbf{B}$ and x occurs earlier in $\mathbf{B}$ or in an input position of H.

Consider now an occurrence of x in $\mathbf{B}$ which contradicts nicety. Let A be the atom in $\mathbf{B}$ in which this occurrence of x takes place, and let z be a fresh variable. Replace this occurrence of x in A by z and denote the resulting atom A'. Replace A in $\mathbf{B}$ by $A', z =_{oc} x$.

Scan now $\mathbf{B}$ and perform this replacement repeatedly for all occurrences of variables which contradict the nicety of the original clause $H \leftarrow \mathbf{B}$. Call the resulting sequence of atoms $\mathbf{B}'$. It is easy to see that $H \leftarrow \mathbf{B}$ is nicely moded. Note that by unfolding (in the sense of Tamaki and Sato [30]) the inserted calls of "$=_{oc}$" in $H \leftarrow \mathbf{B}'$, we obtain the original clause $H \leftarrow \mathbf{B}$.

The same transformation applied to an arbitrary goal transforms it into a nicely moded goal. Finally, a similar transformation ensures that the head H of $H \leftarrow \mathbf{B}$ is input linear. It suffices to repeatedly replace every occurrence of a variable x which contradicts linearity of H by a fresh variable z, and replace $\mathbf{B}$ by $z =_{oc} x, \mathbf{B}$. Clearly, the head of the resulting clause $H \leftarrow \mathbf{B}'$ is input linear and this transformation does not destroy the nicety of the clause. Again, the original clause $H \leftarrow \mathbf{B}$ can be obtained by unfolding the inserted calls of "$=_{oc}$".

The following result summarizes the effect of these transformations.

THEOREM 10.2. *For every program P and goal G there exists a program P' and a goal G' such that*

—*P' and G' are nicely moded,*

—*the head of every clause of P' different from $\mathtt{X} =_{oc} \mathtt{X}$ is input linear,*

—*P is the result of unfolding some calls of "$=_{oc}$" in P',*

—*G is the result of evaluating some calls of "$=_{oc}$" in G',*

—*all systems of equations considered in the LD-derivations of $P' \cup \{G'\}$, but not associated with the calls of "$=_{oc}$", are NSTO.*

Note that the clause $\mathtt{X} =_{oc} \mathtt{X}$ is not input linear, so Corollary 5.4 cannot be applied to P' and G'.

Proof. By construction and Theorem 10.1. □

As behaviour of an unfolded program is closely related to the original program (see e.g. Bossi and Cocco [7]), it is indeed justified to summarize this result by saying that every program and goal is equivalent to a nicely moded program and nicely moded goal such that the heads of all clauses, except $\mathtt{X} =_{oc} \mathtt{X}$, are input linear. In the Prolog execution of the latter program and goal *only* the inserted calls

of "$=_{oc}$" need to be evaluated by means of a unification algorithm with the occur-check. Note that this transformation trades some "fragments" of the unification with the call of the relation "$=_{oc}$". These inserted calls of "$=_{oc}$" can be viewed as the overhead needed to correctly implement the original program without the occur check.

Alternatively, the part of the transformation which ensures that the head of each clause is input linear, could be dropped and Theorem 10.1 could be applied.

To conclude, let us see how this transformation can be applied to the above program `curry`. Consider the moding `curry(+,+,-), in(+,+)`. Then the second clause of `curry` is not nicely moded, because the second occurrence of `S` contradicts its nicety. The corresponding transformed clause is nicely moded:

`curry(R, apply(M,N), T)` $\leftarrow$ `curry(R, M, S` $\rightarrow$ `T), curry(R, N, Z), Z` $=_{oc}$ `S`.

Another problem is that the head of the second clause of `in` is not input linear. The transformed version is

`in(X, [Z | Xs])` $\leftarrow$ `Z` $=_{oc}$ `X`.

Call the transformed program `curry'`. It is nicely moded and the head of every clause is input linear. By Corollary 5.4 we conclude that when `t` is linear and $Var(\mathtt{r},\mathtt{m}) \cap Var(\mathtt{t}) = \emptyset$, `curry'` $\cup \{\leftarrow$ `curry(r, m, t)`$\}$ is occur-check free. This allows us to draw the desired conclusion for the previously considered goal $\leftarrow$ `curry([], m, T)` with `m = lambda(X, apply(var(X), var(X)))`.

The proposed transformation can be easily used "manually" and also can be efficiently implemented using two passes through the goal and the program, one to ensure nice modedness and the other to ensure the input linearity of the heads of the program clauses. This approach deals with the problem of inserting occur-checks at the source level and is orthogonal to that of Beer [6] who proposed to use a revised implementation in which a new tag in the Warren Abstract Machine is used. This tag maintains information about the context in which a variable is used. This makes possible to optimize the generated code by avoiding calls to the occur-check routine at the cost a small overhead at run-time. It should be pointed out that in his approach also unnecessary calls to the occur-check routine can be generated. For example, he reports that 49 occur-checks were invoked for the `quicksort` program.

11. CONCLUDING REMARKS

We provided here a systematic account of an approach for proving occur-check freedom of Prolog programs based on syntactic analysis. In this approach, also advocated by Chadha and Plaisted [8], it is shown that existence of specific relationships between the variables of the goal and the variables of the program implies occur-check freedom. As a side effect we also explained how this approach can be used to prove absence of floundering. Finally, we showed how these results can be used to deal with the problem of insertion of occur-check tests in the program text by means of a program transformation.

The results on the occur-check freedom were established following a similar approach. First, systems of equations that are free from the occur-check were identified. Then a property of a moded goal and a moded program was defined and

proved to be "persistent" throughout the executions of the programs. This property ensured that in all executions the selected atoms lead to desired systems of equations. To deal with programs that use difference-lists a modification of these results, that involved two different modes, was needed.

Two other approaches to the subject of proving occur-check freedom were proposed in the literature. One is based on the abstract interpretations and another uses the attribute grammars.

The first approach originated with Plaisted [22] and was further developed in Søndergaard [27]. Søndergaard used an abstract interpretation in which the information on the possibility of creating a *sharing* of a variable or forming multiple occurrences of the same variable (called *spawning*) is maintained. Then using abstract unification this sharing and spawn information is propagated among the program representation in order to discover whether the abstract unification may lead to circularity. The absence of circularity guarantees occur-check freedom.

The abstract interpretations were also used to prove the absence of floundering. The strongest results were obtained by Marriott, Søndergaard and Dart [19]. To this end they expressed a dataflow analysis of a general program by means of a finitely computable approximation of the denotational semantics. Such an approximation is determined by suitable functions which approximate the groundness information and the unification algorithm.

The approach based on attribute grammars was originated by Deransart and Maluszynski [14] and was further developed in Deransart, Ferrand and Téguia [13]. This approach exploits a close relationship between the abstract skeletons associated with the executions of a goal and a program and the derivation trees of the grammar associated with the goal and the program. The attributes are used to model relation between equations (like variable sharing). Then it is shown that the occur-check freedom is implied by a combination of syntactic conditions and of non circularity of the attribute dependency scheme. This approach was applied recently by Dumant [16] to deal with the problem of inserting occur-checks in arbitrary resolution strategies.

The syntactic approach advocated in this paper is much more straightforward and has in our opinion two important advantages. First, it can be trivially implemented. Secondly, it can be easily used "manually". In fact, we showed that it can be readily applied to several well-known Prolog programs. Consequently, it seems to be sufficient to deal satisfactorily with most common Prolog programs. It would be interesting to clarify the precise relationship between this aproach and the other two.

ACKNOWLEDGMENTS

We thank Pierre Deransart and the referees for constructive remarks on the subject of this paper and Dino Pedreschi for providing the `curry` program example.

REFERENCES

1. L. Albert, R. Casas, and F. Fages. Average case analysis of unification algorithms. *Theoretical Computer Science*, 113(1, 24):3–34, 1993.
2. K. R. Apt. Logic programming. In J. van Leeuwen, editor, *Handbook of Theoretical Computer Science*, pages 493–574. Elsevier, 1990. Vol. B.

3. K. R. Apt and A. Pellegrini. Why the occur-check is not a problem. In M. Bruynooghe and M. Wirsing, editors, *Proceedings of the Fourth International Symposium on Programming Language Implementation and Logic Programming (PLILP 92)*, Lecture Notes in Computer Science 631, pages 69–86, Berlin, 1992. Springer-Verlag.
4. K.R. Apt and K. Doets. A new definition of SLDNF-resolution. ILLC Prepublication Series CT-92-03, Department of Mathematics and Computer Science, University of Amsterdam, The Netherlands, 1992. To appear in *Journal of Logic Programming*.
5. K.R. Apt, P. van Emde Boas, and A. Welling. The NSTO problem is CoNP-Complete. ILLC prepublication series, Department of Mathematics and Computer Science, University of Amsterdam, The Netherlands, 1993. To appear.
6. J. Beer. The occur-check problem revisited. *Journal of Logic Programming*, 5:243–261, 1988.
7. A. Bossi and N. Cocco. Basic transformation operations for logic programs which preserve computed answer substitutions. Technical Report 16, Dipartimento di Matematica Pura ed Applicata, Università di Padova, 1990.
8. R. Chadha and D.A. Plaisted. Correctness of unification without occur check in Prolog. Technical report, Department of Computer Science, University of North Carolina, Chapel Hill, N.C., 1991.
9. K. L. Clark. Predicate logic as a computational formalism. Res. Report DOC 79/59, Imperial College, Dept. of Computing, London, 1979.
10. H.B. Curry and R. Feys. *Combinatory Logic, Volume I, Studies in Logic and the Foundation of Mathematics*. North-Holland, Amsterdam, 1958.
11. H. Decker. On generalized cover axioms. In K. Furukawa, editor, *Proceedings of the Eighth International Conference on Logic Programming*, pages 693–707, Paris, France, 1991. MIT Press.
12. P. Dembinski and J. Maluszynski. AND-parallelism with intelligent backtracking for annotated logic programs. In *Proceedings of the International Symposium on Logic Programming*, pages 29–38, Boston, 1985.
13. P. Deransart, G. Ferrand, and M. Téguia. NSTO programs (not subject to occur-check). In V. Saraswat and K. Ueda, editors, *Proceedings of the International Logic Symposium*, pages 533–547. The MIT Press, 1991.
14. P. Deransart and J. Maluszynski. Relating Logic Programs and Attribute Grammars. *Journal of Logic Programming*, 2:119–156, 1985.
15. W. Drabent. Do Logic Programs Resemble Programs in Conventional Languages? In *International Symposium on Logic Programming*, pages 389–396. San Francisco, IEEE Computer Society, August 1987.
16. B. Dumant. Checking soundness of resolution schemes. In K.R. Apt, editor, *Proc. of the Joint International Conference and Symposium on Logic Programming*, pages 37–51. MIT Press, 1992.
17. J.-L. Lassez, M. J. Maher, and K. Marriott. Unification Revisited. In J. Minker, editor, *Foundations of Deductive Databases and Logic Programming*, pages 587–625. Morgan Kaufmann, Los Altos, Ca., 1988.
18. J. W. Lloyd. *Foundations of Logic Programming*. Springer-Verlag, Berlin, second edition, 1987.
19. K. Marriott, H. Sø ndergaard, and P. Dart. A Characterization of Non-Floundering Logic Programs. In S. Debray and M. Hermenegildo, editors, *Proc. North American Conference on Logic Programming'90*, pages 661–680. The MIT Press, Cambridge, Mass., 1990.
20. A. Martelli and U. Montanari. An efficient unification algorithm. *ACM Transactions on Programming Languages and Systems*, 4:258–282, 1982.
21. C. S. Mellish. The Automatic Generation of Mode Declarations for Prolog Programs. DAI Research Paper 163, Department of Artificial Intelligence, Univ. of Edinburgh, August 1981.
22. D.A. Plaisted. The occur-check problem in Prolog. In *Proc. International Conference on Logic Programming*, pages 272–280. IEEE Computer Science Press, 1984.
23. U. S. Reddy. Transformation of logic programs into functional programs. In *International Symposium on Logic Programming*, pages 187–198, Silver Spring, MD, February 1984. Atlantic City, IEEE Computer Society.
24. U.S. Reddy. On the relationship between logic and functional languages. In D. DeGroot and G. Lindstrom, editors, *Functional and Logic Programming*, pages 3–36. Prentice-Hall, 1986.

25. D.A. Rosenblueth. Using program transformation to obtain methods for eliminating backtracking in fixed-mode logic programs. Technical Report 7, Universidad Nacional Autonoma de Mexico, Instituto de Investigaciones en Matematicas Aplicadas y en Sistemas, 1991.
26. J. C. Shepherdson. Unsolvable problems for SLDNF resolution. *Journal of Logic Programming*, 10(1):19–22, 1991.
27. H. Sondergaard. An Application of Abstract Interpretation of Logic Programs: Occur Check Reduction. In *Proc. of ESOP'86*, pages 327–338, Sarrbruecken (FRG), 1986.
28. L. Sterling and E. Shapiro. *The Art of Prolog*. MIT Press, 1986.
29. K. Stroetman. A completeness result for SLDNF resolution. *The Journal of Logic Programming*, 15:337–357, 1993.
30. H. Tamaki and T. Sato. Unfold/Fold Transformation of Logic Programs. In *Proceedings of the 2nd International Conference on Logic Programming, Uppsala*, pages 127–137, 1984.

Appendix

We prove here the promised undecidability results and Lemma 5.3. The following theorem summarizes the undecidability issues.

THEOREM 11.1. *For some moded program P the following properties are undecidable:*

—G is such that $P \cup \{G\}$ is occur-check free,

—G is such that all LD-derivations of $P \cup \{G\}$ are data driven,

—G is such that all LD-derivations of $P \cup \{G\}$ are output driven.

Proof. Below M_P denotes the least Herbrand model of a program P and L_P the language determined by P.

Let P_0 be a strictly moded program, p a new binary relation, moded $p(+,-)$, and let $P_1 = P_0 \cup \{p(y, f(y)) \leftarrow\}$.

The system $E = \{x = y, x = f(y)\}$ is not NSTO and by Corollary 6.5 for every ground atom A, $P_1 \cup \{\leftarrow A\}$ is occur-check free. Thus for a ground atom A in L_{P_0}, $P_1 \cup \{\leftarrow A,\ p(x,x)\}$ is not occur-check free iff E is considered in an LD-derivation of $P_1 \cup \{\leftarrow A,\ p(x,x)\}$ iff there exists an LD-refutation of $P_1 \cup \{\leftarrow A\}$ iff (by the completeness of LD-resolution) $A \in M_{P_1}$ iff $A \in M_{P_0}$.

So we showed that for every ground atom A in L_{P_0}

$$A \notin M_{P_0} \text{ iff } P_1 \cup \{\leftarrow A,\ p(x,x)\} \text{ is occur-check free.}$$

An analogous argument using Theorem 4.2 (resp. Theorem 5.2) shows that for every ground atom A in L_{P_0}

$$A \notin M_{P_0} \text{ iff all LD-derivations of } P \cup \{\leftarrow A,\ p(x,x)\} \text{ are data driven,}$$
$$\text{(resp. iff all LD-derivations of } P \cup \{\leftarrow A,\ p(x,x)\} \text{ are output driven).}$$

Thus to prove the theorem it suffices to show that there exists a strictly moded program P_0 for which the set M_{P_0} is undecidable. Now, Corollary 4.7 in Apt [2] gives this result for some program P_0, so it suffices to check that this corollary can be appropriately sharpened.

To this end it is enough to show that every recursive function can be computed by a strictly moded program. The proof of computability of recursive functions by logic programs given in Shepherdson [26] and based on a straigthforward encoding of register machines yields the needed result. Indeed, the obvious moding $p(+,+,\ldots,-)$ for all relations p turns the generated logic programs into strictly moded ones. This completes the proof. □

We now turn to Lemma 5.3. We start by establishing a number of auxiliary lemmas. The notation used below was defined in Section 1.

LEMMA 11.2. *Let θ be a substitution and* $\mathbf{s}$ *and* $\mathbf{t}$ *sequences of terms such that*

—$Var(\mathbf{s}) \cap Var(\mathbf{t}) = \emptyset$,
—$Ran(\theta|\, Var(\mathbf{s})) \cap Ran(\theta|\, Var(\mathbf{t})) = \emptyset$,
—$Var(\mathbf{s}) \cap Ran(\theta|\, Var(\mathbf{t})) = \emptyset$,
—$Var(\mathbf{t}) \cap Ran(\theta|\, Var(\mathbf{s})) = \emptyset$.

Then $Var(\mathbf{s}\theta) \cap Var(\mathbf{t}\theta) = \emptyset$.

Proof. This is an immediate consequence of the fact that for any sequence of terms $\mathbf{u}$ and substitution σ we have $Var(\mathbf{u}\sigma) \subseteq Var(\mathbf{u}) \cup Ran(\sigma|\, Var(\mathbf{u}))$. □

The next two lemmas use the following notion.

DEFINITION 11.3. A substitution $\{x_1/t_1, \ldots, x_n/t_n\}$ is called *linear* if $t_1, \ldots, t_n$ is a linear family of terms. □

LEMMA 11.4. *Let θ be a substitution and* $\mathbf{t}$ *a family of terms. Suppose that*

—θ *is linear,*
—$\mathbf{t}$ *is linear,*
—$Ran(\theta) \cap Var(\mathbf{t}) = \emptyset$.

Then $\mathbf{t}\theta$ *is a linear family of terms, as well.*

Proof. Suppose a variable x has two distinct occurrences in $\mathbf{t}\theta$. Then one of the following statements holds about these occurrences:

—they are both occurrences in $Range(\theta)$,
—they are both occurrences in $\mathbf{t}$,
—one is an occurrence in $Range(\theta)$ and the other is an occurrence in $\mathbf{t}$.

But each assumption of the lemma excludes the corresponding statement above, so the claim follows. □

The following lemma is stated in Deransart and Maluszynski [14].

LEMMA 11.5. *Consider two atoms A and H with the same relation symbol. Suppose that*

—*they have no variable in common,*
—A *is linear.*

Assume that A and H are unifiable. Then there exists a relevant mgu θ of A and H such that

—$\theta|\, Var(H)$ *is linear,*
—$Ran(\theta|\, Var(H)) \subseteq Var(A)$.

Proof. Given a set of equations E, let

$$R\,Var(E) = \bigcup_{s=t \in E} Var(t),$$

$$E_H = \{\ s = t \in E \mid Var(s) \cap Var(H) \neq \emptyset\}.$$

Also, call a term t *singular* if each variable of it occurs in E only once. Call an equation $s = t$ *singular* if either s is a variable and singular or t is singular. Finally, call E *singular* if every equation in it is singular.

Consider the set of equations $H = A$ (note the reverse ordering). We claim that the conjunction of the following three statements is initially true for E equal to $H = A$, and is preserved by the actions (1), (2), (3), (5), (6) of the Martelli-Montanari algorithm:

(1) E_H is right linear,
(2) $R\,Var(E) \subseteq Var(A)$,
(3) E is singular.

The checking of this claim is simple. The only subtle point arises when action (5) applies. Let $x = t$ be the chosen equation. x occurs elsewhere so it is not singular. Thus t is singular and by Lemma 11.4 after performing action (5) E_H remains right linear. Moreover, x becomes then singular, so the equation $x = t$ remains singular, though now on the account of x. The other equations clearly remain singular. The remaining cases are straightforward.

This shows that, when applying to the set $H = A$, the Martelli-Montanari algorithm with action (4) omitted, eventually a set of equations E is produced, which satisfies statements 1-3 and to which only action (4) can be applied. Let now

$$E_1 = \{\ s = t \in E \mid \text{ s is not a variable}\},$$

$$E_2 = E - E_1.$$

None of the actions (1), (2), (3), (5), (6) can be applied to E_1. Thus each of its equations is of the form $s = x$ where x is a variable. Moreover, by virtue of statement 3

$$E_1 = \{s_1 = x_1, \ldots, s_n = x_n\}$$

where $x_1, \ldots, x_n$ are different variables, each of which occurs in E only once. Thus

$$F = \{x = s \mid s = x \in E_1\}$$

is in solved form and it determines a relevant mgu θ_1 of E_1 such that $E_2\theta_1 = E_2$.

Next, none of the actions of the Martelli-Montanari algorithm can be applied to E_2. Thus E_2 is in solved form and it determines a relevant mgu θ_2 of E_2 and so of $E_2\theta_1$. By statement 1 $\theta_2|\,Var(H)$ is linear and by statement 2 $Ran(\theta_2|\,Var(H)) \subseteq Var(A)$.

By Lemma 2.4 $\theta_1\theta_2$ is a relevant mgu of E. Moreover, by statement 2 $Dom(\theta_1) \subseteq Var(A)$, so by the disjointness of A and H we get $Dom(\theta_1) \cap Var(H) = \emptyset$. Thus $\theta_1\theta_2|\,Var(H) = \theta_2|\,Var(H)$.

This shows that $\theta = \theta_1\theta_2$ is the desired mgu. □

In Deransart and Maluszynski [14] this claim is actually stated (without proof) for an arbitrary mgu θ (see Proposition 3 on page 143). However, for $A = p(z, u)$, $H = p(x, y)$ and $\theta = \{x/y,\ y/u,\ z/y\}$ we get then a counterexample.

Below, given an atom A, we denote by $VarIn(A)$ (resp. $VarOut(A)$) the set of variables occurring in the input (resp. output) positions of A. Similar notation is used for sequences of atoms.

Finally, we need the following technical lemma.

LEMMA 11.6. *Consider two atoms A and H with the same relation symbol. Suppose that*

—they have no variable in common,

—A is input-output disjoint and output linear.

Assume that A and H are unifiable. Then there exists a relevant mgu θ of A and H such that for $V = VarOut(H) - VarIn(H)$, $\eta_1 = \theta|V$ and $\eta_2 = \theta|VarIn(H)$

(i) η_1 is linear,

(ii) $Ran(\eta_1) \subseteq Var(A)$,

(iii) $Ran(\eta_2) \cap (Ran(\eta_1) \cup V) = \emptyset$.

Proof. Let $i_1^A, \ldots, i_m^A$ (resp. $i_1^H, \ldots, i_m^H$) be the terms filling in the input positions of A (resp. H) and $o_1^A, \ldots, o_n^A$ (resp. $o_1^H, \ldots, o_n^H$) the terms filling in the output positions of A (resp. H). Let θ_1 be the relevant mgu of $\{o_1^A = o_1^H, \ldots, o_n^A = o_n^A\}$ constructed in the proof of Lemma 11.5. By the disjointness of A and H we have $\theta_1|Var(H) = \theta_1|VarOut(H)$, so by Lemma 11.5

$$\theta_1|Var(H) \text{ is linear} \tag{3}$$

and

$$Ran(\theta_1|Var(H)) \subseteq VarOut(A). \tag{4}$$

Let θ_2 be a relevant mgu of $\{i_1^A = i_1^H, \ldots, i_m^A = i_m^H\}\theta_1$. By Lemma 2.4 θ_2 exists and $\theta = \theta_1\theta_2$ is a relevant mgu of $A = H$.

By the relevance of θ_1 we have $Dom(\theta_1) \subseteq VarOut(A) \cup VarOut(H)$, so by the input-output disjointness of A and the disjointness of A and H we get $\{i_1^A = i_1^H, \ldots, i_m^A = i_m^H\}\theta_1 = \{i_1^A = i_1^H\theta_1, \ldots, i_m^A = i_m^H\theta_1\}$.

By the relevance of θ_2 we have $Var(\theta_2) \subseteq Var(\{i_1^A = i_1^H\theta_1, \ldots, i_m^A = i_m^H\theta_1\}) \subseteq VarIn(A) \cup VarIn(H) \cup Ran(\theta_1|VarIn(H))$.

Thus, by the disjointness of A and H and (4),

$$Var(\theta_2) \cap V = \emptyset. \tag{5}$$

For the same reasons and additionally by the input-output disjointness of A and (3)

$$Var(\theta_2) \cap Ran(\theta_1|V) = \emptyset. \tag{6}$$

Now, (5) and (6) imply that

$$\eta_1 = \theta_1|V. \tag{7}$$

Thus $\eta_1 \subseteq \theta_1|Var(H)$, so by (3) we conclude (i) and by (4) we conclude (ii).

Consider now η_2. Note that $\eta_2 \subseteq (\theta_1 | \mathit{VarIn}(H))\ \theta_2$, so

$$\mathit{Ran}(\eta_2) \subseteq \mathit{Ran}(\theta_1 | \mathit{VarIn}(H)) \cup \mathit{Var}(\theta_2). \tag{8}$$

But by (3), (6), (4), disjointness of A and H, and (5)

$$(\mathit{Ran}(\theta_1 | \mathit{VarIn}(H)) \cup \mathit{Var}(\theta_2)) \cap (\mathit{Ran}(\theta_1 | V) \cup V) = \emptyset,$$

so by (8) and (7) we conclude (*iii*). □

We can now return to Lemma 5.3.

Proof of Lemma 5.3. First, we prove three claims that appropriately refine those of Lemma 4.3.

Claim 1. *Suppose that A and H satisfy the assumptions of Lemma 11.6 and assume that θ is a relevant mgu of $A = H$ which satisfies conditions (i) – (iii) of Lemma 11.6. Let $H \leftarrow \mathbf{B}$ be a nicely moded clause with no variables in common with A. Then $\leftarrow \mathbf{B}\theta$ is nicely moded.*

Proof. Below, by the standardization apart we mean the assumption that $H \leftarrow \mathbf{B}$ and A have no variables in common. Let V, η_1 and η_2 be as in the formulation of Lemma 11.6.

Let $\theta_1 = \theta | \mathit{VarOut}(\mathbf{B})$ and $\theta_2 = \theta | (\mathit{VarIn}(\mathbf{B}) - \mathit{VarOut}(\mathbf{B}))$. We first establish some claims about θ_1 and θ_2. By the standardization apart and the definition of a nicely moded clause

$$\mathit{VarOut}(\mathbf{B}) \cap (\mathit{Var}(A) \cup \mathit{Var}(H)) \subseteq V, \tag{9}$$

so by the fact that θ is relevant

$$\theta_1 \subseteq \eta_1. \tag{10}$$

Thus by the linearity of η_1 (condition (*i*) of Lemma 11.6)

$$\theta_1 \text{ is linear.} \tag{11}$$

Moreover, by (10), (*ii*) of Lemma 11.6 and standardization apart

$$\mathit{Ran}(\theta_1) \cap \mathit{Var}(\mathbf{B}) = \emptyset. \tag{12}$$

Now, let $\theta_2' = \theta_2 | V$ and $\theta_2'' = \theta_2 | \mathit{VarIn}(H)$. We have

$$\theta_2 = \theta_2' \dot{\cup}\ \theta_2'', \tag{13}$$

$$\theta_2' \subseteq \eta_1, \tag{14}$$

and

$$\theta_2'' \subseteq \eta_2. \tag{15}$$

Consider now θ_2'. We have $\mathit{Dom}(\theta_1) \cap \mathit{Dom}(\theta_2) = \emptyset$, so $\mathit{Dom}(\theta_1) \cap \mathit{Dom}(\theta_2') = \emptyset$. Thus, by (10), (14) and the linearity of η_1

$$\mathit{Ran}(\theta_2') \cap \mathit{Ran}(\theta_1) = \emptyset \tag{16}$$

Moreover, by (14), (*ii*) of Lemma 11.6 and the standardization apart

$$Ran(\theta_2') \cap VarOut(\mathbf{B}) = \emptyset. \tag{17}$$

Consider now θ_2''. By (10), (15) and (*iii*) of Lemma 11.6 we get

$$Ran(\theta_2'') \cap Ran(\theta_1) = \emptyset. \tag{18}$$

Also, by the fact that θ is relevant $Ran(\theta_2'') \subseteq Var(A) \cup Var(H)$, so by (9) $Ran(\theta_2'') \cap VarOut(\mathbf{B}) \subseteq V$. Thus by (15) and (*iii*) of Lemma 11.6

$$Ran(\theta_2'') \cap VarOut(\mathbf{B}) = \emptyset. \tag{19}$$

Combining (16) with (18) and (17) with (19) we get by virtue of (13)

$$Ran(\theta_2) \cap (Ran(\theta_1) \cup VarOut(\mathbf{B})) = \emptyset. \tag{20}$$

Now, let us consider $\mathbf{B}$ more in detail. Suppose $\mathbf{B} = p_1(\mathbf{s_1}, \mathbf{t_1}), \ldots, p_n(\mathbf{s_n}, \mathbf{t_n})$. By assumption $\mathbf{t_1}, \ldots, \mathbf{t_n}$ is a linear family of terms and for $i \in [1, n]$ $\mathbf{t_i}\theta \equiv \mathbf{t_i}\theta_1$. So by (11), (12) and Lemma 11.4 $\mathbf{t_1}\theta, \ldots, \mathbf{t_n}\theta$ is a linear family of terms, as well.

Fix now $i \in [1, n]$ and $j \in [i, n]$. We have

$$Ran(\theta | Var(\mathbf{s_i})) \subseteq Ran(\theta_1 | Var(\mathbf{s_i})) \cup Ran(\theta_2 | Var(\mathbf{s_i})) \tag{21}$$

and

$$Ran(\theta | Var(\mathbf{t_j})) = Ran(\theta_1 | Var(\mathbf{t_j})). \tag{22}$$

$\leftarrow \mathbf{B}$ is nicely moded, so

$$Var(\mathbf{s_i}) \cap Var(\mathbf{t_j}) = \emptyset. \tag{23}$$

Thus by the linearity of θ_1 $Ran(\theta_1 | Var(\mathbf{s_i})) \cap Ran(\theta_1 | Var(\mathbf{t_j})) = \emptyset$, and consequently by (21), (22) and (20)

$$Ran(\theta | Var(\mathbf{s_i})) \cap Ran(\theta | Var(\mathbf{t_j})) = \emptyset. \tag{24}$$

Next, by (22) and (12)

$$Var(\mathbf{s_i}) \cap Ran(\theta | Var(\mathbf{t_j})) = \emptyset. \tag{25}$$

Finally, by (21), (12) and (20)

$$Var(\mathbf{t_j}) \cap Ran(\theta | Var(\mathbf{s_i})) = \emptyset. \tag{26}$$

Now, by (23), (24), (25), (26) and Lemma 11.2 we conclude that $Var(\mathbf{s_i}\theta) \cap Var(\mathbf{t_j}\theta) = \emptyset$.

This proves that $\leftarrow \mathbf{B}\theta$ is nicely moded. □

CLAIM 2. *Let θ be a substitution and $\leftarrow \mathbf{A}$ a nicely moded goal such that $Var(\theta) \cap VarOut(\mathbf{A}) = \emptyset$. Then $\leftarrow \mathbf{A}\theta$ is nicely moded, as well.*

Proof. For any term s and a substitution σ we have $Var(s\sigma) \subseteq Var(s) \cup Var(\sigma)$. Moreover, for any term t occurring at an output position of $\mathbf{A}$ by the assumption about θ we have $t\theta = t$. The claim now follows by the definition of a nicely moded goal. □

CLAIM 3. *Suppose $\leftarrow \mathbf{A}$ and $\leftarrow \mathbf{B}$ are nicely moded goals such that $VarOut(\mathbf{A}) \cap Var(\mathbf{B}) = \emptyset$. Then $\leftarrow \mathbf{B}, \mathbf{A}$ is a nicely moded goal, as well.*

Proof. Immediate by the definition of a nicely moded goal. □

Consider now a nicely moded goal $\leftarrow A, \mathbf{A}$ and a disjoint with it nicely moded clause $H \leftarrow \mathbf{B}$, such that A and H unify. Observe that A and H satisfy the assumptions of Lemma 11.6. Assume now that θ is a relevant mgu of $A = H$ which satisfies conditions $(i) - (iii)$ of Lemma 11.6. By Claim 1 $\leftarrow \mathbf{B}\theta$ is nicely moded.

θ is relevant and $Var(A) \cap VarOut(\mathbf{A}) = \emptyset$, so by the standardization apart

$$Var(\theta) \cap VarOut(\mathbf{A}) = \emptyset. \tag{27}$$

By Claim 2 $\leftarrow \mathbf{A}\theta$ is nicely moded.

But (27) implies that $VarOut(\mathbf{A}\theta) = VarOut(\mathbf{A})$. Moreover, $Var(\mathbf{B}\theta) \subseteq Var(\mathbf{B}) \cup Var(\theta)$ and by the standardization apart $VarOut(\mathbf{A}) \cap Var(\mathbf{B}) = \emptyset$, so, again by (27),

$$VarOut(\mathbf{A}\theta) \cap Var(\mathbf{B}\theta) = \emptyset. \tag{28}$$

Now (28) establishes the last assumption of Claim 3 with $\leftarrow \mathbf{A}$ replaced by $\leftarrow \mathbf{A}\theta$ and $\leftarrow \mathbf{B}$ replaced by $\leftarrow \mathbf{B}\theta$. We conclude by Claim 3 that the LD-resolvent $\leftarrow (\mathbf{B}, \mathbf{A})\theta$ of the goal $\leftarrow A, \mathbf{A}$ and the clause $H \leftarrow \mathbf{B}$ is nicely moded.

To draw the same conclusion for an arbitrary LD-resolvent of $\leftarrow A, \mathbf{A}$ and $H \leftarrow \mathbf{B}$ it suffices now to use Lemma 2.3. □